

# FCC Test Report

# Report No.: AGC01110231034FR02A

FCC ID	:	2AOKB-A3955		
APPLICATION PURPOSE	:	Class II Permissive Change		
PRODUCT DESIGNATION	:	Wireless Headphone		
BRAND NAME	:	soundcore		
MODEL NAME	:	A3955		
APPLICANT	:	Anker Innovations Limited		
DATE OF ISSUE	:	May 13, 2024		
STANDARD(S)	:	FCC Part 15 Subpart C §15.247		
<b>REPORT VERSION</b>	:	V1.0		





# **Report Revise Record**

<b>Report Version</b>	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 13, 2024	Valid	Initial Release

Note: The original test report AGC01110231034FR02 (dated Nov. 23, 2023 and tested from Oct. 30, 2023 – Nov. 23, 2023) was modified on May 11, 2024, including the following changes and additions:

- Replaced the battery of earphone and charging case, The batteries are the same except for the manufacturer and model, see below for details :

Original:

Model: M1154A7
Rated Voltage & Cap.: 3.85V 60mAh 0.231Wh
Manufacturer name: Guangdong Mic-power New Energy Co., Ltd.
Model: M13450-B02
Rated Voltage & Cap.: 3.72V 800mAh 2.976Wh
Manufacturer name: Guangdong Mic-power New Energy Co., Ltd.
Model: 1154PF4B
Rated Voltage & Cap.: 3.85V 60mAh 0.231Wh
Manufacturer name: Chongqing VDL Electronics Co., Ltd.
Model: 13450PN3
Rated Voltage & Cap.: 3.72V 800mAh 2.976Wh
Chongqing VDL Electronics Co., Ltd.

For the above described change(s) the following tests was considered to be necessary:

Clause	Testing
§15.209	Radiated Emission



# **Table of Contents**

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Test Frequency List	5
2.3 Related Submittal(S) / Grant (S)	6
2.4 Test Methodology	6
2.5 Receiver Input Bandwidth	6
2.6 Equally Average Use of Frequencies And Behaviour	6
2.7 Pseudorandom Frequency Hopping Sequence	7
2.8 Special Accessories	
2.9 Equipment Modifications	
2.10 Antenna Requirement	
3. Test Environment	9
3.1 Address of The Test Laboratory	9
3.2 Test Facility	9
3.3 Environmental Conditions	
3.4 Measurement Uncertainty	
3.5 List of Equipment Used	11
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used In Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	14
6. Radiated Spurious Emission	
6.1 Measurement Limits	
6.2 Measurement Procedure	
6.3 Measurement Setup (Block Diagram of Configuration)	
6.4 Measurement Result	
Appendix I: Photographs of Test Setup	
Appendix II: Photographs of Test EUT	



# **1. General Information**

Applicant	Anker Innovations Limited					
Address	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon,					
	Hongkong					
Manufacturer	Anker Innovations Limited					
Address	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon,					
	Hongkong					
Factory	N/A					
Address	N/A					
Product Designation	Wireless Headphone					
Brand Name	soundcore					
Test Model	A3955					
Series Model(s)	N/A					
Difference Description	N/A					
Date of receipt of test item	Apr. 28, 2024					
Date of Test	Apr. 28, 2024 – May 11, 2024					
Deviation from Standard	No any deviation from the test method					
Condition of Test Sample	Normal					
Test Result	Pass					
Test Report Form No	AGCER-FCC-BR_EDR-V1					

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By

Cool cheny

Cool Cheng (Project Engineer)

May 13, 2024

Reviewed By

Min Lin

Calvin Liu (Reviewer)

May 13, 2024

Approved By

ax 2nan

Max Zhang Authorized Officer

May 13, 2024





# 2. Product Information

## 2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz				
Operation Frequency Range	2402MHz-2480MHz				
Bluetooth Version	V5.3				
Modulation Type	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK				
Number of channels	79 Channels				
Channel Separation	1 MHz				
Maximum Transmitter Power	Left: 7.537dBm Right: 6.533dBm				
Hardware Version	V3.0				
Software Version	V0.1.9				
Antenna Designation	FPC Antenna				
Antenna Gain	Left: -2.47dBi Right: -2.25dBi				
Power Supply	DC 3.85V by battery				
Adapter Information	N/A				
Note: The EUT comprises left and right channel earphones, both are the same in SCH and layout of main					

board but different in the FPC Layout. The RF output power of each earphone had been tested and recorded in the report. For the other test items, the left earphone had been tested and recorded in this report as the worst case.

## 2.2 Test Frequency List

Frequency Band	Channel Number	Frequency		
2400~2483.5MHz	0	2402 MHz		
	1	2403 MHz		
	:	:		
	39	2441MHz		
	:	:		
	77 2479	2479 MHz		
	78	2480 MHz		
Note: f = 2402 + 1k MHz, k = 0,, 78 ; "f "is the operating frequency (MHz); "k" is the operating channel.				



## 2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: 2AOKB-A3955, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

## 2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

#### 2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

#### 2.6 Equally Average Use of Frequencies And Behaviour

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD\_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.



## 2.7 Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

44	35	78	03	20	76	02 19	 21	64	75
					!		 		
			i				!		
				- i	1	i	÷		
				-	i		1		

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



## 2.8 Special Accessories

Not available for this EUT intended for grant.

## **2.9 Equipment Modifications**

Not available for this EUT intended for grant.

## 2.10 Antenna Requirement

#### **Standard Requirement**

#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

## 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

#### EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the Left antenna is -2.47dBi, the gain of the Right antenna is -2.25dBi.



## 3. Test Environment

## 3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

#### A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



## **3.3 Environmental Conditions**

	NORMAL CONDITIONS		
Temperature range ( $^{\circ}$ C)	15 - 35		
Relative humidity range	20 % - 75 %		
Pressure range (kPa)	86 - 106		
Power supply	3.85V		
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.			

## 3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of $k=2$ providing a level of config	lance of approximately 05%	

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



## 3.5 List of Equipment Used

Radiated Spurious Emission													
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)						
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31						
$\boxtimes$	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023-06-03	2024-06-02						
$\boxtimes$	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31						
$\boxtimes$	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04						
$\boxtimes$	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10						
$\boxtimes$	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2025-03-22						
$\boxtimes$	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23						
$\boxtimes$	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03						
$\boxtimes$	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2023-06-01	2024-05-31						
$\square$	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08						
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08						

• A	AC Power Line Conducted Emission														
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)								
	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2023/06/03	2024/06/02								
	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2024-06-08								
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2023/06/03	2024/06/02								

Test Software													
Used	d Equipment No. Test Equipment		Manufacturer	Model No.	Version Information								
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A								
	AGC-EM-S011	RSE Test System	Tonscend	TS <sup>+</sup> Ver2.1(JS36-RSE)	4.0.0.0								
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71								
	AGC-ER-S009	BT/WIFI Test System	Tonscend	JS1120-3	2.6.77.0518								



# **4.System Test Configuration**

## **4.1 EUT Configuration**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

## 4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

## 4.3 Configuration of Tested System

Radiated Emission Configure:



## 4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

### ☐ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1					
	Test Accessories	Come From The	Manufacturer		

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1					



#### 4.5 Summary of Test Results

ltem	FCC Rules	Description of Test	Result
1	§15.209	Radiated Spurious Emission	



# 5. Description of Test Modes

	Summary table of Test Cas	ses					
	Data Rat	te / Modulation					
Test Item	Bluetooth – BR_EDR (	GFSK/π /4-DQPSK/8DPSK)					
Radiated & Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2 Mode 2: Bluetooth Tx CH39_2 Mode 3: Bluetooth Tx CH78_2 Mode 4: Bluetooth Tx CH00_2 Mode 5: Bluetooth Tx CH39_2 Mode 6: Bluetooth Tx CH78_2 Mode 7: Bluetooth Tx CH00_2 Mode 8: Bluetooth Tx CH39_2 Mode 8: Bluetooth Tx CH39_2 Mode9: Bluetooth Tx CH78_2 Mode10: Bluetooth Tx Ho Mode11: Bluetooth Tx Ho	2402 MHz_1Mbps (Battery powered) 2441 MHz_1Mbps (Battery powered) 2480 MHz_1Mbps (Battery powered) 2402 MHz_2Mbps (Battery powered) 2441 MHz_2Mbps(Battery powered) 2480 MHz_2Mbps(Battery powered) 2402 MHz_3Mbps (Battery powered) 2441 MHz_3Mbps(Battery powered) 2440 MHz_3Mbps(Battery powered) 2480 MHz_3Mbps(Battery powered)					
AC Conducted Emission		N/A					
<ol> <li>Only the result of the wo</li> <li>The battery is full-charge</li> <li>For Radiated Emission, 3</li> <li>For Conducted Test met</li> <li>WQ TWS RF TOOL</li> <li>Fie Device</li> <li>Werkes</li> <li>Pert ID Address</li> <li>Name Address</li> <li>COM2 0x</li> <li>WQ Private</li> </ol>	A state Note Authenticatic Encryption Version Found 11 IDLE UNDEFL.	AD OTHER Cases. applicable mode. s provided by the manufacture. m × <u>BE</u> T DEBUG Setting: Scanning Inquiry Tr Mode WOO TEST <b>BE</b>   KOR TRANSMITTER TEST <b>BE</b>   KOR TRANSMITTER TEST <b>F</b> Tx Hode <b>TEST MODE TX JEST</b> <b>Packet Type</b> <b>TX ITTEL</b> <b>F</b> Tx Hode <b>TEST MODE TX JEST</b> <b>Packet Type</b> <b>TX ITTEL</b> <b>F</b> Crequency Channel <b>Repping Bode</b> <b>I opping OFF</b> <b>I ddress</b> <b>I ddress</b>					
Selected Local Davice Traces       Selected Peer         (PARAW) Length - 0004       (PARAW) Length - 0004         (PARAW) Command Packets = 0005       (PARAW) Command Packets = 0005         (PARAW) Command Opcode = 000505 (cmcmest       (PARAW) Command Packets = 0005         hci_send: 015+fc150120200015301000052000000       (PARAW) Total Command Packets = 0005         (PARAW) Total Command Packets = 0005       (PARAW) Total Command Packets = 0005         (PARAW) Total Command Packets = 0005       (PARAW) Total Command Packets = 0005         (PARAW) Total Length = 0006       (PARAW) Total Length = 0006         (PARAW) Total Length = 0006       (PARAW) Total Length = 0006         (PARAW) Tracket ungth = 0006       (PARAW) Tracket ungth = 0006         (PARAW) Tracket ungth = 0006       (PARAW) Tracket = 0005         (PARAW) Tracket ungth = 0006       (PARAW) Tracket = 0005         (PARAW) Tracket ungth = 0006       (PARAW) Tracket = 0006         (PARAW) Tracket ungth = 0006       (PARAW) Tracket = 0006         (PARAW) Tracket ungth = 0006       (PARAW) Tracket = 0006         (PARAW) Tracket ungth = 0006       (PARAW) Command Packets = 0005         (PARAW) Status = 0006       (PARAW) Command Packets = 0005         (PARAW) Status = 0006       (PARAW) Command Packets = 0005         (PARAW) Status = 0006       (PARAW) Command Packets = 0005	X Derice Traces Decofffffff	Tr Interval 0 0 0 Tr Facket Humber Or FFFFFFF Start TX Test Stop TX Test External Wake-up Platform Timeout(ms): 0 Set 0x dd Pee o Sett Reset Symo Ox Send					



# 6. Radiated Spurious Emission

## **6.1 Measurement Limits**

#### 15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

#### 6.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection"

Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start Stan Fraguency	1GHz~26.5GHz
Start ~Stop Frequency	1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP



## • Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

#### Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

#### • Average Measurements above 1GHz (Method VB)

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle  $\ge$  98%, set VBW = 10 Hz.
- 5. If the EUT duty cycle is < 98%, set VBW  $\ge$  1/T. T is the minimum transmission duration.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold
- 8. Trace was allowed to stabilize



## 6.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



#### **6.4 Measurement Result**

#### Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

Radiated Emission Test Results at 30MHz-1GHz																					
EUT Name		Wireless Headphone N									Mod	el N	ame			A:	3955	5			
Temperatu	re	22.9° C								Relative Humidity 59.7%											
Pressure		960	hPa	à							Test	Vol	tage			N	orma	al Vo	olta	age	
Test Mode		Мос	de 3	6							Ante	enna	Pola	arity	y	н	orizo	onta	l		
72.0 dBuV/m																					
12.0	72.0 dBuV/m													Lin	nit:		-				
																Ma	irgin:	_	-		
-																			ſ		
																			-1		
-		_					ſ											ŝ			
32							1							A		5		Å	~		
														Ă٩	JANNA .	1 million	whythe	Ĩ			
-			1					2 1	WARLAL II		on a list	3 Harris	and the work								
	MAR	Anderwo	madi	n/shijk	handlow	hillow	Maria .	4 d	A MARINA MARINA AND A MARINA	re Welderberr	p2444p1-335-340										
l l																					
_																					
-8 30.	.000	40	50	06	50 7	0 80			(MHz)			300	400	)	500	600	700	10	00.0	00	
						Re	ead	ing	Correct	Me	asure	<u>-</u>			-				_		
	No	. Mk	۲.	Fr	eq.	L	eve	el	Factor	n	nent		Limit		Ove	er					
				М	Hz		dBu\	V	dB	dB	3uV/m	d	BuV/n	n	dB		Dete	ector	r		
	1		4	9.0	145		6.2	9	13.27	19	9.56	4	0.00		-20.4	44	pe	ak	_		
	2		11	5.72	256	5.41		16.36	2	1.77	4	3.50	-	-21.1	73	pe	ak	_			
	3		29	9.3	158		5.59		16.45	22	2.04	4	6.00	-	-23.9	96	pe	ak	_		
	4		44	7.9	822		5.73		24.82	30	0.55	4	6.00	-	-15.4	45	pe	ak	_		
	5		60	1.42	265		6.1	7	25.11	3	1.28	4	6.00	-	-14.	72	2 peak		_		
	6	*	89	3.8	567		6.5	9	31.03	3	7.62	4	6.00		-8.3	8	ре	ak	_		
																			_		



Radiated Emission Test Results at 30MHz-1GHz																		
EUT Name	e	Wireless Headphone							Model Name				A	A3955				
Temperatu	ure	22.9° C								Relative Humidity				59	9.7%			
Pressure 960hPa							Test Voltage				Ν	orma	I Volt	tage				
Test Mode	;	Мос	de 3							Antenna Polarity				Ve	ertica	d		
72.0 dBuV/m																		
														Li	Limit: —			
														M	argin:			
																f		
																	-	
				_	_				Τ_					_			1	
												4			. A	Å		
32												Ň	wind our	mp.	New Press	ALCON THE REAL PROPERTY AND A DECIMAL ADDRESS ADDRESS ADDRESS ADDRESS ADDRESS ADDRESS ADDRESS ADDRESS ADDRESS A		
				2				and the state of t		And	Wanterstat	man						
	иририрыя	Kondinkala	p-regulations	MNALS OF	maga.	Armitwilly.	harwar	Auth An	a served and	44							]	
		_															{	
0																		
-8	0.000	40	50	60	70	80		(MHz)			300	400	500	600	700	1000	_   .000	
						Read	ing	Correct	Me	asure	e-							
	No	. M	K.	Freq		Level		Factor	n	nent Li		Limit Ove		er	r			
			MHz			dBuV		dB	dB	BuV/m dBuV/m		d	3	Dete	ector			
	1		47	.491	8	6.07		16.97	23	3.04	.04 40.00		-16	.96	ре	ak		
	2	2	66.0342		2	6.36		17.04	23	3.40 40.00		-16	.60	ре	ak			
	3	3	153.7385		5	6.18		18.20	24	4.38 43.50		-19	.12	pe	ak			
	4	443.2943		3	5.84		25.95	3′	1.79 46.00		-14	21	pe	ak				
	5	)	813	.111	5	7.3	39	27.73	3	5.12	4	6.00	-10	.88	pe	ak		
	6	; *	945	.439	9	5.2	24	30.78	36	6.02	4	6.00	-9.	98	pe	ak		

## **RESULT: Pass**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.



Wireless H	leadphone		Mode	I Name	A3955	A3955	
22.9°C			Relat	ive Humidity	59.7%	59.7%	
960hPa			Test \	Voltage	Normal V	Normal Voltage	
Mode 1			Anter	nna Polarity	Horizonta	I	
					·		
er Reading	Emissio	Emission Level Limits					
(dBµV)	(dB)	(dBµV/m)		(dBµV/m)	(dB)	value Type	
47.86	0.08	47.94		74	-26.06	peak	
38.42	0.08	38.5		54	-15.5	AVG	
42.91	2.21	45.2	2	74	-28.88	peak	
31.27	2.21	33.48		54	-20.52	AVG	
actor + Cabl	e Loss – Pre-a	amplifier.					
Wireless H	leadphone		Mode	I Name	A3955		
22.9°C				ive Humidity	59.7%		
960hPa				Voltage	Normal V	Normal Voltage	
Mode 1			Anter	nna Polarity	Vertical	Vertical	
-						<b></b>	
er Reading	Factor	Emissio	n Level	Limits	Margin	Value Type	
(dBµV)	(dB)	(dBµV/m)		(dBµV/m)	(dB)		
47.39	0.08	47.47		74	-26.53	peak	
37.42	0.08	37.5		54	-16.5	AVG	
42.53	2.21	44.74		74	-29.26	peak	
32.34 2.21		34.55		54	-19.45	AVG	
	Wireless H         22.9° C         960hPa         Mode 1         Mode 1         ter Reading (dBµV)         47.86         38.42         42.91         31.27         actor + Cable         Wireless H         22.9° C         960hPa         Mode 1         er Reading (dBµV)         47.39         37.42         42.53         32.34	Wireless Headphone         22.9° C         960hPa         Mode 1         ter Reading       Factor         (dBµV)       (dB)         47.86       0.08         38.42       0.08         42.91       2.21         31.27       2.21         actor + Cable Loss – Pre-a         Wireless Headphone         22.9° C         960hPa         Mode 1         ter Reading       Factor         (dBµV)       (dB)         47.39       0.08         37.42       0.08         42.53       2.21	Wireless Headphone         22.9° C         960hPa         Mode 1         ter Reading       Factor         (dBµV)       (dB)         (dBµV)       (dB)         47.86       0.08         38.42       0.08         38.42       0.08         31.27       2.21         47.86       0.08         42.91       2.21         31.27       2.21         33.42       0.08         actor + Cable Loss – Pre-amplifier.         Wireless Headphone         22.9° C         960hPa         Mode 1         ter Reading       Factor         Emission         (dBµV)       (dB)         (dBµV)       (dB)         47.39       0.08         37.42       0.08         37.42       0.08         32.34       2.21         34.5	Wireless Headphone       Mode         22.9° C       Relat         960hPa       Test V         Mode 1       Anter         ter Reading       Factor       Emission Level         (dBµV)       (dB)       (dBµV/m)         47.86       0.08       47.94         38.42       0.08       38.5         42.91       2.21       45.12         31.27       2.21       33.48         actor + Cable Loss – Pre-amplifier.       Mode         22.9° C       Relat         960hPa       Test V         Mode 1       Anter         ter Reading       Factor         P60hPa       Test V         960hPa       Anter         960hPa       Test V         960hPa       Anter         Mode 1       Anter         ter Reading       Factor       Emission Level         (dBµV)       (dB)       (dBµV/m)         47.39       0.08       37.5         42.53       2.21       44.74         32.34       2.21       34.55	Wireless HeadphoneModel Name22.9° CRelative Humidity960hPaTest VoltageMode 1Antenna Polarityter ReadingFactorEmission LevelLimits(dBµV)(dB)(dBµV/m)(dBµV/m)47.860.0847.947438.420.0838.55442.912.2145.127431.272.2133.4854actor + Cable Loss – Pre-amplifier.Model Name22.9° CRelative Humidity960hPaTest VoltageMode 1Antenna PolarityHumidity960hPaGMode 1Antenna PolarityImits(dBµV)(dB)(dBµV)(dB)(dBµV/m)47.390.0847.4737.420.0837.55442.532.2144.747432.342.2134.5554	Wireless Headphone         Model Name         A3955           22.9° C         Relative Humidity         59.7%           960hPa         Test Voltage         Normal V           Mode 1         Antenna Polarity         Horizonta           ter Reading         Factor         Emission Level         Limits         Margin           (dBµV)         (dB)         (dBµV/m)         (dBµV/m)         (dB)           47.86         0.08         47.94         74         -26.06           38.42         0.08         38.5         54         -15.5           42.91         2.21         45.12         74         -28.88           31.27         2.21         33.48         54         -20.52           actor + Cable Loss – Pre-amplifier.	

## **Radiated Emissions Test Results Above 1 GHz**

## **RESULT: Pass**



EUT Name		Wireless H	eadphone		Mode	el Name	A3955	A3955		
Temperature		22.9°C			Relat	ive Humidity	59.7%	59.7% Normal Voltage		
Pressure		960hPa			Test	Voltage	Normal			
Test Mode		Mode 2			Ante	nna Polarity	Horizontal			
Frequency	Μ	eter Reading	g Factor Emissio		n Level	Limits	Margin			
(MHz)		(dBµV)	(dB)	(dBµV/m)		(dBµV/m)	(dB)	value i ype		
4882.000		48.94	0.14	49.08		74	-24.92	peak		
4882.000		37.53	0.14	37.67		54	-16.33	AVG		
7323.000		42.19	2.36	44.55		74	-29.45	peak		
7323.000		32.35	2.35 2.36		71	54	-19.29	AVG		
Remark:										
Factor = Anter	nna F	Factor + Cabl	e Loss – Pre-	amplifier.						
EUT Name		Wireless H	eadphone		Mode	el Name	A3955			
Temperature		22.9°C				ive Humidity	59.7%			
Pressure		960hPa				Voltage	Normal	Voltage		
lest Mode		Mode 2				nna Polarity	Vertical			
Fraguanay	N.4	otor Pooding	Factor	Emissio		Limite	Margin			
(MH-7)				(dRu)	//m)	(dBuV/m)	(dR)	Value Type		
/1882.000	+	/8 37	0.14		51 7 <i>1</i>		-25 /0	neak		
4882.000	-	37 53	0.14	27 6	37.67 54		-16.33	AVG		
7323 000	-	42.06	2.36	44.4	44.42 74		-29.58	peak		
7323.000	3,000 42		32.00 2.30		78	54	-19.22	AVG		
1020.000		JL.7L	2.00		5		10.22			
Remark:										
Factor = Anter	nna F	actor + Cabl	e Loss – Pre-	amplifier.						

## Radiated Emissions Test Results for Above 1 GHz

## **RESULT: Pass**



EUT Name		Wireless He	adphone		Model	Name	A3955	A3955		
Temperature		22.9°C			Relativ	ve Humidity	59.7%	59.7%		
Pressure		960hPa			Test V	oltage	Normal \	Normal Voltage		
Tes	st Mode	Mode 3			Anten	na Polarity	Horizonta	Horizontal		
	Frequency	Meter Reading	Factor Emiss		on Level	Limits	Margin			
	(MHz)	(dBµV)	(dB)	(dBµ	V/m)	(dBµV/m)	(dB)	value Type		
	4960.000	48.65	0.22	48.87		74	-25.13	peak		
	4960.000	37.53	0.22	37.	.75	54	-16.25	AVG		
	7440.000	42.16	2.64	44	.8 74		-29.2	peak		
	7440.000	32.46	2.64	35	5.1	54	-18.9	AVG		
	Remark:									
	Factor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier.					l	
EUT Name		Wireless He	adphone		Model	Name	A3955			
Ter	nperature	22.9°C			Relativ	ve Humidity	59.7%			
Pre	essure	960hPa			Test V	oltage	Normal \	Normal Voltage		
Tes	st Mode	Mode 3			Anten	na Polarity	Vertical	Vertical		
	Frequency	Meter Reading	Factor	Emissio	on Level	Limits	Margin	Value Type		
	(MHz)	(dBµV)	(dBµV) (dB)		V/m)	(dBµV/m)	(dB)			
	4960.000	48.12	0.22	48.34		34 74		peak		
	4960.000	37.42	37.42 0.22		.64	54	-16.36	AVG		
	7440.000	42.36	2.64	45		74	-29	peak		
	7440.000	32.24	2.64	34.88		54	-19.12	AVG		
	Demerly									
	Remark:		alaaa Diir							
	ractor = Anter	ina Factor + Cabl	e Loss – Pre-	ampliner.						

## Radiated Emissions Test Results for Above 1 GHz

#### **RESULT: Pass**

Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.



Report No.: AGC01110231034FR02A Page 24 of 24

# Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC01110231034AP02A

# Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC01110231034AP03A

-----End of Report-----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.