

FCC SAR Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2425-1
FCC ID : IHDT56AP6
STANDARD : FCC 47 CFR Part 2 (2.1093)

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Shenzhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China

Table of Contents

1. Statement of Compliance	4
2. Administration Data	6
3. Guidance Applied.....	6
4. Data Reuse Approach	7
4.1 Introduction Section	7
4.2 Model Difference Information	7
4.3 Reference detail Section	7
5. Equipment Under Test (EUT) Information.....	8
5.1 General Information	8
5.2 General LTE SAR Test and Reporting Considerations	9
6. RF Exposure Limits.....	11
6.1 Uncontrolled Environment.....	11
6.2 Controlled Environment.....	11
7. Specific Absorption Rate (SAR).....	12
7.1 Introduction	12
7.2 SAR Definition.....	12
8. System Description and Setup	13
8.1 E-Field Probe	14
8.2 Data Acquisition Electronics (DAE)	14
8.3 Phantom.....	15
8.4 Device Holder.....	16
9. Measurement Procedures	17
9.1 Spatial Peak SAR Evaluation	17
9.2 Power Reference Measurement.....	18
9.3 Area Scan	18
9.4 Zoom Scan.....	19
9.5 Volume Scan Procedures.....	19
9.6 Power Drift Monitoring.....	19
10. Test Equipment List.....	20
11. System Verification	21
11.1 Tissue Simulating Liquids	21
11.2 Tissue Verification	22
11.3 System Performance Check Results	24
12. RF Exposure Positions	26
12.1 Ear and handset reference point.....	26
12.2 Definition of the cheek position	27
12.3 Definition of the tilt position	28
12.4 Body Worn Accessory	29
12.5 Product Specific 10g SAR Exposure.....	30
12.6 Wireless Router.....	30
14. Antenna Location	31
15. Spot Check SAR Test Results.....	32
15.1 Head SAR	32
15.2 Hotspot SAR	34
15.3 Body Worn Accessory SAR.....	36
15.4 Product specific 10g SAR	38
15.5 Repeated SAR Measurement	40
16. Simultaneous Transmission Analysis	41
16.1 Head Exposure Conditions	42
16.2 Hotspot Exposure Conditions.....	43
16.3 Body-Worn Accessory Exposure Conditions	45
16.4 Product specific 10g SAR Exposure Conditions.....	47
16.5 SPLSR Evaluation and Analysis.....	49
17. Uncertainty Assessment	55
18. References	56
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA3O1717-01	Rev. 01	Initial issue of report	Nov. 15, 2023

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, XT2425-1**, are as follows.

Highest 1g SAR Summary						
Equipment Class	Frequency Band		Head (Separation 0mm)	Hotspot (Separation 5mm)	Body-worn (Separation 5mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.59	1.43	1.43	1.59
		GSM1900	0.31	1.43	1.30	
	WCDMA	WCDMA V	0.53	1.43	1.43	
		WCDMA IV	0.38	1.41	1.41	
		WCDMA II	0.39	1.38	1.38	
	LTE	LTE Band 13	0.45	1.43	1.43	
		LTE Band 26/5	0.46	1.35	1.35	
		LTE Band 66/4	0.33	1.41	1.39	
		LTE Band 2	0.37	1.40	1.39	
		LTE Band 7	0.25	1.43	1.37	
		LTE Band 38	0.11	1.38	1.38	
DTS	WLAN	WLAN2.4GHz	1.17	1.15	1.15	1.58
NII		WLAN5GHz	1.16	1.16	1.18	1.56
DSS	Bluetooth	Bluetooth	0.29	0.21	0.21	1.59

Highest 10g SAR Summary				
Equipment Class	Frequency Band		Product Specific 10g SAR (W/kg) (Separation 0mm)	Highest Simultaneous Transmission 10g SAR (W/kg)
Licensed	GSM	GSM850	3.46	3.77
		GSM1900	3.58	
	WCDMA	WCDMA V	2.62	
		WCDMA IV	3.51	
		WCDMA II	3.57	
	LTE	LTE Band 13	2.17	
		LTE Band 26/5	2.46	
		LTE Band 66/4	3.49	
		LTE Band 2	3.37	
		LTE Band 7	3.40	
		LTE Band 38	3.52	
DTS	WLAN	WLAN2.4GHz	1.60	3.77
NII		WLAN5GHz	2.86	3.74
Date of Testing:			2023/10/22~2023/11/9	

Remark: This device supports LTE B4 / B5 and B66 / B26. Since the supported frequency span for LTE B4 / B5 falls completely within the supports frequency span for LTE B66 / B26, both LTE bands have the same target power, and both LTE bands share the same transmission path; therefore, SAR was only assessed for LTE B66 / B26.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2. Administration Data

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR02-SZ, SAR03-SZ, SAR05-SZ	CN1256	421272

Applicant	
Company Name	Motorola Mobility LLC
Address	222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility LLC
Address	222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02



4. Data Reuse Approach

4.1 Introduction Section

This application re-uses data collected on a similar device, FCC ID: IHDT56AP1 (reference model) and FCC ID: IHDT56AP6 (variant model). Due to the same design are identical between parent model and variant model, SAR data reuse is requested and spot check data in this report is used to justify the SAR data reuse.

For variant model 1g SAR and 10g spot check SAR result does not exceed 30% and 1g SAR < 1.2W/kg, 10g SAR < 3.0W/kg of the reference model, the WWAN/WLAN max SAR summary was always choose the higher SAR between parent model and variant model.

The applicant should take full responsibility that the test data as referenced in this report represent compliance for this FCC ID: IHDT56AP6

4.2 Model Difference Information

The main difference between FCC ID: IHDT56AP1 and FCC ID: IHDT56AP6 is as below:

- Change battery capacity is 6000mAh, and charge IC apply to 15W & 33W.

Other differences and all the details of similarity and can be found in the confidential documents (XT2425-1_Operational Description of Product Equality Declaration).

4.3 Reference detail Section

Rule Part	Equipment Class	Wireless Technology	Frequency Band (MHz)	FCC ID (Reference)	Type Grant/ Permissive Change	Reference Title	FCC ID Filling (Variant)	Test on the variant
Part 2.1093	PCE	GSM	GSM850/1900	IHDT56AP1	Original Grant	FA3O1717	IHDT56AP6	Spot check
		WCDMA	B2/5/4	IHDT56AP1	Original Grant	FA3O1717	IHDT56AP6	Spot check
		LTE	B2/4/5/7/13/26/66/38	IHDT56AP1	Original Grant	FA3O1717	IHDT56AP6	Spot check
	DTS	BLE/ Wi-Fi	2400~2483.5	IHDT56AP1	Original Grant	FA3O1717	IHDT56AP6	Spot check
	NII	Wi-Fi	5150 ~ 5250 5250 ~ 5350 5470 ~ 5725 5725 ~ 5850	IHDT56AP1	Original Grant	FA3O1717	IHDT56AP6	Spot check
	DSS	Bluetooth	2400~2483.5	IHDT56AP1	Original Grant	FA3O1717	IHDT56AP6	Spot check

5. Equipment Under Test (EUT) Information

5.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2425-1
FCC ID	IHDT56AP6
IMEI Code	Sample 1: IMEI 1: 355913380008503 IMEI 2: 355913380011028 Sample 2: IMEI 1: 355913380013651 IMEI 2: 355913380014121
Frequency Band	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 38: 2570 MHz ~ 2620 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GSM/GPRS/EGPRS AMR / RMC 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+ (16QAM uplink is supported) LTE: QPSK, 16QAM, 64QAM WLAN 2.4GHz : 802.11b/g/n HT20/ HT40 WLAN 5GHz : 802.11a/n/ac HT20/HT40/VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DVT2
SW Version	UTA34.66
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: - This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation. - This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications. - This device 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only). - This device does not support DTM operation and supports GPRS/EGPRS mode up to multi-slot class 12. - For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests. - There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we chose dual SIM card mobile to perform all tests. - The device implements the power management and proximity sensor /receiver detection/hotspot mode for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity). Details about the power	

management decision and sensor detection are provided in the operational description. And the device will invoke corresponding work scenarios power level base on frequency bands/antennas, power table which can refer to reference model test report.

8. There are two samples, the different between them refer to the XT2425-1_Operational Description of Product Equality Declaration which is exhibit separately. According to the differences, sample 1 was chosen to perform full SAR testing and sample 2 verified the worst case of sample 1.

5.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																																													
FCC ID	IHDT56AP6																																																																												
Equipment Name	Mobile Cellular Phone																																																																												
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 66: 1710 MHz ~ 1780 MHz																																																																												
Channel Bandwidth	LTE Band 2:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 4:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 13: 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz LTE Band 26:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz																																																																												
Uplink Modulations used	QPSK / 16QAM / 64QAM																																																																												
LTE Voice / Data requirements	Voice and Data																																																																												
LTE Release Version	R9, Cat 5																																																																												
CA Support	Not Supported																																																																												
LTE MPR permanently built-in by design	<table><tr><th colspan="8">Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</th></tr><tr><th rowspan="2">Modulation</th><th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th><th rowspan="2">MPR (dB)</th></tr><tr><th>1.4 MHz</th><th>3.0 MHz</th><th>5 MHz</th><th>10 MHz</th><th>15 MHz</th><th>20 MHz</th></tr><tr><td>QPSK</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 2</td></tr><tr><td>64 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 2</td></tr><tr><td>64 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 3</td></tr><tr><td>256 QAM</td><td colspan="6">≥ 1</td><td>≤ 5</td></tr></table>							Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3								Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3																																																																													
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																																																						
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																																							
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																																						
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																																						
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																																						
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																																						
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																																						
256 QAM	≥ 1						≤ 5																																																																						
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																																												
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																																												
Power reduction applied to satisfy SAR compliance	Yes, when operating in Proximity sensors/receiver/hotspot detect mechanism, head/body-worn /hotspot/extremity will trigger reduced power for some bands applied to satisfy SAR compliance, the detail please referred to reference model test report.																																																																												

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535				
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)					
L	23205		779.5		23230		782					
M	23230		782									
H	23255		784.5									
LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5		
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5		
H	27033	848.3	27025	847.5	27015	.5	26990	844	26965	841.5		
LTE Band 38												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580				
M	38000	2595	38000	2595	38000	2595	38000	2595				
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610				
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770

6. RF Exposure Limits

6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

7. Specific Absorption Rate (SAR)

7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

8.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Photo of DAE

8.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices or for evaluating transmitters operating at low frequencies. ELI is fully compatible with standard and all known tissue simulating liquids.

8.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			$\leq 3 \text{ GHz}$	$> 3 \text{ GHz}$
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASYS measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1099	Dec. 15, 2021	Dec. 14, 2024
SPEAG	835MHz System Validation Kit	D835V2	4d162	Dec. 17, 2021	Dec. 16, 2024
SPEAG	1750MHz System Validation Kit	D1750V2	1090	Feb. 24, 2022	Feb. 23, 2025
SPEAG	1900MHz System Validation Kit	D1900V2	5d182	Dec. 20, 2021	Dec. 19, 2024
SPEAG	2450MHz System Validation Kit	D2450V2	1040	Apr. 25, 2023	Apr. 24, 2024
SPEAG	2600MHz System Validation Kit	D2600V2	1070	Dec. 20, 2021	Dec. 19, 2024
SPEAG	5000MHz System Validation Kit	D5GHzV2	1341	Dec. 13, 2021	Dec. 12, 2024
SPEAG	Data Acquisition Electronics	DAE4	1664	Jun. 06, 2023	Jun. 05, 2024
SPEAG	Data Acquisition Electronics	DAE3	360	Dec. 28, 2022	Dec. 27, 2023
SPEAG	Data Acquisition Electronics	DAE4	715	Jan. 23, 2023	Jan. 22, 2024
SPEAG	Dosimetric E-Field Probe	EX3DV4	7641	Apr. 24, 2023	Apr. 23, 2024
SPEAG	Dosimetric E-Field Probe	EX3DV4	7577	Nov. 23, 2022	Nov. 22, 2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	3975	Jun. 22, 2023	Jun. 21, 2024
SPEAG	SAM Twin Phantom	QD 000 P40 CD	1670	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CD	1795	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P41 AA	2033	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201300653	Jul. 05, 2023	Jul. 04, 2024
Anritsu	Radio communication analyzer	MT8820C	6201341952	Dec. 27, 2022	Dec. 26, 2023
Anritsu	Radio communication analyzer	MT8821C	6262314715	Jul. 05, 2023	Jul. 04, 2024
Anritsu	Radio communication analyzer	MT8821C	6272278319	Jul. 05, 2023	Jul. 04, 2024
Anritsu	Radio communication analyzer	MT8821C	6272416837	Apr. 03, 2023	Apr. 02, 2024
Keysight	Network Analyzer	E5071C	MY46523671	Oct. 16, 2023	Oct. 15, 2024
Speag	Dielectric Assessment KIT	DAK-3.5	1071	Feb. 20, 2023	Feb. 19, 2024
Agilent	Signal Generator	N5181A	MY50145381	Dec. 27, 2022	Dec. 26, 2023
Anritsu	Power Sensor	MA2411B	1306099	Oct. 16, 2023	Oct. 15, 2024
Anritsu	Power Meter	ML2495A	1349001	Oct. 16, 2023	Oct. 15, 2024
Anritsu	Power Sensor	MA2411B	1542004	Dec. 27, 2022	Dec. 26, 2023
Anritsu	Power Meter	ML2495A	1339473	Dec. 27, 2022	Dec. 26, 2023
R&S	Power Sensor	NRP8S	109228	Apr. 06, 2023	Apr. 05, 2024
R&S	CBT BLUETOOTH TESTER	CBT	100963	Dec. 27, 2022	Dec. 26, 2023
R&S	Spectrum Analyzer	FSP7	100818	Jul. 05, 2023	Jul. 04, 2024
TES	Hygrometer	1310	200505600	Jul. 08, 2023	Jul. 07, 2024
Anymetre	Thermo-Hygrometer	JR593	2015030903	Dec. 30, 2022	Dec. 29, 2023
Anymetre	Thermo-Hygrometer	JR593	2015102801	Dec. 30, 2022	Dec. 29, 2023
Anymetre	Thermo-Hygrometer	JR593	2020062101	Jul. 08, 2023	Jul. 07, 2024
AR	Amplifier	5S1G4	0333096	Note 1	
Mini-Circuits	Amplifier	ZVE-3W-83+	599201528	Note 1	
Mini-Circuits	Amplifier	ZVA-183W-S+	726202215	Note 1	
SPEAG	Device Holder	N/A	N/A	Note 1	
ARRA	Power Divider	A3200-2	N/A	Note 1	
ET Industries	Dual Directional Coupler	C-058-10	N/A	Note 1	
Jinkexinhua	Attenuator	10db-8G	N/A	Note 1	

Note:

- Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
- The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.

11. System Verification

11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1 Photo of Liquid Height for Head SAR



Fig 10.2 Photo of Liquid Height for Body SAR

11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε _r)	Conductivity Target (σ)	Permittivity Target (ε _r)	Delta (σ) (%)	Delta (ε _r) (%)	Limit (%)	Date
750	Head	22.1	0.883	40.810	0.89	41.90	-0.79	-2.60	±5	2023/10/22
750	Head	22.3	0.911	42.879	0.89	41.90	2.36	2.34	±5	2023/10/31
835	Head	22.5	0.930	42.770	0.90	41.50	3.33	3.06	±5	2023/10/31
835	Head	22.5	0.904	42.080	0.90	41.50	0.44	1.40	±5	2023/11/1
835	Head	22.6	0.915	41.980	0.90	41.50	1.67	1.16	±5	2023/11/3
1750	Head	22.7	1.356	40.425	1.37	40.10	-1.02	0.81	±5	2023/10/27
1750	Head	22.5	1.363	41.115	1.37	40.10	-0.51	2.53	±5	2023/11/2
1900	Head	22.4	1.417	40.994	1.40	40.00	1.21	2.49	±5	2023/10/26
1900	Head	22.3	1.436	38.697	1.40	40.00	2.57	-3.26	±5	2023/11/3
1900	Head	22.7	1.427	41.191	1.40	40.00	1.93	2.98	±5	2023/11/6
2450	Head	22.4	1.825	39.664	1.80	39.20	1.39	1.18	±5	2023/11/1
2450	Head	22.4	1.843	40.377	1.80	39.20	2.39	3.00	±5	2023/11/5
2450	Head	22.2	1.878	40.464	1.80	39.20	4.33	3.22	±5	2023/11/6
2600	Head	22.3	1.912	38.499	1.96	39.00	-2.45	-1.28	±5	2023/11/2
2600	Head	22.2	1.904	38.499	1.96	39.00	-2.86	-1.28	±5	2023/11/4
2600	Head	22.2	2.056	37.284	1.96	39.00	4.90	-4.40	±5	2023/11/8
5250	Head	22.3	4.803	37.045	4.71	35.95	1.97	3.05	±5	2023/10/28
5250	Head	22.5	4.617	35.683	4.71	35.95	-1.97	-0.74	±5	2023/11/6
5250	Head	22.5	4.595	36.652	4.71	35.95	-2.44	1.95	±5	2023/11/7
5600	Head	22.2	5.238	36.275	5.07	35.50	3.31	2.18	±5	2023/10/29
5600	Head	22.3	4.970	35.188	5.07	35.50	-1.97	-0.88	±5	2023/11/7
5600	Head	22.8	5.125	35.435	5.07	35.50	1.08	-0.18	±5	2023/11/8
5750	Head	22.5	5.413	35.968	5.22	35.35	3.70	1.75	±5	2023/10/29
5750	Head	22.7	5.009	36.365	5.22	35.35	-4.04	2.87	±5	2023/11/7
5750	Head	22.6	5.127	34.965	5.22	35.35	-1.78	-1.09	±5	2023/11/9

11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

<1g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2023/10/22	750	Head	250	1099	3975	715	2.020	8.540	8.08	-5.39
2023/10/31	750	Head	250	1099	7577	360	2.130	8.540	8.52	-0.23
2023/10/31	835	Head	250	4d162	3975	715	2.510	9.640	10.04	4.15
2023/11/1	835	Head	250	4d162	7577	360	2.290	9.640	9.16	-4.98
2023/11/3	835	Head	250	4d162	7641	1664	2.430	9.640	9.72	0.83
2023/10/27	1750	Head	250	1090	3975	715	8.660	37.000	34.64	-6.38
2023/11/2	1750	Head	250	1090	7577	360	8.720	37.000	34.88	-5.73
2023/10/26	1900	Head	250	5d182	3975	715	9.780	39.600	39.12	-1.21
2023/11/3	1900	Head	250	5d182	7577	360	9.230	39.600	36.92	-6.77
2023/11/6	1900	Head	250	5d182	7641	1664	9.370	39.600	37.48	-5.35
2023/11/1	2450	Head	250	1040	7641	1664	12.300	52.700	49.2	-6.64
2023/11/5	2450	Head	250	1040	7577	360	12.700	52.700	50.8	-3.61
2023/11/6	2450	Head	250	1040	3975	715	13.500	52.700	54	2.47
2023/11/2	2600	Head	250	1070	3975	715	14.200	56.200	56.8	1.07
2023/11/4	2600	Head	250	1070	7577	360	13.300	56.200	53.2	-5.34
2023/11/8	2600	Head	250	1070	7641	1664	14.100	56.200	56.4	0.36
2023/10/28	5250	Head	100	1341	3975	715	7.550	80.700	75.5	-6.44
2023/11/6	5250	Head	100	1341	7577	360	7.870	80.700	78.7	-2.48
2023/11/7	5250	Head	100	1341	7641	1664	7.510	80.700	75.1	-6.94
2023/10/29	5600	Head	100	1341	3975	715	7.950	84.500	79.5	-5.92
2023/11/7	5600	Head	100	1341	7577	360	8.150	84.500	81.5	-3.55
2023/11/8	5600	Head	100	1341	7641	1664	7.890	84.500	78.9	-6.63
2023/10/29	5750	Head	100	1341	3975	715	7.950	80.600	79.5	-1.36
2023/11/7	5750	Head	100	1341	7641	1664	7.410	80.600	74.1	-8.06
2023/11/9	5750	Head	100	1341	7577	360	7.760	80.600	77.6	-3.72

<10g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2023/10/22	750	Head	250	1099	3975	715	1.350	5.650	5.4	-4.42
2023/10/31	750	Head	250	1099	7577	360	1.360	5.650	5.44	-3.72
2023/10/31	835	Head	250	4d162	3975	715	1.660	6.260	6.64	6.07
2023/11/1	835	Head	250	4d162	7577	360	1.510	6.260	6.04	-3.51
2023/11/3	835	Head	250	4d162	7641	1664	1.550	6.260	6.2	-0.96
2023/10/27	1750	Head	250	1090	3975	715	4.720	19.500	18.88	-3.18
2023/11/2	1750	Head	250	1090	7577	360	4.750	19.500	19	-2.56
2023/10/26	1900	Head	250	5d182	3975	715	5.170	20.200	20.68	2.38
2023/11/3	1900	Head	250	5d182	7577	360	4.780	20.200	19.12	-5.35
2023/11/6	1900	Head	250	5d182	7641	1664	4.850	20.200	19.4	-3.96
2023/11/1	2450	Head	250	1040	7641	1664	5.700	24.600	22.8	-7.32
2023/11/5	2450	Head	250	1040	7577	360	5.890	24.600	23.56	-4.23
2023/11/6	2450	Head	250	1040	3975	715	6.410	24.600	25.64	4.23
2023/11/2	2600	Head	250	1070	3975	715	6.070	24.600	24.28	-1.30
2023/11/4	2600	Head	250	1070	7577	360	6.090	24.600	24.36	-0.98
2023/11/8	2600	Head	250	1070	7641	1664	6.120	24.600	24.48	-0.49
2023/10/28	5250	Head	100	1341	3975	715	2.230	23.100	22.3	-3.46
2023/11/6	5250	Head	100	1341	7577	360	2.400	23.100	24	3.90
2023/11/7	5250	Head	100	1341	7641	1664	2.150	23.100	21.5	-6.93
2023/10/29	5600	Head	100	1341	3975	715	2.260	24.000	22.6	-5.83
2023/11/7	5600	Head	100	1341	7577	360	2.470	24.000	24.7	2.92
2023/11/8	5600	Head	100	1341	7641	1664	2.250	24.000	22.5	-6.25
2023/10/29	5750	Head	100	1341	3975	715	2.360	22.700	23.6	3.96
2023/11/7	5750	Head	100	1341	7641	1664	2.120	22.700	21.2	-6.61
2023/11/9	5750	Head	100	1341	7577	360	2.350	22.700	23.5	3.52




Fig 10.3.1 System Performance Check Setup

Fig 10.3.2 Setup Photo

12. RF Exposure Positions

12.1 Ear and handset reference point

Figure 11.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 11.1.2. The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 11.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 11.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 11.1.1 Front, back, and side views of SAM twin phantom




Fig 11.1.2 Close-up side view of phantom showing the ear region.




Fig 11.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

12.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 11.2.1 and Figure 11.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 11.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 11.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 11.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 11.2.3. The actual rotation angles should be documented in the test report.




Fig 11.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 11.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 11.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

12.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 11.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 11.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

12.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 11.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 11.4 Body Worn Position

12.5 Product Specific 10g SAR Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, that can provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets and support voice calls next to the ear, according to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

12.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.



14. Antenna Location

The detailed antenna location information can refer to SAR Test Setup Photos.

15. Spot Check SAR Test Results

General Note:

- SAR spot check verification on the worst cases from the original model was performed to demonstrate the test data from original model remains representative for the variant model.
- If the 1-g SAR spot check result "does not exceed 30%, but larger than 1.2 W/kg", more spot check on the next-higher exposure position until the spot check result does not exceed 1.2 W/kg. Similarly, if the 10-g SAR spot check result "does not exceed 30%, but larger than 3.0 W/kg", more spot check on the next-higher exposure position until the spot check result does not exceed 3.0 W/kg.
 - When the Spot check SAR results is less than 0.4 W/kg for 1-g SAR and the corresponding 1.0 W/kg for 10-g SAR, while the SAR hot-spot distribution does not change. Due to the low SAR value, even if Spot-check Deviation that are 30% or larger, a full test or the addition of more test data is not required.
 - When the Spot check SAR results is far less than reference model test report, while the SAR hot-spot distribution does not change. Due to the SAR value is far less than reference model test report, even if Spot-check Deviation that are 30% or larger, a full test or the addition of more test data is not required.
- The Spot check results showed that Deviation of the SAR results did not exceed 30%, therefore referring to the guidance in the KDB inquiry, SAR data reuse is justified.
- 1st as parent model, 2nd as variant model.

15.1 Head SAR

Plot No.	Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Deviation
750MHz																						
	1st	LTE Band 13	0M	QPSK	1	25	-	Right Cheek	0mm	DSI2	23230	782	1	22.91	24.00	1.285	-	-	0.15	0.351	0.451	-28%
01	2nd	LTE Band 13	10M	QPSK	1	25	-	Right Cheek	0mm	DSI2	23230	782	1	22.91	24.00	1.285	-	-	-0.11	0.254	0.326	
835MHz																						
	1st	GSM850	-	-	-	-	GPRS (2 Tx slots)	Right Cheek	0mm	DSI2	189	836.4	1	30.38	31.50	1.294	-	-	-0.03	0.454	0.588	-28%
02	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Right Cheek	0mm	DSI2	189	836.4	1	30.38	31.50	1.294	-	-	-0.18	0.326	0.422	
	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Right Cheek	0mm	DSI2	189	836.4	2	30.38	31.50	1.294	-	-	0.05	0.315	0.408	
	1st	WCDMA V	-	-	-	-	RMC 12.2Kbps	Right Cheek	0mm	DSI2	4182	836.4	1	22.95	24.00	1.274	-	-	0.08	0.416	30	-27%
03	2nd	WCDMA V	-	-	-	-	RMC 12.2Kbps	Right Cheek	0mm	DSI2	4182	836.4	1	22.95	24.00	1.274	-	-	-0.12	0.302	0.385	
	1st	LTE Band 26	15M	QPSK	1	37	-	Right Cheek	0mm	DSI2	26865	831.5	1	22.92	24.00	1.282	-	-	0.1	0.361	0.463	-19%
04	2nd	LTE Band 26	15M	QPSK	1	37	-	Right Cheek	0mm	DSI2	26865	831.5	1	22.92	24.00	1.282	-	-	-0.14	0.292	0.374	
1750MHz																						
	1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Right Cheek	0mm	DSI2	1413	1732.6	1	23.12	24.00	1.225	-	-	0.12	0.313	0.383	-3%
05	2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Right Cheek	0mm	DSI2	1413	1732.6	1	23.12	24.00	1.225	-	-	-0.13	0.304	0.372	
	1st	LTE Band 66	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	132322	1745	1	23.12	24.00	1.225	-	-	0.06	0.268	0.328	-2%
06	2nd	LTE Band 66	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	132322	1745	1	23.12	24.00	1.225	-	-	0.03	0.262	0.321	
1900MHz																						
	1st	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Right Cheek	0mm	DSI2	512	1850.2	1	27.55	28.50	1.245	-	-	0.06	0.192	0.239	28%
07	2nd	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Right Cheek	0mm	DSI2	512	1850.2	1	27.55	28.50	1.245	-	-	-0.17	0.247	0.307	
	1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Right Cheek	0mm	DSI2	9400	1880	1	23.30	24.00	1.175	-	-	0.03	0.276	0.324	20%
08	2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Right Cheek	0mm	DSI2	9400	1880	1	23.30	24.00	1.175	-	-	-0.04	0.331	0.389	
	2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Right Cheek	0mm	DSI2	9400	1880	2	23.30	24.00	1.175	-	-	-0.13	0.244	0.287	
		LTE Band 2	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	18900	1880	1	23.00	24.00	1.259	-	-	-0.05	0.255	0.321	16%
09		LTE Band 2	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	18900	1880	1	23.00	24.00	1.259	-	-	-0.08	0.295	0.371	
2600MHz																						
	1st	LTE Band 7	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	21100	2535	1	22.99	24.00	1.262		1.000	-0.06	0.158	0.199	23%
10	2nd	LTE Band 7	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	21100	2535	1	22.99	24.00	1.262		1.000	0.09	0.194	0.245	
	1st	LTE Band 38	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	38000	2595	1	23.03	24.00	1.250	62.9	1.006	0.04	0.069	0.087	25%
11	2nd	LTE Band 38	20M	QPSK	1	49	-	Right Cheek	0mm	DSI2	38000	2595	1	23.03	24.00	1.250	62.9	1.006	-0.05	0.087	0.109	



FCC SAR Test Report

Report No. : FA3O1717-01

Plot No.	Plot No.	Band	Mode	Test Position	Gap (mm)	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Deviation
2450MHz																		
	1st	Bluetooth	DH5 1Mbps	Left Cheek	0mm	Full	39	2441	1	10.90	12.00	1.288	76.8	1.302	0.07	0.174	0.292	-28%
12	2nd	Bluetooth	DH5 1Mbps	Left Cheek	0mm	Full	39	2441	1	10.90	12.00	1.288	76.8	1.302	0.16	0.125	0.210	
	1st	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Receiver on	6	2437	1	14.90	16.00	1.288	100	1.000	0.15	0.905	1.166	-10%
13	2nd	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Receiver on	6	2437	1	14.90	16.00	1.288	100	1.000	0.04	0.811	1.045	
	2nd	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Receiver on	6	2437	2	14.90	16.00	1.288	100	1.000	-0.18	0.661	0.852	
WLAN5GHz																		
	1st	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	0mm	Receiver on	54	5270	1	16.19	18.00	1.517	93.53	1.069	-0.02	0.709	1.150	-8%
14	2nd	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	0mm	Receiver on	54	5270	1	16.19	18.00	1.517	93.53	1.069	0.06	0.650	1.054	
	1st	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Receiver on	122	5610	1	14.05	15.50	1.396	87.8	1.139	-0.12	0.693	1.102	2%
15	2nd	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Receiver on	122	5610	1	14.05	15.50	1.396	87.8	1.139	0.07	0.709	1.128	
	1st	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Receiver on	155	5775	1	13.32	15.00	1.472	87.8	1.139	0.02	0.604	1.013	14%
16	2nd	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Receiver on	155	5775	1	13.32	15.00	1.472	87.8	1.139	0.06	0.690	1.157	
	2nd	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Receiver on	155	5775	2	13.32	15.00	1.472	87.8	1.139	0.05	0.551	0.924	



15.2 Hotspot SAR

Plot	Plot	Band	BW	Modulation	RB	RB	Mode	Test	Gap	Power	Ch.	Freq.	Sample	Average	Tune-Up	Tune-up	Duty	Duty	Power	Measured	Reported	Deviation
No.	No.		(MHz)		Size	offset		Position	(mm)	State		(MHz)		Power	Limit	Scaling	Cycle	Cycle	Drift	1g SAR	1g SAR	
														(dBm)	(dBm)	Factor	%	Scaling	(dB)	(W/kg)	(W/kg)	
750MHz																						
	1st	LTE Band 13	10M	QPSK	1	25	-	Back	5mm	DSI3	23230	782	1	22.91	24.00	1.285	-	-	-0.07	1.110	1.427	-19%
17	2nd	LTE Band 13	10M	QPSK	1	25	-	Back	5mm	DSI3	23230	782	1	22.91	24.00	1.285	-	-	-0.16	0.904	1.162	
835MHz																						
	1st	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm	DSI3	251	848.8	1	27.81	29.00	1.315	-	-	0.09	1.090	1.434	-18%
18	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm	DSI3	251	848.8	1	27.81	29.00	1.315	-	-	0.16	0.893	1.174	
	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm	DSI3	251	848.8	2	27.81	29.00	1.315	-	-	-0.09	0.790	1.039	
	1st	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	DSI3	4233	846.6	1	21.37	22.50	1.297	-	-	0.03	1.100	1.427	-20%
19	2nd	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	DSI3	4233	846.6	1	21.37	22.50	1.297	-	-	-0.19	0.875	1.135	
	1st	LTE Band 26	15M	QPSK	1	37	-	Back	5mm	DSI3	26865	831.5	1	21.87	23.00	1.297	-	-	0.06	1.040	1.349	-22%
20	2nd	LTE Band 26	15M	QPSK	1	37	-	Back	5mm	DSI3	26865	831.5	1	21.87	23.00	1.297	-	-	0.06	0.810	1.051	
1750MHz																						
	1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	5mm	DSI3	1312	1712.4	1	15.39	16.50	1.291	-	-	0.14	1.090	1.407	-68%
21	2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	5mm	DSI3	1312	1712.4	1	15.39	16.50	1.291	-	-	0.04	0.347	0.448	
	1st	LTE Band 66	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	132072	1720	1	15.70	16.50	1.202	-	-	-0.15	1.170	1.407	-39%
22	2nd	LTE Band 66	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	132072	1720	1	15.70	16.50	1.202	-	-	0.18	0.718	0.863	
1900MHz																						
	1st	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Bottom side	5mm	DSI7	661	1880	1	17.32	18.50	1.312	-	-	0.05	1.090	1.430	-41%
23	2nd	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Bottom side	5mm	DSI7	661	1880	1	17.32	18.50	1.312	-	-	0.1	0.641	0.841	
	1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	DSI3	9262	1852.4	1	14.32	15.50	1.312	-	-	-0.09	1.050	1.378	-61%
24	2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	DSI3	9262	1852.4	1	14.32	15.50	1.312	-	-	-0.13	0.410	0.538	
	1st	LTE Band 2	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	18700	1860	1	13.78	15.00	1.324	-	-	-0.12	1.060	1.404	-38%
25	2nd	LTE Band 2	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	18700	1860	1	13.78	15.00	1.324	-	-	0.13	0.661	0.875	
	2nd	LTE Band 2	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	18700	1860	2	13.78	15.00	1.324	-	-	0.01	0.655	0.867	
2600MHz																						
	1st	LTE Band 7	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	20850	2510	1	11.27	12.50	1.327	-	-	0.07	1.040	1.380	4%
26	2nd	LTE Band 7	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	20850	2510	1	11.27	12.50	1.327	-	-	0.06	1.080	1.434	
	2nd	LTE Band 7	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	20850	2510	2	11.27	12.50	1.327	-	-	0.14	0.832	1.104	
	1st	LTE Band 7	20M	QPSK	1	49	-	Back	5mm	DSI3	21100	2535	1	12.50	13.50	1.259	-	-	0.12	1.030	1.297	6%
	2nd	LTE Band 7	20M	QPSK	1	49	-	Back	5mm	DSI3	21100	2535	1	12.50	13.50	1.259	-	-	-0.1	1.090	1.372	
	1st	LTE Band 7	20M	QPSK	1	49	-	Front	5mm	DSI3	21100	2535	1	12.50	13.50	1.259	-	-	0.18	0.448	0.564	12%
	2nd	LTE Band 7	20M	QPSK	1	49	-	Front	5mm	DSI3	21100	2535	1	12.50	13.50	1.259	-	-	0.04	0.502	0.632	
	1st	LTE Band 38	20M	QPSK	1	49	-	Back	5mm	DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	0.15	1.070	1.377	-5%
27	2nd	LTE Band 38	20M	QPSK	1	49	-	Back	5mm	DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	-0.07	1.020	1.313	
	1st	LTE Band 38	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	38000	2595	1	13.47	14.50	1.268	62.9	1.006	-0.11	1.070	1.365	-6%
	2nd	LTE Band 38	20M	QPSK	1	49	-	Bottom side	5mm	DSI7	38000	2595	1	13.47	14.50	1.268	62.9	1.006	-0.1	1.010	1.288	
	1st	LTE Band 38	20M	QPSK	1	49	-	Front	5mm	DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	-0.04	0.552	0.710	-3%
	2nd	LTE Band 38	20M	QPSK	1	49	-	Front	5mm	DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	0.07	0.533	0.686	



Plot No.	Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Deviation
2450MHz																						
	1st	Bluetooth	-	-	-	-	DH5 1Mbps	Back	5mm	Full	39	2441	1	10.90	12.00	1.288	76.8	1.302	0.03	0.125	0.210	-27%
28	2nd	Bluetooth	-	-	-	-	DH5 1Mbps	Back	5mm	Full	39	2441	1	10.90	12.00	1.288	76.8	1.302	0.01	0.091	0.153	
	1st	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Back	5mm	Reduced	6	2437	1	16.40	17.50	1.288	100	1.000	-0.11	0.893	1.150	-26%
29	2nd	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Back	5mm	Reduced	6	2437	1	16.40	17.50	1.288	100	1.000	-0.02	0.659	0.849	
WLAN5GHz																						
	1st	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	42	5210	1	12.70	14.50	1.514	87.8	1.139	0.16	0.599	1.033	10%
30	2nd	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	42	5210	1	12.70	14.50	1.514	87.8	1.139	-0.14	0.660	1.138	
	2nd	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	42	5210	2	12.70	14.50	1.514	87.8	1.139	0.04	0.511	0.881	
	1st	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Top Side	5mm	Reduced	155	5775	1	11.33	13.00	1.469	87.8	1.139	0.03	0.693	1.159	-9%
31	2nd	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Top Side	5mm	Reduced	155	5775	1	11.33	13.00	1.469	87.8	1.139	0.16	0.629	1.052	



15.3 Body Worn Accessory SAR

Plot No.	No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Headset	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Deviation
750MHz																							
	1st	LTE Band 13	10M	QPSK	1	25		Back	5mm		DSI3	23230	782	1	22.91	24.00	1.285		1.000	-0.07	1.110	1.427	-19%
32	2nd	LTE Band 13	10M	QPSK	1	25		Back	5mm		DSI3	23230	782	1	22.91	24.00	1.285		1.000	-0.16	0.904	1.162	
835MHz																							
	1st	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm		DSI3	251	848.8	1	27.81	29.00	1.315		1.000	0.09	1.090	1.434	-18%
33	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm		DSI3	251	848.8	1	27.81	29.00	1.315		1.000	0.16	0.893	1.174	
	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm		DSI3	251	848.8	2	27.81	29.00	1.315		1.000	-0.09	0.790	1.039	
	1st	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm		DSI3	4233	846.6	1	21.37	22.50	1.297		1.000	0.03	1.100	1.427	-20%
34	2nd	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm		DSI3	4233	846.6	1	21.37	22.50	1.297		1.000	-0.19	0.875	1.135	
	1st	LTE Band 26	15M	QPSK	1	37		Back	5mm		DSI3	26865	831.5	1	21.87	23.00	1.297		1.000	0.06	1.040	1.349	-22%
35	2nd	LTE Band 26	15M	QPSK	1	37		Back	5mm		DSI3	26865	831.5	1	21.87	23.00	1.297		1.000	0.06	0.810	1.051	
1750MHz																							
	1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	5mm		DSI3	1312	1712.4	1	15.39	16.50	1.291		1.000	0.14	1.090	1.407	-68%
36	2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	5mm		DSI3	1312	1712.4	1	15.39	16.50	1.291		1.000	0.04	0.347	0.448	
	1st	LTE Band 66	20M	QPSK	1	49		Back	5mm		DSI3	132072	1720	1	16.75	17.50	1.189		1.000	0.13	1.170	1.391	-62%
37	2nd	LTE Band 66	20M	QPSK	1	49		Back	5mm		DSI3	132072	1720	1	16.75	17.50	1.189		1.000	-0.1	0.443	0.527	
1900MHz																							
	1st	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Back	5mm		DSI3	661	1880	1	17.32	18.50	1.312		1.000	0.14	0.988	1.296	-68%
38	2nd	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Back	5mm		DSI3	661	1880	1	17.32	18.50	1.312		1.000	-0.15	0.319	0.419	
	1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm		DSI3	9262	1852.4	1	14.32	15.50	1.312		1.000	-0.09	1.050	1.378	-61%
39	2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm		DSI3	9262	1852.4	1	14.32	15.50	1.312		1.000	-0.13	0.410	0.538	
	1st	LTE Band 2	20M	QPSK	1	49		Back	5mm		DSI3	18700	1860	1	14.91	16.00	1.285		1.000	-0.14	1.080	1.388	-59%
40	2nd	LTE Band 2	20M	QPSK	1	49		Back	5mm		DSI3	18700	1860	1	14.91	16.00	1.285		1.000	0.15	0.439	0.564	
	2nd	LTE Band 2	20M	QPSK	1	49		Back	5mm		DSI3	18700	1860	2	14.91	16.00	1.285		1.000	0.08	0.417	0.536	
2600MHz																							
	1st	LTE Band 7	20M	QPSK	1	49		Back	5mm		DSI3	21100	2535	1	12.50	13.50	1.259		1.000	0.12	1.030	1.297	6%
41	2nd	LTE Band 7	20M	QPSK	1	49		Back	5mm		DSI3	21100	2535	1	12.50	13.50	1.259		1.000	-0.1	1.090	1.372	
	2nd	LTE Band 7	20M	QPSK	1	49		Back	5mm		DSI3	21100	2535	2	12.50	13.50	1.259		1.000	0.03	0.811	1.021	
	1st	LTE Band 7	20M	QPSK	1	49		Back	5mm	Headset	DSI3	21100	2535	1	12.50	13.50	1.259		1.000	0.09	1.010	1.272	-3%
	2nd	LTE Band 7	20M	QPSK	1	49		Back	5mm	Headset	DSI3	21100	2535	1	12.50	13.50	1.259		1.000	0.05	0.978	1.231	
	1st	LTE Band 7	20M	QPSK	1	49		Front	5mm		DSI3	21100	2535	1	12.50	13.50	1.259		1.000	0.18	0.448	0.564	12%
	2nd	LTE Band 7	20M	QPSK	1	49		Front	5mm		DSI3	21100	2535	1	12.50	13.50	1.259		1.000	0.04	0.502	0.632	
	1st	LTE Band 38	20M	QPSK	1	49		Back	5mm		DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	0.15	1.070	1.377	-5%
42	2nd	LTE Band 38	20M	QPSK	1	49		Back	5mm		DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	-0.07	1.020	1.313	
	1st	LTE Band 38	20M	QPSK	1	49		Back	5mm	Headset	DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	0.09	1.050	1.351	-5%
	2nd	LTE Band 38	20M	QPSK	1	49		Back	5mm	Headset	DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	0.08	1.000	1.287	
	1st	LTE Band 38	20M	QPSK	1	49		Front	5mm		DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	-0.04	0.552	0.710	-3%
	2nd	LTE Band 38	20M	QPSK	1	49		Front	5mm		DSI3	38000	2595	1	14.43	15.50	1.279	62.9	1.006	0.07	0.533	0.686	



FCC SAR Test Report

Report No. : FA3O1717-01

Plot No.	Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Deviation
2450MHz																			
	1st	Bluetooth	DH5 1Mbps	Back	5mm		Full	39	2441	1	10.90	12.00	1.288	76.8	1.302	0.03	0.125	0.210	
43	2nd	Bluetooth	DH5 1Mbps	Back	5mm		Full	39	2441	1	10.90	12.00	1.288	76.8	1.302	0.01	0.091	0.153	-27%
	1st	WLAN2.4GHz	802.11b 1Mbps	Back	5mm		Reduced	6	2437	1	16.40	17.50	1.288	100	1.000	-0.11	0.893	1.150	
44	2nd	WLAN2.4GHz	802.11b 1Mbps	Back	5mm		Reduced	6	2437	1	16.40	17.50	1.288	100	1.000	-0.02	0.659	0.849	-26%
WLAN5GHz																			
		WLAN5.3GHz	802.11ac-VHT80 MCS0	Back	5mm		Reduced	58	5290	1	12.11	14.00	1.545	87.8	1.139	0.04	0.633	1.114	
45		WLAN5.3GHz	802.11ac-VHT80 MCS0	Back	5mm		Reduced	58	5290	1	12.11	14.00	1.545	87.8	1.139	0.1	0.574	1.010	-9%
	1st	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm		Reduced	122	5610	1	11.55	13.50	1.567	87.8	1.139	0.12	0.662	1.181	
46	2nd	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm		Reduced	122	5610	1	11.55	13.50	1.567	87.8	1.139	-0.15	0.646	1.153	-2%
	2nd	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm		Reduced	122	5610	2	11.55	13.50	1.567	87.8	1.139	0.19	0.531	0.948	
	1st	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm		Reduced	155	5775	1	11.85	13.50	1.462	87.8	1.139	-0.06	0.659	1.098	
47	2nd	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm		Reduced	155	5775	1	11.85	13.50	1.462	87.8	1.139	0.18	0.646	1.076	-2%

15.4 Product specific 10g SAR

Plot No.	Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)	Deviation
750MHz																						
	1st	LTE Band 13	10M	QPSK	1	25	-	Back	0mm	DS16	23230	782	1	22.91	24.00	1.285	-	-	0.03	1.690	2.172	-14%
48	2nd	LTE Band 13	10M	QPSK	1	25	-	Back	0mm	DS16	23230	782	1	22.91	24.00	1.285	-	-	0.01	1.460	1.877	
835MHz																						
	1st	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	0mm	DS16	128	824.2	1	30.29	31.50	1.321	-	-	-0.05	2.620	3.462	-19%
49	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	0mm	DS16	128	824.2	1	30.29	31.50	1.321	-	-	-0.05	2.130	2.814	
	2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	0mm	DS16	128	824.2	2	30.29	31.50	1.321	-	-	0.02	1.890	2.497	
	1st	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	DS16	4132	826.4	1	22.90	24.00	1.288	-	-	-0.09	2.030	2.615	-7%
50	2nd	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	DS16	4132	826.4	1	22.90	24.00	1.288	-	-	0.05	1.890	2.435	
	1st	LTE Band 26	15M	QPSK	1	37	-	Back	0mm	DS16	26865	831.5	1	22.92	24.00	1.282	-	-	0.16	1.920	2.462	-3%
51	2nd	LTE Band 26	15M	QPSK	1	37	-	Back	0mm	DS16	26865	831.5	1	22.92	24.00	1.282	-	-	0.05	1.870	2.398	
1750MHz																						
	1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Bottom side	0mm	DS16	1312	1712.4	1	19.67	20.50	1.211	-	-	0.07	2.900	3.511	-12%
52	2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Bottom side	0mm	DS16	1312	1712.4	1	19.67	20.50	1.211	-	-	-0.18	2.550	3.087	
	1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	0mm	DS16	1312	1712.4	1	19.67	20.50	1.211	-	-	0.09	2.010	2.433	-7%
	2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	0mm	DS16	1312	1712.4	1	19.67	20.50	1.211	-	-	0.04	1.870	2.264	
	1st	LTE Band 66	20M	QPSK	1	49	-	Bottom side	0mm	DS16	132072	1720	1	19.95	21.00	1.274	-	-	0.04	2.740	3.489	-7%
53	2nd	LTE Band 66	20M	QPSK	1	49	-	Bottom side	0mm	DS16	132072	1720	1	19.95	21.00	1.274	-	-	-0.17	2.550	3.247	
	2nd	LTE Band 66	20M	QPSK	1	49	-	Bottom side	0mm	DS16	132072	1720	2	19.95	21.00	1.274	-	-	0.04	2.050	2.611	
	1st	LTE Band 66	20M	QPSK	1	49	-	Back	0mm	DS16	132072	1720	1	19.95	21.00	1.274	-	-	-0.07	1.990	2.534	-10%
	2nd	LTE Band 66	20M	QPSK	1	49	-	Back	0mm	DS16	132072	1720	1	19.95	21.00	1.274	-	-	0.05	1.800	2.292	
1900MHz																						
	1st	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Bottom side	0mm	DS16	661	1880	1	24.29	25.50	1.321	-	-	0.05	2.710	3.581	-15%
54	2nd	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Bottom side	0mm	DS16	661	1880	1	24.29	25.50	1.321	-	-	-0.02	2.300	3.039	
	1st	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Back	0mm	DS16	661	1880	1	24.29	25.50	1.321	-	-	0.09	2.260	2.986	-17%
	2nd	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Back	0mm	DS16	661	1880	1	24.29	25.50	1.321	-	-	0.09	1.880	2.484	
	1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom side	0mm	DS16	9262	1852.4	1	18.77	20.00	1.327	-	-	0.05	2.690	3.571	-15%
55	2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom side	0mm	DS16	9262	1852.4	1	18.77	20.00	1.327	-	-	-0.08	2.300	3.053	
	1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	0mm	DS16	9262	1852.4	1	18.77	20.00	1.327	-	-	-0.19	2.360	3.133	-12%
	2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	0mm	DS16	9262	1852.4	1	18.77	20.00	1.327	-	-	0.08	2.080	2.761	
	1st	LTE Band 2	20M	QPSK	1	49	-	Bottom side	0mm	DS16	18700	1860	1	18.74	20.00	1.337	-	-	0.12	2.520	3.368	-14%
56	2nd	LTE Band 2	20M	QPSK	1	49	-	Bottom side	0mm	DS16	18700	1860	1	18.74	20.00	1.337	-	-	-0.13	2.160	2.887	
2600MHz																						
	1st	LTE Band 7	20M	QPSK	1	49	-	Back	0mm	DS16	20850	2510	1	17.39	18.50	1.291	-	-	-0.01	2.420	3.125	9%
57	2nd	LTE Band 7	20M	QPSK	1	49	-	Back	0mm	DS16	20850	2510	1	17.39	18.50	1.291	-	-	-0.11	2.630	3.396	
	1st	LTE Band 7	20M	QPSK	1	49	-	Front	0mm	DS16	21100	2535	1	17.47	18.50	1.268	-	-	0.14	1.290	1.635	3%
	2nd	LTE Band 7	20M	QPSK	1	49	-	Front	0mm	DS16	21100	2535	1	17.47	18.50	1.268	-	-	0.01	1.330	1.686	
	1st	LTE Band 38	20M	QPSK	1	49	-	Back	0mm	DS16	38000	2595	1	19.95	21.00	1.274	62.9	1.006	0.18	2.630	3.369	5%
58	2nd	LTE Band 38	20M	QPSK	1	49	-	Back	0mm	DS16	38000	2595	1	19.95	21.00	1.274	62.9	1.006	0.09	2.750	3.523	
	2nd	LTE Band 38	20M	QPSK	1	49	-	Back	0mm	DS16	38000	2595	2	19.95	21.00	1.274	62.9	1.006	-0.05	1.680	2.152	
	1st	LTE Band 38	20M	QPSK	1	49	-	Front	0mm	DS16	38000	2595	1	19.95	21.00	1.274	62.9	1.006	-0.12	1.470	1.883	5%
	2nd	LTE Band 38	20M	QPSK	1	49	-	Front	0mm	DS16	38000	2595	1	19.95	21.00	1.274	62.9	1.006	0.04	1.550	1.986	



FCC SAR Test Report

Report No. : FA3O1717-01

Plot No.	Plot No.	Band	Mode	Test Position	Gap (mm)	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)	Deviation
2450MHz																		
	1st	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Full	1	2412	1	19.10	20.00	1.230	100	1.000	0.09	1.300	1.599	-6%
59	2nd	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Full	1	2412	1	19.10	20.00	1.230	100	1.000	0.04	1.220	1.501	
WLAN5GHz																		
	1st	WLAN5.2GHz	802.11a 6Mbps	Back	0mm	Full	48	5240	1	17.83	19.50	1.468	96.53	1.036	-0.12	1.450	2.205	14%
60	2nd	WLAN5.2GHz	802.11a 6Mbps	Back	0mm	Full	48	5240	1	17.83	19.50	1.468	96.53	1.036	0.05	1.650	2.509	
	1st	WLAN5.3GHz	802.11a 6Mbps	Back	0mm	Full	60	5300	1	17.74	19.50	1.500	96.53	1.036	0.13	1.570	2.439	17%
61	2nd	WLAN5.3GHz	802.11a 6Mbps	Back	0mm	Full	60	5300	1	17.74	19.50	1.500	96.53	1.036	-0.12	1.840	2.859	
	2nd	WLAN5.3GHz	802.11a 6Mbps	Back	0mm	Full	60	5300	2	17.74	19.50	1.500	96.53	1.036	-0.12	1.530	2.377	17%
	1st	WLAN5.5GHz	802.11a 6Mbps	Back	0mm	Full	116	5580	1	17.71	19.50	1.510	96.53	1.036	0.07	1.560	2.441	
62	2nd	WLAN5.5GHz	802.11a 6Mbps	Back	0mm	Full	116	5580	1	17.71	19.50	1.510	96.53	1.036	0.07	1.820	2.847	
	1st	WLAN5.8GHz	802.11a 6Mbps	Back	0mm	Full	149	5745	1	17.82	19.00	1.311	96.53	1.036	0.05	1.480	2.010	28%
63	2nd	WLAN5.8GHz	802.11a 6Mbps	Back	0mm	Full	149	5745	1	17.82	19.00	1.311	96.53	1.036	0.15	1.900	2.581	

15.5 Repeated SAR Measurement

<1g>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Left Cheek	0mm	Receiver on	6	2437	1	14.90	16.00	1.288	100	1.000	0.04	0.811	1	1.045
2nd	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Left Cheek	0mm	Receiver on	6	2437	1	14.90	16.00	1.288	100	1.000	0.02	0.802	1.011	1.033
1st	LTE Band 13	10M	QPSK	1	25	-	Back	5mm	DSI3	23230	782	1	22.91	24.00	1.285	-	-	-0.16	0.904	1	1.162
2nd	LTE Band 13	10M	QPSK	1	25	-	Back	5mm	DSI3	23230	782	1	22.91	24.00	1.285	-	-	-0.15	0.892	1.013	1.146
1st	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm	DSI3	251	848.8	1	27.81	29.00	1.315	-	-	0.16	0.893	1	1.174
2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	5mm	DSI3	251	848.8	1	27.81	29.00	1.315	-	-	0.17	0.882	1.012	1.160
1st	LTE Band 7	20M	QPSK	1	49	-	Back	5mm	DSI3	21100	2535	1	12.50	13.50	1.259	-	-	-0.1	1.090	1	1.372
2nd	LTE Band 7	20M	QPSK	1	49	-	Back	5mm	DSI3	21100	2535	1	12.50	13.50	1.259	-	-	0.07	1.050	1.038	1.322

<10g>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power State	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	0mm	DSI6	128	824.2	1	30.29	31.50	1.321	-	-	-0.05	2.130	1	2.814
2nd	GSM850	-	-	-	-	GPRS (2 Tx slots)	Back	0mm	DSI6	128	824.2	1	30.29	31.50	1.321	-	-	-0.02	2.100	1.014	2.775
1st	LTE Band 66	20M	QPSK	1	49	-	Bottom side	0mm	DSI6	132072	1720	1	19.95	21.00	1.274	-	-	-0.17	2.550	1	3.247
2nd	LTE Band 66	20M	QPSK	1	49	-	Bottom side	0mm	DSI6	132072	1720	1	19.95	21.00	1.274	-	-	-0.15	2.510	1.016	3.196
1st	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Bottom side	0mm	DSI6	661	1880	1	24.29	25.50	1.321	-	-	-0.02	2.300	1	3.039
2nd	GSM1900	-	-	-	-	GPRS (2 Tx slots)	Bottom side	0mm	DSI6	661	1880	1	24.29	25.50	1.321	-	-	-0.01	2.260	1.018	2.986
1st	LTE Band 38	20M	QPSK	1	49	-	Back	0mm	DSI6	38000	2595	1	19.95	21.00	1.274	62.9	1.006	0.09	2.750	1	3.523
2nd	LTE Band 38	20M	QPSK	1	49	-	Back	0mm	DSI6	38000	2595	1	19.95	21.00	1.274	62.9	1.006	0.1	2.720	1.011	3.485

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The ratio is the difference in percentage between original and repeated *measured SAR*.
5. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Mobile Cellular Phone			
		Head	Body	Hotspot	Product specific 10g SAR
1.	WWAN + WLAN2.4GHz	Yes	Yes	Yes	Yes
2.	WWAN + WLAN5GHz	Yes	Yes	Yes	Yes
3.	WWAN + Bluetooth	Yes	Yes	Yes	Yes
4.	WLAN 5GHz + Bluetooth	Yes	Yes	Yes	Yes
5.	WWAN + WLAN 5GHz + Bluetooth	Yes	Yes	Yes	Yes

General Note:

1. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), and LTE supports VoLTE function.
2. EUT will choose each GSM, WCDMA and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. This device WLAN 2.4GHz supports hotspot operation and Bluetooth support tethering applications.
4. This device 2.4GHz WLAN/ 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WLAN Direct (GC/GO), and 5.3GHz / 5.5GHz supports WLAN Direct (GC only).
5. According to the EUT characteristic, WLAN 5GHz and Bluetooth can transmit simultaneously.
6. According to the EUT characteristic, WLAN 5GHz and WLAN 2.4GHz cannot transmit simultaneously.
7. WLAN 2.4GHz and Bluetooth share the same antenna and they cannot transmit simultaneously.
8. The worst case 5 GHz WLAN SAR for each configuration was used for SAR summation.
9. When stand-alone SAR is not required for a transmitter or antenna, its SAR is considered zero in the SAR summing process to assess Multi-band transmission SAR compliance.
10. The maximum SAR summation is calculated based on the same configuration and test position.
11. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$ for 1g SAR and $SPLSR \leq 0.10$ for 10g SAR, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.
 - v) The SPLSR calculated results please refer to section 16.5.

Conclusion:

- For simultaneously transmission SAR analysis, WLAN/BT SAR values considered which did perform SAR testing on this report, Simultaneous transmission analysis for all WWAN bands and all position are based on max SAR results chosen between the original SAR results (Sporton SAR report no.: FA3O1717) and Spot check results.

16.1 Head Exposure Conditions

WWAN Band	Exposure Position	1	3	4	5	1+3	1+4	1+5
		WWAN	WLAN2.4GHz Ant 5	WLAN5GHz Ant 5	Bluetooth Ant 5	Summed	Summed	Summed
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
LTE Band 13 Ant 0	Right Cheek	0.451	0.277	0.694	0.109	0.73	1.15	0.56
	Right Tilted	0.292	0.311	0.847	0.057	0.60	1.14	0.35
	Left Cheek	0.414	1.166	1.075	0.292	1.58	1.49	0.71
	Left Tilted	0.261	0.453	1.157	0.158	0.71	1.42	0.42
GSM850 Ant 0	Right Cheek	0.588	0.277	0.694	0.109	0.87	1.28	0.70
	Right Tilted	0.252	0.311	0.847	0.057	0.56	1.10	0.31
	Left Cheek	0.405	1.166	1.075	0.292	1.57	1.48	0.70
	Left Tilted	0.251	0.453	1.157	0.158	0.70	1.41	0.41
WCDMA V Ant 0	Right Cheek	0.530	0.277	0.694	0.109	0.81	1.22	0.64
	Right Tilted	0.257	0.311	0.847	0.057	0.57	1.10	0.31
	Left Cheek	0.408	1.166	1.075	0.292	1.57	1.48	0.70
	Left Tilted	0.232	0.453	1.157	0.158	0.69	1.39	0.39
LTE Band 26 Ant 0	Right Cheek	0.463	0.277	0.694	0.109	0.74	1.16	0.57
	Right Tilted	0.263	0.311	0.847	0.057	0.57	1.11	0.32
	Left Cheek	0.405	1.166	1.075	0.292	1.57	1.48	0.70
	Left Tilted	0.185	0.453	1.157	0.158	0.64	1.34	0.34
WCDMA IV Ant 0	Right Cheek	0.383	0.277	0.694	0.109	0.66	1.08	0.49
	Right Tilted	0.192	0.311	0.847	0.057	0.50	1.04	0.25
	Left Cheek	0.282	1.166	1.075	0.292	1.45	1.36	0.57
	Left Tilted	0.196	0.453	1.157	0.158	0.65	1.35	0.35
LTE Band 66 Ant 0	Right Cheek	0.328	0.277	0.694	0.109	0.61	1.02	0.44
	Right Tilted	0.164	0.311	0.847	0.057	0.48	1.01	0.22
	Left Cheek	0.250	1.166	1.075	0.292	1.42	1.33	0.54
	Left Tilted	0.205	0.453	1.157	0.158	0.66	1.36	0.36
GSM1900 Ant 0	Right Cheek	0.307	0.277	0.694	0.109	0.58	1.00	0.42
	Right Tilted	0.107	0.311	0.847	0.057	0.42	0.95	0.16
	Left Cheek	0.116	1.166	1.075	0.292	1.28	1.19	0.41
	Left Tilted	0.103	0.453	1.157	0.158	0.56	1.26	0.26
WCDMA II Ant 0	Right Cheek	0.389	0.277	0.694	0.109	0.67	1.08	0.50
	Right Tilted	0.192	0.311	0.847	0.057	0.50	1.04	0.25
	Left Cheek	0.199	1.166	1.075	0.292	1.37	1.27	0.49
	Left Tilted	0.189	0.453	1.157	0.158	0.64	1.35	0.35
LTE Band 2 Ant 0	Right Cheek	0.371	0.277	0.694	0.109	0.65	1.07	0.48
	Right Tilted	0.159	0.311	0.847	0.057	0.47	1.01	0.22
	Left Cheek	0.189	1.166	1.075	0.292	1.36	1.26	0.48
	Left Tilted	0.215	0.453	1.157	0.158	0.67	1.37	0.37
LTE Band 7 Ant 0	Right Cheek	0.245	0.277	0.694	0.109	0.52	0.94	0.35
	Right Tilted	0.048	0.311	0.847	0.057	0.36	0.90	0.11
	Left Cheek	0.105	1.166	1.075	0.292	1.27	1.18	0.40
	Left Tilted	0.082	0.453	1.157	0.158	0.54	1.24	0.24
LTE Band 38 Ant 0	Right Cheek	0.109	0.277	0.694	0.109	0.39	0.80	0.22
	Right Tilted	0.063	0.311	0.847	0.057	0.37	0.91	0.12
	Left Cheek	0.045	1.166	1.075	0.292	1.21	1.12	0.34
	Left Tilted	0.025	0.453	1.157	0.158	0.48	1.18	0.18

16.2 Hotspot Exposure Conditions

WWAN Band	Exposure Position	1	3	4	5	1+3	1+4	1+5	Case No
		WWAN 1g SAR (W/kg)	WLAN2.4GHz Ant 5 1g SAR (W/kg)	WLAN5GHz Ant 5 1g SAR (W/kg)	Bluetooth Ant 5 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	
LTE Band 13 Ant 0	Front	0.724	0.534	0.253	0.122	1.26	0.98	0.85	
	Back	1.427	1.150	1.138	0.210	2.58	2.57	1.64	Case1/2/3
	Left side	0.470	0.078	0.088	0.018	0.55	0.56	0.49	
	Right side	0.824	0.559	0.478	0.126	1.38	1.30	0.95	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	0.994				0.99	0.99	0.99	
GSM850 Ant 0	Front	0.707	0.534	0.253	0.122	1.24	0.96	0.83	
	Back	1.434	1.150	1.138	0.210	2.58	2.57	1.64	Case4/5/6
	Left side	0.264	0.078	0.088	0.018	0.34	0.35	0.28	
	Right side	0.542	0.559	0.478	0.126	1.10	1.02	0.67	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	0.703				0.70	0.70	0.70	
WCDMA V Ant 0	Front	0.656	0.534	0.253	0.122	1.19	0.91	0.78	
	Back	1.427	1.150	1.138	0.210	2.58	2.57	1.64	Case7/8/9
	Left side	0.323	0.078	0.088	0.018	0.40	0.41	0.34	
	Right side	0.537	0.559	0.478	0.126	1.10	1.02	0.66	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	0.659				0.66	0.66	0.66	
LTE Band 26 Ant 0	Front	0.719	0.534	0.253	0.122	1.25	0.97	0.84	
	Back	1.349	1.150	1.138	0.210	2.50	2.49	1.56	Case10/11
	Left side	0.383	0.078	0.088	0.018	0.46	0.47	0.40	
	Right side	0.607	0.559	0.478	0.126	1.17	1.09	0.73	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	0.623				0.62	0.62	0.62	
WCDMA IV Ant 0	Front	0.450	0.534	0.253	0.122	0.98	0.70	0.57	
	Back	1.407	1.150	1.138	0.210	2.56	2.55	1.62	Case 12/13/14
	Left side	0.073	0.078	0.088	0.018	0.15	0.16	0.09	
	Right side	0.078	0.559	0.478	0.126	0.64	0.56	0.20	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	1.382				1.38	1.38	1.38	
LTE Band 66 Ant 0	Front	0.385	0.534	0.253	0.122	0.92	0.64	0.51	
	Back	1.391	1.150	1.138	0.210	2.54	2.53	1.60	Case 15/16/17
	Left side	0.095	0.078	0.088	0.018	0.17	0.18	0.11	
	Right side	0.077	0.559	0.478	0.126	0.64	0.56	0.20	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	1.407				1.41	1.41	1.41	
GSM1900 Ant 0	Front	0.493	0.534	0.253	0.122	1.03	0.75	0.62	
	Back	1.296	1.150	1.138	0.210	2.45	2.43	1.51	Case 18/19
	Left side	0.017	0.078	0.088	0.018	0.10	0.11	0.04	
	Right side	0.102	0.559	0.478	0.126	0.66	0.58	0.23	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	1.430				1.43	1.43	1.43	
WCDMA II Ant 0	Front	0.448	0.534	0.253	0.122	0.98	0.70	0.57	
	Back	1.378	1.150	1.138	0.210	2.53	2.52	1.59	Case 20/21
	Left side	0.016	0.078	0.088	0.018	0.09	0.10	0.03	
	Right side	0.083	0.559	0.478	0.126	0.64	0.56	0.21	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	1.345				1.35	1.35	1.35	
LTE Band 2	Front	0.390	0.534	0.253	0.122	0.92	0.64	0.51	

Ant 0	Back	1.388	1.150	1.138	0.210	2.54	2.53	1.60	Case 22/23/24
	Left side	0.056	0.078	0.088	0.018	0.13	0.14	0.07	
	Right side	0.085	0.559	0.478	0.126	0.64	0.56	0.21	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	1.404				1.40	1.40	1.40	
LTE Band 7 Ant 0	Front	0.632	0.534	0.253	0.122	1.17	0.89	0.75	
	Back	1.372	1.150	1.138	0.210	2.52	2.51	1.58	Case 25/26
	Left side	0.035	0.078	0.088	0.018	0.11	0.12	0.05	
	Right side	0.014	0.559	0.478	0.126	0.57	0.49	0.14	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	1.434				1.43	1.43	1.43	
LTE Band 38 Ant 0	Front	0.710	0.534	0.253	0.122	1.24	0.96	0.83	
	Back	1.377	1.150	1.138	0.210	2.53	2.52	1.59	Case 27/28
	Left side	0.028	0.078	0.088	0.018	0.11	0.12	0.05	
	Right side	0.019	0.559	0.478	0.126	0.58	0.50	0.15	
	Top side		0.482	1.159	0.114	0.48	1.16	0.11	
	Bottom side	1.365				1.37	1.37	1.37	



16.3 Body-Worn Accessory Exposure Conditions

WWAN Band	Exposure Position	1	3	4	5	1+3	1+4	1+5	Case No
		WWAN	WLAN2.4GHz Ant 5	WLAN5GHz Ant 5	Bluetooth Ant 5	Summed	Summed	Summed	
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	
LTE Band 13 Ant 0	Front	0.724	0.534	0.285	0.122	1.26	1.01	0.85	
	Back	1.427	1.150	1.181	0.210	2.58	2.61	1.64	Case1/30/3
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.388				1.39	1.39	1.39	
GSM850 Ant 0	Front	0.707	0.534	0.285	0.122	1.24	0.99	0.83	
	Back	1.434	1.150	1.181	0.210	2.58	2.62	1.64	Case4/31/6
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.150				1.15	1.15	1.15	
WCDMA V Ant 0	Front	0.656	0.534	0.285	0.122	1.19	0.94	0.78	
	Back	1.427	1.150	1.181	0.210	2.58	2.61	1.64	Case7/32/9
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.195				1.20	1.20	1.20	
LTE Band 26 Ant 0	Front	0.719	0.534	0.285	0.122	1.25	1.00	0.84	
	Back	1.349	1.150	1.181	0.210	2.50	2.53	1.56	Case10/33
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.284				1.28	1.28	1.28	
WCDMA IV Ant 0	Front	0.450	0.534	0.285	0.122	0.98	0.74	0.57	
	Back	1.407	1.150	1.181	0.210	2.56	2.59	1.62	Case 12/34/14
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.356				1.36	1.36	1.36	
LTE Band 66 Ant 0	Front	0.385	0.534	0.285	0.122	0.92	0.67	0.51	
	Back	1.391	1.150	1.181	0.210	2.54	2.57	1.60	Case 15/35/17
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.367				1.37	1.37	1.37	
GSM1900 Ant 0	Front	0.493	0.534	0.285	0.122	1.03	0.78	0.62	
	Back	1.296	1.150	1.181	0.210	2.45	2.48	1.51	Case 18/36
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.283				1.28	1.28	1.28	
WCDMA II Ant 0	Front	0.448	0.534	0.285	0.122	0.98	0.73	0.57	
	Back	1.378	1.150	1.181	0.210	2.53	2.56	1.59	Case 20/37
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.352				1.35	1.35	1.35	
LTE Band 2 Ant 0	Front	0.390	0.534	0.285	0.122	0.92	0.68	0.51	
	Back	1.388	1.150	1.181	0.210	2.54	2.57	1.60	Case 22/38/24
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.375				1.38	1.38	1.38	
LTE Band 7 Ant 0	Front	0.632	0.534	0.285	0.122	1.17	0.92	0.75	
	Back	1.372	1.150	1.181	0.210	2.52	2.55	1.58	Case 25/39
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.272				1.27	1.27	1.27	
LTE Band 38 Ant 0	Front	0.710	0.534	0.285	0.122	1.24	1.00	0.83	
	Back	1.377	1.150	1.181	0.210	2.53	2.56	1.59	Case 27/40
	Front with Headset					0.00	0.00	0.00	
	Back with Headset	1.351				1.35	1.35	1.35	

Sensor-off

WWAN Band	Exposure Position	1	3	4	1+3	1+4
		WWAN	WLAN2.4GHz Ant 5	WLAN5GHz Ant 5	Summed	Summed
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
GSM850 Ant 0	Front	0.409	0.284	0.265	0.69	0.67
	Back	0.413	0.209	0.861	0.62	1.27
WCDMA V Ant 0	Front	0.364	0.284	0.265	0.65	0.63
	Back	0.373	0.209	0.861	0.58	1.23
LTE Band 26 Ant 0	Front	0.371	0.284	0.265	0.66	0.64
	Back	0.405	0.209	0.861	0.61	1.27
WCDMA IV Ant 0	Front	0.531	0.284	0.265	0.82	0.80
	Back	0.314	0.209	0.861	0.52	1.18
LTE Band 66 Ant 0	Front	0.429	0.284	0.265	0.71	0.69
	Back	0.282	0.209	0.861	0.49	1.14
GSM1900 Ant 0	Front	0.287	0.284	0.265	0.57	0.55
	Back	0.396	0.209	0.861	0.61	1.26
WCDMA II Ant 0	Front	0.701	0.284	0.265	0.99	0.97
	Back	0.533	0.209	0.861	0.74	1.39
LTE Band 2 Ant 0	Front	0.578	0.284	0.265	0.86	0.84
	Back	0.568	0.209	0.861	0.78	1.43
LTE Band 7 Ant 0	Front	0.934	0.284	0.265	1.22	1.20
	Back	0.702	0.209	0.861	0.91	1.56
LTE Band 38 Ant 0	Front	0.571	0.284	0.265	0.86	0.84
	Back	0.337	0.209	0.861	0.55	1.20



16.4 Product specific 10g SAR Exposure Conditions

WWAN Band	Exposure Position	1	3	4	1+3	1+4	Case No
		WWAN	WLAN2.4GHz Ant 5	WLAN5GHz Ant 5	Summed	Summed	
		10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	
LTE Band 13 Ant 0	Front			0.705	0.00	0.71	
	Back	2.172	1.599	2.859	3.77	5.03	Case 41
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side				0.00	0.00	
GSM850 Ant 0	Front			0.705	0.00	0.71	
	Back	3.462	1.599	2.859	5.06	6.32	Case 42/43
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	2.490			2.49	2.49	
WCDMA V Ant 0	Front			0.705	0.00	0.71	
	Back	2.615	1.599	2.859	4.21	5.47	Case 44/45
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side				0.00	0.00	
LTE Band 26 Ant 0	Front			0.705	0.00	0.71	
	Back	2.462	1.599	2.859	4.06	5.32	Case 46/47
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side				0.00	0.00	
WCDMA IV Ant 0	Front	1.211		0.705	1.21	1.92	
	Back	2.433	1.599	2.859	4.03	5.29	Case 48/49
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	3.511			3.51	3.51	
LTE Band 66 Ant 0	Front	1.204		0.705	1.20	1.91	
	Back	2.534	1.599	2.859	4.13	5.39	Case 50/51
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	3.489			3.49	3.49	
GSM1900 Ant 0	Front	1.681		0.705	1.68	2.39	
	Back	2.986	1.599	2.859	4.59	5.85	Case 52/53
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	3.581			3.58	3.58	
WCDMA II Ant 0	Front	1.335		0.705	1.34	2.04	
	Back	3.133	1.599	2.859	4.73	5.99	Case 54/55
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	3.571			3.57	3.57	
LTE Band 2 Ant 0	Front	1.289		0.705	1.29	1.99	
	Back	3.034	1.599	2.859	4.63	5.89	Case 56/57


	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	3.368			3.37	3.37	
LTE Band 7 Ant 0	Front	1.686		0.705	1.69	2.39	
	Back	3.396	1.599	2.859	5.00	6.26	Case 58/59
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	1.200			1.20	1.20	
LTE Band 38 Ant 0	Front	1.986		0.705	1.99	2.69	
	Back	3.523	1.599	2.859	5.12	6.38	Case 60/61
	Left side			0.075	0.00	0.08	
	Right side			1.989	0.00	1.99	
	Top side			2.114	0.00	2.11	
	Bottom side	1.024			1.02	1.02	

16.5 SPLSR Evaluation and Analysis

General Note:

1. When standalone SAR is measured for both antennas in the pair, the peak location separation distance is computed by the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates in the area scans or extrapolated peak SAR locations in the zoom scans, as appropriate.
2. $SPLSR = (SAR_1 + SAR_2)1.5 / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$ for 1g SAR and $SPLSR \leq 0.10$ for 10g SAR, simultaneously transmission SAR measurement is not necessary.

For Hotspot/Body worn



WWAN + WLAN 5GHz/2.4GHz + Bluetooth Back_5mm

For Extremity



WWAN + WLAN 5GHz/2.4GHz Back_0mm



For Hotspot

Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 1	LTE Band 13	Back	1.427	5	-0.018	-0.0795	-0.206	150.4	2.58	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 2	LTE Band 13	Back	1.427	5	-0.018	-0.0795	-0.206	153.9	2.57	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 3	LTE Band 13	Back	1.427	5	-0.018	-0.0795	-0.206	149.9	1.64	0.01	Not required
	Bluetooth		0.21	5	-0.0542	0.066	-0.205				
Case 4	GSM850	Back	1.434	5	-0.022	-0.0815	-0.206	151.5	2.58	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 5	GSM850	Back	1.434	5	-0.022	-0.0815	-0.206	155.2	2.57	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 6	GSM850	Back	1.434	5	-0.022	-0.0815	-0.206	151.0	1.64	0.01	Not required
	Bluetooth		0.21	5	-0.0542	0.066	-0.205				
Case 7	WCDMA V	Back	1.427	5	-0.0185	-0.083	-0.206	153.7	2.58	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 8	WCDMA V	Back	1.427	5	-0.0185	-0.083	-0.206	157.3	2.57	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 9	WCDMA V	Back	1.427	5	-0.0185	-0.083	-0.206	153.2	1.64	0.01	Not required
	Bluetooth		0.21	5	-0.0542	0.066	-0.205				
Case 10	LTE Band 26 Cube 0	Back	1.349	5	-0.0155	-0.0795	-0.206	151.0	2.50	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 11	LTE Band 26 Cube 0	Back	1.349	5	-0.0155	-0.0795	-0.206	154.3	2.49	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 10	LTE Band 26 Cube 1	Back	1.349	5	-0.0325	-0.089	-0.206	157.1	2.50	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 11	LTE Band 26 Cube 1	Back	1.349	5	-0.0325	-0.089	-0.206	161.5	2.49	0.02	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				



Case	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 12	WCDMA IV	Back	1.407	5	-0.038	-0.085	-0.207	152.6	2.56	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 13	WCDMA IV	Back	1.407	5	-0.038	-0.085	-0.207	157.2	2.55	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 14	WCDMA IV	Back	1.407	5	-0.038	-0.085	-0.207	151.9	1.62	0.01	Not required
	Bluetooth		0.21	5	-0.0542	0.066	-0.205				
Case 15	LTE Band 66	Back	1.391	5	-0.0355	-0.085	-0.206	152.8	2.54	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 16	LTE Band 66	Back	1.391	5	-0.0355	-0.085	-0.206	157.3	2.53	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 17	LTE Band 66	Back	1.391	5	-0.0355	-0.085	-0.206	152.2	1.60	0.01	Not required
	Bluetooth		0.21	5	-0.0542	0.066	-0.205				
Case 18	GSM1900	Back	1.296	5	-0.0305	-0.0825	-0.207	151.0	2.45	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 19	GSM1900	Back	1.296	5	-0.0305	-0.0825	-0.207	155.2	2.43	0.02	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 20	WCDMA II	Back	1.378	5	-0.035	-0.0825	-0.206	150.4	2.53	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 21	WCDMA II	Back	1.378	5	-0.035	-0.0825	-0.206	154.8	2.52	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 22	LTE Band 2	Back	1.388	5	-0.0305	-0.0825	-0.206	151.0	2.54	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 23	LTE Band 2	Back	1.388	5	-0.0305	-0.0825	-0.206	155.2	2.53	0.03	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 24	LTE Band 2	Back	1.388	5	-0.0305	-0.0825	-0.206	150.4	1.60	0.01	Not required
	Bluetooth		0.21	5	-0.0542	0.066	-0.205				



Case 25	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 7	Back	1.372	5	-0.0074	-0.0852	-0.205	158.7	2.52	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 26	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 7	Back	1.372	5	-0.0074	-0.0852	-0.205	161.6	2.51	0.02	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				
Case 27	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 38	Back	1.377	5	-0.0062	-0.084	-0.205	157.9	2.53	0.03	Not required
	WLAN2.4GHz		1.15	5	-0.053	0.0668	-0.205				
Case 28	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 38	Back	1.377	5	-0.0062	-0.084	-0.205	160.8	2.52	0.02	Not required
	WLAN5GHz		1.138	5	-0.045	0.072	-0.207				

For Body

Case 30	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 13	Back	1.427	5	-0.018	-0.0795	-0.206	159.8	2.61	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 31	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	GSM850	Back	1.434	5	-0.022	-0.0815	-0.206	161.2	2.62	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 32	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	WCDMA V	Back	1.427	5	-0.0185	-0.083	-0.206	163.2	2.61	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 33	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 26 Cube 0	Back	1.349	5	-0.0155	-0.0795	-0.206	160.2	2.53	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 33	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 26 Cube 1	Back	1.349	5	-0.0325	-0.089	-0.206	167.5	2.53	0.02	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 34	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	WCDMA IV	Back	1.407	5	-0.038	-0.085	-0.207	163.2	2.59	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 35	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	LTE Band 66	Back	1.391	5	-0.0355	-0.085	-0.206	163.3	2.57	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 36	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	GSM1900	Back	1.296	5	-0.0305	-0.0825	-0.207	161.2	2.48	0.02	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 37	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	
	WCDMA II	Back	1.378	5	-0.035	-0.0825	-0.206	160.8	2.56	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 38	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D distance	Summed	SPLSR	Simultaneous SAR
				(mm)	X	Y	Z	(mm)	SAR (W/kg)	Results	

	LTE Band 2	Back	1.388	5	-0.0305	-0.0825	-0.206	161.2	2.57	0.03	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 39	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 7	Back	1.372	5	-0.0074	-0.0852	-0.205	167.5	2.55	0.02	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				
Case 40	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 38	Back	1.377	5	-0.0062	-0.084	-0.205	166.6	2.56	0.02	Not required
	WLAN5GHz		1.181	5	-0.045	0.078	-0.207				

For Extremity

Case 41	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 13 Cube 0	Back	2.172	0	-0.0195	-0.081	-0.206	157.8	5.03	0.07	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 41	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 13 Cube 1	Back	2.172	0	-0.05	-0.081	-0.206	156.2	5.03	0.07	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 42	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM850	Back	3.462	0	-0.0275	-0.08	-0.206	151.6	5.06	0.08	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 43	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM850	Back	3.462	0	-0.0275	-0.08	-0.206	155.8	6.32	0.10	Not required
	WLAN2.4GHz		2.859	0	-0.043	0.075	-0.206				
Case 44	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V Cube 0	Back	2.615	0	-0.0445	-0.0825	-0.206	152.3	4.21	0.06	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 45	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V Cube 0	Back	2.615	0	-0.0445	-0.0825	-0.206	157.5	5.47	0.08	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 44	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V Cube 1	Back	2.615	0	-0.0395	-0.083	-0.206	153.1	4.21	0.06	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 45	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V Cube 1	Back	2.615	0	-0.0395	-0.083	-0.206	158.0	5.47	0.08	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 46	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 26	Back	2.462	0	-0.046	-0.084	-0.206	153.7	4.06	0.05	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 47	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 26	Back	2.462	0	-0.046	-0.084	-0.206	159.0	5.32	0.08	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 48	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Back	2.433	0	-0.03	-0.0855	-0.207	156.6	4.03	0.05	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				



Case 49	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Back	2.433	0	-0.03	-0.0855	-0.207	161.0	5.29	0.08	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 50	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 66	Back	2.534	0	-0.0375	-0.0845	-0.206	154.8	4.13	0.05	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				

Case 51	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 66	Back	2.534	0	-0.0375	-0.0845	-0.206	159.6	5.39	0.08	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 52	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM1900	Back	2.986	0	-0.0355	-0.083	-0.207	153.5	4.59	0.06	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 53	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM1900	Back	2.986	0	-0.0355	-0.083	-0.207	158.2	5.85	0.09	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 54	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II	Back	3.133	0	-0.0345	-0.083	-0.206	153.6	4.73	0.07	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 55	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II	Back	3.133	0	-0.0345	-0.083	-0.206	158.2	5.99	0.09	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 56	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Back	3.034	0	-0.0355	-0.083	-0.206	153.5	4.63	0.06	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 57	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Back	3.034	0	-0.0355	-0.083	-0.206	158.2	5.89	0.09	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 58	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 7	Back	3.396	0	-0.0038	-0.081	-0.205	158.1	5.00	0.07	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 59	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 7	Back	3.396	0	-0.0038	-0.081	-0.205	160.9	6.26	0.10	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				
Case 60	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 38	Back	3.523	0	-0.0038	-0.0792	-0.205	156.4	5.12	0.07	Not required
	WLAN2.4GHz		1.599	0	-0.0518	0.0696	-0.205				
Case 61	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 38	Back	3.523	0	-0.0038	-0.0792	-0.205	159.1	6.38	0.10	Not required
	WLAN5GHz		2.859	0	-0.043	0.075	-0.206				

Test Engineer : Hank Huang, Kevin Xu, David Dai, Bin He

17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [12] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.
- [13] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015

-----THE END-----