

## RF TEST REPORT

**Report Reference No.**..... : **MAX25040119P01-R09RF**

**FCC ID**..... : 2BL3Q-BM103

Compiled by  
( position+printed name+signature)..: Engineer/ Cindy Zheng

Supervised by  
( position+printed name+signature)..: Manager/Haley Wen

Approved by  
( position+printed name+signature)..: RF Manager/ Vivian Jiang

Date of issue..... : May 12, 2025

*Cindy zheng*  
*Haley wen*  
*Vivian Jiang*

**Testing Laboratory Name** ..... : **MAXLAB Testing Co.,Ltd.**

Address..... : 1/F, Building B, Xinshidai GR Park,Shiyan Street, Bao'an District, Shenzhen,Guangdong, 518052, People's Republic of China

**Applicant's name**..... : **SHENZHEN MINGSHIDA COMMUNICATION TECHNOLOGY CO.,LTD**

Address..... : Building D, No. 4 Longshan Industrial Zone, Nanwan Street, Longgang District, Shenzhen

**Test specification**..... :

Standard..... : FCC Part 15.231  
KDB 447498 D01 V06  
ANSI C95.1-2019  
FCC §1.1310

**MAXLAB Testing Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description**..... : **Car keys**

Trade Mark..... : N/A

Manufacturer..... : SHENZHEN MINGSHIDA COMMUNICATION TECHNOLOGY CO.,LTD

Model/Type reference..... : 2BL3Q-BM103

Listed Models ..... : N/A

Ratings..... : DC 3V From Battery

Modulation ..... : ASK

Frequency..... : 315MHz

Result..... : **PASS**

## RF Exposure Evaluation

1. The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [V_f(\text{GHz})] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, 16 where

>  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

> Power and distance are rounded to the nearest mW and mm before calculation

> The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:

a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) : ( $f(\text{MHz})/150$ )] mW, at 100 MHz to 1500 MHz

b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) - 10] mW at  $> 1500$  MHz and  $\leq 6$  GHz

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.

b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $/2$  for test separation distances  $\leq 50$  mm.

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

## 2. CLASSIFICATION

The antenna of this product, under normal use condition, is at less than 20cm away from the body of the user. So, this device is classified as Portable Device.

## EUT Specification

<b>Antenna type:</b>	PCB Antenna
<b>Antenna gain (Max)</b>	2.0 dBi
<b>Evaluation applied</b>	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

### 3. SAR TEST EXCLUSION THRESHOLDS

The measured conducted PK Power

Mode	Frequency(MHz)	Field strength(dBuV/m@3)	EIRP (dBm)
TX	315	70.13	-29.83

Note:

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 109.5$$

EIRP is the equivalent isotropically radiated power, in dBm

$E_{\text{Meas}}$  is the field strength of the emission at the measurement distance, in dBuV/m

$d_{\text{Meas}}$  is the measurement distance, in m

$$\text{EIRP} = E + 20\log(d) - 109.5$$

The tuned conducted PK Power (declared by client)

Mode	Frequency(MHz)	Target Power (dBm)	Tolerance $\pm$ (dBm)
TX	315	-29	1

Frequency (MHz)	Minimum Separation distance (mm)	RF Output power		Result	Limit for 1-g SAR	Verdict
		(dBm)	(mW)			
315	5	-18	0.001585	0.0001779	3.0	Exempt from SAR

### Conclusion

Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.