

FCC 47 CFR MPE REPORT

TCL Entertainment Solutions Limited

2.1 Channel Sound Bar with Wireless Subwoofer,

Model Number: S642W

Additional Model: S210W, S4210, S642WE, S642WK, S642W*
(*can be any numerica number "0~9" or alphebtical number "A~Z")

FCC ID: 2ARUDS210W

| | |
|--------------------------|---|
| Applicant: | TCL Entertainment Solutions Limited |
| Address: | 7/F, building 22E, 22 science park east avenue Hong Kong science |
| | park, SHATIN, N.T. ,Hong Kong, China |
| | |
| Prepared By: | EST Technology Co., Ltd. |
| | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 | |

| | |
|-----------------|-----------------------|
| Report Number: | ESTE-R2302011 |
| Date of Test: | Jan. 07~Feb. 01, 2023 |
| Date of Report: | Feb. 03, 2023 |

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times $ E ^2, H ^2$ or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-10000 | | | 5 | 6 |

(b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times $ E ^2, H ^2$ or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-10000 | | | 1.0 | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) |
|---------------|-----------------|-------------------------|------------------------|
| GFSK | 2402 | 6.28 | 4.246 |
| | 2441 | 5.65 | 3.673 |
| | 2480 | 5.83 | 3.828 |
| $\pi/4$ DQPSK | 2402 | 6.93 | 4.932 |
| | 2441 | 6.27 | 4.236 |
| | 2480 | 6.21 | 4.178 |
| 8-DPSK | 2402 | 6.95 | 4.955 |
| | 2441 | 6.32 | 4.285 |
| | 2480 | 6.35 | 4.315 |
| BLE 1M | 2402 | 5.01 | 3.170 |
| | 2440 | 4.27 | 2.673 |
| | 2480 | 4.38 | 2.742 |
| BLE 2M | 2402 | 5.21 | 3.319 |
| | 2440 | 4.54 | 2.844 |
| | 2480 | 4.68 | 2.938 |

3. Calculated Result and Limit

| Mode | Peak output power (dBm) | Target power (dBm) | MAX Target power (dBm) | Antenna gain | | Power Density (S) (mW /cm2) | Limited of Power Density (S) (mW /cm2) | Test Result |
|---------------|----------------------------------|--------------------------|---------------------------------|--------------|----------|---|--|----------------|
| | | | | (dBi) | (Linear) | | | |
| 2.4G Band | | | | | | | | |
| GFSK | 6.28 | 6±1 | 7 | 2.29 | 1.694 | 0.0017 | 1 | Complies |
| $\pi/4$ DQPSK | 6.93 | 6±1 | 7 | 2.29 | 1.694 | 0.0017 | 1 | Complies |
| 8-DPSK | 6.95 | 6±1 | 7 | 2.29 | 1.694 | 0.0017 | 1 | Complies |
| BLE 1M | 5.01 | 5±1 | 6 | 2.29 | 1.694 | 0.0013 | 1 | Complies |
| BLE 2M | 5.21 | 5±1 | 6 | 2.29 | 1.694 | 0.0013 | 1 | Complies |

End of Test Report