



EMC

TEST REPORT

REPORT NO. : F88082303
MODEL NO. : 5301
DATE OF TEST : Aug. 23, 1999

PREPARED FOR: BEHAVIOR TECH COMPUTER CORP.

ADDRESS : 2F, 51, TUNG HSING RD.,
TAIPEI, TAIWAN, R.O.C.

PREPARED BY: ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory

11F, NO.1, SEC.4, NAN-KING EAST RD.,
TAIPEI, TAIWAN, R.O.C.

This test report consists of 15 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory. It should not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. government. The test result in the report only applies to the tested sample.



TABLE OF CONTENTS

1. CERTIFICATION	3
2. GENERAL INFORMATION.....	4
2.1 GENERAL DESCRIPTION OF EUT	4
2.2 DESCRIPTION OF SUPPORT UNITS	5
2.3 TEST METHODOLOGY AND CONFIGURATION	5
3. TEST INSTRUMENTS	6
3.1 TEST INSTRUMENTS (EMISSION)	6
3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION.....	7
4. TEST RESULTS (EMISSION).....	8
4.1 RADIO DISTURBANCE.....	8
4.2 EUT OPERATION CONDITION.....	8
4.3 TEST DATA OF CONDUCTED EMISSION	9
4.4 TEST DATA OF RADIATED EMISSION	11
5. PHOTOGRAPHS OF THE TEST CONFIGURATION WITH MINIMUM MARGIN	13
6. APPENDIX - INFORMATION OF THE TESTING LABORATORY.....	15

**1. CERTIFICATION**

Issue Date: Aug. 27, 1999

Product : KEYBOARD
Trade Name : BTC
Model No. : 5301
Applicant : BEHAVIOR TECH COMPUTER CORP.
Standard : FCC Part 15, Subpart B, Class B
ANSI C63.4-1992
CISPR 22: 1993 +A1: 1995+A2: 1996, Class B

We hereby certify that one sample of the designation has been tested in our facility on Aug. 23, 1999. The test record, data evaluation and Equipment Under Test (EUT) configurations represent herein are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

The test results show that the EUT as described in this report is in compliance with the Class B limits of conducted and radiated emission of applicable standards

TESTED BY : Kevin Pan. , DATE: 8/27/99
(Kevin Pan)

CHECKED BY : Yemmy , DATE: 8/27/99
(Yemmy Soong)

APPROVED BY : Mike Su , DATE: 8/27/99
(Mike Su)

ADVANCE DATA TECHNOLOGY CORPORATION**NVLAP[®]**

Accredited Laboratory



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product	:	KEYBOARD
Model No.	:	5301
Power Supply	:	DC 5V (from PC)
Data Cable	:	Shielded (1.7 m)

Note: For more detailed features description, please refer to manufacturer's specification or User's Manual.



2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

No	Product	Brand	Model No.	FCC ID	I/O Cable
1	PERSONAL COMPUTER	NTI	PII-333T	FCC DoC Approved	Nonshielded Power (1.8m)
2	MONITOR	ADI	PD-959	FCC DoC Approved	Shielded Signal (1.5m) Nonshielded Power (1.8m)
3	PRINTER	HP	2225C+	DSI6XU2225	Shielded Signal (1.2m) Nonshielded Power (1.2m)
4	MODEM	ACEEX	1414	IFAXDM1414	Shielded Signal (1.2m) Nonshielded Power (1.2m)
5	MOUSE	DEXIN	A2P800A	NIYA2P800A	Shielded Signal (1.5m)
6	SPEAKER	J-S	J-008	NA	Shielded Signal (1.2m)
7	VGA CARD	CARDEX	CD-GX2A44T	ICUVGA-GW710	NA

2.3 TEST METHODOLOGY AND CONFIGURATION

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 1992. Radiated testing was performed at an antenna to EUT distance of 10 m on an open area test site.

Please refer to the photos of test configuration in Item 5.



3. TEST INSTRUMENTS

3.1 TEST INSTRUMENTS (EMISSION)

CONDUCTED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ Test Receiver	ESH3	893495/006	July 7, 2000
ROHDE & SCHWARZ Spectrum Monitor	EZM	893787/013	July 8, 2000
ROHDE & SCHWARZ Artificial Mains Network	ESH3-Z5	839135/006	July 7, 2000
EMCO-L.I.S.N.	3825/2	9204-1964	July 7, 2000
Shielded Room	Site 2	ADT-C02	NA

Note: 1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.
And the calibrations are traceable to NML/ROC and NIST/USA.

RADIATED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated until
HP Spectrum Analyzer	8590L	3544A00941	Dec. 06, 1999
HP Pre-Amplifier	8447D	2944A08312	Sept. 15, 1999
HP Preamplifier	8347A	3307A01088	Sept. 9, 1999
R&S Receiver	ESVS10	844594/010	Sept. 24, 1999
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 25, 1999
CHASE BILOG Antenna	CBL6111A	1500	Sept. 4, 1999
EMCO Double Ridged Guide Antenna	3115	9312-4192	April 5, 2000
EMCO Turn Table	1060-04	1196	NA
EMCO Tower	1051	1264	NA
Open Field Test Site	Site 1	ADT-R01	Aug. 28, 1999

Note: 1. The measurement uncertainty is less than $\pm 3\text{dB}$, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.
And the calibrations are traceable to NML/ROC and NIST/USA.



3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION

LIMIT OF RADIATED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (at 10m) *	Class B (at 10m) *
	dBuV/m	dBuV/m
30 - 230	40	30
230 - 1000	47	37

* Detector Function: Quasi-Peak

LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	Peak	Average	Peak	Average
Above 1000	80.0	60.0	74.0	54.0

- Note: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

LIMIT OF CONDUCTED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- Note: (1) The lower limit shall apply at the transition frequencies.
 (2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4. TEST RESULTS (EMISSION)

4.1 RADIO DISTURBANCE

Frequency Range : 0.15 - 30 MHz (Conducted Emission)
30 - 1000 MHz (Radiated Emission)
Input Voltage : 120 Vac, 60 Hz
Temperature : 26 °C
Humidity : 70 %
Atmospheric Pressure : 992 mbar

TEST RESULT	Remarks
PASS	Minimum passing margin of conducted emission: -17.6 dB at 0.776 MHz Minimum passing margin of radiated emission: -5.1 dB at 48.02 MHz

4.2 EUT OPERATION CONDITION

1. Turn on the power of all equipment.
2. PC reads a test program to enable all functions.
3. PC reads and writes messages from FDD and HDD.
4. EUT sends "H" character to PC.
5. PC sends "H" messages to monitor and monitor displays "H" patterns on screen.
6. PC sends "H" messages to modem.
7. PC sends "H" messages to printer, and the printer prints them on paper.
8. PC sends audio messages to speaker.
9. Repeat steps 3-9.



4.3 TEST DATA OF CONDUCTED EMISSION

EUT: **KEYBOARD**MODEL: **5301**

6 dB Bandwidth: 10 kHz

PHASE: LINE (L)

Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.154	0.2	45.9	-	46.1	-	65.8	55.8	-19.7	-
0.276	0.2	34.2	-	34.4	-	60.9	50.9	-26.5	-
0.502	0.2	37.1	-	37.3	-	56.0	46.0	-18.7	-
0.776	0.2	38.2	-	38.4	-	56.0	46.0	-17.6	-
0.961	0.2	34.9	-	35.1	-	56.0	46.0	-20.9	-
1.918	0.2	30.0	-	30.2	-	56.0	46.0	-25.8	-

Remarks: 1. "***": Undetectable


2. Q.P. and AV. are abbreviations of quasi-peak and average individually.

3. "-": The Quasi-peak emission level also meets average limit and measurement with the average detector is unnecessary.

4. The emission levels of other frequencies were very low against the limit.

5. Margin value = Emission level - Limit value

6. Emission Level = Correction Factor + Reading Value.



---- Date 23.AUG '99 Time 22:11:08
CISPR 22 CLASS B CONDUCTION TEST (PEAK VALUE)
MODEL: 5301 ADT CROP
LISN: L




TEST DATA OF CONDUCTED EMISSION

EUT: KEYBOARDMODEL: 53016 dB Bandwidth: 10 kHzPHASE: NEUTRAL (N)

Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.154	0.2	44.9	-	45.1	-	65.8	55.8	-20.7	-
0.276	0.2	35.7	-	35.9	-	60.9	50.9	-25.0	-
0.502	0.2	37.8	-	38.0	-	56.0	46.0	-18.0	-
0.776	0.2	37.9	-	38.1	-	56.0	46.0	-17.9	-
0.961	0.2	33.8	-	34.0	-	56.0	46.0	-22.0	-
1.918	0.2	30.5	-	30.7	-	56.0	46.0	-25.3	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak emission level also meets average limit and measurement with the average detector is unnecessary.
 4. The emission levels of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value
 6. Emission Level = Correction Factor + Reading Value.



ADT CROP
LISN: N

(PEAK VALUE)



4.4 TEST DATA OF RADIATED EMISSION

EUT: **KEYBOARD**MODEL: **5301**ANT. POLARITY: HorizontalDETECTOR FUNCTION: Quasi-peak6 dB BANDWIDTH: 120 kHzFREQUENCY RANGE: 30-1000 MHzMEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
48.06	11.1	7.9	19.0	30.0	-11.0	400	344
124.15	14.2	5.3	19.5	30.0	-10.5	400	227
138.26	13.9	6.3	20.2	30.0	-9.8	400	259
192.03	11.0	6.7	17.7	30.0	-12.3	400	248
214.80	12.2	8.4	20.6	30.0	-9.4	400	103
229.11	13.3	6.5	19.8	30.0	-10.2	400	105
288.09	15.4	11.3	26.7	37.0	-10.3	400	130

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)
+ Reading value (dBuV).
 2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION

EUT: KEYBOARDMODEL: 5301ANT. POLARITY: VerticalDETECTOR FUNCTION: Quasi-peak6 dB BANDWIDTH: 120 kHzFREQUENCY RANGE: 30-1000 MHzMEASURED DISTANCE: 10 M



Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
48.02	10.6	14.3	24.9	30.0	-5.1	100	21
69.99	7.1	13.7	20.8	30.0	-9.2	100	259
124.14	14.6	9.5	24.1	30.0	-5.9	100	230
138.25	14.0	9.7	23.7	30.0	-6.3	100	218
180.57	11.0	9.5	20.5	30.0	-9.5	100	338
214.80	12.3	10.1	22.4	30.0	-7.6	100	329
225.71	12.7	9.2	21.9	30.0	-8.1	100	348
288.06	15.7	13.4	29.1	37.0	-7.9	100	29
303.89	15.9	11.8	27.7	37.0	-9.3	100	16

- REMARKS:
1. Emission level (dBuV/m) = Correction Factor (dB)
+ Reading value (dBuV).
 2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value




**5. PHOTOGRAPHS OF THE TEST CONFIGURATION WITH
MINIMUM MARGIN**

CONDUCTED EMISSION TEST





RADIATED EMISSION TEST





6. APPENDIX - INFORMATION OF THE TESTING LABORATORY

Information of the testing laboratory

We, ADT Corp., are founded in 1988, to provide our best service in EMC and Safety consultation. Our laboratory is accredited by the following approval agencies according to ISO/IEC Guide 25 or EN 45001:

- | | |
|---------------|---------------------|
| ● USA | FCC, UL, NVLAP |
| ● Germany | TUV Rheinland |
| | TUV Product Service |
| ● Japan | VCCI |
| ● New Zealand | RFS |
| ● Norway | NEMKO, DNV |
| ● U.K. | INCHCAPE |
| ● R.O.C. | BSMI |

Enclosed please find some certificates of our laboratory obtained from approval agencies. If you have any comments, please feel free to contact us with the following:

Lin Kou EMC Lab.:
Tel: 886-2-26032180
Fax: 886-2-26022943

Hsin Chu EMC Lab:
Tel: 886-35-935343
Fax: 886-35-935342

Lin Kou Safety Lab.:
Tel: 886-2-26093195
Fax: 886-2-26093184

Design Center:
Tel: 886-2-26093195
Fax: 886-2-26093184

E-mail: service@mail.adt.com.tw
<http://www.adt.com.tw>