



MEASUREMENT REPORT

FCC ID : 2BH7FBE68
Applicant : TP-Link Systems Inc
Application Type : Certification
Product : BE14000 Whole Home Mesh Wi-Fi 7 System
Model No. : Deco BE68
Brand Name : tp-link
FCC Classification : Unlicensed National Information Infrastructure (NII)
FCC Rule Part(s) : Part15 Subpart E (Section 15.407)
Received Date : December 16, 2024
Test Date : December 30, 2024 ~ February 17, 2025

Test By : Owen Tsai
(Owen Tsai)
Reviewed By : Paddy Chen
(Paddy Chen)
Approved By : Chenz Ker
(Chenz Ker)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02v02r01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2412TW0116-U4	1.0	Original Report	2025-03-04	

CONTENTS

Description	Page
1. INTRODUCTION	7
1.1. Scope	7
1.2. MRT Test Location	7
2. PRODUCT INFORMATION	8
2.1. Equipment Description.....	8
2.2. Product Specification Subjective to this Report.....	8
2.3. Working Frequencies for this report	9
2.4. Description of Available Antennas.....	10
2.5. Test Mode	11
2.6. Configuration of Test System.....	12
2.7. Test System Details.....	13
2.8. Description of Test Software	13
2.9. Applied Standards	13
2.10. Duty Cycle	14
2.11. Test Configuration	17
2.12. EMI Suppression Device(s)/Modifications.....	17
2.13. Labeling Requirements.....	17
3. DESCRIPTION OF TEST	18
3.1. Evaluation Procedure	18
3.2. AC Line Conducted Emissions	18
3.3. Radiated Emissions.....	19
4. ANTENNA REQUIREMENTS.....	20
5. TEST EQUIPMENT CALIBRATION DATE.....	21
6. MEASUREMENT UNCERTAINTY.....	23
7. TEST RESULT	24
7.1. Summary	24
7.2. 26dB Bandwidth Measurement.....	25
7.2.1. Test Limit	25
7.2.2. Test Procedure used.....	25
7.2.3. Test Setting.....	25
7.2.4. Test Setup	25
7.2.5. Test Result.....	26
7.3. 6dB Bandwidth Measurement.....	68

7.3.1. Test Limit	68
7.3.2. Test Procedure used	68
7.3.3. Test Setting	68
7.3.4. Test Setup	68
7.3.5. TestResult	69
7.4. Output Power Measurement	83
7.4.1. Test Limit	83
7.4.2. Test Procedure Used	83
7.4.3. Test Setting	83
7.4.4. Test Setup	83
7.4.5. Test Result	84
7.5. Transmit Power Control	92
7.5.1. Test Limit	92
7.5.2. Test Procedure Used	92
7.5.3. Test Setting	92
7.5.4. Test Setup	92
7.5.5. Test Result	92
7.6. Power Spectral Density Measurement	93
7.6.1. Test Limit	93
7.6.2. Test Procedure Used	93
7.6.3. Test Setting	93
7.6.4. Test Setup	94
7.6.5. Test Result	95
7.7. Frequency Stability Measurement	207
7.7.1. Test Limit	207
7.7.2. Test Limit	207
7.7.3. Test Setup	208
7.7.4. Test Result	208
7.8. Radiated Spurious Emission Measurement	209
7.8.1. Test Limit	209
7.8.2. Test Procedure Used	209
7.8.3. Test Setting	209
7.8.4. Test Setup	211
7.8.5. Test Result	212
7.9. Radiated Restricted Band Edge Measurement	644
7.9.1. Test Limit	644
7.9.2. Test Procedure Used	645
7.9.3. Test Setting	645
7.9.4. Test Setup	646

7.9.5. Test Result.....	647
7.10. AC Conducted Emissions Measurement.....	1031
7.10.1. Test Limit	1031
7.10.2. Test Procedure	1031
7.10.3. Test Setup	1032
7.10.4. Test Result.....	1033
8. CONCLUSION.....	1035
Appendix A : Test Setup Photograph	1036
Appendix B : EUT Photograph.....	1036
Appendix C : Internal Photograph	1036

General Information

Applicant	TP-Link Systems Inc
Applicant Address	10 Mauchly, Irvine, CA 92618
Manufacturer	TP-Link Systems Inc
Manufacturer Address	10 Mauchly, Irvine, CA 92618
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	291082
FCC Rule Part(s)	Part 15.407

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Canada, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name:	BE14000 Whole Home Mesh Wi-Fi 7 System
Model No.:	Deco BE68
Brand Name:	tp-link
Specification:	WLAN: 802.11a/b/g/n/ac/ax/be WPAN: Bluetooth Mode: V5.4
EUT Identification No.:	#1-1 (Conducted) #1-2 (Radiated)
Accessory	
Adapter	Brand: tp-link Model No: T120330-2B4 Input: AC 100-240V~ 50-60Hz 1A Output: 12.0V=3.3A DC Cable Out: Non-Shielded, 1.5m

2.2. Product Specification Subjective to this Report

Frequency Range:	For 802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20: 5180~5240MHz, 5260~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40: 5190~5230MHz, 5270~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80/ax-HE80/be-EHT80: 5210MHz, 5290MHz, 5530MHz, 5610 MHz, 5690MHz, 5775MHz For 802.11ac-VHT160/ax-HE160/be-EHT160: 5250MHz, 5570MHz
Type of Modulation:	802.11a/n/ac: OFDM 802.11ax/be: OFDMA
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 450Mbps 802.11ac: up to 2600.1Mbps 802.11ax: up to 3602.9Mbps 802.11be: up to 4323.5Mbps

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11a/n-HT20/ac-VHT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	144	5720 MHz	149	5745 MHz
153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825 MHz	--	--	--	--

802.11n-HT40/ac-VHT40/ax-HE40/be-EHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	54	5270 MHz
62	5310 MHz	102	5510 MHz	110	5550MHz
118	5590 MHz	126	5630 MHz	134	5670 MHz
142	5710 MHz	151	5755 MHz	159	5795 MHz

802.11ac-VHT80/ax-HE80/be-EHT80

Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	58	5290 MHz	106	5530 MHz
122	5610 MHz	138	5690 MHz	155	5775 MHz

802.11ac-VHT160/ax-HE160/be-EHT160

Channel	Frequency	Channel	Frequency	Channel	Frequency
50	5250MHz	114	5570 MHz	--	--

2.4. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	Tx Paths	Number of spatial streams	Antenna Gain (dBi)				Beamforming Directional Gain (dBi)	CDD Directional Gain (dBi)	
				Ant 0	Ant 1	Ant 2	Ant 3		For Power	For PSD
Wi-Fi 5G (Ant 0+1+2)										
Dipole	5150 ~ 5250	3	1	2.89	2.07	5.25	--	6.39	2.39	6.39
	5250 ~ 5350	3	1	2.03	2.69	5.74	--	6.85	2.58	6.85
	5470 ~ 5725	3	1	2.57	2.82	4.84	--	6.15	1.90	6.15
	5725 ~ 5850	3	1	2.33	3.06	4.92	--	5.61	1.64	5.61
Wi-Fi 5G (Ant 0+1+3)										
Dipole	5150 ~ 5250	3	1	2.89	2.07	--	5.86	6.55	2.04	6.55
	5250 ~ 5350	3	1	2.03	2.69	--	4.30	6.00	1.36	6.00
	5470 ~ 5725	3	1	2.57	2.82	--	5.94	5.38	1.57	5.38
	5725 ~ 5850	3	1	2.33	3.06	--	5.77	5.09	1.56	5.09
1. The device supports CDD Mode and Beamforming mode, details refer to the table as below. 2. CDD signals are correlated, the directional gain as follows, When $N_{SS}=1$, for power measurements: the max directional gain (each angle) = $10 \log[(10^{G^1/10} + 10^{G^2/10} + \dots + 10^{G^N/10}) / N_{ANT}]$ For power spectral density (PSD) measurements: the max directional gain (each angle) = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}]$ When $N_{SS}=2$, the max directional gain (each angle) = $10 \log[(10^{G^1/10} + 10^{G^2/10} + \dots + 10^{G^N/10}) / N_{ANT}]$ 3. Beamforming signals are correlated, the directional gain as follows, the max directional gain (each angle) = $10 \log[(10^{G^1/20} + 10^{G^2/20} + \dots + 10^{G^N/20})^2 / N_{ANT}]$ 4. The information as above is from the antenna report.										


Test Mode	Tx Paths	CDD Mode	Beamforming Mode
802.11a/n (NII)	3	√	X
802.11ac/ax/be (NII)	3	√	√

2.5. Test Mode

CDD Mode
Mode 1: Transmit by 802.11a_Nss=1 (6Mbps)
Mode 2: Transmit by 802.11ac-VHT20_Nss=1 (MCS0)
Mode 3: Transmit by 802.11ac-VHT40_Nss=1 (MCS0)
Mode 4: Transmit by 802.11ac-VHT80_Nss=1 (MCS0)
Mode 5: Transmit by 802.11ac-VHT160_Nss=1 (MCS0)
Mode 6: Transmit by 802.11ax-HE20_Nss=1 (MCS0)
Mode 7: Transmit by 802.11ax-HE40_Nss=1 (MCS0)
Mode 8: Transmit by 802.11ax-HE80_Nss=1 (MCS0)
Mode 9: Transmit by 802.11ax-HE160_Nss=1 (MCS0)
Mode 10: Transmit by 802.11be-EHT20_Nss=1 (MCS0)
Mode 11: Transmit by 802.11be-EHT40_Nss=1 (MCS0)
Mode 12: Transmit by 802.11be-EHT80_Nss=1 (MCS0)
Mode 13: Transmit by 802.11be-EHT160_Nss=1 (MCS0)
Remark: 1. For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. This device supports 3 N_{SS} and power level of 3 N_{SS} is less than or equal to the power of 1 N_{SS}. The worst case is N_{SS}=1. 3. 802.11n and 802.11ac have same modulation type and same power value, so we only show 802.11ac test data in report. 4. For beamforming operation, the manufacturer automatically reduces power based on a factor calculated as the difference between the beamforming directional gain and the CDD directional power gain. Thus, only the CDD mode was evaluated in this report. 5. EUT supports one configuration only in 802.11ax/be full RU mode. 6. As Designated by manufacturer, the lowest data rate was the worst condition, so all the tests were done with lowest data rate.

2.6. Configuration of Test System

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.



2.7. Test System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

No.	Product	Brand	Model No.	Serial No.	Power Cord
1	Notebook PC	Lenovo	20SL	N/A	Non-shielded, 0.8m

2.8. Description of Test Software

The test utility software used during testing was “MT7990 QA”, the version is ver0.0.2.94.

Note: Final power setting please refer to operational description.

2.9. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.407
- KDB 789033 D02v02r01,
- KDB 662911 D01v02r01
- ANSI C63.10-2013


2.10. Duty Cycle

5GHz (NII) operation is possible in 20MHz, 40MHz, 80MHz and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than $50/T$, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:


Test Mode	Duty Cycle
802.11a	97.96%
802.11ac-VHT20	98.67%
802.11ac-VHT40	96.28%
802.11ac-VHT80	94.91%
802.11ac-VHT160	92.48%
802.11ax-HE20	98.50%
802.11ax-HE40	96.14%
802.11ax-HE80	93.97%
802.11ax-HE160	90.91%
802.11be-EHT20	98.01%
802.11be-EHT 40	96.66%
802.11be-EHT 80	93.93%
802.11be-EHT 160	90.85%

Duty Cycle (T = Transmission Duration)


802.11a




802.11ac-VHT20




802.11ac-VHT40




802.11ac-VHT80




802.11ac-VHT160




802.11ax-HE20




802.11ax-HE40



802.11ax-HE80





2.11. Test Configuration

The device was tested per the guidance of KDB 789033 D02v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.12. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.13. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the devices so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 789033 D02v02r01 were used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50 Ω /50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the provisions **attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2025/3/5
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2025/4/21
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2025/5/14
DIVA PLUS Funk-Wetter station	TFA	35.1083	MRTTWA00050	1 year	2025/6/2

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2025/5/7
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00086	1 year	2025/11/5
Broadband Hornantenna	RFSPIN	DRH18-E	MRTTWA00087	1 year	2025/5/20
Broadband Preamplifier	EMC Instruments corporation	EMC118A45SE	MRTTWA00088	1 year	2025/5/14
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2025/3/26
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2025/3/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2025/3/5
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2025/3/14
Antenna Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2025/6/14
Cable	Rosnol	K1K50-UP0264 -K1K50-4M	MRTTWE00012	1 year	2025/6/14
Temperature/Humidity Meter	TFA	35.1083	MRTTWA00050	1 year	2025/6/2

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2025/4/16
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2025/9/24
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2025/8/12
Attenuator	WTI	218FS-20	MRTTWE00026	1 year	2025/10/31
Attenuator	WTI	218FS-10	MRTTWE00027	1 year	2025/6/13
Temperature & Humidity Chamber	TEN BILLION	TTH-B3UP	MRTTWA00036	1 year	2025/6/6
DIVA PLUS Funk-Wetterstation	TFA	35.1083	MRTTWA00050	1 year	2025/6/2

Software	Version	Function
e3	9.160520a	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 150kHz~30MHz: $\pm 2.53\text{dB}$
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 9kHz ~ 1GHz: $\pm 4.25\text{dB}$ 1GHz ~ 40GHz: $\pm 4.45\text{dB}$
Conducted Power (Carrier Power / Power Density)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 3.3\%$
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 0.82^\circ\text{C} / \pm 3\%$
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): $\pm 78.4\text{Hz}$

7. TEST RESULT

7.1. Summary

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(a)	26dB Bandwidth	N/A	Conducted	Pass	Section 7.2
15.407(e)	6dB Bandwidth	$\geq 500\text{kHz}$		Pass	Section 7.3
15.407(a)(1)(ii), (2), (3)	Maximum Conducted Output Power	Refer to section 7.4		Pass	Section 7.4
15.407(h)(1)	Transmit Power Control	$\leq 24\text{ dBm}$		Pass	Section 7.5
15.407(a)(1)(ii), (2), (3), (12)	Peak Power Spectral Density	Refer to section 7.6		Pass	Section 7.6
15.407(g)	Frequency Stability	N/A		Pass	Section 7.7
15.407(b)(1), (2), (3), (4)(i)	Undesirable Emissions	Refer to Section 7.8	Radiated	Pass	Section 7.8 & 7.9
15.205, 15.209 15.407(b)(8), (9), (10)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		Pass	
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.10

Notes:

- Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

7.2. 26dB Bandwidth Measurement

7.2.1. Test Limit

N/A

7.2.2. Test Procedure used


K DB 789033 D02v02r01- Section II)C.1) (26dB Bandwidth)

KDB 789033 D02v02r01- Section II)D) (99% Bandwidth)

7.2.3. Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. $VBW \geq 3 \times RBW$.
4. Detector = Peak.
5. Trace mode = max hold.

7.2.4. Test Setup



7.2.5.Test Result

Product	BE14000 Whole Home Mesh Wi-Fi 7 System	Test Engineer	Marvin
Test Site	SR6	Test Date	2025/1/23~2025/2/4
Test Mode	CDD (Ant1)_with Ant0+1+2		

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
802.11a	6Mbps	36	5180	18.66	16.292
802.11a	6Mbps	40	5200	20.04	16.318
802.11a	6Mbps	48	5240	17.92	16.305
802.11a	6Mbps	52	5260	17.88	16.280
802.11a	6Mbps	60	5300	19.03	16.302
802.11a	6Mbps	64	5320	18.30	16.277
802.11a	6Mbps	100	5500	18.35	16.299
802.11a	6Mbps	116	5580	17.96	16.276
802.11a	6Mbps	140	5700	20.19	16.305
802.11a	6Mbps	144	5720	17.91	16.288
802.11a	6Mbps	149	5745	28.27	16.543
802.11a	6Mbps	157	5785	23.39	16.357
802.11a	6Mbps	165	5825	29.17	16.528
802.11ac-VHT20	MCS0	36	5180	18.74	17.434
802.11ac-VHT20	MCS0	40	5200	18.60	17.462
802.11ac-VHT20	MCS0	48	5240	18.95	17.469
802.11ac-VHT20	MCS0	52	5260	18.67	17.434
802.11ac-VHT20	MCS0	60	5300	18.56	17.461
802.11ac-VHT20	MCS0	64	5320	18.69	17.465
802.11ac-VHT20	MCS0	100	5500	19.21	17.465
802.11ac-VHT20	MCS0	116	5580	18.71	17.437
802.11ac-VHT20	MCS0	140	5700	18.68	17.461
802.11ac-VHT20	MCS0	144	5720	18.68	17.443
802.11ac-VHT20	MCS0	149	5745	32.55	17.729
802.11ac-VHT20	MCS0	157	5785	28.45	17.564
802.11ac-VHT20	MCS0	165	5825	29.76	17.617


Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
802.11ac-VHT40	MCS0	38	5190	37.73	35.594
802.11ac-VHT40	MCS0	46	5230	39.59	35.866
802.11ac-VHT40	MCS0	54	5270	37.68	35.603
802.11ac-VHT40	MCS0	62	5310	37.79	35.591
802.11ac-VHT40	MCS0	102	5510	37.85	35.595
802.11ac-VHT40	MCS0	110	5550	37.56	35.591
802.11ac-VHT40	MCS0	134	5670	37.85	35.704
802.11ac-VHT40	MCS0	142	5710	37.68	35.710
802.11ac-VHT40	MCS0	151	5755	48.08	36.028
802.11ac-VHT40	MCS0	159	5795	40.50	35.713
802.11ac-VHT80	MCS0	42	5210	78.40	74.868
802.11ac-VHT80	MCS0	58	5290	78.28	74.625
802.11ac-VHT80	MCS0	106	5530	78.37	74.647
802.11ac-VHT80	MCS0	122	5610	78.36	74.668
802.11ac-VHT80	MCS0	138	5690	78.46	74.877
802.11ac-VHT80	MCS0	155	5775	78.26	74.688
802.11ac-VHT160	MCS0	50	5250	159.6	153.90
802.11ac-VHT160	MCS0	114	5570	159.6	153.12
802.11ax-HE20	MCS0	36	5180	19.66	18.788
802.11ax-HE20	MCS0	40	5200	22.44	18.808
802.11ax-HE20	MCS0	48	5240	19.72	18.773
802.11ax-HE20	MCS0	52	5260	19.75	18.751
802.11ax-HE20	MCS0	60	5300	19.71	18.795
802.11ax-HE20	MCS0	64	5320	19.65	18.796
802.11ax-HE20	MCS0	100	5500	19.74	18.818
802.11ax-HE20	MCS0	116	5580	19.69	18.742
802.11ax-HE20	MCS0	140	5700	19.70	18.763
802.11ax-HE20	MCS0	144	5720	19.75	18.794
802.11ax-HE20	MCS0	149	5745	29.55	18.937
802.11ax-HE20	MCS0	157	5785	22.79	18.835
802.11ax-HE20	MCS0	165	5825	28.28	18.870

Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
802.11ax-HE40	MCS0	38	5190	39.13	37.396
802.11ax-HE40	MCS0	46	5230	40.51	37.424
802.11ax-HE40	MCS0	54	5270	39.14	37.195
802.11ax-HE40	MCS0	62	5310	39.16	37.370
802.11ax-HE40	MCS0	102	5510	39.21	37.273
802.11ax-HE40	MCS0	110	5550	39.08	37.214
802.11ax-HE40	MCS0	134	5670	39.28	37.274
802.11ax-HE40	MCS0	142	5710	39.05	37.433
802.11ax-HE40	MCS0	151	5755	51.95	37.568
802.11ax-HE40	MCS0	159	5795	42.96	37.392
802.11ax-HE80	MCS0	42	5210	79.60	76.472
802.11ax-HE80	MCS0	58	5290	79.54	76.401
802.11ax-HE80	MCS0	106	5530	79.69	76.633
802.11ax-HE80	MCS0	122	5610	79.68	76.412
802.11ax-HE80	MCS0	138	5690	79.62	76.615
802.11ax-HE80	MCS0	155	5775	79.58	76.495
802.11ax-HE160	MCS0	50	5250	161.5	155.76
802.11ax-HE160	MCS0	114	5570	161.3	155.11
802.11be-EHT20	MCS0	36	5180	19.79	18.792
802.11be-EHT20	MCS0	40	5200	19.89	18.839
802.11be-EHT20	MCS0	48	5240	19.70	18.756
802.11be-EHT20	MCS0	52	5260	19.74	18.797
802.11be-EHT20	MCS0	60	5300	19.64	18.772
802.11be-EHT20	MCS0	64	5320	19.74	18.803
802.11be-EHT20	MCS0	100	5500	19.77	18.787
802.11be-EHT20	MCS0	116	5580	19.67	18.731
802.11be-EHT20	MCS0	140	5700	19.85	18.769
802.11be-EHT20	MCS0	144	5720	19.75	18.792
802.11be-EHT20	MCS0	149	5745	31.42	19.002
802.11be-EHT20	MCS0	157	5785	23.89	18.844
802.11be-EHT20	MCS0	165	5825	24.00	18.880


Test Mode	Data Rate/ MCS	Channel No.	Frequency (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
802.11be-EHT40	MCS0	38	5190	39.32	37.307
802.11be-EHT40	MCS0	46	5230	42.55	37.472
802.11be-EHT40	MCS0	54	5270	39.12	37.322
802.11be-EHT40	MCS0	62	5310	39.14	37.310
802.11be-EHT40	MCS0	102	5510	39.10	37.296
802.11be-EHT40	MCS0	110	5550	39.03	37.219
802.11be-EHT40	MCS0	134	5670	39.18	37.311
802.11be-EHT40	MCS0	142	5710	39.10	37.369
802.11be-EHT40	MCS0	151	5755	48.65	37.563
802.11be-EHT40	MCS0	159	5795	39.29	37.404
802.11be-EHT80	MCS0	42	5210	79.57	76.494
802.11be-EHT80	MCS0	58	5290	79.63	76.315
802.11be-EHT80	MCS0	106	5530	79.58	76.455
802.11be-EHT80	MCS0	122	5610	79.62	76.320
802.11be-EHT80	MCS0	138	5690	79.66	76.499
802.11be-EHT80	MCS0	155	5775	79.58	76.260
802.11be-EHT160	MCS0	50	5250	161.50	155.790
802.11be-EHT160	MCS0	114	5570	161.10	155.540

802.11a 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 116 (5580MHz)






802.11ac-VHT20 26dB Bandwidth & 99% Bandwidth


Channel 36 (5180MHz)




Channel 40 (5200MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 116 (5580MHz)






802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth


Channel 38 (5190MHz)




Channel 46 (5230MHz)




Channel 54 (5270MHz)




Channel 62 (5310MHz)




Channel 102 (5510MHz)




Channel 110 (5550MHz)




Channel 134 (5670MHz)




Channel 142 (5710MHz)






802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth


Channel 42 (5210MHz)




Channel 58 (5290MHz)




Channel 106 (5530MHz)




Channel 122 (5610MHz)



Channel 138 (5690MHz)




Channel 155 (5775MHz)



802.11ac-VHT160 26dB Bandwidth & 99% Bandwidth

Channel 50 (5250MHz)



Channel 114 (5570MHz)

