



MODEL : BH437A

X1
 X1

S X1
 S X1

M X1
 M X1

L X1
 L X1

(Size M is preinstalled on earbuds)

X1
 X1

X1

The diagram illustrates the components of the AirPods Pro (2nd generation) charging case and earbuds. It includes the following labels and their corresponding parts:

- LED light**: Points to the status light on the inside of the charging case lid.
- Type-C charging port**: Points to the USB-C port on the bottom of the charging case.
- MFB (Touch Control)**: Points to the touch sensor on the stem of the left earbud.
- LED light**: Points to the status light on the stem of the right earbud.
- Magnetic charging connectors**: Points to the charging contacts on the back of the right earbud.
- L/R logo**: Points to the 'L' logo on the back of the right earbud.
- Talking mic**: Points to the microphone on the back of the right earbud.

Mode 1

The diagram shows the device in its closed, open position, and then in its closed position with the LED light on. A red arrow points from the closed device to the open device. A red dashed line connects the LED light to the device. A red arrow points down to a button labeled "ON".

Mode 2

The diagram shows the device in its closed position with the LED light on, and then in its open position with the LED light on. A red dashed line connects the LED light to the device. A red arrow points down to a button labeled "ON".

Nota: l'auricolare si riconnetterà al dispositivo accoppiato per priorità. Se si desidera associare il secondo smartphone, disabilitare Bluetooth sullo smartphone associato.

www.xmpow.com | support@xmpow.com
MPOW TECHNOLOGY CO., LTD
 Copyright © MPOW Inc. All rights reserved.