

## RF Exposure Report

**Report No.:** SA170906C12H

**FCC ID:** PY318200411

**Test Model:** EX7700

**Received Date:** Aug. 25, 2017

**Test Date:** Aug. 25 ~ Sep. 07, 2017

**Issued Date:** Jul. 24, 2018

**Applicant:** NETGEAR, INC.

**Address:** 350 East Plumeria Drive San Jose, CA 95134

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /** 788550 / TW0003  
**Designation Number:**



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits for Maximum Permissible Exposure (MPE) .....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
<b>3 Calculation Result of Maximum Conducted Power</b> .....	<b>6</b>

### Release Control Record

Issue No.	Description	Date Issued
SA170906C12H	Original release.	Jul. 24, 2018

## 1 Certificate of Conformity

**Product:** Nighthawk X6 AC2200 Tri-band WiFi Range Extender

**Brand:** NETGEAR

**Test Model:** EX7700

**Sample Status:** Engineering sample

**Applicant:** NETGEAR, INC.

**Test Date:** Aug. 25 ~ Sep. 07, 2017

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Celine Chou , **Date:** Jul. 24, 2018  
Celine Chou / Specialist

**Approved by :** Bruce Chen , **Date:** Jul. 24, 2018  
Bruce Chen / Project Engineer

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

### 3 Calculation Result of Maximum Conducted Power

Function	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
WLAN	CDD Mode					
	2412-2462	24.93	5.71	20	0.231	1
	5180-5240	23.24	5.01	20	0.133	1
	5260-5320	23.38	5.63	20	0.158	1
	5500-5700	23.91	5.71	20	0.182	1
	5745-5825	27.89	4.65	20	0.357	1
	Beamforming Mode					
	2412-2462	24.10	5.71	20	0.190	1
	5180-5240	23.24	5.01	20	0.133	1
	5260-5320	23.38	5.63	20	0.158	1
	5500-5700	23.91	5.71	20	0.182	1
	5745-5825	27.89	4.65	20	0.357	1

Note: The Max Power = Max tune up power

2412~2462MHz Directional gain = 5.71dBi

5180~5240MHz Directional gain = 5.01dBi

5260~5320MHz Directional gain = 5.63dBi

5500~5700MHz Directional gain = 5.71dBi

5745~5825MHz Directional gain = 4.65dBi

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. WLAN 2.4GHz + WLAN 5GHz band 1 + WLAN 5GHz band 3 =  $0.231 + 0.133 + 0.171 = 0.535 < 1$

2. WLAN 2.4GHz + WLAN 5GHz band 1 + WLAN 5GHz band 4 =  $0.231 + 0.133 + 0.357 = 0.721 < 1$

3. WLAN 2.4GHz + WLAN 5GHz band 2 + WLAN 5GHz band 3 =  $0.231 + 0.158 + 0.171 = 0.560 < 1$

4. WLAN 2.4GHz + WLAN 5GHz band 2 + WLAN 5GHz band 4 =  $0.231 + 0.158 + 0.357 = 0.746 < 1$

---END---