

# RJ Brands LLC RF TEST REPORT

**Report Type:** FCC Part 15.247 & ISED RSS-247 RF report

Model: CQ60-PR-01, CQ60-PR-02, CQ60-PR-03, CQ60-PR-04, CQ60-PR-05

**REPORT NUMBER:** 220302039SHA-001

**ISSUE DATE:** May 30, 2022

**DOCUMENT CONTROL NUMBER:** TTRF15.247-02\_V1 © 2018 Intertek



Total Quality. Assured.

Telephone: 86 21 6127 8200 www.intertek.com

Report no.: 220302039SHA-001

Applicant:	RJ Brands LLC
	200 Performance Drive, Mahwah, NJ 07495 USA
Manufacturer:	Hzsamko Technologies Co.,Ltd.
	No.8, Jiaqi Road, Xianlin Street, Yuhang District, Hangzhou, China.
Product Name:	Smart Thermometer CHEF PROBE
Type/Model:	CQ60-PR-01, CQ60-PR-02, CQ60-PR-03,CQ60-PR-04,CQ60-PR-05
FCC ID:	2A2YP-CQ60PROBE
IC:	27740-CQ60PROBE

#### SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2020): Radio Frequency Devices (Subpart C)

**ANSI C63.10 (2013):** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

**RSS-247 Issue 2 (February 2017):** Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5 (February 2021) Amendment 2: General Requirements for Compliance of Radio Apparatus

PREPARED BY:

Vylan tan

Project Engineer Dylan Tang

**REVIEWED BY:** 

Wakeyou

Reviewer Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No.: 220302039SHA-001



## Content

RE	REVISION HISTORY			
М	EASU	REMENT RESULT SUMMARY	. 6	
1	G	ENERAL INFORMATION	. 7	
	1.1	DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7	
	1.2 1.3	TECHNICAL SPECIFICATION DESCRIPTION OF TEST FACILITY	/ 8	
2	TE	EST SPECIFICATIONS	10	
	2.1	STANDARDS OR SPECIFICATION	10	
	2.2	MODE OF OPERATION DURING THE TEST	10	
	2.3	TEST SOFTWARE LIST	11	
	2.4	TEST PERIPHERALS LIST	11	
	2.5		11	
	2.0 2.7		12	
2	2.7		1.7	
3			14	
	3.1		14	
	3.Z 2.2	Test Configuration	14 17	
	3.4	TEST RESULTS OF MINIMUM 6DB BANDWIDTH	14	
4	M	AXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P.	15	
	11		15	
	4.1	MEASUREMENT PROCEDURE	15	
	4.3	TEST CONFIGURATION	16	
	4.4	TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER	16	
5	PC	OWER SPECTRUM DENSITY	17	
	51	LIMIT	17	
	5.2	Measurement Procedure	17	
	5.3	TEST CONFIGURATION	18	
	5.4	Test Results of Power spectrum density	18	
6	Eľ	MISSION OUTSIDE THE FREQUENCY BAND	19	
	6.1	LIMIT	19	
	6.2	Measurement Procedure	19	
	6.3	TEST CONFIGURATION	20	
	6.4	THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND	20	
7	R	ADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS	21	
	7.1	LIMIT	21	
	7.2	MEASUREMENT PROCEDURE	21	
	7.3 7 /	LEST CONFIGURATION	23 25	
0	/.4		20	
ð	0		۷ŏ	
	8.1		28	
	8.2 0 0		28	
	ō.3	TEST CONFIGURATION	۷ð	

## Intertek Total Quality. Assured. TEST REPORT

	8.4	The results of Occupied Bandwidth	. 28
9	A	NTENNA REQUIREMENT	29
A	PPEND	DIX A: TEST RESULTS	30





## **Revision History**

Report No.	Version	Description	Issued Date
220302039SHA-001	Rev. 01	Initial issue of report	May <b>30, 2022</b>



## **Measurement result summary**

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT	
Minimum 6dB Bandwidth	15.247(a)(2)	RSS-247 Issue 2	Pass	
		Clause 5.2		
Maximum conducted output power	15.247(b)(3)	RSS-247 Issue 2	Pass	
and e.i.r.p.	2012 17 (0)(0)	Clause 5.4	1 000	
Power spectrum density	15.247(e)	RSS-247 Issue 2	Pass	
	2012 17 (0)	Clause 5.2	1 435	
Emission outside the frequency band	15.247(d)	RSS-247 Issue 2	Pass	
	2012 17 (0)	Clause 5.5		
Radiated Emissions in restricted	15.247(d),	RSS-Gen Issue 5	Pass	
frequency bands	15.205&15.209	Clause 8.9&8.10	1 435	
Power line conducted emission	15 207(a)	RSS-Gen Issue 5	Pass	
	13.207 (4)	Clause 8.8		
Occupied bandwidth	_	RSS-Gen Issue 5	Tested	
		Clause 6.6	lested	
Antenna requirement	15.203	_	Pass	

Notes: 1: NA =Not Applicable

**INTERLEAK** Total Quality. Assured. TEST REPORT

## **1 GENERAL INFORMATION**

## 1.1 Description of Equipment Under Test (EUT)

Product name:	CHEF PROBE
Type/Model:	CQ60-PR-01, CQ60-PR-02, CQ60-PR-03, CQ60-PR-04, CQ60-PR-05
	The EUT is CHEF PROBE, it supports Bluetooth function. The differences
	between CQ60-PR-01 CQ60-PR-02, CQ60-PR-03, CQ60-PR-04 and
	CQ60-PR-05 is that the decal number/color on the ceramic handle.
	The models PCB layout and circuit design is the same. so choose CQ60-
Description of EUT:	PR-03 to test as representative.
Rating:	DC 3V, 0.03A
Category of EUT:	Class B
EUT type:	Table top 🔲 Floor standing
Product Marketing Name:	CQ60-PR-01, CQ60-PR-02, CQ60-PR-03, CQ60-PR-04, CQ60-PR-05
HVIN:	CQ60-PR-01, CQ60-PR-02, CQ60-PR-03, CQ60-PR-04, CQ60-PR-05
Software Version:	0.5.3
Hardware Version:	н
	0220601-17-001(for radiation sample),
Serial numbers:	0220601-17-002(for conduction sample)
Sample received date:	March 31, 2022
Date of test:	May 20, 2022 ~ May 30, 2022

## **1.2 Technical Specification**

Frequency Range:	2402-2480MHz
Support Standards:	IEEE 802.15.1
Type of Modulation:	GFSK
Channel Number:	3
Data Rate:	1Mbps
Antenna Information:	-13.71dBi, Metal antenna

Total Quality. Assured. TEST REPORT

## **1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is	CNAS Accreditation Lab
recognized,	Registration No. CNAS L0139
certified, or accredited by these	FCC Accredited Lab Designation Number: CN1175
organizations.	IC Registration Lab Registration code No.: 2042B-1
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	NVLAP Accreditation Lab NVLAP LAB CODE: 200849-0
	A2LA Accreditation Lab Certificate Number: 3309.02

Total Quality. Assured.

All tests were sub-contracted.

#### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng Science and Technology Park, Longhua District, Shenzhen, China 518109 Telephone: +86 (0) 755 2823 0888 Fax: +86 (0) 755 2823 0886

All tests were sub-contracted at Shenzhen UnionTrust Quality and Technology Co., Ltd, and conducted by Kieron Luo

Reviewed and approved by Wakeyou Wang from Intertek Testing Services Shanghai.

#### The test facility is recognized, certified, or accredited by the following organizations:

Name:	Shenzhen UnionTrust Quality and Technology Co., Ltd.		
	Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and		
Address:	technology park, Longhua district, Shenzhen, China, China 518109		
Telephone:	+86 (0) 755 2823 0888		
Telefax:	+86 (0) 755 2823 0886		

The test facility is	CNAS Accreditation Lab
recognized,	Registration No. CNAS L9069
certified, or accredited by	FCC Accredited Lab Designation Number: CN1194
these organizations:	IC Registration Lab CAB identifier.: CN0032
	A2LA Accreditation Lab Certificate Number: 4312.01

## Total Quality. Assured. TEST REPORT

## **2 TEST SPECIFICATIONS**

#### 2.1 Standards or specification

47CFR Part 15 (2020) ANSI C63.10 (2013) RSS-247 Issue 2 (February 2017) RSS-Gen Issue 5 (April 2018) KDB 558074 (v05)

#### 2.2 Mode of operation during the test

The lowest, middle and highest channel were tested as representatives.

Frequency Band (MHz)			2402 ~ 2480				
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	38	2426	39	2480		

#### Data rate VS Power:

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

Test software and Power Setting parameter						
Test Software		-				
Working Mode	BLE					
Test Channel	2402MHz	2426MHz	2480MHz			
Power Setting	default	default	default			



While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

Radiated test mode: EUT transmitted signal with BT antenna;

Conducted test mode: EUT transmitted signal from BT RF port connected to SPA directly;

#### 2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

#### 2.4 Test peripherals list

Item No.	Name	Band and Model	Description

#### **2.5** Test environment condition:

Test items	Temperature	Humidity		
Minimum 6dB Bandwidth				
Maximum conducted output power and e.i.r.p.		52% RH		
Power spectrum density	23°C			
Emission outside the frequency band				
Occupied bandwidth				
Radiated Emissions in restricted frequency bands	22°C	55% RH		
Power line conducted emission	21°C	52% RH		

## Intertek Total Quality. Assured. TEST REPORT

## 2.6 Instrument list

Radiated Emission									
Used	Equipment	Manufacturer	Туре	Internal no.	Due date				
$\boxtimes$	3m Chamber SAC	ETS-LINDGREN	3m	NA	2024-01-21				
$\boxtimes$	Receiver	R&S	ESIB26	100114	2022-11-04				
$\boxtimes$	Broadband Antenna (Pre-amplifier)	ETS-Lindgren	3142E-PA	00201891	2023-04-29				
$\boxtimes$	6dB Attenuator	Talent	RA6A5-N-18	18103001	2023-11-10				
$\boxtimes$	Preamplifier	HP	8447F	2805A02960	2022-11-04				
$\boxtimes$	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ged Horn a ETS-Lindgren 3117-PA 00201541 iier)		2023-04-29					
$\boxtimes$	Pre-amplifier	ETS-Lindgren	00118385	00201874	2022-11-05				
$\boxtimes$	Band Reject Filter(2400MHz~2 500MHz)	Micro-Tronics	BRM50702	G248	2022-11-05				
$\boxtimes$	Test Software	Audix	e3	Software Version: 9.160323					
			RF test						
Used	Equipment	Manufacturer	Туре	Internal no.	Due date				
$\boxtimes$	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	2022-11-04				
$\boxtimes$	EXA Signal Analyzer	KEYSIGHT	N9010A	MY51440197	2023-04-20				
$\boxtimes$	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	2022-11-04				
$\boxtimes$	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	2022-11-04				
$\boxtimes$	Test Software	AutomationTestSys tem	ECIT	Software Version: 1.0.7515.16529					

#### 2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74$ dB
Radiated Emissions in restricted frequency bands below 1GHz	± 4.90dB
Radiated Emissions in restricted frequency bands above 1GHz	± 5.02dB
Emission outside the frequency band	± 2.89dB

## Intertek Total Quality. Assured. TEST REPORT

## 3 Minimum 6dB bandwidth

Test result: Pass

#### 3.1 Limit

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.2 Measurement Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\ge$  3 × RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 3.3 Test Configuration



#### 3.4 Test Results of Minimum 6dB bandwidth

Please refer to Appendix A

Total Quality. Assured.

## 4 Maximum conducted output power and e.i.r.p.

#### Test result: Pass

#### 4.1 Limit

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

#### 4.2 Measurement Procedure

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq$  3 × RBW.
- c) Set span  $\geq$  3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



## 4.3 Test Configuration



## 4.4 Test Results of Maximum conducted output power

Please refer to Appendix A

## 5 Power spectrum density

Test result: Pass

#### 5.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and 8+ (6 –antenna gain-beam forming gain).

#### 5.2 Measurement Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq$  3 × RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



## 5.3 Test Configuration



## 5.4 Test Results of Power spectrum density

Please refer to Appendix A

Intertek Total Quality. Assured. TEST REPORT

## 6 Emission outside the frequency band

Test result: Pass

#### 6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

#### 6.2 Measurement Procedure

#### **Reference level measurement**

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq$  1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq$  3 x RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

#### **Emission level measurement**

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq$  3 x RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.



## 6.3 Test Configuration



#### 6.4 The results of Emission outside the frequency band

Please refer to Appendix A

Total Quality. Assured.

## 7 Radiated Emissions in restricted frequency bands

Test result: Pass

#### 7.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### 7.2 Measurement Procedure

#### For Radiated emission below 30MHz:

- a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.



#### For Radiated emission above 30MHz:

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

#### Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 3 x RBW (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported

Report No.: 220302039SHA-001

Total Quality. Assured. TEST REPORT

## 7.3 Test Configuration

For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:





#### For Radiated emission above 1GHz:





#### 7.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

The worst waveform from 30MHz to 1000MHz is listed as below:



TTRF15.247-02\_V1 © 2018 Intertek

## **Intertek** Total Quality. Assured. TEST REPORT

#### Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
Н	35.762	22.35	5.14	40.00	17.65	РК
Н	43.845	19.55	10.4	40.00	20.45	РК
н	178.770	15.94	9.75	43.50	27.56	РК
н	406.782	21.82	4.37	46.00	24.18	РК
Н	781.961	28.05	-2.03	46.00	17.95	РК
Н	932.141	30.64	-4.52	46.00	15.36	РК
V	35.016	23.58	4.28	40.00	16.42	РК
V	45.733	21.74	11.7	40.00	18.26	РК
V	103.335	14.89	15.76	43.50	28.61	РК
V	233.488	16.59	10.03	46.00	29.41	РК
V	665.261	26.93	-0.82	46.00	19.07	РК
V	893.656	29.63	-4.26	46.00	16.37	РК

#### Test result above 1GHz:

The emission was conducted from 1GHz to 25GHz

СН	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
	Н	2402.00	32.5	77.8	Fundamental	/	РК
	V	2402.00	32.5	90.6	Fundamental	/	РК
	Н	2390.00	32.6	48.0	74.00	26.0	РК
	V	2390.00	32.6	48.2	74.00	25.8	РК
L	Н	4804.00	2.7	31.8	74.00	42.2	РК
	Н	7206.00	7.7	37.5	74.00	36.5	РК
	V	4804.00	2.7	34.5	74.00	39.5	РК
	V	7206.00	7.7	42.1	74.00	31.9	РК
	Н	4852.00	3.0	33.3	74.00	40.7	РК
5.4	Н	7278.00	8.0	40.0	74.00	34.0	РК
IVI	V	4852.00	3.0	32.9	74.00	41.1	РК
	V	7278.00	8.0	36.5	74.00	37.5	РК

Total Quality. Assured. TEST REPORT

	Н	2480.00	32.7	91.2	Fundamental	/	РК
	V	2480.00	32.7	80.6	Fundamental	/	РК
	Н	2483.50	32.7	48.6	74.00	25.4	РК
	V	2483.50	32.7	47.9	74.00	26.1	РК
п	Н	4960.00	3.2	35.0	74.00	39.0	РК
	Н	7440.00	8.3	37.2	74.00	36.8	РК
	V	4960.00	3.2	31.2	74.00	42.8	РК
	V	7440.00	8.3	34.8	74.00	39.2	РК

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

- 2. Corrected Reading = Original Receiver Reading + Correct Factor
- 3. Margin = Limit Corrected Reading
- 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,

Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, Limit = 40.00dBuV/m. Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;

Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;

Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

## 8 Occupied Bandwidth

Test result: Tested

#### 8.1 Limit

None

#### 8.2 Measurement Procedure

The occupied bandwidth per RSS-Gen was measured using the Spectrum Analyzer.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

#### 8.3 Test Configuration



#### 8.4 The results of Occupied Bandwidth

Please refer to Appendix A



## 9 Antenna requirement

#### **Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **Result:**

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.



## **Appendix A: Test results**