

Antenna Specification

Specifications
Summary

ITEM	SPEC.	
Center Frequency	2402 MHz	0.15 dBi
	2442 MHz	0.11 dBi
	2484 MHz	0.21 dBi
MAX. GAIN	0.21 dBi	
Impedance	50Ω	

ITEM	SPEC.	
Center Frequency	5150 MHz	-0.35 dBi
	5300 MHz	0.88 dBi
	5500 MHz	1.51 dBi
	5800 MHz	0.73 dBi
MAX. GAIN	1.51 dBi	
Impedance	50Ω	

Antenna Photo & Length

天线类型/
ANT Type:

Metal


天线型号/
ANT Model:

BT/Wi-Fi ANT

制造商/
Manufactory:


YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
No.666 Hu'an Rd,Huli District Xiamen City, Fujian, P.R. China

天线图/ANT Photo




3D Antenna pattern

2402MHz




2442MHz



3D Antenna pattern


2484MHz



Point Values	Minimum Gain (dBi)	Maximum Gain (dBi)
Frequency (MHz)		
2402	-15.22	0.15
2442	-15.60	0.11
2484	-16.76	0.21


5150MHz

3D Antenna pattern




5300MHz

3D Antenna pattern




5500MHz

3D Antenna pattern



5800MHz

3D Antenna pattern



Point Values	Minimum Gain (dB)		Maximum Gain (dB)	
Frequency (MHz)				
5150	-19.7402		-0.35193	
5300	-15.4953		0.87825	
5500	-19.4714		1.50761	
5800	-31.4457		0.73362	