

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

| | |
|--------------------------|---|
| Applicant: | Scosche Industries Inc |
| Address of applicant: | 1550 Pacific Ave, Oxnard, CA 93033, USA |
| Manufacturer: | Shenzhen Sunveytech Co., Ltd |
| Address of manufacturer: | 5th Floor, Bldg A, Penglongpan Hight-tech Park, #11 Dafu Industrial Zone, Guanlan Street, Longhua New District, Shenzhen ,China |

General Description of EUT:

| | |
|-------------------|-----------------------|
| Product Name: | Car Camera |
| Trade Name: | / |
| Model No.: | WBUSSPF43 |
| Adding Model(s): | / |
| FCC ID: | IKQWBUSSPFC |
| Rated Voltage: | DC 5V; Battery DC3.6V |
| Battery capacity: | 2500mAh |

Technical Characteristics of EUT:

| | |
|-----------------------|--------------------------|
| Support Standards: | 802.11b |
| Frequency Range: | 2412-2462MHz for 802.11b |
| RF Output Power: | 13.09dBm (Conducted) |
| Type of Modulation: | DBPSK,BPSK,DQPSK,QPSK |
| Data Rate: | 1-11Mbps |
| Quantity of Channels: | 11 for 802.11b |
| Channel Separation: | 5MHz |
| Type of Antenna: | Integral Antenna |
| Antenna Gain: | 2.0dBi |

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | / | / | F/300 | 6 |
| 1500-100000 | / | / | 5 | 6 |

(b) Limits for General Population / Uncontrolled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | F/1500 | 30 |
| 1500-100000 | / | / | 1 | 30 |

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum Tune-Up output power: 14(dBm)

Maximum peak output power at antenna input terminal: 25.12(mW)

Prediction distance: >20(cm)

Prediction frequency: 2462(MHz)

Antenna gain: 2.0(dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.0079(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass