



Report No.:

T211229R01-SF

FCC ID: 2A4DE-3S001

Page: 1 / 34
Rev.: 01

SAR TEST REPORT

**FCC 47 CFR § 2.1093
IEEE Std 1528-2013**

for
TRIOS 5

Model: L1P-1F

Prepared for:

**3Shape TRIOS A/S
Holmens Kanal 7, 1060 Copenhagen K**

Prepared by

**Compliance Certification Services Inc.
Wugu Lab.**

**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan. (R.O.C.)**

Issue Date: September 1, 2022

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No.: T211229R01-SF

Revision History

Rev.	Issue Date	Revisions	Revised By
00	April 22, 2022	Initial Issue	Doris Chu
01	September 1, 2022	See the following Note Rev. (01)	Doris Chu

Rev. (01)

- 1.Revised Product name TRIOS to TRIOS 5, Model No. L1P-1 to L1P-1F and FCC ID SQG-60SIPT to 2A4DE-3S001 in page 1, 4, 6.
- 2.Revised Antenna gain in page 7.

Table of Contents



1	ATTESTATION OF TEST RESULTS	4
2	TEST SPECIFICATION, METHODS AND PROCEDURES.....	5
3	DEVICE UNDER TEST (DUT) INFORMATION	6
3.1	DUT DESCRIPTION	6
3.2	WIRELESS TECHNOLOGIES.....	7
4	SAR MEASUREMENT SYSTEM.....	8
4.1	SYSTEM COMPONENTS	9
4.2	SAR SCAN PROCEDURES	12
5	MEASUREMENT UNCERTAINTY	14
6	RF EXPOSURE CONDITIONS (TEST CONFIGURATIONS)	15
6.1	STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	15
6.2	REQUIRED TEST CONFIGURATIONS.....	18
7	DIELECTRIC PROPERTY MEASUREMENTS & SYSTEM CHECK.....	19
7.1	DIELECTRIC PROPERTY MEASUREMENTS	19
7.2	SYSTEM CHECK.....	22
8	CONDUCTED OUTPUT POWER MEASUREMENTS.....	24
8.1	WI-FI 5GHZ (U-NII BANDS)	24
8.2	BLUETOOTH.....	25
9	MEASURED AND REPORTED (SCALED) SAR RESULTS.....	27
9.1	WI-FI (U-NII BAND)	27
9.2	BLUETOOTH.....	27
10	SAR MEASUREMENT VARIABILITY	28
11	SIMULTANEOUS TRANSMISSION SAR ANALYSIS.....	29
11.1	SUM OF THE SAR FOR WI-FI & BT	32
12	EQUIPMENT LIST & CALIBRATION STATUS.....	33
13	FACILITIES.....	34
14	APPENDIXES.....	34

Report No.: T211229R01-SF

1 Attestation of Test Results

Applicant Name	3Shape TRIOS A/S	
Model Name	L1P-1F	
Applicable Standards	FCC 47 CFR § 2.1093 Published RF exposure KDB procedures IEEE Std 1528-2013	
Exposure Category	SAR Limits (W/Kg)	
	Extremities (hands, wrists, ankles, etc.) (10g of tissue)	
General population	4	
RF Exposure Conditions	Equipment Class - Highest Reported SAR (W/kg)	
	NII	DSS
Extremity	1.799	0.175
Simultaneous TX	3.212	
Receive EUT Date:	December 29, 2021	
Date Tested	March 21 ~ 25, 2022	
Test Results	Pass	

Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty. All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved & Released By:	Tested by:
	
Kevin Tsai Deputy Manager Compliance Certification Services Inc.	Sky Zhou Asst. Section Manager Compliance Certification Services Inc.

Report No.: T211229R01-SF

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures:

- 248227 D01 802.11 Wi-Fi SAR v02r02
- 447498 D01 General RF Exposure Guidance v06
- 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- 865664 D02 RF Exposure Reporting v01r02

In addition to the above, the following information was used:

- TCB workshop October, 2016; Page 7, RF Exposure Procedures (Bluetooth Duty Factor)

3 Device Under Test (DUT) Information

3.1 DUT Description

Applicant Name	3Shape TRIOS A/S
Applicant Address	Holmens Kanal 7, 1060 Copenhagen K
Manufacturer Name	3Shape TRIOS A/S
Manufacturer Address	Holmens Kanal 7, 1060 Copenhagen K
Product	TRIOS 5
Trade Name	TRIOS
Model No.	L1P-1F
Model Discrepancy	N/A
Device Dimension	Overall (Length x Width): 265 mm x 35 mm
Back Cover	<input checked="" type="checkbox"/> Normal Battery Cover <input type="checkbox"/> Normal Battery Cover with NFC <input type="checkbox"/> Wireless Charger Battery Cover <input type="checkbox"/> Wireless Charger Battery Cover with NFC <input type="checkbox"/> The Back Cover is not removable.
Battery Options	<input checked="" type="checkbox"/> Standard – Lithium-ion battery, Rating 3.6Vdc, 3300mAh <input type="checkbox"/> Extended (large capacity) <input type="checkbox"/> The rechargeable battery is not user accessible.
Hardware Version	2.2
Software Version	Laird Communications LRU tool 8.5.0.7 WiFi module driver version 8.5.0.7
Sample Stage	PVT

Report No.: T211229R01-SF

3.2 Wireless Technologies


Wireless technologies	Frequency bands	Peak Antenna Gain (dBi)	Operating mode	Duty Cycle used for SAR testing
Wi-Fi (Main)	5.2 GHz 5.8 GHz	-0.1	802.11n (HT20) 802.11n (HT40) 802.11ac (VHT20) 802.11ac (VHT40) 802.11ac (VHT80)	100% (802.11n/ac 20MHz BW) 100% (802.11n/ac 40MHz BW) 100% (802.11ac 80MHz BW)
Antenna Specification	Brand Name	TAOGLAS		
	Type	Monopole Flex PCB Antenna		
	Parts Number	FXP840.54.0018B		
Wi-Fi (Aux)	5.2 GHz 5.8 GHz	1.15	802.11n (HT20) 802.11n (HT40) 802.11ac (VHT20) 802.11ac (VHT40) 802.11ac (VHT80)	100% (802.11n/ac 20MHz BW) 100% (802.11n/ac 40MHz BW) 100% (802.11ac 80MHz BW)
Bluetooth	2.4 GHz	-3.95	BR,EDR,LE	76.8%
Antenna Specification	Brand Name	TAOGLAS		
	Type	Monopole Flex PCB Antenna		
	Parts Number	FXP840.54.0018B		

Notes:

- The sample selected for test was prototype that representative to production product and was provided by manufacturer
- Variant information between/among model numbers / trademarks is provided by the applicant, test results of this report are applicable to the sample EUT received of main test model name.
- Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received

Report No.: T211229R01-SF

4 SAR Measurement System






The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7 or Windows XP.
- DASY software version: NEO52 D10.3 S14.6.13.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.



Report No.: T211229R01-SF

4.1 System Components


DASY5 Measurement Server	
	<p>The DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE4 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.</p> <p>The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.</p>
	<p>The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.</p>
Data Acquisition Electronics (DAE)	
	<p>The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.</p>

Report No.: T211229R01-SF


EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements

	<p>Construction: Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p> <p>Calibration: Basic Broad Band Calibration in air: 10-3000 MHz. Conversion Factors (CF) for HSL 900 and HSL 1800 CF-Calibration for other liquids and frequencies upon request.</p> <p>Frequency: 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)</p> <p>Directivity: ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in HSL (rotation normal to probe axis)</p> <p>Dynamic Range: 10 μW/g to > 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μW/g)</p>
	<p>Dimensions: Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1 mm</p> <p>Application: High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.</p>

SAM Phantom

	<p>Construction: The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE1528: 2013. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.</p> <p>Shell Thickness: 2 ± 0.2 mm</p> <p>Filling Volume: Approx. 25 liters</p> <p>Dimensions: Height: 810mm; Length: 1000mm; Width: 500mm</p>
---	--

ELI Phantom

	<p>Construction: Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEEE1528: 2013 and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles</p> <p>Shell Thickness: 2.0 ± 0.2 mm (sagging: <1%)</p> <p>Filling Volume: Approx. 25 liters</p> <p>Dimensions: Major ellipse axis: 600 mm Minor axis: 400 mm 500mm</p>
---	--


Report No.: T211229R01-SF

Device Holder for SAM Twin Phantom



Construction: In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).

System Validation Kits for SAM Phantom



Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.


Frequency: 2450, 5300, 5600, 5800 MHz

Return loss: > 20 dB at specified validation position

Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz)

Dimensions:
D2450V2: dipole length: 51.5 mm; overall height: 290 mm
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm

System Validation Kits for ELI phantom



Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

Frequency: 2450, 5300, 5600, 5800 MHz

Return loss: > 20 dB at specified validation position

Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz)

Dimensions:
D2450V2: dipole length: 51.5 mm; overall height: 290 mm
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm

Report No.: T211229R01-SF

4.2 SAR Scan Procedures

Step 1: Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE1528 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Report No.: T211229R01-SF

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

- Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}$
Maximum zoom scan spatial resolution, normal to phantom surface	Uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Maximum zoom scan volume	x, y, z	$\geq 30 \text{ mm}$	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$	

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction

5 Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE1528: 2013 is not required in SAR reports submitted for equipment approval.

Therefore, the measurement uncertainty is not required.

6 RF Exposure Conditions (Test Configurations)

Refer to Appendixes 1 for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

6.1 Standalone SAR Test Exclusion Considerations

Since the *Dedicated Host Approach* is applied, the standalone SAR test exclusion procedure in KDB 447498 is applied in conjunction with KDB 616217 § 4.3 to determine the minimum test separation distance:

- When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
- When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.

Report No.: T211229R01-SF

SAR Test Exclusion Calculations for WLAN

Antennas < 50mm to adjacent edges

Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Calculated Threshold Value					
		dBm	mW	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4
Main Antenna															
Wi-Fi 5.2 GHz	5240	15.00	32	5	25	8	210	20	5	14.7 -MEASURE-	2.9 -EXEMPT-	9.2 -MEASURE-	> 50 mm	3.7 -EXEMPT-	14.7 -MEASURE-
Wi-Fi 5.8 GHz	5825	17.00	50	5	25	8	210	20	5	24.1 -MEASURE-	4.8 -EXEMPT-	15.1 -MEASURE-	> 50 mm	6 -EXEMPT-	24.1 -MEASURE-
Aux Antenna															
Wi-Fi 5.2 GHz	5240	18.00	63	5	25	20	210	8	5	28.8 -MEASURE-	5.8 -EXEMPT-	7.2 -EXEMPT-	> 50 mm	18 -MEASURE-	28.8 -MEASURE-
Wi-Fi 5.8 GHz	5825	18.00	63	5	25	20	210	8	5	30.4 -MEASURE-	6.1 -EXEMPT-	7.6 -MEASURE-	> 50 mm	19 -MEASURE-	30.4 -MEASURE-
Bluetooth	2480	10.00	10	5	25	20	210	8	5	3.1 -EXEMPT-	0.6 -EXEMPT-	0.8 -EXEMPT-	> 50 mm	2 -EXEMPT-	3.1 -EXEMPT-

Note(s):

According to KDB 447498, if the calculated threshold value is >7.5 then SAR testing is required.

Report No.: T211229R01-SF

SAR Test Exclusion Calculations for WLAN

Antennas > 50mm to adjacent edges

Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Calculated Threshold Value					
		dBm	mW	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4
Main Antenna															
Wi-Fi 5.2 GHz	5240	15.00	32	5	25	8	210	20	5	< 50 mm	< 50 mm	< 50 mm	1665.5 mW -EXEMPT-	< 50 mm	< 50 mm
Wi-Fi 5.8 GHz	5825	17.00	50	5	25	8	210	20	5	< 50 mm	< 50 mm	< 50 mm	1662.2 mW -EXEMPT-	< 50 mm	< 50 mm
Aux Antenna															
Wi-Fi 5.2 GHz	5240	18.00	63	5	25	20	210	8	5	< 50 mm	< 50 mm	< 50 mm	1665.5 mW -EXEMPT-	< 50 mm	< 50 mm
Wi-Fi 5.8 GHz	5825	18.00	63	5	25	20	210	8	5	< 50 mm	< 50 mm	< 50 mm	1662.2 mW -EXEMPT-	< 50 mm	< 50 mm
Bluetooth	2480	10.00	10	5	25	20	210	8	5	< 50 mm	< 50 mm	< 50 mm	1695.3 mW -EXEMPT-	< 50 mm	< 50 mm

Note(s):

According to KDB 447498, if the calculated Power threshold is less than the output power then SAR testing is required.

Report No.: T211229R01-SF

6.2 Required Test Configurations

The table below identifies the standalone test configurations required for this device according to the findings in Section 6.1:

Test Configurations	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4
Main Antenna						
Wi-Fi 5.2 GHz	Yes	No	Yes	No	No	Yes
Wi-Fi 5.8 GHz	Yes	No	Yes	No	No	Yes
Aux Antenna						
Wi-Fi 5.2 GHz	Yes	No	No	No	Yes	Yes
Wi-Fi 5.8 GHz	Yes	No	Yes	No	Yes	Yes
Bluetooth	No	No	No	No	No	No

Note(s):

Yes = Testing is required.

No = Testing is not required.

7 Dielectric Property Measurements & System Check

7.1 Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

The dielectric constant (ϵ_r) and conductivity (σ) of typical tissue-equivalent media recipes are expected to be within $\pm 5\%$ of the required target values; but for SAR measurement systems that have implemented the SAR error compensation algorithms documented in IEEE Std 1528-2013, to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, the tolerance for ϵ_r and σ may be relaxed to $\pm 10\%$. This is limited to frequencies $\leq 3\text{ GHz}$.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

Report No.: T211229R01-SF

Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16 MΩ⁺ resistivity HEC: Hydroxy thyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

Dielectric Property Measurements Results:

Date	Tissue Type	Frequency (MHz)	Relative Permittivity (ϵ_r)			Conductivity (σ)		
			Measured	Target	Delta (%)	Measured	Target	Delta (%)
2022/3/25	Head	2400	39.75	39.30	1.15	1.70	1.76	-3.24
		2450	39.52	39.20	0.82	1.76	1.80	-2.17
		2480	39.40	39.16	0.61	1.80	1.83	-1.80
2022/3/21	Head	5150	35.75	36.05	-0.83	4.79	4.61	3.95
		5200	35.69	36.00	-0.86	4.86	4.66	4.29
		5250	35.69	35.95	-0.72	4.85	4.71	2.99
2022/3/22	Head	5150	36.10	36.05	0.14	4.77	4.61	3.58
		5200	35.92	36.00	-0.22	4.83	4.66	3.73
		5250	35.96	35.95	0.03	4.85	4.71	2.87
2022/3/23	Head	5725	34.52	35.38	-2.43	5.41	5.20	4.10
		5800	34.51	35.30	-2.24	5.33	5.27	1.21
		5850	34.12	35.25	-3.21	5.30	5.32	-0.47
2022/3/24	Head	5725	34.65	35.38	-2.06	5.45	5.20	4.97
		5800	34.67	35.30	-1.78	5.32	5.27	1.02
		5850	34.33	35.25	-2.61	5.33	5.32	0.08

Report No.: T211229R01-SF

7.2 System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ± 0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube
- Distance between probe sensors and phantom surface was set to 2 mm.
- The dipole input power (forward power) was 250 mW (below 2GHz) and 100 mW
- The results are normalized to 1 W input power.

Report No.: T211229R01-SF

System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within $\pm 10\%$ of the manufacturer calibrated dipole SAR target. Refer to Appendix 2 for the SAR System Check Plots.

Date	Tissue Type	Dipole S/N	Input Power (mW)	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Delta 1g ± 10 (%)	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Delta 10g ± 10 (%)	Plot No.
2022/3/25	Head	D2450V2-727	250	13.00	53.90	52	-3.53	6.27	25.10	25.08	-0.08	1
2022/3/21	Head	D5GHzV2-1040-5200	100	7.26	76.90	72.6	-5.59	2.09	21.80	20.9	-4.13	2
2022/3/22	Head	D5GHzV2-1040-5200	100	7.78	76.90	77.8	1.17	2.24	21.80	22.4	2.75	3
2022/3/23	Head	D5GHzV2-1040-5800	100	7.91	77.50	79.1	2.06	2.23	21.90	22.3	1.83	4
2022/3/24	Head	D5GHzV2-1040-5800	100	8.22	77.50	82.2	6.06	2.32	21.90	23.2	5.94	5

8 Conducted Output Power Measurements

8.1 Wi-Fi 5GHz (U-NII Bands)

The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures.

When the same transmission mode configurations have the same maximum output power on the same channel for the 802.11 a/g/n/ac modes, the channel in the lower order/sequence 802.11 mode (i.e. a, g, n then ac) is selected.

SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band. Additional output power measurements were not deemed necessary.

Measured Results

Measured Results										
Band	Mode	Data Rate	Ch #	Freq. (MHz)	Meas. Avg Pwr (dBm)		Tune-up Limit (dBm)		SAR Test (Yes/No)	
					Chain 0	Chain 1	Chain 0	Chain 1	Chain 0	Chain 1
5.2GHz (U-NII 1)	802.11n (HT20)	MCS0	36	5180	10.57	13.11	11.0	13.5	Yes	Yes
			40	5200	14.62	17.31	15.0	18.0		
			44	5220	14.66	17.56				
			48	5240	14.81	17.65				
	802.11ac (VHT20)	MCS0	36	5180	10.70	13.03	11.0	13.5	No	No
			40	5200	14.68	17.18	15.0	18.0		
			44	5220	14.72	17.49				
			48	5240	14.74	17.60				
	802.11n (HT40)	MCS0	38	5190	10.27	12.12	10.5	12.5	No	No
			46	5230	13.56	15.65	14.0	16.0		
	802.11ac (VHT40)	MCS0	38	5190	10.30	12.08	10.5	12.5	No	No
			46	5230	13.58	15.63	14.0	16.0		
802.11ac (VHT80)	MCS0	42	5210	8.21	9.65	8.5	10.0	No	No	
5.8GHz (U-NII 3)	802.11n (HT20)	MCS0	149	5745	16.81	17.07	17.0	18.0	Yes	Yes
			157	5785	16.86	17.44				
			165	5825	16.90	17.61				
	802.11ac (VHT20)	MCS0	149	5745	16.82	17.31	17.0	18.0	No	No
			157	5785	16.79	17.43				
			165	5825	16.83	17.62				
	802.11n (HT40)	MCS0	151	5755	15.54	15.29	16.0	15.5	No	No
			159	5795	15.58	15.47				
	802.11ac (VHT40)	MCS0	151	5755	15.83	15.28	16.0	15.5	No	No
			159	5795	15.81	15.46				
	802.11ac (VHT80)	MCS0	155	5775	13.85	13.88	14.0	14.0	No	No

Report No.: T211229R01-SF

8.2 Bluetooth.

Average Power Measured Results


Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Meas. Avg Pwr (dBm)	Meas. Avg Pwr (mW)	Tune-up Limit (dBm)	SAR Test (Yes/No)
2.4	GFSK	1 Mbps	0	2402	9.89	9.75	10.0	Yes
			39	2441	9.73	9.40		
			78	2480	9.71	9.35		
	EDR, $\pi/4$ DQPSK	2 Mbps	0	2402	6.85	4.84	7.0	No
			39	2441	6.78	4.76		
			78	2480	6.63	4.60		
	EDR, 8-DPSK	3 Mbps	0	2402	6.74	4.72	7.0	No
			39	2441	6.68	4.66		
			78	2480	6.59	4.56		
	LE, GFSK	1 Mbps	0	2402	6.91	4.91	7.0	No
			19	2440	6.84	4.83		
			39	2480	6.75	4.73		

Duty Factor Measured Results

Mode	Type	T on (ms)	Period (ms)	Duty Cycle	Crest Factor (1/duty cycle)
GFSK	DH5	2.88	3.75	76.80%	1.30

Duty Cycle plots

GFSK



Report No.: T211229R01-SF

9 Measured and Reported (Scaled) SAR Results

9.1 Wi-Fi (U-NII Band)

RF Exposure Conditions	Frequency Band	Mode	Antenna	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Duty Cycle	Power (dBm)		10-g SAR (W/kg)		Plot No.
									Tune-up Limit	Meas.	Meas.	Scaled	
Extremity	5.2GHz (U-NII 1)	802.11n20	SISO Main 0	0	Front	48	5240	100.0%	15.0	14.81	1.170	1.222	1
					Edge 1	48	5240	100.0%	15.0	14.81	0.586	0.612	
					Edge 4	48	5240	100.0%	15.0	14.81	0.312	0.326	
		802.11n20	SISO Aux 1	0	Front	48	5240	100.0%	18.0	17.65	1.660	1.799	2
					Edge 3	48	5240	100.0%	18.0	17.65	0.989	1.072	
					Edge 4	48	5240	100.0%	18.0	17.65	0.417	0.452	
Extremity	5.8 (U-NII 3)	802.11n20	SISO Main 0	0	Front	165	5825	100.0%	17.0	16.90	1.210	1.238	3
					Edge 1	165	5825	100.0%	17.0	16.90	0.757	0.775	
					Edge 4	165	5825	100.0%	17.0	16.90	0.357	0.365	
		802.11n20	SISO Aux 1	0	Front	165	5825	100.0%	18.0	17.61	1.330	1.455	4
					Edge 1	165	5825	100.0%	18.0	17.61	0.215	0.235	
					Edge 3	165	5825	100.0%	18.0	17.61	0.785	0.859	
					Edge 4	165	5825	100.0%	18.0	17.61	0.121	0.132	

9.2 Bluetooth

RF Exposure Conditions	Mode	Antenna	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Duty Cycle	Power (dBm)		10-g SAR (W/kg)		Plot No.
								Tune-up Limit	Meas.	Meas.	Scaled	
Extremity	GFSK	Aux 1	0	Front	0	2402	76.8%	10.0	9.89	0.131	0.175	5
				Edge 4	0	2402	76.8%	10.0	9.89	0.024	0.032	

Report No.: T211229R01-SF

10 SAR Measurement Variability

In accordance with published RF Exposure KDB 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.8 or 2 W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.8 or 2 W/kg (1-g or 10-g respectively), repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 or 3.6 W/kg (~ 10% from the 1-g or 10-g respective SAR limit).
- 4) Perform a third repeated measurement only if the original, first, or second repeated measurement is ≥ 1.5 or 3.75 W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

N/A

11 Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance provides two procedures for determining simultaneous transmission SAR test exclusion: Sum of SAR and SAR to Peak Location Ratio (SPLSR)

Sum of SAR

To qualify for simultaneous transmission SAR test exclusion based upon Sum of SAR the sum of the reported standalone SARs for all simultaneously transmitting antennas shall be below the applicable standalone SAR limit. If the sum of the SARs is above the applicable limit then simultaneous transmission SAR test exclusion may still apply if the requirements of the SAR to Peak Location Ratio (SPLSR) evaluation are met.

SAR to Peak Location Ratio (SPLSR)

KDB 447498 D01 General RF Exposure Guidance explains how to calculate the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i$$

Where:

SAR₁ is the highest measured or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR₂ is the highest measured or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

R_i is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$

In order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i \leq 0.04$$

When an individual antenna transmits at on two bands simultaneously, the sum of the highest reported SAR for the frequency bands should be used to determine SAR₁ or SAR₂. When SPLSR is necessary, the smallest distance between the peak SAR locations for the antenna pair with respect to the peaks from each antenna should be used.

The antennas in all antenna pairs that do not qualify for simultaneous transmission SAR test exclusion must be tested for SAR compliance, according to the enlarged zoom scan and volume scan post-processing procedures in KDB Publication 865664 D01

Report No.: T211229R01-SF

Simultaneous Transmission Condition

RF Exposure Condition	Item	Capable Transmit Configurations			
Standalone	1	U-NII (Main)	+	U-NII (Aux)	
	2	U-NII (Main)	+	U-NII (Aux)	+ BT

Notes:

1. Wi-Fi SISO mode SAR result can also represent for MIMO mode SAR and is used for MIMO mode simultaneous transmission analysis because antennas are not overlapping and the MIMO mode maximum power is equal or less than SISO mode.

Report No.: T211229R01-SF

Estimated SAR for Simultaneous Transmission SAR Analysis

Considerations for SAR estimation

- When standalone SAR test exclusion applies, standalone SAR must also be estimated to determine simultaneous transmission SAR test exclusion.
- Dedicated Host Approach criteria for SAR test exclusion is likewise applied to SAR estimation, with certain distinctions between test exclusion and SAR estimation:
 - When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied for SAR estimation; this is the same between test exclusion and SAR estimation calculations.
 - When the separation distance from the antenna to an adjacent edge is > 5 mm but ≤ 50 mm, the actual antenna-to-edge separation distance is applied for SAR estimation.
 - When the minimum test separation distance is > 50 mm, the estimated SAR value is 0.4 W/kg
- Please refer to Estimated SAR Tables to see which test positions are inherently compliant as they consist of only estimated SAR values for all applicable transmitters and consequently will always have sum of SAR values < 1.2 W/kg. Simultaneous transmission SAR analysis was therefore not performed for these test positions.

Estimated SAR for WLAN

Estimated SAR for WLAN															
Tx Interface	Frequency (MHz)	Output Power		Separation Distances (mm)						Estimated 1-g SAR Value (W/kg)					
		dBm	mW	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4	Front	Rear	Edge 1	Edge 2	Edge 3	Edge 4
Main Antenna															
Wi-Fi 5.2 GHz	5240	15.00	32	5	25	8	210	20	5	-MEA SURE-	0.156	-MEA SURE-	0.400	0.195	-MEA SURE-
Wi-Fi 5.8 GHz	5825	17.00	50	5	25	8	210	20	5	-MEA SURE-	0.257	-MEA SURE-	0.400	0.322	-MEA SURE-
Aux Antenna															
Wi-Fi 5.2 GHz	5240	18.00	63	5	25	20	210	8	5	-MEA SURE-	0.308	0.385	0.400	-MEA SURE-	-MEA SURE-
Wi-Fi 5.8 GHz	5825	18.00	63	5	25	20	210	8	5	-MEA SURE-	0.324	-MEA SURE-	0.400	-MEA SURE-	-MEA SURE-
Bluetooth	2480	10.00	10	5	25	20	210	8	5	0.168	0.034	0.042	0.400	0.105	0.168

Report No.: T211229R01-SF

11.1 Sum of the SAR for Wi-Fi & BT

Test Position	Standalone SAR (W/kg)			Σ 10-g SAR (W/kg)	
	U-NII		BT	U-NII + U-NII	U-NII + U-NII + BT
	Chain 0 ①	Chain 1 ②	③	① + ②	① + ② + ③
Front	1.238	1.799	0.175	3.037	3.212
Edge 1	0.775	0.235	0.042	1.010	1.052
Edge 3	0.322	1.072	0.105	1.394	1.499
Edge 4	0.365	0.452	0.032	0.817	0.849

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either the sum of the 10 g SAR is < 4.0 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

Report No.: T211229R01-SF

12 Equipment List & Calibration Status

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Network Analyzer	SPEAG	DAKS_VNA R140	0140417	2023/1/124
Dielectric Assessment Kit	SPEAG	DAKS-3.5	1001	2023/1/26
Thermometer	TES	TES-1306	210801061	2022/10/21

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Signal Generator	Agilent	N5181A	MY50144143	2022/5/13
Power Meter	Agilent	E4417A	MY52240003	2022/10/26
Power Sensor	Agilent	E9301H	MY52200004	2022/10/24
Power Meter	Anritsu	ML2496A	2136002	2022/12/6
Power Sensor	Anritsu	MA2411B	1911387	2022/8/19
Dual Directional Coupler	Agilent	772D	MY46151242	2022/9/10
Amplifier	EMCI	ZVE-8G	S1900977	N/A
Data Acquisition Electronics	SPEAG	DAE4	1260	2022/9/19
Dosimetric E-Field Probe	SPEAG	EX3DV4	3665	2022/8/24
System Validation Dipole	SPEAG	D2450V2	727	2022/4/13
System Validation Dipole	SPEAG	D5GHzV2	1040	2022/6/3
Humidity/Temp meter	TECPEL	DTM-303A	TP130074	2022/4/26
Thermometer	TES	TES-1306	210801061	2022/10/21

Software Version

DASY NEO52 D10.3 S14.6.13

SEMCAD-X-PostPro

Report No.: T211229R01-SF

13 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

14 Appendixes

Exhibit	Content
1	SAR Setup Photos
2	SAR System Check Plots
3	Highest SAR Test Plots
4	SAR DAE and Probe Calibration Certificates
5	SAR Dipole Calibration Certificates

END OF REPORT