

Appendix B

Highest Test Plots

Table of Contents

1. BT Body-worn 0mm SAR.....3

1. BT Body-worn 0mm SAR

Date: 17.10.2024

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24092429-1E

DUT: Incase Bluetooth Keyboard; Model Number:OB1898; Serial: S24092429-001

Communication System: UID 0, Bluetooth (0); Communication System Band: BLE; Frequency: 2440 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005
Medium parameters used: $f = 2440 \text{ MHz}$; $\sigma = 1.783 \text{ S/m}$; $\epsilon_r = 40.827$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ConvF(7.95, 7.95, 7.95); Calibrated: 29.04.2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sa1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1197
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Bottom side BLE 2440/Area Scan (11x13x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$
Maximum value of SAR (measured) = 0.107 W/kg

Configuration/Bottom side BLE 2440/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 3.416 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 0.133 W/kg
SAR(1 g) = 0.127 W/kg; SAR(10 g) = 0.122 W/kg
Maximum value of SAR (measured) = 0.133 W/kg

