


Scale Type

Span 4.650 GHz Sweep 8.000 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Graph 802.11n40 ANT1 5755 MCS0 Frequency Band2


#VBW 3.0 MHz

Center 3.325 GHz #Res BW 1.0 MHz


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/












Freq Offset 0 Hz

Scale Type

Log

Span 4.650 GHz Sweep 8.000 ms (30000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test Graph 802.11n40 ANT1 5795 MCS0 Frequency Band2

#VBW 3.0 MHz

Center 3.325 GHz #Res BW 1.0 MHz











Page 170 of 205

11. Radiated Spurious Emission

11.1 Measurement Limit

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

	Applicable to	Limit		
Restricted	789033 D02 General UNII Test	Field stre	ength at 3m (dBuV/m)	
bands	Procedures New Rules v02r01	PK: 74	AV: 54	
	Applicable to	EIRP Limit (dBm/MHz)	Equivalent field Strength at 3m (dBuV/m)	
Out of the	FCC 15.407(b)(1)			
restricted bands	15.407(b)(2)	PK: -27	PK: 68.2	
	15.407(b)(3)			
	15.407(b)(4)	See Note 2		

Note 1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

E =
$$\frac{1000000 - \sqrt{30 P}}{3}$$
 µV/m, where P is the eirp (Watts).

Note 2: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.



Page 171 of 205

11.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Page 172 of 205

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.Section G) Unwanted emissions measurement.

♦ Procedure for Unwanted Emissions Measurements Below 1000MHz:

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

♦ Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz:


- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

Procedures for Average Unwanted Emissions Measurements Above 1000MHz:

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Procedures for Average Unwanted Emissions Measurements Above 1000MHz:


- RBW = 1 MHz
- VBW = 3 MHz Detector = power averaging (rms), set span/(# of points in sweep) ≥ RBW/2.
- Averaging type = power averaging (RMS)
- The correction factor shall be offset is 10 $\log (1/x)$, where x is the duty cycle.






11.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz






11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

Radiated Emission Test Results at 30MHz-1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n(20MHz)_5180MHz	Antenna	Horizontal




1 39.4371 6.41 13.66 20.07 40.00 -19.93 peak 2 119.8556 6.03 16.40 22.43 43.50 -21.07 peak 3 216.0240 8.70 14.42 23.12 46.00 -22.88 peak 4 447.9822 6.15 24.82 30.97 46.00 -15.03 peak 5 601.4265 6.16 25.11 31.27 46.00 -14.73 peak	No.	Mi	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
2 119.8556 6.03 16.40 22.43 43.50 -21.07 peak 3 216.0240 8.70 14.42 23.12 46.00 -22.88 peak 4 447.9822 6.15 24.82 30.97 46.00 -15.03 peak 5 601.4265 6.16 25.11 31.27 46.00 -14.73 peak			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
3 216.0240 8.70 14.42 23.12 46.00 -22.88 peak 4 447.9822 6.15 24.82 30.97 46.00 -15.03 peak 5 601.4265 6.16 25.11 31.27 46.00 -14.73 peak	1		39.4371	6.41	13.66	20.07	40.00	-19.93	peak
4 447.9822 6.15 24.82 30.97 46.00 -15.03 peak 5 601.4265 6.16 25.11 31.27 46.00 -14.73 peak	2		119.8556	6.03	16.40	22.43	43.50	-21.07	peak
5 601.4265 6.16 25.11 31.27 46.00 -14.73 peak	3		216.0240	8.70	14.42	23.12	46.00	-22.88	peak
	4		447.9822	6.15	24.82	30.97	46.00	-15.03	peak
6 * 903.3094 5.80 31.34 37.14 46.00 -8.86 peak	5		601.4265	6.16	25.11	31.27	46.00	-14.73	peak
	6	*	903.3094	5.80	31.34	37.14	46.00	-8.86	peak

Result: Pass



EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n(20MHz)_5180MHz	Antenna	Vertical



No.	Mk.	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	67.2022	14.80	17.03	31.83	40.00	-8.17	peak
2		146.8877	9.23	18.20	27.43	43.50	-16.07	peak
3		216.0240	14.60	16.70	31.30	46.00	-14.70	peak
4		443.2943	6.87	25.95	32.82	46.00	-13.18	peak
5		714.1734	6.87	28.60	35.47	46.00	-10.53	peak
6		935.5463	7.01	30.40	37.41	46.00	-8.59	peak

Result: Pass

Note:

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. All test modes had been pre-tested, Refer to Chapter 5 of the report for details.



Page 176 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name IMILAB C30 Dual		Model Name	CMSXJ111A
Temperature	22.7℃ Relative Humidity		56.9%
Pressure	ssure 960hPa Test Voltage		DC 5V by adapter
Test Mode	802.11n20_5180MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type		
10360.042	46.90	9.14	56.04	68.20	-12.16	peak		
15540.063	40.20	10.22	50.42	74.00	-23.58	peak		
15540.063	32.15	10.22	42.37	54.00	-11.63	AVG		
Remark:	Remark:							
Factor = Antenna Factor + Cable Loss – Pre-amplifier.								

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type		
10360.042	46.07	9.14	55.21	68.20	-12.99	peak		
15540.063	40.98	10.22	51.20	74.00	-22.80	peak		
15540.063	32.92	10.22	43.14	54.00	-10.86	AVG		
Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.								

Result: Pass



Page 177 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5200MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
10400.042	46.43	9.14	55.57	68.20	-12.63	peak	
15600.063	40.38	10.22	50.60	74.00	-23.40	peak	
15600.063	32.21	10.22	42.43	54.00	-11.57	AVG	
Remark:							
Factor = Antenna Factor + Cable Loss – Pre-amplifier.							

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	- value Type			
10400.042	46.57	9.14	55.71	68.20	-12.49	peak			
15600.063	40.90	10.22	51.12	74.00	-22.88	peak			
15600.063	32.36	10.22	42.58	54.00	-11.42	AVG			
Remark:	Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

Result: Pass



Page 178 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5240MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
10480.042	46.93	9.14	56.07	68.20	-12.13	peak			
15720.063	40.96	10.22	51.18	74.00	-22.82	peak			
15720.063	32.86	10.22	43.08	54.00	-10.92	AVG			
Remark:	Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
10480.042	46.68	9.14	55.82	68.20	-12.38	peak			
15720.063	40.79	10.22	51.01	74.00	-22.99	peak			
15720.063	32.72	10.22	42.94	54.00	-11.06	AVG			
Remark:	Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

Result: Pass



Page 179 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5260MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10520.022	46.10	9.14	55.24	68.20	-12.96	peak
15780.054	40.30	10.22	50.52	74.00	-23.48	peak
15780.054	32.04	10.22	42.26	54.00	-11.74	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
10520.022	46.59	9.14	55.73	68.20	-12.47	peak			
15780.054	40.45	10.22	50.67	74.00	-23.33	peak			
15780.054	33.00	10.22	43.22	54.00	-10.78	AVG			
Remark:	Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

Result: Pass



Page 180 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5300MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10600.022	50.52	9.14	59.66	74.00	-14.34	peak
10600.022	34.61	9.14	43.75	54.00	-10.25	AVG
15900.045	49.91	10.22	60.13	74.00	-13.87	peak
15900.045	33.30	10.22	43.52	54.00	-10.48	AVG
Remark:						

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10600.022	50.77	9.14	59.91	74.00	-14.09	peak
10600.022	34.71	9.14	43.85	54.00	-10.15	AVG
15900.045	49.14	10.22	59.36	74.00	-14.64	peak
15900.045	33.37	10.22	43.59	54.00	-10.41	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Result: Pass



Page 181 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5320MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10640.015	50.67	9.14	59.81	74.00	-14.19	peak
10640.015	34.92	9.14	44.06	54.00	-9.94	AVG
15900.045	49.36	10.22	59.58	74.00	-14.42	peak
15900.045	33.50	10.22	43.72	54.00	-10.28	AVG
Remark:	1		1			•
Factor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10640.015	50.29	9.14	59.43	74.00	-14.57	peak
10640.015	34.10	9.14	43.24	54.00	-10.76	AVG
15900.045	49.54	10.22	59.76	74.00	-14.24	peak
15900.045	33.13	10.22	43.35	54.00	-10.65	AVG
Remark:						

Radiated Emission Above 1GHz-Vertical

Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 182 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5500MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type		
11000.056	46.06	9.14	55.20	68.20	-13.00	peak		
11000.056	32.58	10.22	42.80	54.00	-11.20	AVG		
16500.023	40.22	10.22	50.44	74.00	-23.56	peak		
Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.								

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type				
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	- value Type				
11000.056	46.19	9.14	55.33	68.20	-12.87	peak				
11000.056	32.46	10.22	42.68	54.00	-11.32	AVG				
16500.023	40.86	10.22	51.08	74.00	-22.92	peak				
Remark:	Remark:									
Factor = Anter	Factor = Antenna Factor + Cable Loss – Pre-amplifier.									
				_						

Result: Pass



Page 183 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5580MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
11200.022	46.77	9.14	55.91	68.20	-12.29	peak			
11200.022	32.86	10.22	43.08	54.00	-10.92	AVG			
16800.025	40.06	10.22	50.28	74.00	-23.72	peak			
Remark:	Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type				
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type				
11200.022	46.98	9.14	56.12	68.20	-12.08	peak				
11200.022	32.10	10.22	42.32	54.00	-11.68	AVG				
16800.025	40.64	10.22	50.86	74.00	-23.14	peak				
Remark:	Remark:									
Factor = Anter	Factor = Antenna Factor + Cable Loss – Pre-amplifier.									

Result: Pass



Page 184 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.1n20_5700MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type		
11400.025	46.67	9.14	55.81	68.20	-12.39	peak		
11400.025	32.15	10.22	42.37	54.00	-11.63	AVG		
17100.056	40.03	10.22	50.25	74.00	-23.75	peak		
Remark:								
Factor = Antenna Factor + Cable Loss – Pre-amplifier.								

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type				
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type				
11400.025	46.74	9.14	55.88	68.20	-12.32	peak				
11400.025	32.50	10.22	42.72	54.00	-11.28	AVG				
17100.056	40.81	10.22	51.03	74.00	-22.97	peak				
Remark:	Remark:									
Factor = Antenna Factor + Cable Loss – Pre-amplifier.										

Result: Pass



Page 185 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5745MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type				
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type				
11490.042	46.66	9.14	55.80	68.20	-12.40	peak				
11490.042	32.81	10.22	43.03	54.00	-10.97	AVG				
17235.063	40.38	10.22	50.60	74.00	-23.40	peak				
Remark:	Remark:									
Factor = Antenna Factor + Cable Loss – Pre-amplifier.										

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11490.042	46.53	9.14	55.67	68.20	-12.53	peak
11490.042	32.57	10.22	42.79	54.00	-11.21	AVG
17235.063	40.58	10.22	50.80	74.00	-23.20	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass



Page 186 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5785MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11570.042	46.94	9.14	56.08	68.20	-12.12	peak
11570.042	32.96	10.22	43.18	54.00	-10.82	AVG
17355.063	40.06	10.22	50.28	74.00	-23.72	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11570.042	46.33	9.14	55.47	68.20	-12.73	peak
11570.042	32.12	10.22	42.34	54.00	-11.66	AVG
17355.063	40.24	10.22	50.46	74.00	-23.54	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass



Page 187 of 205

Radiated Emissions Test Results Above 1GHz

EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	22.7℃	Relative Humidity	56.9%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n20_5825MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz-Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11650.042	47.83	9.14	56.97	68.20	-11.23	peak
11650.042	37.00	10.22	47.22	54.00	-6.78	AVG
17475.063	40.61	10.22	50.83	74.00	-23.17	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Radiated Emission Above 1GHz-Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11650.042	47.07	9.14	56.21	68.20	-11.99	peak
11650.042	36.79	10.22	47.01	54.00	-6.99	AVG
17475.063	40.18	10.22	50.40	74.00	-23.60	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass

Note:

- The amplitude of other spurious emissions from 1GHz to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Amplifier gain, Margin=Measure Result-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.
- 4. All test modes had been pre-tested. Refer to Chapter 5 of the report for details.



EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11a20 5180MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass





EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11a20 5180MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass




EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n40 5190MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass






EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n40 5190MHz	Antenna	Vertical


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass





EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3°C	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11a_5320MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass





EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11a_5320MHz	Antenna	Vertical


Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass






EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n40_5310MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass





EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3°C	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n40_5310MHz	Antenna	Vertical


Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass





EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11a20_5500MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass






EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11a20_5500MHz	Antenna	Vertical


Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass






EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3°C	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n40_5510MHz	Antenna	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass





EUT Name	IMILAB C30 Dual	Model Name	CMSXJ111A
Temperature	21.3℃	Relative Humidity	48%
Pressure	960hPa	Test Voltage	DC 5V by adapter
Test Mode	802.11n40_5510MHz	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass



Page 200 of 205

Note:

- 1. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.
- 2. All test modes had been pre-tested, Refer to Chapter 5 of the report for details.





12. AC Power Line Conducted Emission Test


12.1 Measurement limit

Fraguenay	Maximum RF Line Voltage		
Frequency	Q.P (dBµV)	Average (dBμV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

12.2 Block Diagram of Line Conducted Emission Test





Page 202 of 205

12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 Ohm load; the second scan had Line 1 connected to a 50 Ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case was reported on the Summary Data page.
- The worst mode is 802.11n20 5180MHz.

ь1



12.5 Test Result of Line Conducted Emission Test

AC Power Line Conducted Emission Test				
Test Mode	802.11n(20MHz)5180MHz	LISN Line	Hot Side	



MEASUREMENT RESULT: "agc_fin"

20	025/1/10 16:	57					
	Frequency MHz	Level dBµV			Margin dB	Detector	Line
	0.530000	29.20	10.3	56	26.8	QP	L1
	0.674000	39.70	10.3	56	16.3	QP	L1
	0.718000	32.40	10.3	56	23.6	QP	L1
	1.010000	29.20	10.4	56	26.8	QP	L1
	2.206000	26.70	10.5	56	29.3	QP	L1

28.10 13.7 60 31.9 QP

MEASUREMENT RESULT: "agc fin2"

2	025/1/10 16:5	57					
	Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
	0.678000	34.40	10.3	46	11.6	AV	L1
	0.998000	23.70	10.4	46	22.3	AV	L1
	2.242000	20.90	10.5	46	25.1	AV	L1
	2.554000	20.50	10.5	46	25.5	AV	L1
	3.498000	19.80	10.6	46	26.2	AV	L1
	3.806000	19.70	10.6	46	26.3	AV	L1

Result: Pass


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

16.582000

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



AC Power Line Conducted Emission Test				
Test Mode	802.11n(40MHz)5180MHz	LISN Line	Neutral Side	



MEASUREMENT RESULT: "agc_fin"

2025/1/10	16:55					
Frequen M	.cy Leve Hz dBp			Margin dB	Detector	Line
0.1540	00 34.2	10.3	66	31.6	QP	N
0.2420	00 30.4	10.3	62	31.6	QP	N
0.6940	00 32.1	.0 10.3	56	23.9	QP	N
1.3500	00 25.3	10.4	56	30.7	QP	N
2.2860	00 22.5	0 10.5	56	33.5	QP	N
3.8340	00 21.3	10.6	56	34.7	QP	N

MEASUREMENT RESULT: "agc_fin2"

2025/1/10 16:55											
Frequenc MH	-	Transd dB	Limit dBµV	Margin dB	Detector	Line					
0.35800	0 21.30	10.3	49	27.5	AV	N					
0.68200	0 29.10	10.3	46	16.9	AV	N					
1.00200	0 21.30	10.4	46	24.7	AV	N					
2.28600	0 17.30	10.5	46	28.7	AV	N					
3.84600	0 16.30	10.6	46	29.7	AV	N					
15.64200	0 17.80	13.4	50	32.2	AV	N					

Result: Pass



Page 205 of 205

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC05877241202AP02

Appendix II: Photographs of EUT

Refer to the Report No.: AGC05877241202AP03

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.