

## RF Exposure Evaluation

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## Test Result of RF Exposure Evaluation

Band	Frequency	Max output power (dBm)	Output power (mW)	Antenna gain (dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Verdict
BT EDR	2441MHz	9.59	9.10	4.60	0.0052	1.0	PASS
BLE	2480MHz	2.71	1.87	4.60	0.0011	1.0	
2.4G WIFI	2412MHz ANT 2	14.57	28.64	3.5	0.0128	1.0	
	2437MHz MIMO	8.65	7.33	8.32	0.0099	1.0	
5.2G WIFI	5190MHz ANT 1	13.74	23.66	4.1	0.0121	1.0	
	5210MHz MIMO	11.09	12.85	7.57	0.0146	1.0	
5.3G WIFI	5270MHz ANT 1	14.13	25.88	3.7	0.0120	1.0	
	5270MHz MIMO	11.8	15.14	7.22	0.0159	1.0	
5.6G WIFI	5500MHz ANT 2	13.92	24.66	4.5	0.0138	1.0	
	5550MHz MIMO	11.43	13.90	8.18	0.0182	1.0	
5.8G WIFI	5795MHz ANT 2	14.53	28.38	3.7	0.0132	1.0	
	5795MHz MIMO	11.44	13.93	7.88	0.0170	1.0	

BT and WIFI Simultaneous Transmission:

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$$

BT EDR + 2.4G WIFI MIMO+5.6G WIFI=(0.0052/1)+(0.0128/1)+(0.0182/1)=0.0052+0.0128+0.0182=0.0362<1

The max power density is less than MPE exempt limit, so it is compliance.