Wireless Phone Charger

The Wireless Phone Charger (Model name: J48800) is designed for Lucid Gravity Model, which can charge up to 2 Qi-enabled smartphones or earphones at up to 15W simultaneously.

The operating frequency of the Wireless Phone Charger is 127.7kHz and it doesn't generate any RF power.

Simply place the smartphone or earphone on the Wireless Phone Charger, it will automatically start charging when the vehicle is powered on. The devices will not continue to charge if it is left plugged in after the driver exits the vehicle. Also, the Wireless Phone Charger will not charge the device(s) if the vehicle is turn off.

Use Cases:		In Arpods (Hisridental) In Phone (Vertical)	Le Airpods (Vertical) Le Phone (Vertical)
	In Airpods	-	19
		1a Phone (Horizontal)	2x Phone (Vertical)
		-	1

NOTE: The Wireless Phone Charger may not work properly if the device(s) case is too large or it's metal. Take the device(s) out of the case and place it on the charger if the above problems above occur.

WPT 127.7 KHz: 8.76 dBuA/m@10m

FCC and IC Certification

Component	Manufacturer	Model	FCC ID	IC ID
Wireless Phone Charger	Lucid	J48800	2AXZJ-J48800	27970-J48800

Caution: This equipment and its antennas must not be co-located or operated with another antenna or transmitter.

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment

off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Federal Communication Commission (FCC) Radiation Exposure Statement

This device has been tested and meets applicable limits for Radio Frequency (RF) exposure.

This equipment should be installed and operated with minimum distance 10 cm between the radiator & your body.

Canada

CAN ICES-003 (B)/NMB-003(B)

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- This device may not cause interference.
- This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- L'appareil ne doit pas produire de brouillage;
- L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

RF Exposure Information (MPE)

This device has been tested and meets applicable limits for Radio Frequency (RF) exposure. This equipment should be installed and operated with minimum distance 10 cm between the radiator & your body.

Informations d'exposition RF (MPE)

Cet appareil a été testé et répond aux limites applicables en matière d'exposition aux radiofréquences (RF). Cet équipement doit être installé et utilisé avec une distance minimale de 10 cm entre le radiateur et votre corps.

CE Compliance

Hereby, Lucid USA, Inc. declares that the radio equipment type J48800 is in compliance with Directive 2014/53/EU.

UK Compliance

Hereby, Lucid USA, Inc. declares that the radio equipment type J48800 is in compliance with the Radio Equipment Regulations 2017 (SI 2017/1206).

RF Exposure Information (MPE)

This device has been tested and meets applicable limits for Radio Frequency (RF) exposure.

This equipment should be installed and operated with minimum distance 10 cm between the radiator & your body.

Informations d'exposition RF (MPE)

Cet appareil a été testé et répond aux limites applicables en matière d'exposition aux radiofréquences (RF). Cet équipement doit être installé et utilisé avec une distance minimale de 10 cm entre le radiateur et votre corps.