





RF Exposure Evaluation Report

FCC ID : 2AENP-MTB03L

Equipment: True Wireless In-Ear Headphones

Brand Name : Montblanc

Model Name : MTB 03

Applicant : Montblanc-Simplo GmbH

Hellgrundweg 100, 22525 Hamburg, Germany

Manufacturer : Montblanc-Simplo GmbH

Hellgrundweg 100, 22525 Hamburg, Germany

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Jul. 20, 2021, and testing was started from Jan. 24, 2022 and completed on Mar. 19, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB 447498 D04 Interim General RF Exposure Guidance v01 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 5

FAX: 886-3-327-0973 Issued Date : Aug. 04, 2022

Report Template No.: HE1-A3 Ver5.0 Report Version : 02



Table of Contents

1.	Gene	eral Descriptioneral Description	4
		EUT General Information Testing Location Information	
2.	RF E	xposure Evaluation	5
		Applicable Standard	

Photographs of EUT V01

TEL: 886-3-327-3456 FAX: 886-3-327-0973

Report Template No.: HE1-A3 Ver5.0

FCC ID: 2AENP-MTB03L

Page Number : 2 of 5

Issued Date : Aug. 04, 2022

Report Version : 02



History of This Test Report

Report No.	Version	Description	Issued Date
FA171901	01	Initial issue of report	May 30, 2022
FA171901	02	Revised typo (This report is the latest version replacing for the report issued on May 30, 2022)	Aug. 04, 2022

Reviewed by: Sam Tsai

Report Producer: Amber Chiu

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Aug. 04, 2022

Report Template No.: HE1-A3 Ver5.0 Report Version : 02



1. General Description

1.1. EUT General Information

RF General Information					
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type		
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / π/4-DQPSK / 8DPSK) LE: DSSS (GFSK)		

1.2. Testing Location Information

Tes	Test Lab. : Sporton International Inc. Hsinhua Laboratory					
\boxtimes	Hsinhua	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)				
	(TAF: 3785)	TEL: 886-3-327-3456	FAX: 886-3-327-0973			
	Test site Designation No. TW3785 with FCC.					
	Wen 33rd.St.	d.St. ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)				
	(TAF: 3785)	TEL: 886-3-318-0787	FAX: 886-3-318-0287			
	Test site Designation No. TW0008 with FCC.					

TEL: 886-3-327-3456 Page Number : 4 of 5
FAX: 886-3-327-0973 Issued Date : Aug. 04, 2022

Report Template No.: HE1-A3 Ver5.0 Report Version : 02

2. RF Exposure Evaluation

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

1. Per KDB 447498 D04 Interim General RF Exposure Guidance v01, Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \ cm} (d/20 \ \text{cm})^x & d \leq 20 \ \text{cm} \\ \\ ERP_{20 \ cm} & 20 \ \text{cm} < d \leq 40 \ \text{cm} \end{cases}$$

Where

$$x = -\log_{10}\left(\frac{60}{ERP_{20~Cm}\sqrt{f}}\right)$$
 and f is in GHz;

and

$$ERP_{20\ cm}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases}$$

d = the separation distance (cm);

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	-2.30	4.56	2.26	0.50	1.15080	0.5	В	2.78882	0.01989
2.4G;BT-BR	-2.30	4.52	2.22	0.50	1.14025	0.5	В	2.78882	0.01989
2.4G;BT-EDR	-2.30	4.65	2.35	0.50	1.17490	0.5	В	2.78882	0.01989

2. Per KDB 447498 D04 Interim General RF Exposure Guidance v01 exclusion thresholds is 1.17490 < 2.78882, RF exposure evaluation is not required.

——THE END——

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Aug. 04, 2022

Report Template No.: HE1-A3 Ver5.0 Report Version : 02