



## RF Exposure evaluation

**FCC ID: 2BAYW-XPAW024**

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### **EDR:**

Worse case output power is as below: [2480MHz: 6.45dBm]

Maximum output power is 6.45dBm (4.42 mW).

$(4.42 \text{ mW} / 5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 1.39 < 3.0$  for 1-g SAR.

### **BLE:**

Worse case output power is as below: [2480MHz: 0.26dBm]

Maximum output power is 0.26dBm (1.06 mW).

$(1.06\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.33 < 3.0$  for 1-g SAR.

Then SAR evaluation is not required.