

# FCC REPORT

**Applicant:** SHEN ZHEN TOMSTAR TECHNOLOGY CO., LTD

**Address of Applicant:** Room 2110-2116, Huafeng International Commercial Building,  
Xixiang, BaoAn district, Shenzhen, China

**Equipment Under Test (EUT)**

Product Name: smart watch

Model No.: TS02

**FCC ID:** 2APD3TS02

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B

**Date of sample receipt:** 19 May, 2020

**Date of Test:** 19 May, to 03 Jun., 2020

**Date of report issued:** 04 Jun., 2020

**Test Result:** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	04 Jun., 2020	Original

Tested by:

YT Yang

Test Engineer

Date:

04 Jun., 2020

Reviewed by:

Winner Zhang

Project Engineer

Date:

04 Jun., 2020

## 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 TEST SUMMARY .....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF E.U.T. ....	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY .....	5
5.5 DESCRIPTION OF SUPPORT UNITS .....	6
5.6 RELATED SUBMITTAL(S) / GRANT (S).....	6
5.7 DESCRIPTION OF CABLE USED .....	6
5.8 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD .....	6
5.9 LABORATORY FACILITY .....	6
5.10 LABORATORY LOCATION.....	6
5.11 TEST INSTRUMENTS LIST .....	7
<b>6 TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>8</b>
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION .....	11
<b>7 TEST SETUP PHOTO .....</b>	<b>17</b>
<b>8 EUT CONSTRUCTIONAL DETAILS .....</b>	<b>18</b>

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass
<b>Remark:</b> 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: The EUT not applicable of the test item.		
Test Method:	ANSI C63.4:2014	

## 5 General Information

### 5.1 Client Information

Applicant:	SHEN ZHEN TOMSTAR TECHNOLOGY CO., LTD
Address:	Room 2110-2116, Huafeng International Commercial Building, Xixiang, BaoAn district, Shenzhen, China
Manufacturer/ Factory:	Tomstar Industrial Limited
Address:	Room 2110-2116, Huafeng International Commercial Building, Xixiang, BaoAn district, Shenzhen, China

### 5.2 General Description of E.U.T.

Product Name:	smart watch
Model No.:	TS02
Power supply:	Rechargeable Li-ion Battery DC3.8V, 280mAh
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

### 5.3 Test Mode

Operating mode	Detail description
Charging mode	Keep the EUT in Charging mode(Worst case)
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

### 5.4 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

## 5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX7070	2J8XSZ2	DoC
DELL	MONITOR	SE2018HR	3M7QPY2	DoC
DELL	KEYBOARD	KB216d	N/A	DoC
DELL	MOUSE	MS116t1	N/A	DoC
HP	Printer	HP LaserJet P1007	VNFP409729	DoC

## 5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

## 5.7 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Unshielded	0.74m	EUT	Adapter

## 5.8 Additions to, deviations, or exclusions from the method

No

## 5.9 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

## 5.10 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.  
Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,  
Bao'an District, Shenzhen, Guangdong, China  
Tel: +86-755-23118282, Fax: +86-755-23116366  
Email: [info@ccis-cb.com](mailto:info@ccis-cb.com), Website: <http://www.ccis-cb.com>

## 5.11 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-07-2020	03-06-2021
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2020
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		


## 6.1 Conducted Emission

The diagram illustrates the Reference Plane setup. A horizontal line at the top represents the Reference Plane. Below it, on the left, is a large box labeled "Test table/Insulation plane". Inside this box are three components: "LISN" (Line Impedance Stabilization Network) at the top left, "AUX Equipment" at the bottom left, and "E.U.T." (Equipment Under Test) at the bottom right. A vertical line connects the "LISN" to the "AUX Equipment". A horizontal line connects the "AUX Equipment" to the "E.U.T.". A vertical double-headed arrow between the Reference Plane and the "LISN" is labeled "40cm". A diagonal line connects the "E.U.T." to the "LISN" on the right, labeled "80cm". On the right side, another "LISN" is connected to the Reference Plane. Below this "LISN" is a "Filter" connected to "AC power", and further down is an "EMI Receiver" connected to the "LISN".



Measurement data:

Product name:	smart watch	Product model:	TS02
Test by:	YT	Test mode:	Charging mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%




	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.166	37.53	-0.58	-0.09	10.77	47.63	65.16	-17.53	QP
2	0.502	33.56	-0.43	-0.35	10.76	43.54	56.00	-12.46	QP
3	0.502	26.29	-0.43	-0.35	10.76	36.27	46.00	-9.73	Average
4	0.561	34.71	-0.46	-0.37	10.76	44.64	56.00	-11.36	QP
5	0.561	25.51	-0.46	-0.37	10.76	35.44	46.00	-10.56	Average
6	0.686	35.14	-0.52	-0.40	10.77	44.99	56.00	-11.01	QP
7	0.686	25.32	-0.52	-0.40	10.77	35.17	46.00	-10.83	Average
8	1.005	20.03	-0.62	0.46	10.87	30.74	46.00	-15.26	Average
9	1.016	30.97	-0.62	0.44	10.87	41.66	56.00	-14.34	QP
10	2.622	21.33	-0.46	-0.25	10.93	31.55	46.00	-14.45	Average
11	2.839	28.31	-0.44	-0.23	10.93	38.57	56.00	-17.43	QP
12	2.839	22.52	-0.44	-0.23	10.93	32.78	46.00	-13.22	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	smart watch	Product model:	TS02
Test by:	YT	Test mode:	Charging mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%





	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.415	34.41	-0.63	-0.05	10.73	44.46	57.55	-13.09	QP
2	0.415	26.72	-0.63	-0.05	10.73	36.77	47.55	-10.78	Average
3	0.521	23.81	-0.65	0.03	10.76	33.95	46.00	-12.05	Average
4	0.541	32.46	-0.65	0.03	10.76	42.60	56.00	-13.40	QP
5	0.627	31.50	-0.64	0.04	10.77	41.67	56.00	-14.33	QP
6	0.665	22.26	-0.64	0.04	10.77	32.43	46.00	-13.57	Average
7	0.697	21.95	-0.64	0.04	10.77	32.12	46.00	-13.88	Average
8	0.727	31.18	-0.64	0.04	10.78	41.36	56.00	-14.64	QP
9	1.016	27.84	-0.68	0.08	10.87	38.11	56.00	-17.89	QP
10	1.016	19.27	-0.68	0.08	10.87	29.54	46.00	-16.46	Average
11	2.664	19.35	-0.67	0.27	10.93	29.88	46.00	-16.12	Average
12	2.736	27.15	-0.66	0.28	10.93	37.70	56.00	-18.30	QP

## Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

## 6.2 Radiated Emission


Test Requirement:	FCC Part 15 B Section 15.109				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak RMS	1MHz 1MHz	3MHz 3MHz	Peak Value Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0 74.0		Average Value Peak Value
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					
Test Procedure:	<div>1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</div> <div>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</div> <div>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</div>				

	<p>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p>
Test Instruments:	Refer to section 5.11 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	All of the observed value above 6GHz were the noise floor , which were no recorded

## Measurement Data:

### Below 1GHz:

Product Name:	smart watch	Product Model:	TS02
Test By:	YT	Test mode:	Charging mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	dBuV/m	dBuV/m	dB
1	36.001	50.02	11.43	1.07	0.00	29.94	32.58	40.00	-7.42 QP
2	38.752	41.12	12.10	1.18	0.00	29.91	24.49	40.00	-15.51 QP
3	47.659	39.38	12.20	1.27	0.00	29.84	23.01	40.00	-16.99 QP
4	104.903	39.46	12.09	2.00	0.00	29.49	24.06	43.50	-19.44 QP
5	153.739	40.56	9.05	2.54	0.00	29.19	22.96	43.50	-20.54 QP
6	340.782	39.30	14.44	3.07	0.00	28.54	28.27	46.00	-17.73 QP

#### Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product Name:	smart watch	Product Model:	TS02
Test By:	YT	Test mode:	Charging mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	dBuV/m	dBuV/m	dB
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	107.134	35.10	11.90	2.02	0.00	29.48	19.54	43.50	-23.96 QP
2	119.018	36.58	10.96	2.16	0.00	29.40	20.30	43.50	-23.20 QP
3	153.200	42.23	9.02	2.54	0.00	29.19	24.60	43.50	-18.90 QP
4	171.393	39.62	9.69	2.66	0.00	29.04	22.93	43.50	-20.57 QP
5	230.099	36.56	11.91	2.83	0.00	28.65	22.65	46.00	-23.35 QP
6	298.268	33.44	13.58	2.93	0.00	28.45	21.50	46.00	-24.50 QP

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

**Above 1GHz:**

<b>Product Name:</b>	smart watch	<b>Product Model:</b>	TS02
<b>Test By:</b>	YT	<b>Test mode:</b>	Charging mode
<b>Test Frequency:</b>	1 GHz ~ 6 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	AC 120V/60Hz	<b>Environment:</b>	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Limit Level	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	4353.737	47.20	29.88	6.03	2.31	41.93	43.49	74.00	-30.51 Peak
2	4353.737	42.48	29.88	6.03	2.31	41.93	38.77	54.00	-15.23 Average
3	5198.752	46.85	31.63	6.73	2.55	41.95	45.81	74.00	-28.19 Peak
4	5198.752	42.52	31.63	6.73	2.55	41.95	41.48	54.00	-12.52 Average
5	5716.644	46.93	32.39	7.10	2.72	41.92	47.22	74.00	-26.78 Peak
6	5716.644	41.12	32.39	7.10	2.72	41.92	41.41	54.00	-12.59 Average

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	smart watch	Product Model:	TS02
Test By:	YT	Test mode:	Charging mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24°C Humi: 57%



	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	4361.545	47.18	29.90	6.04	2.31	41.94	43.49	74.00	-30.51 Peak
2	4361.545	42.86	29.90	6.04	2.31	41.94	39.17	54.00	-14.83 Average
3	4979.933	47.65	31.14	6.54	2.49	41.87	45.95	74.00	-28.05 Peak
4	4979.933	42.96	31.14	6.54	2.49	41.87	41.26	54.00	-12.74 Average
5	5685.998	47.56	32.37	7.08	2.70	41.89	47.82	74.00	-26.18 Peak
6	5685.998	42.43	32.37	7.08	2.70	41.89	42.69	54.00	-11.31 Average

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.