

FCC - TEST REPORT

Report Number : **7095021029110-00** Date of Issue: Dec.23,2021

Model : AXY2S

Product Type : Wi-Fi and Bluetooth Module

Applicant : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room701,Building3,More Center,No.87 GuDun
Road, Hangzhou, Zhejiang China

Manufacturer : Hangzhou Tuya Information Technology Co.,Ltd

Address : Room701,Building3,More Center,No.87 GuDun
Road, Hangzhou, Zhejiang China

Test Result : ☒ **Positive** ☐ **Negative**



Total pages including Appendices : 63

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment under Test	4
4	Summary of Test Standards.....	6
5	Summary of Test Results.....	7
6	General Remarks	8
7	Test Setups	9
8	Systems test configuration.....	12
9	Technical Requirement	13
9.1	Conducted Emission	13
9.2	Conducted peak output power.....	16
9.3	6dB bandwidth	17
9.4	Power spectral density.....	23
9.5	Spurious RF conducted emissions	29
9.6	Band edge	45
9.7	Spurious radiated emissions for transmitter	51
10	Test Equipment List.....	60
11	System Measurement Uncertainty	61
12	Photographs of Test Set-ups	62
13	Photographs of EUT	63



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Test Firm FCC
Registration
Number: 820234

Designation
number: CN1183

IC Company
Number: 25988

CAB identifier: CN0101

Telephone: +86 21 6141 0123
Fax: +86 21 6140 8600

3 Description of the Equipment under Test

Product: Wi-Fi and Bluetooth Module

Model no.: AXY2S

FCC ID: 2ANDL-AXY2S

Options and accessories: NA

Rating: 3V-3.6V DC

RF Transmission Frequency: For 802.11b/g/n(HT20)/ax(HE20): 2412~2462 MHz (Wi-Fi)
For 802.11n(HT40): 2422~2452 MHz (Wi-Fi)
For 802.15.1:2402~2480 MHz (BLE 5.1)

No. of Operated Channel: 2.4GHz WIFI: 11 for 802.11b/g/n(HT20)/ax(HE20)
7 for 802.11n(HT40)
2.4GHz BLE: 40

Modulation: Direct Sequence Spread Spectrum (DSSS) for 802.11b
Orthogonal Frequency Division Multiplexing (OFDM) for
802.11g/n; Orthogonal Frequency Division Multiple Access
(OFDMA) for 802.11ax; 2.4GHz BLE: GFSK

Channel list:

802.11b/g/n(HT20)/ax(HE20)					802.11n(HT40)		
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
1	2412	7	2442	3	2422	8	2447MHz
2	2417	8	2447	4	2427	9	2452MHz
3	2422	9	2452	5	2432		
4	2427	10	2457	6	2437		
5	2432	11	2462	7	2442		
6	2437						

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



China

Antenna Type: onboard PCB antenna

Antenna Gain: 1.97dBi

Description of the EUT: The Equipment Under Test (EUT) is a Wi-Fi and Bluetooth module which support 2.4GHz Wi-Fi and BLE 5.1(support 1Mbps and 2Mbps data rate). We tested it and listed the worst data in this report.

Test sample no.: SHA- 616430-1

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	13-15	Site 1	☒	☐	☐
§15.247 (b) (1)	Conducted peak output power	16	Site 1	☒	☐	☐
§15.247(a)(1)	20dB bandwidth	---	---	☐	☐	☒
§15.247(a)(1)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Dwell Time	---	---	☐	☐	☒
§15.247(a)(2)	6dB bandwidth	17-22	Site 1	☒	☐	☐
§15.247(e)	Power spectral density	23-28	Site 1	☒	☐	☐
§15.247(d)	Spurious RF conducted emissions	29-44	Site 1	☒	☐	☐
§15.247(d)	Band edge	45-50	Site 1	☒	☐	☐
§15.247(d) & §15.209	Spurious radiated emissions for transmitter	51-59	Site 1	☒	☐	☐
§15.203	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an onboard PCB antenna, which gain is 1.97dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2ANDL-AXY2S, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

This report is only for the 2.4GHz Wi-Fi test report, for the 2.4GHz BLE test report please refer to 7095021029111-00.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: November 25, 2021

Testing Start Date: December 3, 2021


Testing End Date: December 22, 2021

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:




Hui TONG
Review Engineer

Jiaxi XU
Project Engineer

Cheng Huali
Test Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	E470	PF-OU5TS7 17/09

Test software: RDTool V1.0.19

The system was configured to channel 1(2412MHz), 6(2437MHz), and 11(2462MHz) for 802.11 b/g/n(HT20)/ax(HE20) test and channel 3(2422MHz), 6(2437MHz), 9(2452MHz) for 802.11n (HT40).

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : Wi-Fi and Bluetooth module
 M/N : AXY2S
 Operating Condition : Mode 1: Tx_2412MHz for 802.11n20
 Test Specification : L-line
 Comment : AC 120V/60Hz (powered by notebook)




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.168000	---	28.74	55.06	26.32	1000.0	9.000	L1	19.5
0.168000	43.98	---	65.06	21.08	1000.0	9.000	L1	19.5
0.514500	33.88	---	56.00	22.12	1000.0	9.000	L1	19.5
0.519000	---	27.46	46.00	18.54	1000.0	9.000	L1	19.5
2.080500	25.15	---	56.00	30.85	1000.0	9.000	L1	19.5
2.098500	---	20.34	46.00	25.66	1000.0	9.000	L1	19.5
2.548500	---	24.73	46.00	21.27	1000.0	9.000	L1	19.5
2.602500	29.05	---	56.00	26.95	1000.0	9.000	L1	19.5
11.130000	27.45	---	60.00	32.55	1000.0	9.000	L1	19.7
11.130000	---	21.57	50.00	28.43	1000.0	9.000	L1	19.7
14.023500	33.29	---	60.00	26.71	1000.0	9.000	L1	19.7
14.041500	---	26.68	50.00	23.32	1000.0	9.000	L1	19.7

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

Product Type : Wi-Fi and Bluetooth module
 M/N : AXY2S
 Operating Condition : Mode 1: Tx_2412MHz for 802.11n20
 Test Specification : N-line
 Comment : AC 120V/60Hz (powered by notebook)



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.154500	---	24.10	55.75	31.65	1000.0	9.000	N	19.5
0.154500	44.05	---	65.75	21.70	1000.0	9.000	N	19.5
0.514500	---	26.75	46.00	19.25	1000.0	9.000	N	19.5
0.514500	34.27	---	56.00	21.73	1000.0	9.000	N	19.5
2.112000	---	24.02	46.00	21.98	1000.0	9.000	N	19.5
2.112000	28.94	---	56.00	27.06	1000.0	9.000	N	19.5
2.359500	---	25.72	46.00	20.28	1000.0	9.000	N	19.5
3.052500	28.17	---	56.00	27.83	1000.0	9.000	N	19.5
5.527500	22.95	---	60.00	37.05	1000.0	9.000	N	19.6
11.359500	---	17.51	50.00	32.49	1000.0	9.000	N	19.7
14.563500	---	26.51	50.00	23.49	1000.0	9.000	N	19.8
15.004500	29.16	---	60.00	30.84	1000.0	9.000	N	19.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
RBW > the 6dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Use a power meter to measure the conducted peak output power.

Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30

Test result

802.11b

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2412MHz	18.47	Pass
Middle channel 2437MHz	18.25	Pass
High channel 2462MHz	18.30	Pass

802.11g

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2412MHz	23.74	Pass
Middle channel 2437MHz	23.59	Pass
High channel 2462MHz	23.55	Pass

802.11n(HT20)

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2412MHz	24.44	Pass
Middle channel 2437MHz	24.44	Pass
High channel 2462MHz	24.61	Pass

802.11n(HT40)

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2422MHz	22.92	Pass
Middle channel 2437MHz	22.20	Pass
High channel 2452MHz	22.35	Pass

802.11ax(HE20)

Frequency (MHz)	Conducted Peak Output Power(dBm)	Result
Low channel 2412MHz	23.27	Pass
Middle channel 2437MHz	23.20	Pass
High channel 2462MHz	23.10	Pass

9.3 6dB bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq$ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]

 ≥ 500

Test result

802.11b

Frequency MHz	6dB bandwidth MHz	Result
Top channel 2412MHz	9.096	Pass
Middle channel 2437MHz	9.097	Pass
Bottom channel 2462MHz	9.096	Pass

802.11g

Frequency MHz	6dB bandwidth MHz	Result
Top channel 2412MHz	5.123	Pass
Middle channel 2437MHz	5.325	Pass
Bottom channel 2462MHz	5.337	Pass

802.11n(HT20)

Frequency MHz	6dB bandwidth MHz	Result
Top channel 2412MHz	5.797	Pass
Middle channel 2437MHz	5.811	Pass
Bottom channel 2462MHz	5.116	Pass

802.11n(HT40)


Frequency MHz	6dB bandwidth MHz	Result
Low channel 2422MHz	9.432	Pass
Middle channel 2437MHz	9.182	Pass
High channel 2452MHz	10.094	Pass

802.11ax(HE20)


Frequency MHz	6dB bandwidth MHz	Result
Low channel 2412MHz	5.127	Pass
Middle channel 2437MHz	5.353	Pass
High channel 2462MHz	5.072	Pass

6 dB Bandwidth


802.11b
2412



2437



2462






China


802.11g

2412




Date: 20 DEC 2021 09:39:51

2437



Date: 20 DEC 2021 09:41:56


2462



Date: 20 DEC 2021 09:43:38


802.11n(HT20)

2412




Date: 20 DEC 2021 09:45:49

2437




Date: 20 DEC 2021 09:47:50

2462




Date: 20 DEC 2021 09:49:35

802.11n(HT40)



802.11ax(HE20)



9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.
RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3KHz]

≤ 8

Test result

802.11b

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2412MHz	-9.90	Pass
Middle channel 2437MHz	-9.60	Pass
High channel 2462MHz	-9.49	Pass

802.11g

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2412MHz	-5.26	Pass
Middle channel 2437MHz	-5.83	Pass
High channel 2462MHz	-5.53	Pass

802.11 n(HT20)

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2412MHz	-5.57	Pass
Middle channel 2437MHz	-5.96	Pass
High channel 2462MHz	-4.70	Pass

802.11 n(HT40)

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2422MHz	-10.21	Pass
Middle channel 2437MHz	-10.83	Pass
High channel 2452MHz	-10.48	Pass


802.11 ax(HE20)

Frequency (MHz)	Power spectral density(dBm/3KHz)	Result
Low channel 2412MHz	-7.10	Pass
Middle channel 2437MHz	-7.24	Pass
High channel 2462MHz	-7.20	Pass

Power spectral density


802.11b

2412




Date: 20 DEC 2021 09:34:34

2437



Date: 20 DEC 2021 09:36:25


2462




Date: 20 DEC 2021 09:38:10

802.11g


2412



2437




2462




802.11n(HT20)

2412




Date: 22 DEC 2021 15:13:31

2437



Date: 22 DEC 2021 15:13:09


2462



Date: 22 DEC 2021 15:12:36


802.11n(HT40)

2422




Date: 22 DEC 2021 15:15:51

2437



Date: 22 DEC 2021 15:16:14


2452



Date: 22 DEC 2021 15:16:46


802.11ax(HE20)

2412




Date: 22 DEC. 2021 15:17:43

2437



Date: 22 DEC. 2021 15:18:05

2462



Date: 22 DEC. 2021 15:18:31