

Analysis Report

The equipment under test (EUT) is a 2.1 soundbar with wireless subwoofer with BT 3.0 function operating in 2402-2480MHz, and 2.4GHz wireless data transmission function operating in 2404.5-2479.5MHz with channel separation 5MHz (number of channel 16). The EUT is powered by AC 120V, 60Hz. For more detail information pls. refer to the user manual.

For BT3.0 function operating frequency is 2402-2480MHz:

Modulation Type: GFSK, $\pi/4$ DQPSK, 8DPSK

Antenna Type: Integral antenna

Antenna Gain: 0dBi

The nominal conducted output power specified: 0dBm (Tolerance: +/- 3dB)

The nominal radiated output power (e.i.r.p) specified: 0dBm (Tolerance: +/- 3dB)

According to the KDB 447498:

The maximum radiated emission for the EUT is 95.5dB μ V/m at 3m in the frequency 2.402GHz

= $[(FS \cdot D)^2 / 30]$ mW

= 0.3 dBm which is within the production variation.

The minimum radiated emission for the EUT is 94.1dB μ V/m at 3m in the frequency 2.480GHz

= $[(FS \cdot D)^2 / 30]$ mW

= -1.1dBm which is within the production variation.

The maximum conducted output power specified is 3.0 dBm = 2.0mW

The source- based time-averaging conducted output power

= 2.0 * Duty cycle mW= 2.0 mW (Duty Cycle<=100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.480) mW

= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

INTERTEK TESTING SERVICES

For 2.4GHz wireless data transmission function operating frequency is 2404.5-2479.5MHz

Modulation Type: FSK

Antenna Type: Integral antenna

Antenna Gain: 0dBi

The nominal conducted output power specified: 0dBm (Tolerance: +/- 3dB)

The nominal radiated output power (e.i.r.p) specified: 0dBm (Tolerance: +/- 3dB)

According to the KDB 447498:

The maximum radiated emission for the EUT is 96.8dBμV/m at 3m in the frequency 2404.5MHz

= $[(FS \cdot D)^2 / 30]$ mW

= 1.6dBm which is within the production variation.

The minimum radiated emission for the EUT is 94.0dBμV/m at 3m in the frequency 2404.5MHz

= $[(FS \cdot D)^2 / 30]$ mW

= -1.2dBm which is within the production variation.

The maximum conducted output power specified is 3.0dBm = 2.0mW

The source- based time-averaging conducted output power

= 2.0 * Duty cycle mW= 2.0 mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.4795) mW

= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

Transmitter Duty Cycle Calculation

The EUT transmit continuously during the test, the duty cycle is 1.

This requirement is according to KDB 865664 D02.

INTERTEK TESTING SERVICES

For both BT 3.0 and 2.4GHz wireless data transmission are simultaneous transmissions estimated:

According to the KDB 447498:

When both BT 3.0 and 2.4GHz wireless data transmission are simultaneous transmissions, the maximum conducted output power for BT 3.0 is 2.0mW.

In the simultaneous transmissions, BT 3.0's estimated SAR values:
= (max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm) * [sqrt(freq. in GHz)/7.5] W/kg
= 2.0 / 5 * [sqrt(2.480) / 7.5] W/kg
= 0.084 W/kg

When both BT 3.0 and 2.4GHz wireless data transmission are simultaneous transmissions, the maximum conducted output power for 2.4GHz wireless data transmission is 2.0mW.

In the simultaneous transmissions, 2.4GHz wireless data transmission's estimated SAR values:
= (max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm) * [sqrt(freq. in GHz)/7.5] W/kg
= 2.0 / 5 * [sqrt(2.4795) / 7.5] W/kg
= 0.084 W/kg

Sum of 1-g SAR of all simultaneously transmitting antennas in an operating mode:

BT 3.0's estimated SAR values + 2.4GHz wireless data transmission's estimated SAR values
= 0.084 W/kg + 0.084 W/kg
= 0.168 W/kg

The simultaneous transmissions SAR Evaluation: ≤ 0.4 W/kg

This requirement is according to KDB 865664 D02.