

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 22 SUBPART H and PART 24 SUBPART E REQUIREMENT

OF

Product Name: GSM 850/1900 mobile phone

Brand Name: Sagem

Model Name: A2005sa E2

Market Name: my100B TWIN-my100L TWIN

FCC ID: M9HA5SE2

Report No.: ER/2005/C0012-02

Issue Date: Mar. 16, 2006

FCC Rule Part: 2 & 22H & 24E

Prepared for SAGEM Communication
2,rue du Petit Albi BP28250
95801 CERGY PONTOISE Cedex

Prepared by SGS Taiwan Ltd.

No. 134, Wu Kung Rd., Wuku Industrial Zone,
Taipei County, Taiwan.

***Note:** This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the document.*

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

VERIFICATION OF COMPLIANCE

Applicant: SAGEM Communication
 2,rue du Petit Albi BP28250 95801 CERGY PONTOISE Cedex
Equipment Under Test: GSM 850/1900 mobile phone
FCC ID Number: M9HA5SE2
Brand Name: Sagem
Model No.: A2005sa E2
Market Name: my100B TWIN-my100L TWIN
Model Difference: N/A
File Number: ER/2005/C0012-02
Date of test: Mar. 10, 2006 ~ Mar. 15, 2006
Date of EUT Received: Mar. 10, 2006

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in TIA/EIA-603-1-1998 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rule FCC PART 22 subpart H and FCC PART 24 subpart E.

The test results of this report relate only to the tested sample identified in this report.

Test By:		Date	Mar. 16, 2006
	<hr/>		<hr/>
	Sky Wang		
Prepared By:		Date	Mar. 16, 2006
	<hr/>		<hr/>
	Gigi Yeh		
Approved By		Date	Mar. 16, 2006
	<hr/>		<hr/>
	Vincent Su		

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Version

Version No.	Date
00	Mar. 16, 2006

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Table of Contents

1. GENERAL INFORMATION	6
1.1 Product Description	6
1.2 Related Submittal(s) / Grant (s)	7
1.3 Test Methodology	7
1.4 Test Facility	7
1.5 Special Accessories	7
1.6 Equipment Modifications	7
2. SYSTEM TEST CONFIGURATION	8
2.1 EUT Configuration	8
2.2 EUT Exercise	8
2.3 Test Procedure	8
2.4 Configuration of Tested System	9
3. SUMMARY OF TEST RESULTS	10
4. DESCRIPTION OF TEST MODES	10
5. RF POWER OUTPUT MEASUREMENT	11
5.1 Standard Applicable	11
5.2 Test Set-up:	11
5.3 Measurement Procedure	11
5.4 Measurement Equipment Used:	12
5.5 Measurement Result	13
6. ERP, EIRP MEASUREMENT	14
6.1 Standard Applicable	14
6.2 Test SET-UP (Block Diagram of Configuration)	14
6.3 Measurement Procedure	16
6.4 Measurement Equipment Used:	17
6.5 Measurement Result	18
7. OCCUPIED BANDWIDTH MEASUREMENT	20
7.1 Standard Applicable	20
7.2 Test Set-up:	20
7.3 Measurement Procedure	20
7.4 Measurement Equipment Used:	21
7.5 Measurement Result:	21
8. OUT OF BAND EMISSION AT ANTENNA TERMINALS	26
8.1 Standard Applicable	26

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

8.2	Test SET-UP.....	26
8.3	Measurement Procedure.....	26
8.4	Measurement Equipment Used:.....	27
8.5	Measurement Result.....	28
9.	FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	36
9.1	Standard Applicable	36
9.2	EUT Setup (Block Diagram of Configuration)	36
9.3	Measurement Procedure.....	38
9.4	Measurement Equipment Used:.....	39
9.5	Measurement Result.....	39
10.	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	52
10.1	Standard Applicable	52
10.2	Test Set-up:	52
10.3	Measurement Procedure.....	52
10.4	Measurement Equipment Used:.....	53
10.5	Measurement Result.....	54
11.	FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	55
11.1	Standard Applicable	55
11.2	Test Set-up:	55
11.3	Measurement Procedure.....	55
11.4	Measurement Equipment Used:.....	56
11.5	Measurement Result.....	57
12.	AC POWER LINE CONDUCTED EMISSION TEST	58
12.1	Standard Applicable	58
12.2	EUT Setup.....	58
12.3	Measurement Procedure.....	58
12.4	Measurement Equipment Used:.....	59
12.5	Measurement Result.....	59
	PHOTOGRPHS OF SET UP.....	64
	PHOTOGRPHS OF EUT.....	67

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1. GENERAL INFORMATION

1.1 Product Description

Product	GSM 850/1900 mobile phone	
Model Name	A2005sa E2	
Market Name	my100B TWIN-my100L TWIN	
Model Difference:	N/A	
Trade Name	Sagem	
Frequency Range and Power	TX: 824.2 MHz – 848.8 MHz	33 dBm
	TX: 1850.2MHz –1909.8MHz	30 dBm
Type of Emission	300KGXW	
Software Version	J_3,YA	
Hardware Version	V0x	
IMEI	35399200260175-6	
Power Supply	3.7 Vdc re-chargeable battery or 5Vdc by AC/DC power adapter	
	Model:	18922053-0, Supplier: Sagem

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: M9HA5SE2 filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on chapter 13 of ANSI C63.4 (2003) and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the address of SGS Taiwan Ltd. No. 134, Wu Kung Rd., Wuku Industrial Zone, Taipei Country, Taiwan. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 1993 and CISPR 22/EN 55022 requirements. Site No. 1(3 & 10 meters) Registration Number: 94644, Anechoic chamber (3 meters) was accredited by CNLA(0513)

1.5 Special Accessories

Not available for this EUT intended for grant.

1.6 Equipment Modifications

Not available for this EUT intended for grant.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2. SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 1.0 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4-2003.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Data Cable	Power Cord
1..	N/A					

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§2.1046(a) §22.913(a) §24.232(a)	RF Power Output	Compliant
§2.1046(a) §22.913(a) §24.232(a)	ERP/ EIRP measurement	Compliant
§2.1049(h)	99% Occupied Bandwidth	Compliant
§2.1051 §22.917(a) §24.238(a)	Out of Band Emissions at Antenna Terminals and Band Edge	Compliant
§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	Compliant
§2.1055(a)(1)(b) §24.235	Frequency Stability vs. Temperature	Compliant
§2.1055(d)(1)(2) §24.235	Frequency Stability vs. Voltage	Compliant
§15.107;§15.207	AC Power Line Conducted Emission	Compliant

4. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

EUT staying in continuous transmitting mode. Channel Low, Mid and High for each type and band with rated data rate are chosen for full testing.

The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for both GSM and GPRS with all power adaptors, earphone and Data cable. The worst-case H mode for GSM 850 band and H mode for GSM 1900 band with earphone mode for channel Low, Mid and High at GSM mode was reported.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5. RF POWER OUTPUT MEASUREMENT


5.1 Standard Applicable

According to FCC §2.1046.

FCC 22.913(a) Mobile station are limited to 7W.

FCC 24.232(b) Mobile station are limited to 2W.

5.2 Test Set-up:



Note: Measurement setup for testing on Antenna connector

5.3 Measurement Procedure

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a power meter. Transmitter output was read off the power meter in dBm. The power output at the transmitter antenna port was determined by adding the value of the attenuator to the power meter reading.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5.4 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2005	03/28/2006
Spectrum Analyzer	Agilent	E7405A	US41160416	06/28/2005	06/29/2006
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2005	11/10/2006
Communication Test	R&S	SMU200	N/A	N/A	N/A
Power Sensor	Anritsu	MA2490A	31431	06/28/2005	06/29/2006
Power Meter	Anritsu	ML2487A	6K00002070	06/28/2005	06/29/2006
Temperature Chamber	TERCHY	MHG-120LF	911009	10/14/2005	10/13/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	N/A	N/A
Attenuator	Mini-Circuit	BW-S10W5	N/A	09/23/2005	09/22/2006
Attenuator	Mini-Circuit	BW-S6W5	N/A	09/23/2005	09/22/2006
Splitter	Agilent	11636B	51728	09/23/2005	09/22/2006
AC Power Supply	APW-105N	887592	All Power	N/A	N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

5.5 Measurement Result

EUT Mode	Frequency (MHz)	CH	Power meter Reading (dBm)	Path Loss (dB)	Peak Power (dBm)
GSM 850	824.20	128	5.35	27.4	32.75
	836.60	190	5.50	27.4	32.90
	848.80	251	5.58	27.4	32.98

EUT Mode	Frequency (MHz)	CH	Power Meter Reading (dBm)	Path Loss (dB)	Peak Power (dBm)
PCS 1900	1850.20	512	3.22	27.20	30.42
	1880.00	661	3.38	27.20	30.58
	1909.80	810	3.38	27.20	30.58

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6. ERP, EIRP MEASUREMENT

6.1 Standard Applicable


According to FCC §2.1046

FCC 22.913(a) Mobile station are limited to 7W ERP.

FCC 24.232(b) Mobile station are limited to 2W EIRP.


6.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



(C) Substituted Method Test Set-UP



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6.3 Measurement Procedure

The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.

During the measurement, the EUT was in communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by a dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows:

EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by a horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows:

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6.4 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2005	03/28/2006
Spectrum Analyzer	Agilent	7405A	US41160416	06/28/2005	06/29/2006
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2005	11/10/2006
Communication Test	R&S	SMU200	N/A	N/A	N/A
Bilog Antenna	SCHWAZBECK	VULB9163	152	06/03/2005	06/02/2006
Horn antenna	Schwarzbeck	BBHA 9120D	309/320	08/16/2005	08/15/2006
Pre-Amplifier	HP	8447D	2944A09469	07/19/2005	07/18/2006
Pre-Amplifier	HP	8494B	3008A00578	02/26/2006	02/25/2007
Signal Generator	R&S	SMR40	100210	02/09/2006	02/10/2007
Turn Table	HD	DT420	N/A	N.C.R	N.C.R
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R
Controller	HD	HD100	N/A	N.C.R	N.C.R
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	10/09/2005	10/08/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	10/09/2005	10/08/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-0.5M	0.5m	10/09/2005	10/08/2006
Site NSA	SGS	966 chamber	N/A	11/17/2005	11/16/2006
Attenuator	Mini-Circuit	BW-S10W5	N/A	09/23/2005	09/22/2006
Dipole Antenna	Schwarzbeck	VHAP	908/909	06/10/2004	06/11/2006
Dipole Antenna	Schwarzbeck	UHAP	891/892	06/10/2004	06/11/2006
Horn antenna	Schwarzbeck	BBHA 9120D	N/A	08/16/2004	08/15/2006

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6.5 Measurement Result

Test Configuration Mode: Earphone:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBd)	Cable Loss (dB)	ERP (dBm)	Limit (dBm)
GSM 850	824.20	128	H	V	128.82	41.50	-7.87	3.64	29.98	38.45
				H	129.09	41.44	-7.87	3.64	29.92	38.45
			E1	V	129.45	42.42	-7.88	3.70	30.85	38.45
				H	128.98	41.65	-7.88	3.70	30.07	38.45
			E2	V	129.10	42.36	-7.88	3.75	30.73	38.45
				H	126.30	39.28	-7.88	3.75	27.65	38.45
	836.60	190	H	V	126.00	38.68	-7.87	3.64	27.16	38.45
				H	127.31	39.66	-7.87	3.64	28.14	38.45
			E1	V	126.77	39.74	-7.88	3.70	28.17	38.45
				H	128.30	40.96	-7.88	3.70	29.39	38.45
			E2	V	125.32	38.58	-7.88	3.75	26.95	38.45
				H	126.67	39.65	-7.88	3.75	28.02	38.45
	848.80	251	H	V	130.28	42.96	-7.87	3.64	31.44	38.45
				H	125.79	38.14	-7.87	3.64	26.62	38.45
			E1	V	131.24	44.21	-7.88	3.70	32.64	38.45
				H	127.98	40.65	-7.88	3.70	29.07	38.45
			E2	V	128.57	41.83	-7.88	3.75	30.20	38.45
				H	126.44	39.42	-7.88	3.75	27.79	38.45

Remark :

- The RBW,VBW of SPA for frequency
Below 1GHz was RBW=100 KHz, VBW=300KHz,
Above 1GHz was RBW= 1MHz , VBW= 3MHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Test Configuration Mode: Earphone:

EUT Mode	Frequency (MHz)	CH	EUT Pol.	Antenna Pol.	SPA Reading (dBuV)	S.G. Output (dBm)	Antenna Gain (dBi)	Cable Loss (dB)	EIRP (dBm)	Limit (dBm)
PCS 1900	1850.20	512	H	V	129.98	23.02	9.90	5.41	27.51	33.00
				H	128.63	21.74	9.90	5.41	26.23	33.00
			E1	V	128.71	21.76	9.99	5.46	26.29	33.00
				H	127.81	20.94	9.99	5.46	25.47	33.00
			E2	V	127.54	20.60	10.08	5.51	25.17	33.00
				H	126.05	19.20	9.90	5.84	23.26	33.00
	1880.00	661	H	V	129.31	22.35	9.90	5.41	26.84	33.00
				H	129.74	22.85	9.90	5.41	27.34	33.00
			E1	V	128.23	21.28	9.99	5.46	25.81	33.00
				H	128.80	21.93	9.99	5.46	26.46	33.00
			E2	V	127.03	20.09	10.08	5.51	24.66	33.00
				H	126.70	19.85	10.08	5.51	24.41	33.00
	1909.80	810	H	V	125.84	18.88	9.90	5.41	23.37	33.00
				H	130.51	23.62	9.90	5.41	28.11	33.00
			E1	V	124.80	17.85	9.99	5.46	22.38	33.00
				H	129.45	22.58	9.99	5.46	27.11	33.00
			E2	V	125.72	18.78	10.08	5.51	23.35	33.00
				H	130.29	23.44	10.08	5.51	28.00	33.00

Remark :

- (1) The RBW,VBW of SPA for frequency
Below 1GHz was RBW=100 KHz, VBW=300KHz,
Above 1GHz was RBW= 1MHz , VBW= 3MHz


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

7. OCCUPIED BANDWIDTH MEASUREMENT

7.1 Standard Applicable

According to §FCC 2.1049.

7.2 Test Set-up:



Note: Measurement setup for testing on Antenna connector

7.3 Measurement Procedure

The EUT's output RF connector was connected with a short cable to the spectrum analyzer, RBW (10/30KHz) was set to about 1% of emission BW, VBW= 3 times RBW(30/100KHz), -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

7.4 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2005	03/28/2006
Spectrum Analyzer	Agilent	E7405A	US41160416	06/28/2005	06/29/2006
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2005	11/10/2006
Communication Test	R&S	SMU200	N/A	N/A	N/A
Power Sensor	Anritsu	MA2490A	31431	06/28/2005	06/29/2006
Power Meter	Anritsu	ML2487A	6K00002070	06/28/2005	06/29/2006
Temperature Chamber	TERCHY	MHG-120LF	911009	10/14/2005	10/13/2006
Low Loss Cable	HUBER+SUHNE R	SUCOFLEX 104PEA	N/A	N/A	N/A
Attenuator	Mini-Circuit	BW-S10W5	N/A	09/23/2005	09/22/2006
Attenuator	Mini-Circuit	BW-S6W5	N/A	09/23/2005	09/22/2006
Splitter	Agilent	11636B	51728	09/23/2005	09/22/2006
AC Power Supply	APW-105N	887592	All Power	N/A	N/A

7.5 Measurement Result:.

EUT Mode	Frequency (MHz)	CH	99%Bandwidth (MHz)
GSM 850	824.20	128	0.2494
	836.60	190	0.2499
	848.80	251	0.2493

EUT Mode	Frequency (MHz)	CH	99%Bandwidth (MHz)
PCS 1900	1850.20	512	0.2502
	1880.00	661	0.2530
	1909.80	810	0.2508

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 7-1: GSM Channel Low






Figure 7-2 GSM Channel Mid



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 7-3: GSM Channel High



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 7-4: PCS Channel Low






Figure 7-5 PCS Channel Mid



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 7-6: PCS Channel High



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


8. OUT OF BAND EMISSION AT ANTENNA TERMINALS

8.1 Standard Applicable

According to FCC §2.1051.

FCC §22.917(a), §24.238(a), the magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specified in the instruction manual and/ or alignment procedure, shall not be less than $43 + 10 \log$ (mean output power in watts) dBc below the mean power output outside a license's frequency block (-13dBm)

8.2 Test SET-UP



Note: Measurement setup for testing on Antenna connector

8.3 Measurement Procedure

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.

For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10 th harmonic.
Limit = -13dBm

Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



8.4 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2005	03/28/2006
Spectrum Analyzer	Agilent	7405A	US41160416	06/28/2005	06/29/2006
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2005	11/10/2006
Power Sensor	Anritsu	MA2490A	31431	06/28/2005	06/29/2006
Power Meter	Anritsu	ML2487A	6K00002070	06/28/2005	06/29/2006
Temperature Chamber	TERCHY	MHG-120LF	911009	11/11/2005	11/12/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	N/A	N/A
Attenuator	Mini-Circuit	BW-S10W5	N/A	10/07/2005	10/06/2006
Attenuator	Mini-Circuit	BW-S6W5	N/A	10/07/2005	10/06/2006
Splitter	Mini-Circuit	ZFSC-2-10G	N/A	10/07/2005	10/06/2006
Signal Generator	R&S	SMR40	100210	11/09/2005	11/10/2006

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



8.5 Measurement Result

Figure 8-1: Out of Band emission at antenna terminals– GSM850 Channel Lowest





The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 8-2: Out of Band emission at antenna terminals –GSM850 Channel Mid



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 8-3: Out of Band emission at antenna terminals–GSM850 Channel Highest



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 8-4: Bad edge emission at antenna terminals – GSM850 Channel Lowest







Figure 8-5: Band edge emission at antenna terminals – GSM850 Channel Highest





The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 8-6: Out of Band emission at antenna terminals– PCS1900 Channel Lowest





The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 8-7: Out of Band emission at antenna terminals –PCS1900 Channel Mid



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 8-8: Out of Band emission at antenna terminals–PCS1900 Channel Highest



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Figure 8-9: Bad edge emission at antenna terminals – PCS1900 Channel Lowest





Figure 8-10: Band edge emission at antenna terminals – PCS1900 Channel Highest



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

9. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT


9.1 Standard Applicable

According to FCC §2.1053,

FCC §22.917(a), §24.238(a), the magnitude of each spurious and harmonic emission that can be detected when the equipment is operated under the conditions specified in the instruction manual and/ or alignment procedure, shall not be less than $43 + 10 \log$ (mean output power in watts) dBc below the mean power output outside a license's frequency block (-13dBm)


9.2 EUT Setup (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



(C) Substituted Method Test Set-UP



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

9.3 Measurement Procedure

The EUT was placed on a non-conductive, The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission were identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dBd)} - \text{Cable Loss (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dBi)} - \text{Cable Loss (dB)}$$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

9.4 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2005	03/28/2006
Spectrum Analyzer	Agilent	7405A	US41160416	06/28/2005	06/29/2006
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2005	11/10/2006
Communication Test	R&S	SMU200	N/A	N/A	N/A
Bilog Antenna	SCHWAZBECK	VULB9163	152	06/03/2005	06/02/2006
Horn antenna	Schwarzbeck	BBHA 9120D	309/320	08/16/2005	08/15/2006
Pre-Amplifier	HP	8447D	2944A09469	07/19/2005	07/18/2006
Pre-Amplifier	HP	8494B	3008A00578	02/26/2006	02/25/2007
Signal Generator	R&S	SMR40	100210	02/09/2006	02/10/2007
Turn Table	HD	DT420	N/A	N.C.R	N.C.R
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R
Controller	HD	HD100	N/A	N.C.R	N.C.R
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	10/09/2005	10/08/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	10/09/2005	10/08/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA-0.5M	0.5m	10/09/2005	10/08/2006
Site NSA	SGS	966 chamber	N/A	11/17/2005	11/16/2006
Attenuator	Mini-Circuit	BW-S10W5	N/A	09/23/2005	09/22/2006
Dipole Antenna	Schwarzbeck	VHAP	908/909	06/10/2004	06/11/2006
Dipole Antenna	Schwarzbeck	UHAP	891/892	06/10/2004	06/11/2006
Horn antenna	Schwarzbeck	BBHA 9120D	N/A	08/16/2004	08/15/2006

Measurement Result

Refer to attach tabular data sheets.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Earphone mode

Operation Mode : TX CH Low H Mode
Fundamental Frequency : 824.20 MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Hor.
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	42.72	V	-61.42	-6.43	0.70	-68.55	-13.00	-55.55
61.04	42.66	V	-68.69	-0.52	0.95	-70.17	-13.00	-57.17
823.99	82.38	V	-4.95	-7.87	3.64	-16.47	-13.00	-3.47
1652.50	49.98	V	-57.06	9.30	5.06	-52.82	-13.00	-39.82
2472.60	---	V		10.08	6.30		-13.00	
3296.80	---	V		12.17	7.26		-13.00	
4121.00	---	V		12.61	8.33		-13.00	
4945.20	---	V		12.65	9.19		-13.00	
5769.40	---	V		13.55	9.80		-13.00	
6593.60	---	V		12.05	10.61		-13.00	
7417.80	---	V		11.49	11.28		-13.00	
8242.00	---	V		11.48	12.26		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark”---“ means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + Antenna \text{ Gain } (dBd/dBi) - Cable \text{ loss } (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Earphone mode

Operation Mode : TX CH Low H Mode

Fundamental Frequency : 824.20 MHz

Temperature : 25°C

Humidity : 65%

Test Date: Mar.13, 2006

Test By: Sky

Pol: Hor.

Adaptor Model: 18922053-0

Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	39.70	H	-65.60	-6.43	0.70	-72.73	-13.00	-59.73
60.07	40.37	H	-70.84	-0.46	0.95	-72.25	-13.00	-59.25
159.98	37.91	H	-61.31	-7.81	1.49	-70.61	-13.00	-57.61
823.98	82.15	H	-5.51	-7.87	3.64	-17.03	-13.00	-4.03
1652.50	50.79	H	-56.22	9.30	5.06	-51.98	-13.00	-38.98
2472.60	---	H		10.08	6.30		-13.00	
3296.80	---	H		12.17	7.26		-13.00	
4121.00	---	H		12.61	8.33		-13.00	
4945.20	---	H		12.65	9.19		-13.00	
5769.40	---	H		13.55	9.80		-13.00	
6593.60	---	H		12.05	10.61		-13.00	
7417.80	---	H		11.49	11.28		-13.00	
8242.00	---	H		11.48	12.26		-13.00	

Remark :

1 The emission behaviour belongs to narrowband spurious emission.

2 Remark”---“ means that the emission level is too low to be measured

3 The result basic equation calculation is as follows:

4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + Antenna \text{ Gain} (dBd/dBi) - Cable \text{ loss} (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Earphone mode

Operation Mode : TX CH Mid H Mode

Fundamental Frequency : 836.60 MHz

Temperature : 25°C

Humidity : 65%

Test Date: Mar. 13, 2006

Test By: Sky

Pol: Ver

Adaptor Model: 18922053-0

Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	43.20	V	-60.94	-6.43	0.70	-68.07	-13.00	-55.07
58.13	43.57	V	-66.93	-0.49	0.94	-68.35	-13.00	-55.35
87.23	45.31	V	-58.81	-7.75	1.14	-67.70	-13.00	-54.70
1667.50	51.37	V	-55.66	9.35	5.09	-51.41	-13.00	-38.41
2509.80	---	V		10.09	6.35		-13.00	
3346.40	---	V		12.28	7.29		-13.00	
4183.00	---	V		12.62	8.40		-13.00	
5019.60	---	V		12.67	9.26		-13.00	
5856.20	---	V		13.68	9.85		-13.00	
6692.80	---	V		11.95	10.74		-13.00	
7529.40	---	V		11.45	11.35		-13.00	
8366.00	---	V		11.59	12.43		-13.00	

Remark :

1 The emission behaviour belongs to narrowband spurious emission.

2 Remark”---“ means that the emission level is too low to be measured

3 The result basic equation calculation is as follows:

4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + Antenna \text{ Gain } (dBd/dBi) - Cable \text{ loss } (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Earphone mode

Operation Mode : TX CH Mid H Mode
Fundamental Frequency : 836.60 MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Hor.
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
33.88	39.51	H	-65.19	-5.52	0.72	-71.43	-13.00	-58.43
58.13	40.71	H	-69.72	-0.49	0.94	-71.15	-13.00	-58.15
92.08	43.84	H	-59.76	-7.75	1.17	-68.68	-13.00	-55.68
1667.50	52.85	H	-54.15	9.35	5.09	-49.89	-13.00	-36.89
2509.80	---	H		10.09	6.35		-13.00	
3346.40	---	H		12.28	7.29		-13.00	
4183.00	---	H		12.62	8.40		-13.00	
5019.60	---	H		12.67	9.26		-13.00	
5856.20	---	H		13.68	9.85		-13.00	
6692.80	---	H		11.95	10.74		-13.00	
7529.40	---	H		11.45	11.35		-13.00	
8366.00	---	H		11.59	12.43		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP \text{ (dBm)} = SG \text{ Setting (dBm)} + \text{Antenna Gain (dBd/dBi)} - \text{Cable loss (dB)}$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Earphone mode

Operation Mode : TX CH High H Mode
Fundamental Frequency : 848.8 MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Ver
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	41.46	V	-62.68	-6.43	0.70	-69.81	-13.00	-56.81
61.04	42.83	V	-68.52	-0.52	0.95	-70.00	-13.00	-57.00
143.49	39.98	V	-58.42	-7.79	1.43	-67.65	-13.00	-54.65
849.00	81.62	V	-5.11	-7.88	3.75	-16.74	-13.00	-3.74
1690.00	53.43	V	-53.59	9.41	5.13	-49.31	-13.00	-36.31
2546.40	---	V		10.20	6.40		-13.00	
3395.20	---	V		12.38	7.33		-13.00	
4244.00	---	V		12.63	8.46		-13.00	
5092.80	---	V		12.74	9.32		-13.00	
5941.60	---	V		13.81	9.89		-13.00	
6790.40	---	V		11.86	10.87		-13.00	
7639.20	---	V		11.40	11.48		-13.00	
8488.00	---	V		11.70	12.59		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark”---“ means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP \text{ (dBm)} = SG \text{ Setting(dBm)} + \text{Antenna Gain (dBd/dBi)} - \text{Cable loss (dB)}$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 850 Mode

Earphone mode

Operation Mode : TX CH High H Mode
Fundamental Frequency : 848.8 MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Hor.
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	39.80	H	-65.50	-6.43	0.70	-72.63	-13.00	-59.63
58.13	38.96	H	-71.47	-0.49	0.94	-72.90	-13.00	-59.90
484.93	34.61	H	-59.74	-7.71	2.68	-70.13	-13.00	-57.13
849.00	79.12	H	-7.90	-7.88	3.75	-19.52	-13.00	-6.52
1690.00	52.17	H	-54.82	9.41	5.13	-50.53	-13.00	-37.53
2546.40	---	H		10.20	6.40		-13.00	
3395.20	---	H		12.38	7.33		-13.00	
4244.00	---	H		12.63	8.46		-13.00	
5092.80	---	H		12.74	9.32		-13.00	
5941.60	---	H		13.81	9.89		-13.00	
6790.40	---	H		11.86	10.87		-13.00	
7639.20	---	H		11.40	11.48		-13.00	
8488.00	---	H		11.70	12.59		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark”---“ means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + Antenna \text{ Gain} (dBd/dBi) - Cable \text{ loss} (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 1900 Mode

Earphone mode

Operation Mode : TX CH Low H Mode
Fundamental Frequency : 1850.20MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Ver
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	43.13	V	-61.01	-6.43	0.70	-68.14	-13.00	-55.14
58.13	44.31	V	-66.19	-0.49	0.94	-67.61	-13.00	-54.61
1849.98	82.45	V	-24.51	9.90	5.41	-20.02	-13.00	-7.02
3692.50	49.55	V	-52.06	12.61	7.71	-47.17	-13.00	-34.17
9251.00	---	V		11.92	13.10		-13.00	
11101.20	---	V		11.66	14.33		-13.00	
12951.40	---	V		13.63	15.98		-13.00	
14801.60	---	V		12.76	17.27		-13.00	
16651.80	---	V		15.92	19.04		-13.00	
18502.00	---	V		18.75	21.21		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + Antenna \text{ Gain } (dBd/dBi) - Cable \text{ loss } (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 1900 Mode

Earphone mode

Operation Mode : TX CH Low H Mode

Fundamental Frequency : 1850.20MHz

Temperature : 25°C

Humidity : 65%

Test Date: Mar.13, 2006

Test By: Sky

Pol: Hor.

Adaptor Model: 18922053-0

Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
36.79	40.09	H	-63.71	-4.16	0.75	-68.61	-13.00	-55.61
58.13	39.19	H	-71.24	-0.49	0.94	-72.67	-13.00	-59.67
1849.99	86.82	H	-20.07	9.90	5.41	-15.58	-13.00	-2.58
1315.00	39.66	H	-68.03	7.78	4.44	-64.69	-13.00	-51.69
3692.50	44.63	H	-56.76	12.61	7.71	-51.87	-13.00	-38.87
5550.60	36.68	H	-58.45	13.23	9.68	-54.90	-13.00	-41.90
7400.80	---	H		11.50	11.28		-13.00	
9251.00	---	H		11.92	13.10		-13.00	
11101.20	---	H		11.66	14.33		-13.00	
12951.40	---	H		13.63	15.98		-13.00	
14801.60	---	H		12.76	17.27		-13.00	
16651.80	---	H		15.92	19.04		-13.00	
18502.00	---	H		18.75	21.21		-13.00	

Remark :

1 The emission behaviour belongs to narrowband spurious emission.

2 Remark”---“ means that the emission level is too low to be measured

3 The result basic equation calculation is as follows:

4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + Antenna \text{ Gain} (dBd/dBi) - Cable \text{ loss} (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 1900 Mode

Earphone mode

Operation Mode : TX CH Mid H Mode
Fundamental Frequency : 1880MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Ver
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	44.06	V	-60.08	-6.43	0.70	-67.21	-13.00	-54.21
58.13	44.17	V	-66.33	-0.49	0.94	-67.75	-13.00	-54.75
3752.50	47.24	V	-54.10	12.60	7.81	-49.30	-13.00	-36.30
5642.50	36.89	V	-58.06	13.36	9.73	-54.43	-13.00	-41.43
9400.00	---	V		11.93	13.15		-13.00	
11280.00	---	V		11.92	14.56		-13.00	
13160.00	---	V		13.33	16.11		-13.00	
15040.00	---	V		13.76	17.57		-13.00	
16920.00	---	V		15.27	19.66		-13.00	
18800.00	---	V		18.68	21.34		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + \text{Antenna Gain (dBd/dBi)} - \text{Cable loss (dB)}$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 1900 Mode

Earphone mode

Operation Mode : TX CH Mid H Mode

Fundamental Frequency : 1880MHz

Temperature : 25°C

Humidity : 65%

Test Date: Mar.13, 2006

Test By: Sky

Pol: Hor.

Adaptor Model: 18922053-0

Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
33.88	39.36	H	-65.34	-5.52	0.72	-71.58	-13.00	-58.58
58.13	40.26	H	-70.17	-0.49	0.94	-71.60	-13.00	-58.60
1330.00	43.87	H	-63.78	7.86	4.46	-60.38	-13.00	-47.38
3752.50	43.43	H	-57.71	12.60	7.81	-52.91	-13.00	-39.91
9400.00	---	H		11.93	13.15		-13.00	
11280.00	---	H		11.92	14.56		-13.00	
13160.00	---	H		13.33	16.11		-13.00	
15040.00	---	H		13.76	17.57		-13.00	
16920.00	---	H		15.27	19.66		-13.00	
18800.00	---	H		18.68	21.34		-13.00	

Remark :

1 The emission behaviour belongs to narrowband spurious emission.

2 Remark”---“ means that the emission level is too low to be measured

3 The result basic equation calculation is as follows:

4 $ERP/EIRP\ (dBm) = SG\ Setting(dBm) + Antenna\ Gain\ (dBd/dBi) - Cable\ loss\ (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 1900 Mode

Earphone mode

Operation Mode : TX CH High H Mode
Fundamental Frequency : 1909.8 MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Ver
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	43.37	V	-60.77	-6.43	0.70	-67.90	-13.00	-54.90
58.13	45.29	V	-65.21	-0.49	0.94	-66.63	-13.00	-53.63
1910.02	77.89	V	-29.05	10.08	5.51	-24.48	-13.00	-11.48
3805.00	46.48	V	-54.62	12.60	7.89	-49.91	-13.00	-36.91
5717.50	38.43	V	-56.31	13.48	9.77	-52.60	-13.00	-39.60
5972.40	---	V		13.86	9.91		-13.00	
7963.20	---	V		11.27	11.88		-13.00	
9954.00	---	V		12.08	13.43		-13.00	
11944.80	---	V		13.08	15.21		-13.00	
13935.60	---	V		11.82	16.86		-13.00	
15926.40	---	V		17.08	18.33		-13.00	
17917.20	---	V		9.63	20.12		-13.00	
19908.00	---	V		18.88	20.85		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark”---“ means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP \text{ (dBm)} = SG \text{ Setting(dBm)} + \text{Antenna Gain (dBd/dBi)} - \text{Cable loss (dB)}$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Spurious Emission Measurement Result: GSM 1900 Mode

Earphone mode

Operation Mode : TX CH High H Mode
Fundamental Frequency : 1909.8 MHz
Temperature : 25°C
Humidity : 65%

Test Date: Mar.13, 2006
Test By: Sky
Pol: Hor.
Adaptor Model: 18922053-0
Supplier: Sagem

Freq. (MHz)	SPA. Reading (dBuV)	Ant.Pol. H/V	S.G Output (dBm)	Antenna Gain (dB/dBi)	Cable Loss (dB)	ERP/ EIRP (dBm)	Limit (dBm)	Safe Margin (dBm)
31.94	39.24	H	-66.06	-6.43	0.70	-73.19	-13.00	-60.19
58.13	39.95	H	-70.48	-0.49	0.94	-71.91	-13.00	-58.91
1352.50	45.37	H	-62.20	7.99	4.51	-58.72	-13.00	-45.72
1910.02	84.26	H	-22.59	10.08	5.51	-18.03	-13.00	-5.03
3805.00	44.04	H	-56.88	12.60	7.89	-52.17	-13.00	-39.17
1910.00	80.54	H	-26.31	10.08	5.51	-21.75	-13.00	-8.75
1915.00	64.00	H	-42.85	10.09	5.52	-38.28	-13.00	-25.28
3981.60	47.04	H	-53.14	12.60	8.17	-48.71	-13.00	-35.71
5972.40	---	H		13.86	9.91		-13.00	
7963.20	---	H		11.27	11.88		-13.00	
9954.00	---	H		12.08	13.43		-13.00	
11944.80	---	H		13.08	15.21		-13.00	
13935.60	---	H		11.82	16.86		-13.00	
15926.40	---	H		17.08	18.33		-13.00	

Remark :

- 1 The emission behaviour belongs to narrowband spurious emission.
- 2 Remark"---" means that the emission level is too low to be measured
- 3 The result basic equation calculation is as follows:
- 4 $ERP/EIRP (dBm) = SG \text{ Setting}(dBm) + Antenna \text{ Gain} (dBd/dBi) - Cable \text{ loss} (dB)$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


10. FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT

10.1 Standard Applicable

According to FCC §2.1055(a)(1)(b).

Frequency Tolerance: 2.5 ppm

10.2 Test Set-up:



Note : Measurement setup for testing on Antenna connector

10.3 Measurement Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes re-recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

10.4 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2005	03/28/2006
Spectrum Analyzer	Agilent	E7405A	US41160416	06/28/2005	06/29/2006
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2005	11/10/2006
Communication Test	R&S	SMU200	N/A	N/A	N/A
Power Sensor	Anritsu	MA2490A	31431	06/28/2005	06/29/2006
Power Meter	Anritsu	ML2487A	6K00002070	06/28/2005	06/29/2006
Temperature Chamber	TERCHY	MHG-120LF	911009	10/14/2005	10/13/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	N/A	N/A
Attenuator	Mini-Circuit	BW-S10W5	N/A	09/23/2005	09/22/2006
Attenuator	Mini-Circuit	BW-S6W5	N/A	09/23/2005	09/22/2006
Splitter	Agilent	11636B	51728	09/23/2005	09/22/2006
AC Power Supply	APW-105N	887592	All Power	N/A	N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

10.5 Measurement Result

Reference Frequency: GSM Mid Channel 836.6 MHz @ 25°C				
Limit: +/- 2.5 ppm = 2091 Hz				
Power Supply	Environment	Frequency	Delta (Hz)	Limit (Hz)
Vdc	Temperature (°C)	(MHz)		
3.7	-30	836.59965	290.00	2091
3.7	-20	836.5997	240.00	2091
3.7	-10	836.59972	220.00	2091
3.7	0	836.59987	70.00	2091
3.7	10	836.59990	40.00	2091
3.7	20	836.59994	0.00	2091
3.7	30	836.60005	-110.00	2091
3.7	40	836.60005	-110.00	2091
3.7	50	836.60007	-130.00	2091

Reference Frequency: PCS Mid Channel 1880 MHz @ 25°C				
Limit: +/- 2.5 ppm = 4700 Hz				
Power Supply	Environment	Frequency	Delta (Hz)	Limit (Hz)
Vdc	Temperature (°C)	(MHz)		
3.7	-30	1879.99980	150.00	4700
3.7	-20	1879.99980	150.00	4700
3.7	-10	1879.99986	90.00	4700
3.7	0	1879.99990	50.00	4700
3.7	10	1879.99990	50.00	4700
3.7	20	1879.99995	0.00	4700
3.7	30	1879.99995	0.00	4700
3.7	40	1879.99999	-40.00	4700
3.7	50	1880.00004	-90.00	4700

Note: The battery is rated 3.7V dc.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


11. FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT

11.1 Standard Applicable

According to FCC §2.1055(d)(1)(2)

Frequency Tolerance: 2.5 ppm

11.2 Test Set-up:



Note: Measurement setup for testing on Antenna connector

11.3 Measurement Procedure

Set chamber temperature to 25°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

11.4 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	E4446A	MY43360126	03/29/2005	03/28/2006
Spectrum Analyzer	Agilent	E7405A	US41160416	06/28/2005	06/29/2006
Spectrum Analyzer	R&S	FSP 40	100034	11/09/2005	11/10/2006
Communication Test	R&S	SMU200	N/A	N/A	N/A
Power Sensor	Anritsu	MA2490A	31431	06/28/2005	06/29/2006
Power Meter	Anritsu	ML2487A	6K00002070	06/28/2005	06/29/2006
Temperature Chamber	TERCHY	MHG-120LF	911009	10/14/2005	10/13/2006
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	N/A	N/A
Attenuator	Mini-Circuit	BW-S10W5	N/A	09/23/2005	09/22/2006
Attenuator	Mini-Circuit	BW-S6W5	N/A	09/23/2005	09/22/2006
Splitter	Agilent	11636B	51728	09/23/2005	09/22/2006
AC Power Supply	APW-105N	887592	All Power	N/A	N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

11.5 Measurement Result

Reference Frequency: GSM Mid Channel 836.6 MHz @ 25°C				
Limit: +/- 2.5 ppm = 2091 Hz				
Power Supply	Environment	Frequency	Delta (Hz)	Limit (Hz)
Vdc	Temperature (°C)	(MHz)		
3.70	25.00	836.59994	0.00	2091.00
3.65	25.00	836.5999	40.00	2091.00
4.26	25.00	836.60008	-140.00	2091.00
3.64 (End Point)	25.00	836.59990	40.00	2091.00

Reference Frequency: PCS Mid Channel 1880 MHz @ 25°C				
Limit: +/- 2.5 ppm = 4700 Hz				
Power Supply	Environment	Frequency	Delta (Hz)	Limit (Hz)
Vdc	Temperature (°C)	(MHz)		
3.7	25	1879.99995	0.00	4700
3.35	25	1879.9999	50.00	4700
4.255	25	1880.00002	-70.00	4700
3.34 (Endpoint)	25	1879.99990	50.00	4700

Note: The battery is rated 3.7V dc.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

12. AC POWER LINE CONDUCTED EMISSION TEST

12.1 Standard Applicable

According to §15.207. The emission value for frequency within 150KHz to 30MHz shall not exceed criteria of below chart.

Frequency range MHz	Limits dB(uV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Note		
1.The lower limit shall apply at the transition frequencies		
2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

12.2 EUT Setup

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4-2001.
2. The EUT was plug-in DC power adaptor and was placed on the center of the back edge on the test table. The peripherals like earphone was placed on the side of the EUT. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.
3. The Power adaptor was connected with 110Vac/60Hz power source.

12.3 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

12.4 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMC Analyzer	HP	8594EM	3624A00203	09/02/2005	09/03/2006
EMI Test Receiver	R&S	ESCS30	828985/004	06/09/2005	06/10/2006
Transient Limiter	HP	11947A	3107A02062	09/02/2005	09/03/2006
LISN	Rolf-Heine	NNB-2/16Z	99012	12/31/2005	12/30/2006
LISN	Rolf-Heine	NNB-2/16Z	99013	12/24/2005	12/23/2006
Coaxial Cables	N/A	No. 3, 4	N/A	12/24/2005	12/23/2006

12.5 Measurement Result

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode : GSM 850
 Fundamental Frequency : N/A
 Temperature : 22°C
 Humidity : 59%
 Test Voltage : 120Vac

Test Date : Feb.20, 2006
 Test By : Sky
 Pol : Line
 Adaptor Model : 18922053-0
 Supplier : Sagem

Conducted Emission Measurement



Site : 10M OPEN-SITE

Limit: CISPR22 Class B Conduction(QP)

EUT: GSM850/1900 mobile phone

M/N: A2005sa E1

Note: GSM850 LINK //CHARGE & OPERATION MODE

Phase: L1

Power: AC 120V/60Hz

Distance: RBW: 9 KHz

VBW: 10 KHz

Temperature: 22 °C

Humidity: 59 %

Air Pressure: hpa

Sweep Time: 300 ms

No.	Mk.	Freq.	Reading Level	Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	cm	degree	Comment
1		0.1695	38.69	0.71	39.40	64.98	-25.58	QP		
2		0.1695	12.15	0.71	12.86	54.98	-42.12	AVG		
3		0.1891	36.36	0.73	37.09	64.08	-26.99	QP		
4		0.1891	22.15	0.73	22.88	54.08	-31.20	AVG		
5		0.2203	40.80	0.76	41.56	62.81	-21.25	QP		
6		0.2203	28.39	0.76	29.15	52.81	-23.66	AVG		
7		0.3648	44.64	0.82	45.46	58.62	-13.16	QP		
8	*	0.3648	37.56	0.82	38.38	48.62	-10.24	AVG		
9		1.3922	39.46	0.61	40.07	56.00	-15.93	QP		
10		1.3922	29.95	0.61	30.56	46.00	-15.44	AVG		
11		1.5758	39.25	0.62	39.87	56.00	-16.13	QP		
12		1.5758	31.16	0.62	31.78	46.00	-14.22	AVG		


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode : GSM 850
Fundamental Frequency : N/A
Temperature : 22°C
Humidity : 59%
Test Voltage : 120Vac

Test Date : Feb.20, 2006
Test By : Sky
Pol : Neutral
Adaptor Model : 18922053-0
Supplier : Sagem

Conducted Emission Measurement



Site :10M OPEN-SITE

Limit: CISPR22 Class B Conduction(QP)

EUT: GSM850/1900 mobile phone

M/N: A2005sa E1

Note: GSM850 LINK //CHARGE & OPERATION MODE

Phase: N

Power: AC 120V/60Hz

Distance:

RBW: 9 KHz

VBW: 10 KHz

Temperature: 22 °C

Humidity: 59 %

Air Pressure: hpa

Sweep Time: 300 ms

No. Mk.	Freq.	Reading Level	Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	cm	degree
1	0.1578	37.37	0.69	38.06	65.58	-27.52	QP		
2	0.1578	15.67	0.69	16.36	55.58	-39.22	AVG		
3	0.1734	37.08	0.71	37.79	64.80	-27.01	QP		
4	0.1734	15.75	0.71	16.46	54.80	-38.34	AVG		
5	0.3688	44.63	0.82	45.45	58.53	-13.08	QP		
6 *	0.3688	39.19	0.82	40.01	48.53	-8.52	AVG		
7	0.5523	41.07	0.85	41.92	56.00	-14.08	QP		
8	0.5523	32.78	0.85	33.63	46.00	-12.37	AVG		
9	1.3961	37.75	0.61	38.36	56.00	-17.64	QP		
10	1.3961	30.37	0.61	30.98	46.00	-15.02	AVG		
11	1.5758	39.03	0.62	39.65	56.00	-16.35	QP		
12	1.5758	29.48	0.62	30.10	46.00	-15.90	AVG		


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode : GSM1900
Fundamental Frequency : N/A
Temperature : 22°C
Humidity : 59%
Test Voltage : 120Vac

Test Date : Feb.20, 2006
Test By : Sky
Pol : Line
Adaptor Model : 18922053-0
Supplier : Sagem

Conducted Emission Measurement



Site :10M OPEN-SITE

Limit: CISPR22 Class B Conduction(QP)

EUT: GSM850/1900 mobile phone

M/N: A2005sa E1

Note: GSM1900 LINK //CHARGE & OPERATION MODE

Phase: L1

Power: AC 120V/60Hz

Distance:

RBW: 9 KHz

VBW: 10 KHz

Temperature: 22 °C

Humidity: 59 %

Air Pressure: hpa

Sweep Time: 300 ms

No.	Mk.	Freq. MHz	Reading Level dBuV	Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Antenna Height cm	Table Degree degree	Comment
1		0.3688	43.57	0.82	44.39	58.53	-14.14	QP		
2	*	0.3688	36.23	0.82	37.05	48.53	-11.48	AVG		
3		0.7711	39.64	0.72	40.36	56.00	-15.64	QP		
4		0.7711	27.11	0.72	27.83	46.00	-18.17	AVG		
5		1.6148	41.68	0.62	42.30	56.00	-13.70	QP		
6		1.6148	23.47	0.62	24.09	46.00	-21.91	AVG		
7		2.2398	39.76	0.66	40.42	56.00	-15.58	QP		
8		2.2398	27.31	0.66	27.97	46.00	-18.03	AVG		
9		2.4234	37.66	0.68	38.34	56.00	-17.66	QP		
10		2.4234	18.81	0.68	19.49	46.00	-26.51	AVG		
11		3.6266	37.52	0.75	38.27	56.00	-17.73	QP		
12		3.6266	23.45	0.75	24.20	46.00	-21.80	AVG		


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode : GSM1900
Fundamental Frequency : N/A
Temperature : 22°C
Humidity : 59%
Test Voltage : 120Vac

Test Date : Feb.20, 2006
Test By : Sky
Pol : Neutral
Adaptor Model : 18922053-0
Supplier : Sagem

Conducted Emission Measurement



Site : 10M OPEN-SITE

Limit: CISPR22 Class B Conduction(QP)

EUT: GSM850/1900 mobile phone

M/N: A2005sa E1

Note: GSM1900 LINK //CHARGE & OPERATION MODE

Phase: N

Power: AC 120V/60Hz

Distance:

RBW: 9 KHz

VBW: 10 KHz

Temperature: 22 °C

Humidity: 59 %

Air Pressure: hpa

Sweep Time: 300 ms

No. Mk.	Freq.	Reading Level	Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	cm	degree
1	0.1773	36.59	0.72	37.31	64.61	-27.30	QP		
2	0.1773	24.99	0.72	25.71	54.61	-28.90	AVG		
3	0.3648	43.56	0.82	44.38	58.62	-14.24	QP		
4 *	0.3648	39.66	0.82	40.48	48.62	-8.14	AVG		
5	0.5484	40.61	0.85	41.46	56.00	-14.54	QP		
6	0.5484	33.41	0.85	34.26	46.00	-11.74	AVG		
7	1.1734	39.94	0.59	40.53	56.00	-15.47	QP		
8	1.1734	29.87	0.59	30.46	46.00	-15.54	AVG		
9	1.3922	36.79	0.61	37.40	56.00	-18.60	QP		
10	1.3922	30.66	0.61	31.27	46.00	-14.73	AVG		
11	3.7086	38.07	0.75	38.82	56.00	-17.18	QP		
12	3.7086	24.87	0.75	25.62	46.00	-20.38	AVG		


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

APPENDIX 1

PHOTOGRPHS OF SET UP

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Radiated Emission Set up Photos



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Conducted Emission Test Setup Photo(Power Adaptor)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

APPENDIX 2

PHOTOGRPHS OF EUT

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

All of EUT



Adapter(Model : 18922053-0)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Front View of EUT



Back View of EUT



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Left View of EUT



Right View of EUT



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Top View of EUT



Bottom View of EUT



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Open View of EUT - 1



Open View of EUT - 2



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Internal of EUT --- 1



Internal of EUT --- 2



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Internal of EUT --- 3



Internal of EUT --- 4



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Internal of EUT --- 5



Internal of EUT --- 6



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.