

ICOM-406Q-SAR.docx

APPENDIX 1

SAR Measurement Data

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx

Apr 10, 2015

- *All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)*

TABLE OF CONTENTS

Contents

EXHIBIT 1. HEAD SAR MEASUREMENT SUMMARY 3

EXHIBIT 2. BODY SAR MEASUREMENT SUMMARY 14

EXHIBIT 1. HEAD SAR MEASUREMENT SUMMARY

Antenna	Power (W)	CH	CH. Freq	HEAD SAR1g (W/Kg)
				BP-282
			(MHz)	1500mAh
FA-SC59V 156mm 156-163 MHz	4.68	1	156.05	1.24
	4.64	16	156.8	0.987
	4.61	28	157.4	1.02

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx
Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

TEST LABORATORY: ULTRATECH GROUP OF LABS
File Name: BP-282 SC59V 156mm 156.05MHz.da52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022
Program Name: Body Back with FA-SC59V

Communication System: UID 0, CW; Frequency: 156.05 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 156.05$ MHz; $\sigma = 0.736$ S/m; $\epsilon_r = 53.007$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3208; ConvF(7.43, 7.43, 7.43); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Zoom Scan (5x5x7)

(5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 45.50 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.82 W/kg

SAR(1 g) = 1.24 W/kg; SAR(10 g) = 0.924 W/kg (SAR corrected for target medium)

[Info: Interpolated medium parameters used for SAR evaluation.](#)


Maximum value of SAR (measured) = 1.39 W/kg

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Area Scan (61x201x1):

Interpolated grid: dx=1.500 mm, dy=1.500 mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.48 W/kg



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx
Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Laboratory: Ultratech Group of Labs
FILE NAME: BP-282 SC59V 156MM 157.4MHZ.DA52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022
Program Name: Body Back with FA-SC59V

Communication System: UID 0, CW; Frequency: 157.4 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 158 \text{ MHz}$; $\sigma = 0.736 \text{ S/m}$; $\epsilon_r = 52.812$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3208; ConvF(7.43, 7.43, 7.43); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Zoom Scan (5x5x7)

(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 45.16 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.47 W/kg


SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.759 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.13 W/kg

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Area Scan (61x201x1):

Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 1.23 W/kg



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx
Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Laboratory: Ultratech Group of Labs
FILE NAME: BP-282 SC59V 156MM 156.8MHZ .DA52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022
Program Name: Body Back with FA-SC59V

Communication System: UID 0, CW; Frequency: 156.8 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 156.8 \text{ MHz}$; $\sigma = 0.736 \text{ S/m}$; $\epsilon_r = 52.932$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3208; ConvF(7.43, 7.43, 7.43); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Zoom Scan (5x5x7)

(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 42.96 V/m; Power Drift = -1.34 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.987 W/kg; SAR(10 g) = 0.750 W/kg (SAR corrected for target medium)

[Info: Interpolated medium parameters used for SAR evaluation.](#)


Maximum value of SAR (measured) = 1.09 W/kg

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Area Scan (61x201x1):

Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 1.17 W/kg



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx
Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Laboratory: Ultratech Group of Labs

FILE NAME: BP-282 SC59V 156MM 157.4MHZ A.DA52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022

Program Name: Body Back with FA-SC59V

Communication System: UID 0, CW; Frequency: 157.4 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 158 \text{ MHz}$; $\sigma = 0.736 \text{ S/m}$; $\epsilon_r = 52.812$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3208; ConvF(7.43, 7.43, 7.43); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Zoom Scan (5x5x7)

(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 43.69 V/m; Power Drift = -1.36 dB

Peak SAR (extrapolated) = 1.47 W/kg


SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.770 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.13 W/kg

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Area Scan (61x201x1):

Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 1.21 W/kg



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx
Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Laboratory: Ultratech Group of Labs

FILE NAME: BP-282 SC59V 156MM 157.425MHZ A.DA52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022

Program Name: Body Back with FA-SC59V

Communication System: UID 0, CW; Frequency: 157.425 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 158 \text{ MHz}$; $\sigma = 0.736 \text{ S/m}$; $\epsilon_r = 52.812$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3208; ConvF(7.43, 7.43, 7.43); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Zoom Scan (5x5x7)

(5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 39.43 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.39 W/kg


SAR(1 g) = 0.966 W/kg; SAR(10 g) = 0.728 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.08 W/kg

Configuration_Head_IC-M25/Front to Face, P=5W, d=25mm/Area Scan (61x201x1):

Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 1.14 W/kg



0 dB = 1.08 W/kg = 0.32 dBW/kg

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx

Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 2. BODY SAR MEASUREMENT SUMMARY

Antenna	Power (W)	CH	CH. Freq	BODY SAR1g (W/Kg)	BODY SAR10g (W/Kg)
				BP-282	BP-282
			(MHz)	1500mAh	1500mAh
FA-SC59V 156mm 156-163 MHz	4.68	1	156.05	0.5	0.378
	4.64	16	156.8	0.426	0.351
	4.61	28	157.4	0.433	0.328

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx
Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Laboratory: Ultratech Group of Labs
FILE NAME: BP-282 SC59V 156MM 156.05MHZ.DA52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022
Program Name: Body Back with FA-SC59V

Communication System: UID 0, CW; Frequency: 156.05 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 156.05 \text{ MHz}$; $\sigma = 0.766 \text{ S/m}$; $\epsilon_r = 61.889$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:


- Probe: ES3DV3 - SN3208; ConvF(6.93, 6.93, 6.93); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Body_IC-M25/Back to phantom, Belt Clip Touch, P=5W, d=0mm/Zoom Scan (5x5x7) (5x6x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$
Reference Value = 27.29 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.711 W/kg
SAR(1 g) = 0.500 W/kg; SAR(10 g) = 0.378 W/kg (SAR corrected for target medium)

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 0.542 W/kg

Configuration_Body_IC-M25/Back to phantom, Belt Clip Touch, P=5W, d=0mm/Area Scan (61x181x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (interpolated) = 0.543 W/kg



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx

Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Laboratory: Ultratech Group of Labs
FILE NAME: BP-282 SC59V 156MM 157.4MHZ.DA52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022
Program Name: Body Back with FA-SC59V


Communication System: UID 0, CW; Frequency: 157.4 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 158 \text{ MHz}$; $\sigma = 0.767 \text{ S/m}$; $\epsilon_r = 62.099$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3208; ConvF(6.93, 6.93, 6.93); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Body_IC-M25/Back to phantom, Belt Clip Touch, P=5W, d=0mm/Zoom Scan (5x5x7) (6x6x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$
Reference Value = 24.81 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 0.616 W/kg
SAR(1 g) = 0.433 W/kg; SAR(10 g) = 0.328 W/kg (SAR corrected for target medium)
Maximum value of SAR (measured) = 0.470 W/kg

Configuration_Body_IC-M25/Back to phantom, Belt Clip Touch, P=5W, d=0mm/Area Scan (61x181x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$
Maximum value of SAR (interpolated) = 0.469 W/kg



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx

Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Test Laboratory: Ultratech Group of Labs

FILE NAME: BP-282 SC59V 156MM 157.425MHZ.DA52:0

DUT: ICOM VHF Transceiver; Type: IC-M25; Serial: 00000022

Program Name: Body Back with FA-SC59V

Communication System: UID 0, CW; Frequency: 157.425 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 158 \text{ MHz}$; $\sigma = 0.767 \text{ S/m}$; $\epsilon_r = 62.099$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3208; ConvF(6.93, 6.93, 6.93); Calibrated: 1/23/2015;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 10/9/2014
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- ; SEMCAD X Version 14.6.10 (7331)

Configuration_Body_IC-M25/Back to phantom, Belt Clip Touch, P=5W, d=0mm/Zoom

Scan (5x5x7) (5x6x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.57 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.658 W/kg


SAR(1 g) = 0.463 W/kg; SAR(10 g) = 0.351 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 0.502 W/kg

Configuration_Body_IC-M25/Back to phantom, Belt Clip Touch, P=5W, d=0mm/Area

Scan (61x181x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.492 W/kg



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-406Q-SAR-Appendix 1.docx
Apr 10, 2015

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)