



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM180500437005

Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1805004370RG
Applicant: Fibocom Wireless Inc.
Address of Applicant: 5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Manufacturer: Fibocom Wireless Inc.
Address of Manufacturer: 5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Factory: DongGuan Huabel Electronic Technology Co.,Ltd
Address of Factory: No.9,Industrial Northern Road,National High Tech Industrial Development Zone, SongShan Lake DongGuan city, GuangDong province P.R.China
Product Name: LTE Module
Model No.(EUT): L860-GL
Trade Mark: Fibocom
FCC ID: ZMOL860GL
Standards: 47 CFR Part 2
47 CFR Part 22 subpart H
47 CFR Part 24 subpart E
47 CFR Part 27 subpart C
47 CFR Part 90 subpart R
47 CFR Part 90 subpart S
Date of Receipt: 2018-06-12
Date of Test: 2018-06-15 to 2018-09-03
Date of Issue: 2018-09-03

Test Result:	PASS*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Derek Yang
Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf-available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



1 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-09-03		Original

Authorized for issue by:				
				2018-09-03
		<hr/> Mike Hu /Project Engineer		
				2018-09-03
		<hr/> David Chen /Reviewer		



Contents

1	VERSION	2
	CONTENTS.....	3
2	GENERAL INFORMATION.....	4
2.1	CLIENT INFORMATION	4
2.2	GENERAL DESCRIPTION OF EUT	4
2.3	TEST MODE	5
2.4	TEST LOCATION	5
2.5	TEST FACILITY	5
2.6	DEVIATION FROM STANDARDS	5
2.7	ABNORMALITIES FROM STANDARD CONDITIONS	6
2.8	OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
3	RF EXPOSURE EVALUATION	7
3.1	RF EXPOSURE COMPLIANCE REQUIREMENT	7
3.1.1	Limits	7
3.1.2	Test Procedure.....	7
3.1.3	EUT RF Exposure Evaluation.....	8



2 General Information

2.1 Client Information

Applicant:	Fibocom Wireless Inc.
Address of Applicant:	5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Manufacturer:	Fibocom Wireless Inc.
Address of Manufacturer:	5/F, Tower A, Technology Building II, 1057 Nanhai Avenue, Shenzhen, China
Factory:	DongGuan Huabel Electronic Technology Co.,Ltd
Address of Factory:	No.9,Industrial Northern Road,National High Tech Industrial Development Zone, SongShan Lake DongGuan city, GuangDong province P.R.China

2.2 General Description of EUT

Product Name:	LTE Module
Model No.:	L860-GL
Trade Mark:	Fibocom
Hardware Version	V1.2
Software Version	18600.5003.00.17.00.02
Sample Type:	LTE Module
Antenna Type:	Dipole
Antenna Gain:	WCDMA BAND II: 4dBi; WCDMA BAND IV: 4dBi; WCDMA BAND V: 3dBi; LTE BAND 2: 4dBi; LTE BAND 4: 4dBi; LTE BAND 5:3dBi; LTE BAND 7: 4dBi; LTE BAND 12: 3dBi; LTE BAND 13: 2dBi; LTE BAND 14: 2dBi; LTE BAND17: 3dBi; LTE BAND 25: 4dBi; LTE BAND 26: 3dBi; LTE BAND 30: 1dBi; LTE BAND 38: 4dBi; LTE BAND 41: 3dBi; LTE BAND 66: 4dBi;

2.3 Test Mode

Test Mode	Test Modes Description
UMTS/TM1	UMTS system, WCDMA, QPSK modulation
UMTS/TM2	UMTS system, WCDMA, 16QAM modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation
LTE/TM3	LTE system, 64QAM modulation

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

2.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

2.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC

Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

2.6 Deviation from Standards

None.



2.7 Abnormalities from Standard Conditions

None.

2.8 Other Information Requested by the Customer

None.

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
F=frequency in MHz *=Plane-wave equivalent power density RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).				

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.



3.1.3 EUT RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0 / 2.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Operating Band	Frequency (MHz)	Gain (dBi)	Max Conducted Average Output Power (dBm)	Output Power to Antenna (dBm)	EIRP(ERP) Limit (dBm)	Output Power to Antenna (mw)	Power Density at R = 20 cm (mW/cm ²)	Limit (W/m ²)	Gain according to EIRP (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusion
WCDMA B2	1852.4	4.00	24.50	28.50	33.00	281.8383	0.1408	1.0000	8.50	12.51	8.50	Pass
WCDMA B4	1712.4	4.00	24.50	28.50	30.00	281.8383	0.1408	1.0000	5.50	12.51	5.50	Pass
WCDMA B5	826.4	3.00	24.50	25.35	38.45	281.8383	0.1119	0.5509	16.10	9.92	9.92	Pass
LTE B2	1850.7	4.00	24.00	28.00	33.00	251.1886	0.1255	1.0000	9.00	13.01	9.00	Pass
LTE B4	1710.7	4.00	24.00	28.00	30.00	251.1886	0.1255	1.0000	6.00	13.01	6.00	Pass
LTE B5	824.7	3.00	25.00	25.85	38.45	316.2278	0.1255	0.5498	15.60	9.41	9.41	Pass
LTE B7	2502.5	4.00	24.00	28.00	33.00	251.1886	0.1255	1.0000	9.00	13.01	9.00	Pass
LTE B12	699.7	3.00	24.00	24.85	34.77	251.1886	0.0997	0.4665	12.92	9.70	9.70	Pass
LTE B13	779.5	2.00	24.00	23.85	34.77	251.1886	0.0792	0.5197	12.92	10.16	10.16	Pass
LTE B14	790.5	2.00	24.00	23.85	34.77	251.1886	0.0792	0.5270	12.92	10.23	10.23	Pass
LTE B17	706.5	3.00	24.00	24.85	34.77	251.1886	0.0997	0.4710	12.92	9.74	9.74	Pass
LTE B25	1850.7	4.00	24.00	28.00	33.00	251.1886	0.1255	1.0000	9.00	13.01	9.00	Pass
LTE B26(814-824)	814.7	3.00	25.00	25.85	50.00	316.2278	0.1255	0.5431	27.15	9.36	9.36	Pass
LTE B26(824-849)	824.7	3.00	25.00	25.85	38.45	316.2278	0.1255	0.5498	15.60	9.41	9.41	Pass
LTE B30	2307.5	1.00	23.00	24.00	24.00	199.5262	0.0500	1.0000	1.00	14.01	1.00	Pass
LTE B38	2572.5	4.00	24.00	28.00	33.00	251.1886	0.1255	1.0000	9.00	13.01	9.00	Pass
LTE B41	2498.5	4.00	27.50	31.50	33.00	562.3413	0.2810	1.0000	5.50	9.51	5.50	Pass
LTE B66	1710.7	4.00	24.00	28.00	30.00	251.1886	0.1255	1.0000	6.00	13.01	6.00	Pass

Note: Refer to report No. SZEM180500437001 for EUT test Max Conducted Output Power value.