

Choose Scandinavian trust

## **RADIO TEST REPORT**

Report ID

REP089192

Project ID PRJ075234

Type of assessment:

**Class II Permissive Change** 

Applicant:

**GSI Electronics Inc.** 

Model (HVIN):

Raspberry Pi RMO

FCC ID:

2AFLZRPIRM0

ISED Certification number:

11880A-RPIRM0

Specifications:

FCC 47 CFR Part 15 Subpart C, §15.247

RSS-247, Issue 3, Aug 2023, Section 5

Date of issue: May 1, 2025

Kevin Rose, EMC/RF Specialist

Tested by

Andrey Adelberg, Senior RF/EMC Specialist Reviewed by

Signature

Adelberg

Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).

The tests included in this report are within the scope of this accreditation. The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.



ANAB File Number: AT-3195 (Ottawa/Almonte); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)



#### Lab locations

Company name	Nemko Canada In	с.			
Facilities	Ottawa site:	Montre	éal site:	Cambridge site:	Almonte site:
	303 River Road	292 La	brosse Avenue	1-130 Saltsman Drive	1500 Peter Robinson Road
	Ottawa, Ontario	Pointe	Pointe-Claire, Québec	Cambridge, Ontario	West Carleton, Ontario
	Canada	Canada	а	Canada	Canada
	K1V 1H2	H9R 5L	-8	N3E 0B2	KOA 1LO
	Tel: +1 613 737 96	580 Tel: +1	514 694 2684	Tel: +1 519 650 4811	Tel: +1 613 256-9117
	Fax: +1 613 737 9	691 Fax: +1	L 514 694 3528		
Test site identifier	Organization	Ottawa/Almonte	Montreal	Cambridge	
	FCC:	CA2040	CA2041	CA0101	
	ISED:	2040A-4	2040G-5	24676	
Website	www.nemko.com				

#### Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

#### Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. © Nemko Canada Inc.



## Table of Contents

Table of 0	Contents	. 3
Section 1	Report summary	. 4
1.1	Test specifications	. 4
1.2	Test methods	. 4
1.3	Exclusions	. 4
1.4	Statement of compliance	. 4
1.5	Test report revision history	. 4
Section 2	Engineering considerations	. 5
2.1	Modifications incorporated in the EUT for compliance	. 5
2.2	Technical judgment	. 5
2.3	Deviations from laboratory tests procedures	. 5
Section 3	Test conditions	. 6
3.1	Atmospheric conditions	. 6
3.2	Power supply range	. 6
Section 4	Measurement uncertainty	. 7
4.1	Uncertainty of measurement	. 7
Section 5	Information provided by the applicant	. 8
5.1	Disclaimer	. 8
5.2	Applicant/Manufacture	. 8
5.3	EUT information	. 8
5.4	Radio technical information	. 8
5.5	EUT setup details	. 8
Section 6	Summary of test results	10
6.1	Testing location	10
6.2	Testing period	10
6.3	Sample information	10
6.4	FCC Part §15.247 test results	10
6.5	ISED RSS-247, Issue 2, test results	10
Section 7	Test equipment	11
7.1	Test equipment list	11
Section 8	Testing data	12
8.1	Spurious (out-of-band) unwanted emissions	12
Section 9	EUT setup diagrams	22
9.1	Radiated emissions set-up for frequencies below 1 GHz	22
9.2	Radiated emissions set-up for frequencies above 1 GHz	22

## Section 1 Report summary

#### 1.1 Test specifications

Nèmko

FCC 47 CFR Part 15, Subpart C, Clause 15.247	Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–585 MHz
RSS-247, Issue 3, Aug 2023, Section 5	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

## 1.2 Test methods

558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread
(April 2, 2019)	spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules.
ANSI C63.10 v2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
RSS-102, Issue 5, March 19, 2015	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

#### 1.3 Exclusions

Partial testing was performed on the product with the transmitter operating to confirm that the module with the new antenna meets the FCC/ISED requirements. Client also declared that the 5 GHz operation will not be supported, as it will be deactivated in the firmware.

## 1.4 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was performed against all relevant requirements of the test standard except as noted in section 1.3 above. Results obtained indicate that the product under test complies In full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

## 1.5 Test report revision history

Table 1.5-1:	Test report	revision	history
--------------	-------------	----------	---------

Revision #	Date of issue	Details of changes made to test report
REP089192	May 1, 2025	Original report issued

## Section 2 Engineering considerations

## 2.1 Modifications incorporated in the EUT for compliance

There were no modifications performed to the EUT during this assessment.

## 2.2 Technical judgment

Only radiated spurious emissions test with the new antenna was performed.

## 2.3 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.

## Section 3 Test conditions

## 3.1 Atmospheric conditions

Temperature	15 °C – 35 °C
Relative humidity	20 % – 75 %
Air pressure	86 kPa (860 mbar) – 106 kPa (1060 mbar)

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

## 3.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages ±5 %, for which the equipment was designed.

## Section 4 Measurement uncertainty

## 4.1 Uncertainty of measurement

Nèmko

UKAS Lab 34 and TIA-603-B have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada, Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products.

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of K = 2 with 95% certainty.

Test name	Measurement uncertainty, ±dB
Radiated spurious emissions	3.78
AC power line conducted emissions	3.55

## Information provided by the applicant

#### Information provided by the applicant Section 5

#### Disclaimer 5.1

Nèmko

This section contains information provided by the applicant and has been utilized to support the test plan. Inaccurate information provided by the applicant can affect the validity of the results contained within this test report. Nemko accepts no responsibility for the information contained within this section and the impact it may have on the test plan and resulting measurements.

#### 5.2 Applicant/Manufacture

Applicant name	GSI Electronics
Applicant address	5200 Armand-Frappier, St-Hubert, QC, J3Z 1G5, Canada
Manufacture name	Same as applicant
Manufacture address	Same as applicant

#### 5.3 **EUT** information

WiFi radio Model (HVIN)	Raspberry Pi RMO
Power supply requirements	DC: 12 Vdc
Product description and theory	RF WiFi module on vision connect host which provides WiFi connectivity of legacy GSI products.
of operation	

#### Radio technical information 5.4

Category of Wideband Data	Frequency Hopping Spread Spectrum (FHSS) equipment
Transmission equipment	Other types of Wideband Data Transmission equipment (e.g. DSSS, OFDM, etc.).
Frequency band	2400–2483.5 MHz
Frequency Min (MHz)	2412
Frequency Max (MHz)	2462
Channel numbers	1–11
Antenna information	Molex Inc. 146153-0200 2.6 dBi Gain (for 2.4 GHz)

#### 5.5 EUT setup details

#### 5.5.1 Radio exercise details

Operating conditions	The EUT was powered with 12V DC supply through 100–240 V <sub>AC</sub> 50/60 Hz PSU. It was then set to continuous transmission using RealTerm software.
Transmitter state	Transmitter set into continuous mode.



5.5.2 EUT setup configuration

Table 5.5-1: EUT sub assemblies			
Description	Brand name	Model, Part number, Serial number, Revision level	
AC/DC Adapter	GSI	NA	
	Table 5.5-2:	EUT interface ports	
Description			Qty.
3-Pin Supply connector			1

Table 5.5-3: Support equipment

Description	Brand name	Model, Part number, Serial number, Revision level
Laptop	Dell	SN: 6776506622, MN: Precision 7530
Router	D-link	TL-WR1043ND
Antenna	Molex Inc.	MN 1461530200

Table 5.5-4: Inter-connection cables

Cable description	From	То	Length (m)
DC Cable (2C 18-24 AWG Wire)	AC/DC PSU	DC input on EUT	5
AC Cord (3C 18 AWG Wire)	AC Mains	AC/DC PSU	2
Antenna Cable	EUT	Antenna	0.1

## Section 6 Summary of test results

## 6.1 Testing location

Test location (s)	Montreal		
6.2 Testing period			
Test start date	February 27, 2025	Test end date	March 18, 2025
6.3 Sample informatic	n		
Receipt date	February 27, 2025	Nemko sample ID number(s)	PRJ0752340001

## 6.4 FCC Part §15.247 test results

Table 6.4-1: FCC requirements results

Part	Test description	Verdict
§15.247(d)	Spurious emissions	Pass
Notes:	All other specification's requirements are not applicable for this type of assessment, therefore were removed from the table.	

## 6.5 ISED RSS-247, Issue 3, test results

#### Table 6.5-1: ISED requirements results

Part	Test description	Verdict
5.5	Unwanted emissions	Pass
Notes:	All other specification's requirements are not applicable for this type of assessment, therefore were removed from the table.	

## Section 7 Test equipment

## 7.1 Test equipment list

Nèmko

Table 7.1-1: Equipment list					
Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
3 m EMI test chamber (Emissions)	TDK	SAC-3	FA002532e	1 year	May 8, 2025
Flush mount turntable	Sunol	FM2022	FA002550	_	NCR
Controller	Sunol	SC104V	FA002551	-	NCR
Antenna mast	Sunol	TLT2	FA002552	_	NCR
Bilog antenna (20–2000 MHz)	Sunol	JB1	FA002517	1 year	June 6, 2025
Horn antenna (1–18 GHz)	EMCO	3115	FA001451	1 year	June 6, 2025
50 Ω coax cable	Huber + Suhner	None	FA003438	1 year	May 11, 2025
RF Cable Assembly	Huber + Suhner	2M-750-195A- 750	FA002554	1 year	May 11, 2025
LNA (1-18 GHz)	Miteq	N/A	FA003391	1 year	January 20, 2026
2.4 GHz band Notch Filter	Microwave Circuits	N0324413	FA002693	_	NCR
Horn antenna (18–40 GHz)	EMCO	3116	FA002487	1 year	April 9, 2025

Notes: NCR - no calibration required



## Section 8 Testing data

#### 8.1 Spurious (out-of-band) unwanted emissions

#### 8.1.1 References, definitions and limits

#### FCC §15.247:

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### RSS-247, Clause 5.5:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Field strength of emissions				
Frequency, MHz	μV/m	dBµV/m	Measurement distance, m	
0.009–0.490	2400/F	67.6 – 20 × log <sub>10</sub> (F)	300	
0.490-1.705	24000/F	$87.6 - 20 \times \log_{10}(F)$	30	
1.705–30.0	30	29.5	30	
30–88	100	40.0	3	
88–216	150	43.5	3	
216–960	200	46.0	3	
above 960	500	54.0	3	

#### Table 8.1-1: FCC §15.209 and RSS-Gen - Radiated emission limits

Notes: In the emission table above, the tighter limit applies at the band edges.

For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.



Testing data Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

#### References, definitions and limits, continued

Table 8.1-2: ISED	restricted	frequency	bands
-------------------	------------	-----------	-------

MHz	MHz	MHz	GHz
0.090-0.110	12.57675-12.57725	399.9–410	7.25–7.75
0.495–0.505	13.36–13.41	608–614	8.025-8.5
2.1735-2.1905	16.42–16.423	960–1427	9.0–9.2
3.020-3.026	16.69475–16.69525	1435–1626.5	9.3–9.5
4.125-4.128	16.80425-16.80475	1645.5-1646.5	10.6–12.7
4.17725-4.17775	25.5-25.67	1660–1710	13.25–13.4
4.20725-4.20775	37.5–38.25	1718.8–1722.2	14.47–14.5
5.677-5.683	73–74.6	2200–2300	15.35–16.2
6.215-6.218	74.8–75.2	2310–2390	17.7–21.4
6.26775-6.26825	108–138	2483.5-2500	22.01-23.12
6.31175–6.31225	149.9–150.05	2655–2900	23.6–24.0
8.291-8.294	156.52475-156.52525	3260–3267	31.2–31.8
8.362-8.366	156.7–156.9	3332–3339	36.43–36.5
8.37625-8.38675	162.0125-167.17	3345.8–3358	
8.41425-8.41475	167.72–173.2	3500–4400	Above 28.6
12.29–12.293	240–285	4500–5150	ADOVE 38.0
12.51975-12.52025	322–335.4	5350–5460	

Note: Certain frequency bands listed in Table 8.1-2 and above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

#### Table 8.1-3: FCC restricted frequency bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42–16.423	399.9–410	4.5–5.15
0.495–0.505	16.69475-16.69525	608–614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960–1240	7.25–7.75
4.125-4.128	25.5–25.67	1300–1427	8.025-8.5
4.17725-4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725-4.20775	73–74.6	1645.5-1646.5	9.3–9.5
6.215-6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775-6.26825	108–121.94	1718.8-1722.2	13.25–13.4
6.31175-6.31225	123–138	2200–2300	14.47–14.5
8.291-8.294	149.9–150.05	2310-2390	15.35–16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7–21.4
8.37625-8.38675	156.7–156.9	2690–2900	22.01-23.12
8.41425-8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975-12.52025	240–285	3345.8–3358	36.43–36.5
12.57675-12.57725	322–335.4	3600-4400	Above 38.6
13.36–13.41			

## 8.1.2 Test summary

Verdict	Pass		
Test date	March 19, 2025	Temperature	21 °C
Tested by	Kevin Rose	Air pressure	1008 mbar
Test location	Montreal	Relative humidity	36 %

## Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

#### 8.1.3 Observations, settings and special notes

- As part of the current assessment, the test range of 9 kHz to 10<sup>th</sup> harmonic has been fully considered and compared to the actual frequencies utilized within the EUT. Since the EUT contains a transmitter in the GHz range, the EUT has been deemed compliant without formal testing in the 9 kHz to 30 MHz test range, therefore formal test results (tabular data and/or plots) are not provided within this test report.
- EUT was set to transmit with 100 % duty cycle
- Radiated measurements were performed at a distance of 3 m.
- DTS emissions in restricted frequency bands test was performed as per KDB 558074, section 8.6 with reference to ANSI C63.10 subclause 11.12.
- DTS band-edge emission measurements test was performed as per KDB 558074, section 8.7 with reference to ANSI C63.10 subclause 11.13.

#### Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

#### Spectrum analyser settings for peak radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Detector mode:	Peak
Trace mode:	Max Hold

# Spectrum analyser settings or average radiated measurements within restricted bands above 1 GHz: Resolution bandwidth: 1 MHz Video bandwidth: 10 Hz Detector mode: Peak Trace mode: Max Hold

#### 8.1.4 Test data

Notes:

#### Table 8.1-4: Output power results with the new antenna (worst case modulation results)

Channel	Frequency,	Output power, dBm		Margin, Antenna gain,		EIRP, dBm		Margin,
	MHz	Measured	Limit	dB	dBi	Measured	Limit	dB
Low	2412	9.05	30	20.95	2.6	11.65	36	24.35
Mid	2437	9.30	30	20.70	2.6	11.90	36	24.10
High	2462	9.16	30	20.84	2.6	11.76	36	24.24

Notes: The modulation that resulted in the highest output power was 802.11g with 6 Mbps, so it was the basis for the EIRP calculation.

#### Table 8.1-5: Radiated field strength measurement results

Channel	Frequency,	Peak Field strer	Peak Field strength, dBµV/m		Average Field strength, dBµV/m		Margin,
	MHz	Measured	Limit	dB	Measured	Limit	dB
Low	2390.0*	50.2	74.0	32.0	41.6	54.0	12.0
High	2483.5*	50.7	74.0	28.1	41.8	54.0	8.1

Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

\* - peak levels were below the average limit, therefore those frequencies weren't tested with average detector.



Testing data Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

Test data, Continued



#### Testing data

Section 8

Test nameSpurious (out of band) unwanted emissionsSpecificationFCC Part 15 Subpart C and RSS-247, Issue 3







Figure 8.2 2: Band edge spurious emissions at 2483.5 MHz AVG



Testing data Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

Test data, Continued



PRJ0075234 Low channel tx 30 MHz-1 GHz

- Preview Result 1-PK+
- Critical\_Freqs PK+
- FCC 15.209 and RSS-210 limit line RstrB
- Final\_Result QPK

#### Figure 8.2 3: Radiated spurious emissions on 30 MHz to 1 GHz (low channel)



PRJ0075234 Mid channel tx 30 MHz-1 GHz

- Preview Result 1-PK+
  - Critical\_Freqs PK+
     FCC 15.209 and RSS-210 limit line RstrB
- Final\_Result QPK

Figure 8.2.4: Radiated spurious emissions on 30 MHz to 1 GHz (mid channel)



Testing data Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

Test data, Continued



PRJ0075234 High channel tx 30 MHz-1 GHz

- Preview Result 1-PK+
- +
- Critical\_Freqs PK+ FCC 15.209 and RSS-210 limit line RstrB
- ٠ Final\_Result QPK

Figure 8.2 5: Radiated spurious emissions on 30 MHz to 1 GHz (high channel)



PRJ0075234 Low channel tx 1-18 GHz

Preview Result 2-AVG

Preview Result 1-PK+

FCC 15.209 and RSS-210 limit line RstrB pk FCC 15.209 and RSS-210 limit line RstrB

Final\_Result PK+

Final\_Result AVG

Figure 8.2 6: Radiated spurious emissions on 1–18 GHz (low channel)



Testing data Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

Test data, Continued



PRJ0075234 Mid channel tx 1-18 GHz

Preview Result 2-AVG

Preview Result 1-PK+

FCC 15.209 and RSS-210 limit line RstrB pk FCC 15.209 and RSS-210 limit line RstrB

Final\_Result PK+

Final\_Result AVG

Figure 8.2 7: Radiated spurious emissions on 1–18 GHz (mid channel)



high channel tx 1-18 GHz

Preview Result 2-AVG Preview Result 1-PK+

FCC 15.209 and RSS-210 limit line RstrB pk

FCC 15.209 and RSS-210 limit line RstrB

Final\_Result PK+

Final\_Result AVG

Figure 8.2 8: Radiated spurious emissions on 1–18 GHz (high channel)



Testing data Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

Test data, Continued



12:08:05 PM 03/26/2025





12:09:03 PM 03/26/2025

Figure 8.2 10: Radiated spurious emissions on 18-26 GHz (mid channel)



Testing data Spurious (out of band) unwanted emissions FCC Part 15 Subpart C and RSS-247, Issue 3

Test data, Continued



Figure 8.2 11: Radiated spurious emissions on 18-26 GHz (high channel)



## Section 9 EUT setup diagrams





## 9.2 Radiated emissions set-up for frequencies above 1 GHz



End of the test report