



REPORT No.: SZ24060062S01

RF EXPOSURE EVALUATION REPORT

APPLICANT : Soundmax Electronics Limited

PRODUCT NAME : MONITOR WITH RECEIVER

MODEL NAME : DMX5710S, DMX50S, DMX500S,
DMX723WS, DMX80AXS, DMX6523S,
KW-M695BW, KW-M690BW

BRAND NAME : KENWOOD, JVC

FCC ID : 2AB7S-YL5077K00

STANDARD(S) : 47 CFR Part 2(2.1091)

RECEIPT DATE : 2024-06-07

TEST DATE : 2024-07-02 to 2024-08-05

ISSUE DATE : 2024-09-02



Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1 Applicant and Manufacturer Information	3
1.2 Equipment under Test (EUT) Description	3
1.3 Applied Reference Documents	5
2. Device Category and RF Exposure Limit	6
3. Maximum Average Power Summary	7
4. RF Exposure Assessment	8
Annex A Testing Laboratory Information	9

Change History		
Version	Date	Reason for change
1.0	2024-09-02	First edition



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Soundmax Electronics Limited
Applicant Address:	17/F EU YANG SANG TOWER, 11-15 CHATHAM ROAD,T.S.T, KOWLOON, Hong Kong, China
Manufacturer:	Soundmax Electronics Limited
Manufacturer Address:	17/F EU YANG SANG TOWER, 11-15 CHATHAM ROAD,T.S.T, KOWLOON, Hong Kong, China

1.2 Equipment under Test (EUT) Description

Product Name:	MONITOR WITH RECEIVER	
Sample No.:	1#	
Hardware Version:	V1.0	
Software Version:	V1.0	
Frequency Bands:	Bluetooth	2402MHz-2480MHz
	WLAN 5GHz	5745MHz-5825MHz
Modulation Mode:	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8-DPSK
	WLAN 5GHz	OFDM
Antenna Information:	Bluetooth	
	Antenna Type:	PCB Antenna
	Antenna Gain:	-4.44dBi
	WLAN 5GHz	
	Antenna Type:	PCB Antenna
	Antenna Gain:	-6.79dBi



Note 1: According to the certificate holder, they declared that the models DMX5710S, DMX50S, DMX500S, DMX723WS, DMX80AXS, DMX6523S, KW-M695BW and KW-M690BW o have the same hardware and software, the differences are as bellowing, all RF parameters remain the same.

Model	Brand	Display Size	Description
KW-M695BW	JVC	6.8"	- Base Model
KW-M690BW	JVC	6.8"	Compared with base model: - No SiriusXM
DMX5710S	KENWOOD	6.8"	Compared with base model: - Different Brand
DMX50S	KENWOOD	6.8"	Compared with base model: - Different Brand
DMX500S	KENWOOD	6.8"	Compared with base model: - Different Brand - No SiriusXM
DMX6523S	KENWOOD	6.8"	Compared with base model: - No SiriusXM
DMX723WS	KENWOOD	6.8"	Compared with base model: - Different Brand - Different size of front panel - Touch keys on two sides (left & right) - No SiriusXM
DMX80AXS	KENWOOD	9"	Compared with base model: - Different Brand - Different display size and panel size - Touch keys on two sides (left & right) - No SiriusXM

The main measuring model is DMX5710S, only the results for DMX5710S were recorded in this report.



1.3 Applied Reference Documents

Leading reference documents for testing:

Identity	Document Title	Method Determination /Remark
47 CFR Part 2(2.1091)	Radio Frequency Radiation Exposure Assessment: mobile devices	No deviation
KDB 447498 D01v06	General RF Exposure Guidance	No deviation
Note 1: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table. Note 2: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.		



2. Device Category and RF Exposure Limit

Per user manual, based on 47 CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47 CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1 Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density



3. Maximum Average Power Summary

Wireless Mode	Channel	Frequency (MHz)	Max. Average Power (dBm)	Tune-up Limit (dBm)
Bluetooth	CH 78	2480	1.48	2.50
WLAN 5GHz	CH 151	5755	13.78	15.00

Note 1: According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Note 2: The maximum average power refers to report (Report No.: SZ24060062W01/W02).

4. RF Exposure Assessment

➤ Standalone Transmission Assessment

Bands	Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	E.I.R.P. (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
Bluetooth	2480	2.50	-4.44	0.64	<0.001	1.0
WLAN 5GHz	5755	15.00	-6.79	6.62	0.001	1.0

Note:

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. MPE calculate method

$$S = PG/4\pi R^2$$

Where: S= Power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune-up power (in appropriate units, e.g. dBm)

G = numeric gain of the antenna (in appropriate units, e.g. dBi)

R = Separation distance to the centre of radiation of the antenna (20cm)

➤ Simultaneous Transmission Assessment:

According to the user manual, both the WLAN and Bluetooth transmitters in the device cannot operate simultaneously, therefore simultaneous transmission analysis is not required.

➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



Annex A Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

_____ END OF REPORT _____