


Applicant: Otter Products, LLC.	
FCC ID: 2AEEV-OBFTC-0090-A	
Date: 2022-01-04	
RF Exposure Requirements (FCC KDB 680106 D01 v03r01)	
Requirements	Statements
(a) Power transfer frequency is less than 1 MHz	Yes, Power transfer frequency is less than 1MHz; EUT operating frequency range is 0.112~ 0.205 MHz.
(b) Output power from each primary coil is less than 15 watts	Yes, Output power from each primary coil is 7.5 watts (Maximum).
(c) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes, The EUT has only one primary coil.
(d) Client device is placed directly in contact with the transmitter.	Yes, The client device needs to be in contact with the transmitter base, and the contact distance is less than 10 mm.
(e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	No, EUT is mobile/portable device.
(f) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Please refer to RF Exposure Report.

COMPANY NAME: Otter Products, LLC.
 ADDRESS: 209 South Meldrum Street, Fort Collins, Colorado, USA 80521
 Signature: 
 Name: Steve Dressor
 Title: Regulatory Engineering Manager
 E-mail: steve.dressor@otterproducts.com
 TEL: 970-980-2092

Company: Otter Products, LLC.