

# **EXPLORER**<sup>™</sup> Bluetooth Handset for Thrane & Thrane A/S

#### **Bluetooth CTP Handset**

# **General Features**

Cordless Telephone based on Bluetooth Technology Compliant to Bluetooth Version 1.1 Bluetooth Class 1 Radio for extended range Intuitive MMI based on a WAP Browser Supports 6 languages Supports "R"-button for control of additional features in the access point

#### **Profiles**

Cordless Telephony Profile (CTP) Generic Access Profile (GAP)

## **Power Supply**

Battery pack: 3.7V Li-lon battery with a capacity of 950 mAh. Mounted and mechanically fixed to the battery compartment within the handset's cover.

Characteristics: Technology: Li-Ion

Maximum charging time: 4 hours Continuous talk time: 11 hours

Standby: 40 hours

Switched off mode: 250 hours Minimum lifetime cycles: 500 Minimum battery lifetime: 4 years

Overcharging prevention

#### RF

Operating frequency range: 2402 – 2480 MHz

Type of modulation: FHSS modulation

Number of channels: 79 Channel separation: 1 MHz

Output power +16,5 dBm +/- 1dBm Receiver sensitivity -77 - -82 dBm

This power and sensitivity is Bluetooth certified! Range of use outdoor 100 meters with free sight.



## **Keypad**

Separate on hook key Separate off hook key Keys 0-9, \* and # 2 softkeys

Navigation Rocker: The navigation rocker can be pushed up and down to navigate and can be pressed to make a selection or confirmation.

**Emergency button** 

### **Display**

11520 pixels (120\*96)

Display illumination colour: blue Mechanical dimensions: 27\*24mm

Contrast: fixed

#### **Environmental**

-5°C - +45°C Operation Temperature Range -25°C - +55°C storage/transportation conditions -25°C - +60°C storage/transportation conditions (low humidity, slow change of temperature) IP65 Water and Dust Resistance Up to 93% Humidity

#### Mechanical

Dimensions approx. 137x46x21(mm)
Weight (with battery pack) approx. <100g
Rubber outline
Plug on top right side of the handset used as charger interface
Bottom charger contacts for optional charger cradle
Vibrator alarm