

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposure</b>         |                               |                               |                                     |                          |
| 0.3-3.0                                                        | 614                           | 1.63                          | *100                                | 6                        |
| 3.0-30                                                         | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                        |
| 30-300                                                         | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500                                                      |                               |                               | f/300                               | 6                        |
| 1,500-100,000                                                  |                               |                               | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34                                                       | 614                           | 1.63                          | *100                                | 30                       |
| 1.34-30                                                        | 824/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                       |
| 30-300                                                         | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500                                                      |                               |                               | f/1500                              | 30                       |
| 1,500-100,000                                                  |                               |                               | 1.0                                 | 30                       |

f = frequency in MHz \* = Plane-wave equivalent power density

## MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

## Measurement Result

Operation Frequency: 2412-2462MHz for 802.11b/g/11n(HT20)

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: External Antenna

Antenna gain: 3dBi

R=20cm

WIFI:

| Channel Freq. (MHz) | modulation   | conducted power | Tune-up power (dBm) | Max           |        | Antenna |         | Evaluation result | Power density |
|---------------------|--------------|-----------------|---------------------|---------------|--------|---------|---------|-------------------|---------------|
|                     |              | (dBm)           |                     | tune-up power |        | Gain    |         | (mW/cm2 )         | (mW/cm2)      |
|                     |              |                 |                     | (dBm)         | (mW)   | (dBi)   | Numeric |                   |               |
| 2412                | 802.11b      | 15.11           | 15±1                | 16            | 39.811 | 3.00    | 2.00    | 0.0158            | 1             |
| 2437                |              | 14.42           | 15±1                | 16            | 39.811 | 3.00    | 2.00    | 0.0158            | 1             |
| 2462                |              | 14.05           | 15±1                | 16            | 39.811 | 3.00    | 2.00    | 0.0158            | 1             |
| 2412                | 802.11g      | 14.07           | 14±1                | 15            | 31.623 | 3.00    | 2.00    | 0.0126            | 1             |
| 2437                |              | 13.3            | 14±1                | 15            | 31.623 | 3.00    | 2.00    | 0.0126            | 1             |
| 2462                |              | 13.09           | 14±1                | 15            | 31.623 | 3.00    | 2.00    | 0.0126            | 1             |
| 2412                | 802.11n HT20 | 13.98           | 13±1                | 14            | 25.119 | 3.00    | 2.00    | 0.0100            | 1             |
| 2437                |              | 13.22           | 13±1                | 14            | 25.119 | 3.00    | 2.00    | 0.0100            | 1             |
| 2462                |              | 12.94           | 13±1                | 14            | 25.119 | 3.00    | 2.00    | 0.0100            | 1             |

### Conclusion:

For the max result : 0.0158≤ 1.0 for Max Power Density, compliance RF exposure..

Signature:



Date: 2020-01-20

NAME AND TITLE (Please print or type): Alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.