

Ottlite Technologies Inc.

TEST REPORT

SCOPE OF WORK

SAR Assessment– Q26A

REPORT NUMBER

211123018SZN-003

ISSUE DATE

14 February 2022

[REVISED DATE]

[-----]

PAGES

7

DOCUMENT CONTROL NUMBER

RF Exposure

© 2017 INTERTEK



Test Report

Applicant : Ottlite Technologies Inc.
1715 N Westshore Blvd, Suite 950, Tampa, FL
33607, USA

Sample Description
Product : LED Table Lamp with Wireless Charging
Model No. : Q26A

Electrical Rating : N/A

Date Received : 23 November 2021
Date Test Conducted : 30 November 2021 to 29 December 2021

Test Requested : Test for compliance with CFR 47 part 1
Test Method : Environmental evaluation and exposure limit according
to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310
KDB 680106 D01 RF Exposure Wireless Charging App
v03r01

Test Result : Pass
Conclusion : When determining of test conclusion, measurement
uncertainty of tests have been considered.

***** End of Page *****

Prepared and Checked By:

Approved By:

Karot Huang
Assistant Engineer

Sewen Guo
Senior Project Engineer
Date: 14 February 2022

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288

Fax: (86 755) 8601 6751

This product was tested in the following configuration:

Description	Manufacturer	Detail
Mobile phone	NIL (Provided by Intertek)	Manufacturer: Samsung Model: S7
Class 2 Power Supply	DongGuan Teye Electronics Technology Co., Ltd. (Provided by Client)	Model: TY0500200A1mn Input: 100-240Vac 50/60Hz 0.4A Output: 5Vdc 2.0A

Justification

Pertest mode	Description
Mode 1	Standby mode
Mode 2	Mobile phone is charging at 1% battery power
Mode 3	Mobile phone is charging at 50% battery power
Mode 4	Mobile phone is charging at 99% battery power

The EUT was powered by an adapter with 120V/60Hz input during the test. The test system was pre-scanning tested based on the consideration of following EUT operation mode. Only the worst-case data was shown in this report.

Reference Limit:

Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	(100) *	30

Note: * = Plane wave equivalent power density

Test Result:

During test, the mobile handset is being charged.

Worst Case Operating Mode: Mode 2

Test Result for wireless power transmit part:
H-Field Strength at 15 cm surrounding the EUT and 20cm above the top surface of the EUT

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Limits (A/m)
0.113-0.205	1% Battery Level	0.0099	0.0094	0.0094	0.0088	0.0099	1.63
0.113-0.205	50% Battery Level	0.0070	0.0066	0.0066	0.0068	0.0088	1.63
0.113-0.205	99% Battery Level	0.0084	0.0068	0.0064	0.0080	0.0086	1.63
0.113-0.205	Stand-by	0.0064	0.0064	0.0058	0.0064	0.0068	1.63


E-Field Strength at 15 cm surrounding the EUT and 20cm above the top surface of the EUT

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Limits (V/m)
0.113-0.205	1% Battery Level	0.0542	0.0542	0.0388	0.0388	0.0716	614
0.113-0.205	50% Battery Level	0.0407	0.0407	0.0384	0.0384	0.0348	614
0.113-0.205	99% Battery Level	0.0388	0.0384	0.0386	0.0384	0.0366	614
0.113-0.205	Stand-by	0.0368	0.0374	0.0364	0.0376	0.0344	614

Configuration photo of the test:

H-Field & E-Field Strength test photos


Front




Rear




Left



Right



Top



***** End of Report*****