



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

Queclink Wireless Solutions Co.,Ltd

3 Floor, Building 2, No.717 Yishan Road, Xuhui District, shanghai, China 200233

FCC ID: YQD-GB100MG

Report Type: Original Report	Product Type: GPS Tracker
Test Engineer:	Chao Gao <i>chao gao</i>
Report Number:	RSHA200106002-00B
Report Date:	2020-04-16
Reviewed By:	Oscar Ye <i>Oscar.Ye</i> EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §1.1310& §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
APPLICABLE STANDARD	10
CALCULATED FORMULARY:.....	10
CALCULATED DATA:.....	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	15
FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §15.247(d) - BAND EDGE	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(e) - POWER SPECTRAL DENSITY	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Queclink Wireless Solutions Co.,Ltd
Tested Model	GB100MG
Series Model	GB100MG_S
Product Type	GPS Tracker
Power Supply	DC 3.6V from battery and DC 12~24V from DC Source
RF Function	BLE
Operating Band/Frequency	2402~2480MHz
Channel Number	40
Channel Separation	2MHz
Modulation Type	GFSK
Antenna Type	Ceramic antenna
Antenna Gain	4.97dBi

Note: The difference between tested model and series model was explained in the attached declaration letter.

**All measurement and test data in this report was gathered from production sample serial number: 20200106002.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-01-06)*

Objective

This report is prepared on behalf of *Queclink Wireless Solutions Co.,Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s)/grant(s)

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
18	2438	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

Equipment Modifications


No modification was made to the EUT tested.

EUT Exercise Software

The EUT was test engineer mode.

Duty Cycle:

Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
BLE	64.97	0.409	2.44	1.87

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ZHAOXIN	DC Source	RXN-605D	DC002

External I/O Cable


Cable Description	Length (m)	From Port	To
Power cable	1.0	EUT	DC Source
Power cable	1.0	DC Source	AC Source

Block Diagram of Test Setup

For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable (See Note)
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Note: The EUT will use in vehicular environment.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-11-30	2020-11-29
Sunol Sciences	Broadband Antenna	JB3	A040914-2	2020-01-09	2021-01-08
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-08-27	2020-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2019-01-11	2022-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-10-18	2022-10-17
A.H.Systems, inc	Preamplifier	2641-1	491	2020-02-20	2021-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Notch filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator/10dB	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2019-09-21	2020-09-20
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Queclink Wireless Solutions Co.,Ltd	RF Cable	Queclink Wireless Solutions Co.,Ltd C01	C01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310& §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402~2480	4.97	3.14	-3.00	0.50	20	0.0003	1.00
GPRS/EGPRS 850	824~849	2.82	1.91	27.50	562.34	20	0.2141	0.55
GPRS/EGPRS 1900	1850~1910	2.16	1.64	26.50	446.68	20	0.1461	1.00
LTE Band 2	1850-1910	2.16	1.64	24.00	251.19	20	0.0822	1.00
LTE Band 4	1710-1755	1.32	1.36	23.00	199.53	20	0.0538	1.00
LTE Band 5	824-849	2.82	1.91	24.00	251.19	20	0.0956	0.55
LTE Band 12	699-716	0.34	1.08	24.00	251.19	20	0.0540	0.47
LTE Band 13	777-787	2.42	1.75	24.00	251.19	20	0.0872	0.52
LTE Band 25	1850-1910	2.16	1.64	25.00	316.23	20	0.1034	1.00

Note:

- 1) For the above tune up power were declared by the manufacturer.
- 2) The LTE module FCC ID: XMR201707BG96
- 3) BLE and GPRS/EGPRS or LTE can transmit simultaneously, the worst condition was as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0003/1.00 + 0.2141/0.55 = 0.0003 + 0.3893 = 0.3896 < 1.0$$

- 4) For GPRS/EGPRS Mode, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB

GPRS 850: Maximum Tune-up output power with 1 slot is 33.0 dBm, 2 slots is 32.5 dBm, 3 slots is 31.5 dBm, 4 slots is 30.5 dBm, so the max tune-up time based Ave. power compared to slot Ave. power are 27.5 dBm .

EGPRS 850: Maximum Tune-up output power with 1 slot is 27.0 dBm, 2 slots is 27.0 dBm, 3 slots is 26.5 dBm, 4 slots is 26.5 dBm, so the max tune-up time based Ave. power compared to slot Ave. power are 23.5 dBm .

GPRS 1900: Maximum Tune-up output power with 1 slot is 30.0 dBm, 2 slots is 30.0 dBm, 3 slots is 30.0 dBm, 4 slots is 29.5 dBm, so the max tune-up time based Ave. power compared to slot Ave. power are 26.5 dBm .

EGPRS 1900: Maximum Tune-up output power with 1 slot is 26.5 dBm, 2 slots is 26.0 dBm, 3 slots is 26.0 dBm, 4 slots is 26.0 dBm, so the max tune-up time based Ave. power compared to slot Ave. power are 23.0 dBm .

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT a ceramic antenna for BLE which was permanently attached and the antenna gain is 4.97dBi; fulfill the requirement of this section. Please refer to the EUT photos.


Test Result: Compliant

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz - 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) - Corrected Amplitude (dB μ V/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	21.7-22.9 °C
Relative Humidity:	49-50 %
ATM Pressure:	101.1-101.6 kPa


The testing was performed by Chao Gao from 2020-04-08 to 2020-04-15.

EUT operation mode: Transmitting

Spurious Emission Test:

30MHz-1GHz


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low channel of operation in X-axis of orientation** was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
31.006144	18.11	100.0	V	153.0	-4.6	40.00	21.89
66.925850	5.23	200.0	V	145.0	-17.5	40.00	34.77
113.195100	9.42	100.0	V	330.0	-12.4	43.50	34.08
142.738800	9.94	200.0	H	128.0	-12.1	43.50	33.56
208.947850	16.26	200.0	H	231.0	-12.3	43.50	27.24
553.043450	15.92	200.0	H	358.0	-5.6	46.00	30.08

30MHz-1GHz:

(The worst case GSM850 middle channel and low channel of BLE mode transmitting simultaneously was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.882150	21.95	200.0	H	231.0	-4.5	40.00	18.05
59.031600	15.51	100.0	V	261.0	-17.9	40.00	24.49
126.193450	10.76	200.0	V	254.0	-11.4	43.50	32.74
169.388600	22.79	100.0	V	141.0	-13.1	43.50	20.71
339.514050	15.14	100.0	V	114.0	-9.6	46.00	30.86
723.202950	18.69	100.0	V	208.0	-2.8	46.00	27.31

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) - Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1108.80	41.38	---	150.0	H	197.0	-18.5	74.00	32.62
1108.80	---	28.34	150.0	H	197.0	-18.5	54.00	25.66
1612.00	---	27.96	200.0	V	289.0	-15.9	54.00	26.04
1612.00	35.56	---	200.0	V	289.0	-15.9	74.00	38.44
3070.60	40.12	---	150.0	V	222.0	-9.9	74.00	33.88
3070.60	---	33.45	150.0	V	222.0	-9.9	54.00	20.55
4804.00	---	50.31	200.0	V	351.0	-5.6	54.00	3.69
4804.00	55.46	---	200.0	V	351.0	-5.6	74.00	18.54
7694.60	48.48	---	200.0	V	258.0	1.3	74.00	25.52
7694.60	---	40.27	200.0	V	258.0	1.3	54.00	13.73
17481.50	---	46.79	150.0	H	310.0	8.8	54.00	7.21
17481.50	55.19	---	150.0	H	310.0	8.8	74.00	18.81

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1108.80	---	27.72	150.0	H	218.0	-18.5	54.00	26.28
1108.80	41.32	---	150.0	H	218.0	-18.5	74.00	32.68
1593.30	---	31.80	200.0	V	296.0	-16.0	54.00	22.20
1593.30	40.29	---	200.0	V	296.0	-16.0	74.00	33.71
3070.60	---	34.30	150.0	V	233.0	-9.9	54.00	19.70
3070.60	41.05	---	150.0	V	233.0	-9.9	74.00	32.95
4880.00	---	49.60	150.0	V	264.0	-5.4	54.00	4.40
4880.00	52.84	---	150.0	V	264.0	-5.4	74.00	21.16
10569.30	49.76	---	200.0	V	108.0	2.4	74.00	24.24
10569.30	---	40.63	200.0	V	108.0	2.4	54.00	13.37
17966.00	---	47.87	200.0	V	203.0	8.8	54.00	6.13
17966.00	55.03	---	200.0	V	203.0	8.8	74.00	18.97

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1171.70	---	27.82	150.0	H	218.0	-18.1	54.00	26.18
1171.70	39.76	---	150.0	H	218.0	-18.1	74.00	34.24
1596.70	---	32.52	200.0	V	263.0	-16.0	54.00	21.48
1596.70	38.82	---	200.0	V	263.0	-16.0	74.00	35.18
3070.60	---	35.29	200.0	V	202.0	-9.9	54.00	18.71
3070.60	41.59	---	200.0	V	202.0	-9.9	74.00	32.41
4960.00	---	51.86	200.0	V	351.0	-5.3	54.00	2.14
4960.00	55.79	---	200.0	V	351.0	-5.3	74.00	18.21
11550.20	---	41.23	150.0	H	234.0	2.9	54.00	12.77
11550.20	50.60	---	150.0	H	234.0	2.9	74.00	23.40
17486.60	54.66	---	200.0	H	217.0	8.8	74.00	19.34
17486.60	---	47.24	200.0	H	217.0	8.8	54.00	6.76

18GHz - 25GHz


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low** channel of operation in X-axis of orientation was recorded)

Horizontal



Date: 8.APR.2020 12:41:39

Vertical




Date: 8.APR.2020 12:56:00

1GHz-18GHz:

(The worst case GSM850 middle channel and low channel of BLE mode transmitting simultaneously was recorded)

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1113.90	41.97	---	200.0	V	231.0	-18.5	74.00	32.03
1113.90	---	27.73	200.0	V	231.0	-18.5	54.00	26.27
1671.50	---	38.04	200.0	V	339.0	-15.7	54.00	15.96
1671.50	42.81	---	200.0	V	339.0	-15.7	74.00	31.19
3070.60	---	32.77	200.0	H	200.0	-9.9	54.00	21.23
3070.60	39.73	---	200.0	H	200.0	-9.9	74.00	34.27
4804.00	---	45.68	150.0	H	279.0	-5.6	54.00	8.32
4804.00	52.54	---	150.0	H	279.0	-5.6	74.00	21.46
7655.50	48.20	---	150.0	H	143.0	1.3	74.00	25.80
7655.50	---	40.03	150.0	H	143.0	1.3	54.00	13.97
17549.50	---	46.44	200.0	V	108.0	8.9	54.00	7.56
17549.50	54.09	---	200.0	V	108.0	8.9	74.00	19.91

18GHz-25GHz:


(The worst case GSM850 middle channel and low channel of BLE mode transmitting simultaneously was recorded)

Horizontal



Date: 8.APR.2020 12:56:00

Vertical



Date: 8.APR.2020 12:41:39

Restricted Bands Emissions Test:

(Pre-scan in the X, Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)


Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) - Corrected Amplitude (dBμV/m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	48.54	---	150.0	H	246.0	-2.9	74.00	25.46
2390.00	---	39.76	150.0	H	246.0	-2.9	54.00	14.24
High Channel: 2480MHz								
2483.50	63.58	---	150.0	V	242.0	-2.5	74.00	10.42
2483.50	---	49.42	150.0	V	242.0	-2.5	54.00	4.58

Conducted Spurious Emissions at Antenna Port:


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	22.3°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Chao Gao on 2020-04-11.

EUT operation mode: Transmitting


Test Result: Compliant

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	0.721	≥ 0.5
Middle	2440	0.721	≥ 0.5
High	2480	0.721	≥ 0.5


Low Channel



Middle Channel



High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data

Environmental Conditions


Temperature:	23.2°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chao Gao on 2020-04-11.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	-3.42	30	Pass
Middle	2440	-3.55	30	Pass
High	2480	-3.60	30	Pass


Low Channel



Middle Channel



High Channel



FCC §15.247(d) - BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the middleest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the middleest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	23°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chao Gao on 2020-04-11.


EUT operation mode: Transmitting

Test Result: Compliant

Left Side



Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	23.2°C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa


The testing was performed by Chao Gao on 2020-04-11.

EUT operation mode: Transmitting


Test Result: Compliant

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-18.66	≤ 8
Middle	2440	-18.93	≤ 8
High	2480	-19.02	≤ 8


Low Channel



Middle Channel



High Channel



***** END OF REPORT *****