

FCC RF EXPOSURE REPORT

For

Ultra Short Throw Laser Projector

FCC MODEL NUMBER: AL-UK535A, AL-UK**** (* may be 0-9, A-Z) ISED MODEL NUMBER: AL-UK535A

REPORT NUMBER: 4790678406-1-RF-5

ISSUE DATE: January 17, 2023

FCC ID:2ALQL-AL-UK535A

Prepared for

APPOTRONICS CO., LTD 20F to 22F, High-Tech Zone Union Tower, No.63 Xuefu Road, Nanshan District Shenzhen 518051 China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China Tel: +86 769-22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

UL			REPORT No.: 4790678406-1-RF-5 Page 2 of 6
		Revision History	
Rev.	Issue Date	Revisions	Revised By
V0	January 17, 2023	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	. 5
ć	3.1. DESCRIPTION OF EUT	6
4.	REQUIREMENT	. 7



1. ATTESTATION OF TEST RESULTS

Applicant Information Company Name: Address:

APPOTRONICS CO., LTD 20F to 22F, High-Tech Zone Union Tower, No.63 Xuefu Road, Nanshan District Shenzhen 518051 China

Manufacturer Information

Company Name: Address: APPOTRONICS CO., LTD 20F to 22F, High-Tech Zone Union Tower, No.63 Xuefu Road, Nanshan District Shenzhen 518051 China

EUT Information

EUT Name: FCC Model: ISED Model: Brand: Ultra Short Throw Laser Projector AL-UK535A, AL-UK**** (* may be 0-9, A-Z) AL-UK535A



Sample Received Date: Sample Status: Sample ID: Date of Tested: December 20, 2022 Normal 5645955 January 12, 2023 to January 17, 2023

APPLICABLE STANDARDS

STANDARD

TEST RESULTS

PASS

FCC 47CFR§2.1091 KDB-447498 D01 V06

Prepared By:

Kebo Zhang Senior Project Engineer Approved By:

Stephen Guo Operations Manager Checked By:

Denn Sum

Denny Huang Senior Project Engineer



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

3. FACILITIES AND ACCREDITATION

	ADLA (Contificate No. + 4402.04)				
	A2LA (Certificate No.: 4102.01)				
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
	has been assessed and proved to be in compliance with A2LA.				
	FCC (FCC Designation No.: CN1187)				
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
	Has been recognized to perform compliance testing on equipment subject				
	to the Commission's Declaration of Conformity (DoC) and Certification rules				
	ISED (Company No.: 21320)				
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
Accreditation	has been registered and fully described in a report filed with ISED.				
Certificate	The Company Number is 21320 and the test lab Conformity Assessment				
	Body Identifier (CABID) is CN0046.				
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)				
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.				
	has been assessed and proved to be in compliance with VCCI, the				
	Membership No. is 3793.				
	Facility Name:				
	Chamber D, the VCCI registration No. is G-20019 and R-20004				
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011				

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China



3.1. DESCRIPTION OF EUT

EUT Name	Ultra Short Throw Laser Projector		
FCC Model	AL-UK535A, AL-UK**** (* may be 0-9, A-Z)		
ISED Model AL-UK535A			
Model difference	AL-UK**** (* may be 0-9, A-Z) have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction with AL-UK535A. The difference lies only the model number. all these changes do not degrade the unwanted emissions of the certified product.		



4. REQUIREMENT

<u>LIMIT</u>

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)		
0.3-1.34	614	1.63	(100)*	30		
1.34-30	824/f	2.19/f	(180/f2)*	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/150	30		
1500-100,000			1.0	30		
Note 1: f – frequency in MHz * means Plane-wave equivalent nower density						

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

 $S = PG/(4\pi R^2)$

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Radio Frequency Radiation Exposure Evaluation

BT (Worst case)							
Operating	Max. Tune up Power	Antenna Gain		Power density	Limit		
Mode	(dBm)	(dBi)	(num)	(mW/ cm ²)	Linit		
ВТ	8	2.88	1.94	0.00244	1		

WIFI 2.4G (Worst case)							
Operating	Max. Tune up Power Directional Gain		Power density	Limit			
Mode	(dBm)	(dBi)	(num) (mW/cm^2)		Linit		
802.11n HT20	16	5.82	3.82	0.03025	1		

WIFI 5G (Worst case)							
Operating	Max. Tune up Power Directional Gain		Power density	Limit			
Mode	(dBm)	(dBi)	(num)	(mW/ cm ²)			
802.11ac VHT80	18	5.98	3.96	0.04974	1		

Note:

- 1. The Power comes from report operation description.
- 2. The minimum separation distance of the device is greater than 20 cm.
- 3. Calculate by WORST-CASE mode.

END OF REPORT