



RADIO TEST REPORT

Report No.:STS2007325W04

Issued for

Shenzhen Grand Time Technology Co.,Ltd

Unit 1202, 12th floor, Konka R&D Building, Science and
Technology South 12th Road, Nanshan District, Shenzhen,
China.

Product Name:	4G body worn camera
Brand Name:	N/A
Model Name:	F2
Series Model:	F1, F1P, F1B, F1S, F2B, F2P, F2S, F3P, F3B, F3S, F4P, F4B, F4S, F5P, F5B, F5S, F6P, F6B, F6S
FCC ID:	2AM6P-F2
Test Standard:	FCC Part 15.407

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's Name..... : Shenzhen Grand Time Technology Co.,Ltd
Address : Unit 1202, 12th floor, Konka R&D Building, Science and Technology South 12th Road, Nanshan District, Shenzhen, China.
Manufacturer's Name : Shenzhen Grand Time Technology Co.,Ltd
Address : Unit 1202, 12th floor, Konka R&D Building, Science and Technology South 12th Road, Nanshan District, Shenzhen, China.

Product Description

Product Name..... : 4G body worn camera
Brand Name : N/A
Model Name : F2
Series Model..... : F1, F1P, F1B, F1S, F2B, F2P, F2S, F3P, F3B, F3S, F4P, F4B, F4S, F5P, F5B, F5S, F6P, F6B, F6S

Test Standards..... : FCC Part15.407

Test Procedure..... ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date of receipt of test item : 30 July 2020

Date (s) of performance of tests : 30 July 2020 ~ 12 Aug. 2020

Date of Issue..... : 12 Aug. 2020

Test Result..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 TEST SOFTWARE AND POWER LEVEL	12
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	14
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	15
3 . EMC EMISSION TEST	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.2 RADIATED EMISSION AND (BANDEGE) MEASUREMENT	20
4. POWER SPECTRAL DENSITY TEST	51
4.1 LIMIT	51
4.2 TEST PROCEDURE	51
4.3 DEVIATION FROM STANDARD	52
4.4 TEST SETUP	52
4.5 EUT OPERATION CONDITIONS	52
4.6 TEST RESULTS	52
5. BANDWIDTH MEASUREMENT	55
5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	55
5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	59
5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	63
6. MAXIMUM CONDUCTED OUTPUT POWER	65
6.1 LIMIT	65
6.2 TEST PROCEDURE	65
6.3 DEVIATION FROM STANDARD	65
6.4 TEST SETUP	65
6.5 EUT OPERATION CONDITIONS	65
6.6 TEST RESULTS	66
7. AUTOMATICALLY DISCONTINUE TRANSMISSION	74
7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	74
7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	74



Table of Contents	Page
8. ANTENNA REQUIREMENT	75
8.1 STANDARD REQUIREMENT	75
8.2 EUT ANTENNA	75
APPENDIX - PHOTOS OF TEST SETUP	76



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	12 Aug. 2020	STS2007325W04	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

§ 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
15.407 (a) /15.407 (e)	26dB/6dB &99% Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	PASS
15.407(b)/15.205/15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(a)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203/15.204	Antenna Requirement	PASS

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 30-1GHz	$\pm 5.6\text{dB}$
4	All emissions, radiated 1G-6GHz	$\pm 5.5\text{dB}$
5	All emissions, radiated >6G	$\pm 5.8\text{dB}$
6	Conducted Emission (9KHz-150KHz)	$\pm 3.37\text{dB}$
7	Conducted Emission (150KHz-30MHz)	$\pm 3.83\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	4G body worn camera								
Trade Name	N/A								
Model Name	F2								
Series Model	F1, F1P, F1B, F1S, F2B, F2P, F2S, F3P, F3B, F3S, F4P, F4B, F4S, F5P, F5B, F5S, F6P, F6B, F6S								
Model Difference	Only different in model name								
Product Description	The EUT is a 4G body worn camera <table><tr><td>Operation Frequency:</td><td>IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz</td></tr><tr><td>Modulation Type:</td><td>802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM</td></tr><tr><td>Antenna Designation:</td><td>Please refer to the Note 3.</td></tr><tr><td>Max.Output Power(Conducted):</td><td>12.50 dBm</td></tr></table> More details of EUT technical specification, please refer to the User Manual.	Operation Frequency:	IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz	Modulation Type:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM	Antenna Designation:	Please refer to the Note 3.	Max.Output Power(Conducted):	12.50 dBm
Operation Frequency:	IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz								
Modulation Type:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM								
Antenna Designation:	Please refer to the Note 3.								
Max.Output Power(Conducted):	12.50 dBm								
Test Channel	Please refer to the Note 2.								
Adapter	Input: AC 100-240 50/60Hz 0.3A Output: DC 5.0V 2A								
Battery	Rated Voltage: 3.8V Charge Limit: 4.35V Capacity: 3500mA								
Hardware version number	ET9210-MB-V2.0								
Software version number	ET921_BASE_5mo_20200622_V001								
Connecting I/O Port(s)	Please refer to the Note 1.								

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.



2. Operation Frequency of channel			
5.180GHz-5.240GHz		5.745GHz-5.825GHz	
Channel	Frequency	Channel	Frequency
36	5180	149	5745
38	5190	151	5755
40	5200	153	5765
42	5210	157	5785
44	5220	159	5795
46	5230	161	5805
48	5240	165	5825
5.260GHz-5.320GHz			
Channel	Frequency		
52	5260		
54	5270		
56	5280		
58	5290		
60	5300		
62	5310		
64	5320		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n(HT20) /ac (VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	52	5260
40	5200	60	5300
48	5240	64	5320

For 802.11a/n(HT20) /ac (VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
149	5745	157	5785
165	5825		

For 802.11n(HT40) /ac (VHT40)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	54	5270
46	5230	62	5310



For 802.11n(HT40) /ac (VHT40)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
151	5755	159	5795

For 802.11ac (VHT80)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	58	5290

For 802.11ac (VHT80)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
155	5775		

3.	Ant	Brand	Model Name	Ant Type	Connector	Gain (dBi)	NOTE
	A	N/A	F2	PIFA	N/A	1dBi	WLAN Ant



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH52&CH60&CH64	6 Mbps
Mode 3	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 4	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 5	TX IEEE 802.11ac HT20 CH36&CH40&CH48	NSS1 MCS0
Mode 6	TX IEEE 802.11n HT20 CH52&CH60&CH64	MCS 0
Mode 7	TX IEEE 802.11ac HT20 CH52&CH60&CH64	NSS1 MCS0
Mode 8	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 9	TX IEEE 802.11ac HT20 CH149&CH157&CH165	NSS1 MCS0
Mode 10	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 11	TX IEEE 802.11ac HT40 CH38&CH46	NSS1 MCS0
Mode 12	TX IEEE 802.11n HT40 CH54 &CH62	MCS 0
Mode 13	TX IEEE 802.11ac HT40 CH54 &CH62	NSS1 MCS0
Mode 14	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 15	TX IEEE 802.11ac HT40 CH151&CH159	NSS1 MCS0
Mode 16	TX IEEE 802.11ac HT80 CH42	NSS1 MCS0
Mode 17	TX IEEE 802.11ac HT80 CH58	NSS1 MCS0
Mode 18	TX IEEE 802.11ac HT80 CH155	NSS1 MCS0

- Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
(4) The battery is fully-charged during the radiated and RF conducted test.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 19: Keeping TX + WLAN Link




2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	Ant Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	5G WIFI Band1 (5150MHz-5250MHz)	802.11a	1	15	Engineering Mode
		802.11n(HT20)		15	
		802.11n(HT40)		15	
		802.11ac(VHT20)		15	
		802.11ac(VHT40)		15	
		802.11ac(VHT80)		15	
RF Function	Type	Mode Or Modulation type	Ant Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	5G WIFI Band2 (5250MHz-5350MHz)	802.11a	1	15	Engineering Mode
		802.11n(HT20)		15	
		802.11n(HT40)		15	
		802.11ac(VHT20)		15	
		802.11ac(VHT40)		15	
		802.11ac(VHT80)		15	
RF Function	Type	Mode Or Modulation type	Ant Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	5G WIFI Band4 (5725MHz-5875MHz)	802.11a	1	15	Engineering Mode
		802.11n(HT20)		15	
		802.11n(HT40)		15	
		802.11ac(VHT20)		15	
		802.11ac(VHT40)		15	
		802.11ac(VHT80)		15	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-2	Adapter	N/A	N/A	N/A	N/A
C-1	DC Cable	N/A	N/A	110cm	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESCI	101427	2019.10.09	2020.10.08
Signal Analyzer	Agilent	N9020A	MY51110105	2020.03.05	2021.03.04
Active loop Antenna	ZHINAN	ZN30900C	16035	2018.03.11	2021.03.10
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2020.11.1
Horn Antenna	SCHWARZBECK	BBHA 9120D(1201)	9120D-1343	2018.10.19	2021.10.18
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2018.03.11	2021.03.10
Pre-Amplifier (0.1M-3GHz)	EM	EM330	060665	2019.10.09	2020.10.08
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-4 5	SK2018080901	2019.10.12	2020.10.11
Pre-Amplifier (18G-40GHz)	SKET	LNPA-1840-50	SK2018101801	2019.10.12	2020.10.11
Temperature & Humidity	HH660	Mieo	N/A	2019.10.17	2020.10.16
Turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Test SW	BULUN	BL410-E/18.905			

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2019.10.09	2020.10.08
LISN	R&S	ENV216	101242	2019.10.09	2020.10.08
LISN	EMCO	3810/2NM	23625	2019.10.09	2020.10.08
Temperature & Humidity	HH660	Mieo	N/A	2019.10.17	2020.10.16
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 CE)			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2019.10.09	2020.10.08
Signal Analyzer	Agilent	N9020A	MY49100060	2019.10.09	2020.10.08
Temperature & Humidity	HH660	Mieo	N/A	2019.10.17	2020.10.16
Test SW	FARAD	LZ-RF /LzRf-3A3			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support.

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS


Temperature:	27.2(C)	Relative Humidity:	66%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode :	Mode 19		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	37.83	20.19	58.02	66.00	-7.98	QP
2	0.1500	17.88	20.19	38.07	56.00	-17.93	AVG
3	0.3300	30.20	20.69	50.89	59.45	-8.56	QP
4	0.3300	11.77	20.69	32.46	49.45	-16.99	AVG
5	0.6220	28.07	20.34	48.41	56.00	-7.59	QP
6	0.6220	15.28	20.34	35.62	46.00	-10.38	AVG
7	1.3140	27.88	20.15	48.03	56.00	-7.97	QP
8	1.3140	13.95	20.15	34.10	46.00	-11.90	AVG
9	3.2500	27.88	20.08	47.96	56.00	-8.04	QP
10	3.2500	12.66	20.08	32.74	46.00	-13.26	AVG
11	18.6340	18.62	20.49	39.11	60.00	-20.89	QP
12	18.6340	5.63	20.49	26.12	50.00	-23.88	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

100.0 dBuV






Temperature:	27.2(C)	Relative Humidity:	66%RH
Test Voltage	AC 120V/60Hz	Phase:	N
Test Mode	Mode 19		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	37.50	20.19	57.69	66.00	-8.31	QP
2	0.1500	18.85	20.19	39.04	56.00	-16.96	AVG
3	0.3500	30.80	20.64	51.44	58.96	-7.52	QP
4	0.3500	14.27	20.64	34.91	48.96	-14.05	AVG
5	0.7460	27.52	20.26	47.78	56.00	-8.22	QP
6	0.7460	12.50	20.26	32.76	46.00	-13.24	AVG
7	1.2700	28.56	20.16	48.72	56.00	-7.28	QP
8	1.2700	14.69	20.16	34.85	46.00	-11.15	AVG
9	2.7300	25.83	20.10	45.93	56.00	-10.07	QP
10	2.7300	11.81	20.10	31.91	46.00	-14.09	AVG
11	24.2780	16.97	20.68	37.65	60.00	-22.35	QP
12	24.2780	4.55	20.68	25.23	50.00	-24.77	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)





3.2 RADIATED EMISSION AND (BANDEDGE) MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7&15.205/209(a), then the limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	68.2	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Note: In case the emission radiated emission above 1000MHz fall within the restricted band the restricted frequency bands, the peak limit is 74 dBuV/m.

**LIMITS OF EMISSIONS OUTSIDE OF THE FREQUENCY BANDS**

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: dBuV/m(at 3M) = EIRP(dBm) + 95.3.

Peak Limit = -27dBm/MHz + 95.3 = 68.3 dBuV/m.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.


3.2.2 DEVIATION FROM TEST STANDARD

No deviation




3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency (MHz)	FS (dBμV/m)	RA (dBμV/m)	AF (dB)	CL (dB)	AG (dB)	Factor (dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	23.2(C)	Relative Humidity:	59%RH
Test Voltage :	DC 3.8V	Polarization :	--
Test Mode :	TX Mode		


Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.




**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature	23.2(C)	Relative Humidity:	59%RH
Test Voltage	DC 3.8V	Polarization:	Horizontal
Test Mode	Mode 1~18(Mode 3 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.8200	41.88	-15.91	25.97	40.00	-14.03	QP
2	55.2200	53.19	-25.04	28.15	40.00	-11.85	QP
3	263.7700	30.87	-14.75	16.12	46.00	-29.88	QP
4	568.3500	28.84	-5.58	23.26	46.00	-22.74	QP
5	738.1000	29.79	-2.18	27.61	46.00	-18.39	QP
6	949.5600	29.37	1.58	30.95	46.00	-15.05	QP

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain






Temperature	23.2(C)	Relative Humidity:	59%RH
Test Voltage	DC 3.8V	Polarization:	Vertical
Test Mode	Mode 1~18(Mode 3 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.8200	46.23	-15.91	30.32	40.00	-9.68	QP
2	55.2200	55.96	-25.04	30.92	40.00	-9.08	QP
3	416.0600	29.49	-10.28	19.21	46.00	-26.79	QP
4	559.6200	29.45	-5.50	23.95	46.00	-22.05	QP
5	736.1600	29.56	-2.25	27.31	46.00	-18.69	QP
6	971.8700	29.40	2.13	31.53	54.00	-22.47	QP

Remark:

1. Margin = Result (Result = Reading + Factor) - Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain





3.2.8 TEST RESULTS (1GHz - 40GHz)

Band I 5150-5250MHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11a/ 5180 MHz)										
3253.04	45.02	44.70	6.70	28.20	-9.80	35.22	68.20	-32.98	Pk	Vertical
3253.04	40.78	44.70	6.70	28.20	-9.80	30.98	54.00	-23.02	AV	Vertical
3256.82	44.89	44.70	6.70	28.20	-9.80	35.09	68.20	-33.11	Pk	Horizontal
3256.82	41.53	44.70	6.70	28.20	-9.80	31.73	54.00	-22.27	AV	Horizontal
3992.02	39.03	44.20	7.90	29.70	-6.60	32.43	68.20	-35.77	Pk	Vertical
3992.02	36.88	44.20	7.90	29.70	-6.60	30.28	54.00	-23.72	AV	Vertical
3984.47	39.34	44.20	7.90	29.70	-6.60	32.74	68.20	-35.46	Pk	Horizontal
3984.47	35.69	44.20	7.90	29.70	-6.60	29.09	54.00	-24.91	AV	Horizontal
7222.39	37.68	43.50	11.40	35.50	3.40	41.08	68.20	-27.12	Pk	Vertical
7222.39	33.89	43.50	11.40	35.50	3.40	37.29	54.00	-16.71	AV	Vertical
7224.21	36.71	43.50	11.40	35.50	3.40	40.11	68.20	-28.09	Pk	Horizontal
7224.21	34.20	43.50	11.40	35.50	3.40	37.60	54.00	-16.40	AV	Horizontal
10360.17	38.91	44.50	13.80	38.80	8.10	47.01	68.20	-21.19	Pk	Vertical
10360.17	35.98	44.50	13.80	38.80	8.10	44.08	54.00	-9.92	AV	Vertical
10360.43	39.47	44.50	13.80	38.80	8.10	47.57	68.20	-20.63	Pk	Horizontal
10360.43	36.26	44.50	13.80	38.80	8.10	44.36	54.00	-9.64	AV	Horizontal
11017.16	34.17	43.60	14.30	39.50	10.20	44.37	68.20	-23.83	Pk	Vertical
11017.16	31.17	43.60	14.30	39.50	10.20	41.37	54.00	-12.63	AV	Vertical
11024.49	33.59	43.60	14.30	39.50	10.20	43.79	68.20	-24.41	Pk	Horizontal
11024.49	29.96	43.60	14.30	39.50	10.20	40.16	54.00	-13.84	AV	Horizontal
13284.03	32.05	42.60	15.90	38.90	12.20	44.25	68.20	-23.95	Pk	Vertical
13284.03	29.13	42.60	15.90	38.90	12.20	41.33	54.00	-12.67	AV	Vertical
13289.25	32.62	42.60	15.90	38.90	12.20	44.82	68.20	-23.38	Pk	Horizontal
13289.25	29.77	42.60	15.90	38.90	12.20	41.97	54.00	-12.03	AV	Horizontal
Mid Channel (802.11a/ 5200 MHz)										
3253.35	44.85	44.70	6.70	28.20	-9.80	35.05	68.20	-33.15	Pk	Vertical
3253.35	41.84	44.70	6.70	28.20	-9.80	32.04	54.00	-21.96	AV	Vertical
3265.24	44.51	44.70	6.70	28.20	-9.80	34.71	68.20	-33.49	Pk	Horizontal
3265.24	41.17	44.70	6.70	28.20	-9.80	31.37	54.00	-22.63	AV	Horizontal
3993.31	39.12	44.20	7.90	29.70	-6.60	32.52	68.20	-35.68	Pk	Vertical
3993.31	36.94	44.20	7.90	29.70	-6.60	30.34	54.00	-23.66	AV	Vertical
3987.59	39.93	44.20	7.90	29.70	-6.60	33.33	68.20	-34.87	Pk	Horizontal
3987.59	36.90	44.20	7.90	29.70	-6.60	30.30	54.00	-23.70	AV	Horizontal
7228.29	36.87	43.50	11.40	35.50	3.40	40.27	68.20	-27.93	Pk	Vertical
7228.29	33.94	43.50	11.40	35.50	3.40	37.34	54.00	-16.66	AV	Vertical
7231.70	37.32	43.50	11.40	35.50	3.40	40.72	68.20	-27.48	Pk	Horizontal
7231.70	34.50	43.50	11.40	35.50	3.40	37.90	54.00	-16.10	AV	Horizontal
10399.95	38.72	44.50	13.80	38.80	8.10	46.82	68.20	-21.38	Pk	Vertical
10399.95	36.21	44.50	13.80	38.80	8.10	44.31	54.00	-9.69	AV	Vertical
10400.39	40.13	44.50	13.80	38.80	8.10	48.23	68.20	-19.97	Pk	Horizontal
10400.39	35.99	44.50	13.80	38.80	8.10	44.09	54.00	-9.91	AV	Horizontal
11016.98	33.75	43.60	14.30	39.50	10.20	43.95	68.20	-24.25	Pk	Vertical
11016.98	29.95	43.60	14.30	39.50	10.20	40.15	54.00	-13.85	AV	Vertical
11017.82	33.98	43.60	14.30	39.50	10.20	44.18	68.20	-24.02	Pk	Horizontal
11017.82	30.87	43.60	14.30	39.50	10.20	41.07	54.00	-12.93	AV	Horizontal
13284.84	32.60	42.60	15.90	38.90	12.20	44.80	68.20	-23.40	Pk	Vertical
13284.84	29.29	42.60	15.90	38.90	12.20	41.49	54.00	-12.51	AV	Vertical
13283.17	31.95	42.60	15.90	38.90	12.20	44.15	68.20	-24.05	Pk	Horizontal
13283.17	28.96	42.60	15.90	38.90	12.20	41.16	54.00	-12.84	AV	Horizontal



High Channel (802.11a/ 5240 MHz)										
3256.76	44.45	44.70	6.70	28.20	-9.80	34.65	68.20	-33.55	Pk	Vertical
3256.76	41.84	44.70	6.70	28.20	-9.80	32.04	54.00	-21.96	AV	Vertical
3264.68	44.69	44.70	6.70	28.20	-9.80	34.89	68.20	-33.31	Pk	Horizontal
3264.68	42.09	44.70	6.70	28.20	-9.80	32.29	54.00	-21.71	AV	Horizontal
3992.71	39.85	44.20	7.90	29.70	-6.60	33.25	68.20	-34.95	Pk	Vertical
3992.71	36.78	44.20	7.90	29.70	-6.60	30.18	54.00	-23.82	AV	Vertical
3997.82	39.22	44.20	7.90	29.70	-6.60	32.62	68.20	-35.58	Pk	Horizontal
3997.82	36.37	44.20	7.90	29.70	-6.60	29.77	54.00	-24.23	AV	Horizontal
7228.29	37.82	43.50	11.40	35.50	3.40	41.22	68.20	-26.98	Pk	Vertical
7228.29	34.73	43.50	11.40	35.50	3.40	38.13	54.00	-15.87	AV	Vertical
7224.01	37.37	43.50	11.40	35.50	3.40	40.77	68.20	-27.43	Pk	Horizontal
7224.01	34.15	43.50	11.40	35.50	3.40	37.55	54.00	-16.45	AV	Horizontal
10479.95	38.97	44.50	13.80	38.80	8.10	47.07	68.20	-21.13	Pk	Vertical
10479.95	36.04	44.50	13.80	38.80	8.10	44.14	54.00	-9.86	AV	Vertical
10480.32	38.76	44.50	13.80	38.80	8.10	46.86	68.20	-21.34	Pk	Horizontal
10480.32	36.73	44.50	13.80	38.80	8.10	44.83	54.00	-9.17	AV	Horizontal
11033.30	32.88	43.60	14.30	39.50	10.20	43.08	68.20	-25.12	Pk	Vertical
11033.30	30.40	43.60	14.30	39.50	10.20	40.60	54.00	-13.40	AV	Vertical
11016.84	34.06	43.60	14.30	39.50	10.20	44.26	68.20	-23.94	Pk	Horizontal
11016.84	30.58	43.60	14.30	39.50	10.20	40.78	54.00	-13.22	AV	Horizontal
13286.02	32.51	42.60	15.90	38.90	12.20	44.71	68.20	-23.49	Pk	Vertical
13286.02	28.89	42.60	15.90	38.90	12.20	41.09	54.00	-12.91	AV	Vertical
13284.80	32.01	42.60	15.90	38.90	12.20	44.21	68.20	-23.99	Pk	Horizontal
13284.80	28.96	42.60	15.90	38.90	12.20	41.16	54.00	-12.84	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (VHT-20), 802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



Band II 5250-5350MHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11a/ 5260 MHz)										
3259.78	43.89	44.70	6.70	28.20	-9.80	34.09	68.20	-34.11	Pk	Vertical
3259.78	41.00	44.70	6.70	28.20	-9.80	31.20	54.00	-22.80	AV	Vertical
3260.98	44.98	44.70	6.70	28.20	-9.80	35.18	68.20	-33.02	Pk	Horizontal
3260.98	41.91	44.70	6.70	28.20	-9.80	32.11	54.00	-21.89	AV	Horizontal
3996.58	39.54	44.20	7.90	29.70	-6.60	32.94	68.20	-35.26	Pk	Vertical
3996.58	37.05	44.20	7.90	29.70	-6.60	30.45	54.00	-23.55	AV	Vertical
3998.24	39.88	44.20	7.90	29.70	-6.60	33.28	68.20	-34.92	Pk	Horizontal
3998.24	36.75	44.20	7.90	29.70	-6.60	30.15	54.00	-23.85	AV	Horizontal
7231.48	37.06	43.50	11.40	35.50	3.40	40.46	68.20	-27.74	Pk	Vertical
7231.48	33.51	43.50	11.40	35.50	3.40	36.91	54.00	-17.09	AV	Vertical
7222.42	37.90	43.50	11.40	35.50	3.40	41.30	68.20	-26.90	Pk	Horizontal
7222.42	34.29	43.50	11.40	35.50	3.40	37.69	54.00	-16.31	AV	Horizontal
10519.97	39.37	44.50	13.90	38.80	8.20	47.57	68.20	-20.63	Pk	Vertical
10519.97	35.73	44.50	13.90	38.80	8.20	43.93	54.00	-10.07	AV	Vertical
10520.26	39.84	44.50	13.90	38.80	8.20	48.04	68.20	-20.16	Pk	Horizontal
10520.26	36.76	44.50	13.90	38.80	8.20	44.96	54.00	-9.04	AV	Horizontal
11030.62	32.77	43.60	14.30	39.50	10.20	42.97	68.20	-25.23	Pk	Vertical
11030.62	30.50	43.60	14.30	39.50	10.20	40.70	54.00	-13.30	AV	Vertical
11023.90	33.37	43.60	14.30	39.50	10.20	43.57	68.20	-24.63	Pk	Horizontal
11023.90	30.31	43.60	14.30	39.50	10.20	40.51	54.00	-13.49	AV	Horizontal
13281.06	32.93	42.60	15.90	38.90	12.20	45.13	68.20	-23.07	Pk	Vertical
13281.06	28.82	42.60	15.90	38.90	12.20	41.02	54.00	-12.98	AV	Vertical
13299.24	32.21	42.60	15.90	38.90	12.20	44.41	68.20	-23.79	Pk	Horizontal
13299.24	29.96	42.60	15.90	38.90	12.20	42.16	54.00	-11.84	AV	Horizontal
Mid Channel (802.11a/ 5300 MHz)										
3261.63	44.16	44.70	6.70	28.20	-9.80	34.36	68.20	-33.84	Pk	Vertical
3261.63	40.89	44.70	6.70	28.20	-9.80	31.09	54.00	-22.91	AV	Vertical
3250.87	44.35	44.70	6.70	28.20	-9.80	34.55	68.20	-33.65	Pk	Horizontal
3250.87	41.69	44.70	6.70	28.20	-9.80	31.89	54.00	-22.11	AV	Horizontal
3988.83	39.49	44.20	7.90	29.70	-6.60	32.89	68.20	-35.31	Pk	Vertical
3988.83	36.44	44.20	7.90	29.70	-6.60	29.84	54.00	-24.16	AV	Vertical
3988.29	39.61	44.20	7.90	29.70	-6.60	33.01	68.20	-35.19	Pk	Horizontal
3988.29	36.07	44.20	7.90	29.70	-6.60	29.47	54.00	-24.53	AV	Horizontal
7235.86	36.75	43.50	11.40	35.50	3.40	40.15	68.20	-28.05	Pk	Vertical
7235.86	34.87	43.50	11.40	35.50	3.40	38.27	54.00	-15.73	AV	Vertical
7217.10	36.48	43.50	11.40	35.50	3.40	39.88	68.20	-28.32	Pk	Horizontal
7217.10	33.87	43.50	11.40	35.50	3.40	37.27	54.00	-16.73	AV	Horizontal
10600.32	39.66	44.50	13.80	38.80	8.10	47.76	68.20	-20.44	Pk	Vertical
10600.32	36.85	44.50	13.80	38.80	8.10	44.95	54.00	-9.05	AV	Vertical
10600.32	40.13	44.50	13.80	38.80	8.10	48.23	68.20	-19.97	Pk	Horizontal
10600.32	36.52	44.50	13.80	38.80	8.10	44.62	54.00	-9.38	AV	Horizontal
11021.67	33.16	43.60	14.30	39.50	10.20	43.36	68.20	-24.84	Pk	Vertical
11021.67	31.07	43.60	14.30	39.50	10.20	41.27	54.00	-12.73	AV	Vertical
11016.98	34.16	43.60	14.30	39.50	10.20	44.36	68.20	-23.84	Pk	Horizontal
11016.98	29.95	43.60	14.30	39.50	10.20	40.15	54.00	-13.85	AV	Horizontal
13297.90	31.62	42.60	15.90	38.90	12.20	43.82	68.20	-24.38	Pk	Vertical
13297.90	29.46	42.60	15.90	38.90	12.20	41.66	54.00	-12.34	AV	Vertical
13281.57	32.45	42.60	15.90	38.90	12.20	44.65	68.20	-23.55	Pk	Horizontal
13281.57	29.40	42.60	15.90	38.90	12.20	41.60	54.00	-12.40	AV	Horizontal



High Channel (802.11a/ 5320 MHz)										
3262.91	44.13	44.70	6.70	28.20	-9.80	34.33	68.20	-33.87	Pk	Vertical
3262.91	42.19	44.70	6.70	28.20	-9.80	32.39	54.00	-21.61	AV	Vertical
3262.31	45.13	44.70	6.70	28.20	-9.80	35.33	68.20	-32.87	Pk	Horizontal
3262.31	41.13	44.70	6.70	28.20	-9.80	31.33	54.00	-22.67	AV	Horizontal
3981.05	38.92	44.20	7.90	29.70	-6.60	32.32	68.20	-35.88	Pk	Vertical
3981.05	36.11	44.20	7.90	29.70	-6.60	29.51	54.00	-24.49	AV	Vertical
3989.83	39.84	44.20	7.90	29.70	-6.60	33.24	68.20	-34.96	Pk	Horizontal
3989.83	36.11	44.20	7.90	29.70	-6.60	29.51	54.00	-24.49	AV	Horizontal
7231.05	37.90	43.50	11.40	35.50	3.40	41.30	68.20	-26.90	Pk	Vertical
7231.05	34.00	43.50	11.40	35.50	3.40	37.40	54.00	-16.60	AV	Vertical
7228.47	37.90	43.50	11.40	35.50	3.40	41.30	68.20	-26.90	Pk	Horizontal
7228.47	34.31	43.50	11.40	35.50	3.40	37.71	54.00	-16.29	AV	Horizontal
10639.96	39.38	44.50	13.80	38.80	8.10	47.48	68.20	-20.72	Pk	Vertical
10639.96	36.27	44.50	13.80	38.80	8.10	44.37	54.00	-9.63	AV	Vertical
10640.33	39.52	44.50	13.80	38.80	8.10	47.62	68.20	-20.58	Pk	Horizontal
10640.33	36.41	44.50	13.80	38.80	8.10	44.51	54.00	-9.49	AV	Horizontal
11023.26	33.94	43.60	14.30	39.50	10.20	44.14	68.20	-24.06	Pk	Vertical
11023.26	31.03	43.60	14.30	39.50	10.20	41.23	54.00	-12.77	AV	Vertical
11033.49	33.12	43.60	14.30	39.50	10.20	43.32	68.20	-24.88	Pk	Horizontal
11033.49	29.85	43.60	14.30	39.50	10.20	40.05	54.00	-13.95	AV	Horizontal
13281.32	32.28	42.70	18.00	37.10	12.40	44.68	68.20	-23.52	Pk	Vertical
13281.32	29.19	42.70	18.00	37.10	12.40	41.59	54.00	-12.41	AV	Vertical
13286.00	32.27	42.70	18.00	37.10	12.40	44.67	68.20	-23.53	Pk	Horizontal
13286.00	28.75	42.70	18.00	37.10	12.40	41.15	54.00	-12.85	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



Band IV(5.725-5.850) GHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11a/ 5745 MHz)										
3245.82	45.18	44.70	6.70	28.20	-9.80	35.38	68.20	-32.82	Pk	Vertical
3245.82	41.07	44.70	6.70	28.20	-9.80	31.27	54.00	-22.73	AV	Vertical
3249.35	44.47	44.70	6.70	28.20	-9.80	34.67	68.20	-33.53	Pk	Horizontal
3249.35	40.94	44.70	6.70	28.20	-9.80	31.14	54.00	-22.86	AV	Horizontal
3996.17	39.97	44.20	7.90	29.70	-6.60	33.37	68.20	-34.83	Pk	Vertical
3996.17	36.61	44.20	7.90	29.70	-6.60	30.01	54.00	-23.99	AV	Vertical
3985.69	39.71	44.20	7.90	29.70	-6.60	33.11	68.20	-35.09	Pk	Horizontal
3985.69	35.87	44.20	7.90	29.70	-6.60	29.27	54.00	-24.73	AV	Horizontal
7225.22	36.60	43.50	11.40	35.50	3.40	40.00	68.20	-28.20	Pk	Vertical
7225.22	34.27	43.50	11.40	35.50	3.40	37.67	54.00	-16.33	AV	Vertical
7221.27	36.52	43.50	11.40	35.50	3.40	39.92	68.20	-28.28	Pk	Horizontal
7221.27	33.79	43.50	11.40	35.50	3.40	37.19	54.00	-16.81	AV	Horizontal
10509.98	39.11	44.50	13.90	38.80	8.20	47.31	68.20	-20.89	Pk	Vertical
10509.98	36.80	44.50	13.90	38.80	8.20	45.00	54.00	-9.00	AV	Vertical
10508.73	38.92	44.50	13.90	38.80	8.20	47.12	68.20	-21.08	Pk	Horizontal
10508.73	36.29	44.50	13.90	38.80	8.20	44.49	54.00	-9.51	AV	Horizontal
11489.94	33.86	43.60	14.30	39.50	10.20	44.06	68.20	-24.14	Pk	Vertical
11489.94	30.05	43.60	14.30	39.50	10.20	40.25	54.00	-13.75	AV	Vertical
11490.39	32.75	43.60	14.30	39.50	10.20	42.95	68.20	-25.25	Pk	Horizontal
11490.39	30.56	43.60	14.30	39.50	10.20	40.76	54.00	-13.24	AV	Horizontal
13287.27	32.71	42.60	15.90	38.90	12.20	44.91	68.20	-23.29	Pk	Vertical
13287.27	29.61	42.60	15.90	38.90	12.20	41.81	54.00	-12.19	AV	Vertical
13289.80	31.76	42.60	15.90	38.90	12.20	43.96	68.20	-24.24	Pk	Horizontal
13289.80	29.51	42.60	15.90	38.90	12.20	41.71	54.00	-12.29	AV	Horizontal
Mid Channel (802.11a/ 5785 MHz)										
3260.13	45.10	44.70	6.70	28.20	-9.80	35.30	68.20	-32.90	Pk	Vertical
3260.13	41.21	44.70	6.70	28.20	-9.80	31.41	54.00	-22.59	AV	Vertical
3245.76	44.33	44.70	6.70	28.20	-9.80	34.53	68.20	-33.67	Pk	Horizontal
3245.76	41.42	44.70	6.70	28.20	-9.80	31.62	54.00	-22.38	AV	Horizontal
3993.57	39.64	44.20	7.90	29.70	-6.60	33.04	68.20	-35.16	Pk	Vertical
3993.57	36.45	44.20	7.90	29.70	-6.60	29.85	54.00	-24.15	AV	Vertical
3980.80	39.60	44.20	7.90	29.70	-6.60	33.00	68.20	-35.20	Pk	Horizontal
3980.80	35.95	44.20	7.90	29.70	-6.60	29.35	54.00	-24.65	AV	Horizontal
7236.31	37.59	43.50	11.40	35.50	3.40	40.99	68.20	-27.21	Pk	Vertical
7236.31	34.64	43.50	11.40	35.50	3.40	38.04	54.00	-15.96	AV	Vertical
7224.33	37.30	43.50	11.40	35.50	3.40	40.70	68.20	-27.50	Pk	Horizontal
7224.33	34.95	43.50	11.40	35.50	3.40	38.35	54.00	-15.65	AV	Horizontal
10592.33	38.91	44.50	13.80	38.80	8.10	47.01	68.20	-21.19	Pk	Vertical
10592.33	36.32	44.50	13.80	38.80	8.10	44.42	54.00	-9.58	AV	Vertical
10584.29	39.56	44.50	13.80	38.80	8.10	47.66	68.20	-20.54	Pk	Horizontal
10584.29	35.97	44.50	13.80	38.80	8.10	44.07	54.00	-9.93	AV	Horizontal
11570.34	34.09	43.60	14.30	39.50	10.20	44.29	68.20	-23.91	Pk	Vertical
11570.34	30.43	43.60	14.30	39.50	10.20	40.63	54.00	-13.37	AV	Vertical
11570.00	34.06	43.60	14.30	39.50	10.20	44.26	68.20	-23.94	Pk	Horizontal
11570.00	30.59	43.60	14.30	39.50	10.20	40.79	54.00	-13.21	AV	Horizontal
13292.60	32.84	42.60	15.90	38.90	12.20	45.04	68.20	-23.16	Pk	Vertical
13292.60	28.67	42.60	15.90	38.90	12.20	40.87	54.00	-13.13	AV	Vertical
13289.13	32.27	42.60	15.90	38.90	12.20	44.47	68.20	-23.73	Pk	Horizontal
13289.13	28.56	42.60	15.90	38.90	12.20	40.76	54.00	-13.24	AV	Horizontal



High Channel (802.11a/ 5825 MHz)										
3257.92	44.80	44.70	6.70	28.20	-9.80	35.00	68.20	-33.20	Pk	Vertical
3257.92	40.82	44.70	6.70	28.20	-9.80	31.02	54.00	-22.98	AV	Vertical
3261.63	44.82	44.70	6.70	28.20	-9.80	35.02	68.20	-33.18	Pk	Horizontal
3261.63	41.19	44.70	6.70	28.20	-9.80	31.39	54.00	-22.61	AV	Horizontal
3989.41	38.81	44.20	7.90	29.70	-6.60	32.21	68.20	-35.99	Pk	Vertical
3989.41	35.78	44.20	7.90	29.70	-6.60	29.18	54.00	-24.82	AV	Vertical
3987.21	39.41	44.20	7.90	29.70	-6.60	32.81	68.20	-35.39	Pk	Horizontal
3987.21	36.73	44.20	7.90	29.70	-6.60	30.13	54.00	-23.87	AV	Horizontal
7228.20	37.09	43.50	11.40	35.50	3.40	40.49	68.20	-27.71	Pk	Vertical
7228.20	34.35	43.50	11.40	35.50	3.40	37.75	54.00	-16.25	AV	Vertical
7233.33	37.38	43.50	11.40	35.50	3.40	40.78	68.20	-27.42	Pk	Horizontal
7233.33	34.67	43.50	11.40	35.50	3.40	38.07	54.00	-15.93	AV	Horizontal
10637.71	39.58	44.50	13.80	38.80	8.10	47.68	68.20	-20.52	Pk	Vertical
10637.71	35.75	44.50	13.80	38.80	8.10	43.85	54.00	-10.15	AV	Vertical
10640.36	38.90	44.50	13.80	38.80	8.10	47.00	68.20	-21.20	Pk	Horizontal
10640.36	35.84	44.50	13.80	38.80	8.10	43.94	54.00	-10.06	AV	Horizontal
11650.05	33.97	43.60	14.30	39.50	10.20	44.17	68.20	-24.03	Pk	Vertical
11650.05	30.50	43.60	14.30	39.50	10.20	40.70	54.00	-13.30	AV	Vertical
11650.42	32.91	43.60	14.30	39.50	10.20	43.11	68.20	-25.09	Pk	Horizontal
11650.42	30.00	43.60	14.30	39.50	10.20	40.20	54.00	-13.80	AV	Horizontal
13288.90	32.19	42.70	18.00	37.10	12.40	44.59	68.20	-23.61	Pk	Vertical
13288.90	28.97	42.70	18.00	37.10	12.40	41.37	54.00	-12.63	AV	Vertical
13293.68	32.32	42.70	18.00	37.10	12.40	44.72	68.20	-23.48	Pk	Horizontal
13293.68	28.56	42.70	18.00	37.10	12.40	40.96	54.00	-13.04	AV	Horizontal

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (VHT-20), 802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



3.2.9 RESTRICTED FREQUENCY BANDS AND BAND EDGE


Band I 5150-5250MHz

802.11a-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5130.750	59.61	-5.74	53.87	74.00	-20.13	peak
2	5130.750	46.39	-5.74	40.65	54.00	-13.35	AVG
3	5150.000	61.55	-5.73	55.82	74.00	-18.18	peak
4	5150.000	47.18	-5.73	41.45	54.00	-12.55	AVG


802.11a-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5035.500	53.02	-6.03	46.99	74.00	-27.01	peak
2	5150.000	66.90	-5.73	61.17	74.00	-12.83	peak
3	5150.000	53.25	-5.73	47.52	54.00	-6.48	AVG




802.11a-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.64	-5.23	46.41	74.00	-27.59	peak
2	5412.680	52.40	-5.22	47.18	74.00	-26.82	peak


802.11a-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	52.96	-5.23	47.73	74.00	-26.27	peak
2	5394.480	52.89	-5.24	47.65	74.00	-26.35	peak




802.11n40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5126.250	61.19	-5.74	55.45	74.00	-18.55	peak
2	5126.250	40.37	-5.74	34.63	54.00	-19.37	AVG
3	5150.000	70.41	-5.73	64.68	74.00	-9.32	peak
4	5150.000	44.80	-5.73	39.07	54.00	-14.93	AVG


802.11n40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5130.750	62.15	-5.74	56.41	74.00	-17.59	peak
2	5130.750	41.62	-5.74	35.88	54.00	-18.12	AVG
3	5150.000	71.30	-5.73	65.57	74.00	-8.43	peak
4	5150.000	48.34	-5.73	42.61	54.00	-11.39	AVG




802.11n40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.74	-5.23	46.51	74.00	-27.49	peak
2	5360.800	52.85	-5.23	47.62	74.00	-26.38	peak


802.11n40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	52.95	-5.23	47.72	74.00	-26.28	peak
2	5360.180	56.71	-5.23	51.48	74.00	-22.52	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5110.400	63.66	-5.74	57.92	74.00	-16.08	peak
2	5110.400	40.22	-5.74	34.48	54.00	-19.52	AVG
3	5150.000	66.78	-5.73	61.05	74.00	-12.95	peak
4	5150.000	46.42	-5.73	40.69	54.00	-13.31	AVG


802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5079.200	56.92	-5.84	51.08	74.00	-22.92	peak
2	5150.000	68.49	-5.73	62.76	74.00	-11.24	peak
3	5150.000	50.45	-5.73	44.72	54.00	-9.28	AVG




802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	56.87	-5.23	51.64	74.00	-19.36	peak
2	5359.250	57.88	-5.23	52.65	74.00	-21.35	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	58.23	-5.23	53.00	74.00	-21.00	peak
2	5350.000	41.11	-5.23	35.88	54.00	-18.12	AVG
3	5368.240	59.70	-5.24	54.46	74.00	-19.54	peak
4	5368.240	39.88	-5.24	34.64	54.00	-19.36	AVG

Note: All modes have been tested. Only the worst mode shown in the report.




Band II 5250-5350MHz

802.11a-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4704.000	52.63	-7.35	45.28	74.00	-28.72	peak
2	5150.000	50.52	-5.73	44.79	74.00	-29.21	peak


802.11a-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5058.450	52.45	-5.92	46.53	74.00	-27.47	peak
2	5150.000	52.28	-5.73	46.55	74.00	-27.45	peak




802.11a-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	52.31	-5.23	47.08	74.00	-26.92	peak
2	5380.080	53.80	-5.25	48.55	74.00	-25.45	peak


802.11a-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	53.51	-5.23	48.28	74.00	-25.72	peak
2	5365.500	53.88	-5.24	48.64	74.00	-25.36	peak




802.11n40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5089.900	51.30	-5.79	45.51	74.00	-28.49	peak
2	5150.000	49.38	-5.73	43.65	74.00	-30.35	peak


802.11n40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5088.200	51.29	-5.79	45.50	74.00	-28.50	peak
2	5150.000	49.83	-5.73	44.10	74.00	-29.90	peak




802.11n40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	51.43	-5.23	46.20	74.00	-27.80	peak
2	5381.670	52.03	-5.24	46.79	74.00	-27.21	peak


802.11n40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	52.73	-5.23	47.50	74.00	-26.50	peak
2	5367.180	54.16	-5.24	48.92	74.00	-25.08	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5087.350	51.26	-5.80	45.46	74.00	-28.54	peak
2	5150.000	49.31	-5.73	43.58	74.00	-30.42	peak


802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5115.400	52.00	-5.74	46.26	74.00	-27.74	peak
2	5150.000	50.91	-5.73	45.18	74.00	-28.82	peak




802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	61.26	-5.23	56.03	74.00	-17.97	peak
2	5350.000	45.00	-5.23	39.77	54.00	-14.23	AVG
3	5357.820	61.68	-5.23	56.45	74.00	-17.55	peak
4	5357.820	42.93	-5.23	37.70	54.00	-16.30	AVG

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	65.30	-5.23	60.07	74.00	-13.93	peak
2	5350.000	46.72	-5.23	41.49	54.00	-12.51	AVG
3	5359.380	67.08	-5.23	61.85	74.00	-12.15	peak
4	5359.380	44.70	-5.23	39.47	54.00	-14.53	AVG

Note: All modes have been tested. Only the worst mode shown in the report.




Band IV(5.725-5.85 GHz)

802.11a-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5719.063	66.71	-4.60	62.11	110.92	-48.81	peak
2	5725.000	70.51	-4.57	65.94	119.20	-53.26	peak


802.11a-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5717.750	67.26	-4.60	62.66	110.53	-47.87	peak
2	5725.000	72.43	-4.57	67.86	119.20	-51.34	peak




802.11a-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	59.06	-4.10	54.96	119.20	-64.24	peak
2	5853.313	62.45	-4.08	58.37	113.90	-55.53	peak


802.11a-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	62.87	-4.10	58.77	119.20	-60.43	peak
2	5852.175	67.20	-4.09	63.11	115.72	-52.61	peak




802.11ac40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5649.875	52.94	-4.68	48.26	68.20	-19.94	peak
2	5701.625	60.71	-4.66	56.05	105.69	-49.64	peak
3	5725.000	70.43	-4.57	65.86	119.20	-53.34	peak


802.11ac40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5652.500	54.35	-4.68	49.67	70.05	-20.38	peak
2	5703.500	62.57	-4.64	57.93	106.25	-48.32	peak
3	5725.000	72.59	-4.57	68.02	119.20	-51.18	peak




802.11ac40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	51.43	-4.10	47.33	119.20	-71.87	peak
2	5866.637	52.21	-4.02	48.19	107.71	-59.52	peak
3	5932.125	50.70	-3.94	46.76	68.20	-21.44	peak


802.11ac40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	51.69	-4.10	47.59	119.20	-71.61	peak
2	5863.712	52.62	-4.04	48.58	108.59	-60.01	peak
3	5942.525	50.77	-3.95	46.82	68.20	-21.38	peak




802.11ac80-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5653.900	60.83	-4.67	56.16	71.09	-14.93	peak
2	5725.000	72.48	-4.57	67.91	119.20	-51.29	peak
3	5850.000	67.47	-4.10	63.37	119.20	-55.83	peak
4	5926.900	50.85	-3.93	46.92	68.20	-21.28	peak

802.11ac80-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5638.500	62.69	-4.69	58.00	68.20	-10.20	peak
2	5725.000	75.51	-4.57	70.94	119.20	-48.26	peak
3	5850.000	64.76	-4.10	60.66	119.20	-58.54	peak
4	5941.950	51.48	-3.95	47.53	68.20	-20.67	peak

Note: All modes have been tested. Only the worst mode shown in the report.



4. POWER SPECTRAL DENSITY TEST

4.1 LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

1. The setting follows Method SA-1 of FCC KDB D02 General UNII Test Procedures New Rules v01r03.

For devices operating in the band, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (*i.e.*, 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHZ}$ is available on nearly all spectrum analyzers.



4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

5150-5250MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5180	0.055	0.092	0.147	11	PASS
5200	0.433	0.092	0.525	11	PASS
5240	0.846	0.092	0.938	11	PASS
802.11n20					
5180	-0.076	0.081	0.005	11	PASS
5200	-0.449	0.081	-0.368	11	PASS
5240	-0.287	0.081	-0.206	11	PASS
802.11n40					
5190	-2.956	0.232	-2.724	11	PASS
5230	-3.532	0.232	-3.300	11	PASS
802.11ac20					
5180	-0.426	0.113	-0.313	11	PASS
5200	-0.332	0.113	-0.219	11	PASS
5240	0.226	0.113	0.339	11	PASS
802.11ac40					
5190	-3.432	0.243	-3.189	11	PASS
5230	-2.994	0.243	-2.751	11	PASS
802.11ac80					
5210	-6.152	0.498	-5.654	11	PASS



5250-5350MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5260	0.202	0.092	0.294	11	PASS
5300	-0.251	0.092	-0.159	11	PASS
5320	-0.367	0.092	-0.275	11	PASS
802.11n20					
5260	-0.213	0.098	-0.115	11	PASS
5300	-0.950	0.098	-0.852	11	PASS
5320	-1.244	0.098	-1.146	11	PASS
802.11n40					
5270	-3.214	0.233	-2.981	11	PASS
5310	-3.984	0.233	-3.751	11	PASS
802.11ac20					
5260	-0.058	0.097	0.039	11	PASS
5300	-0.367	0.097	-0.270	11	PASS
5320	-1.661	0.097	-1.564	11	PASS
802.11ac40					
5270	-3.206	0.206	-3.000	11	PASS
5310	-3.851	0.206	-3.645	11	PASS
802.11ac80					
5290	-7.068	0.462	-6.606	11	PASS



5725-5850MHz						
Frequency	Use RBW 510KHz direct measurement Direct measurement Power Density (dBm)	Convert to RBW 500KHz direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a						
5745	-2.664	-2.750	0.092	-2.658	30	PASS
5785	-0.763	-0.849	0.092	-0.757	30	PASS
5825	-0.415	-0.501	0.092	-0.409	30	PASS
802.11n20						
5745	-2.856	-2.942	0.098	-2.844	30	PASS
5785	-1.854	-1.940	0.098	-1.842	30	PASS
5825	-1.109	-1.195	0.098	-1.097	30	PASS
802.11n40						
5755	-5.249	-5.335	0.232	-5.103	30	PASS
5795	-4.771	-4.857	0.232	-4.625	30	PASS
802.11ac20						
5745	-2.698	-2.784	0.113	-2.671	30	PASS
5785	-1.497	-1.583	0.113	-1.470	30	PASS
5825	-1.096	-1.182	0.113	-1.069	30	PASS
802.11ac40						
5755	-5.659	-5.745	0.205	-5.540	30	PASS
5795	-4.264	-4.350	0.205	-4.145	30	PASS
802.11ac80						
5775	-7.874	-7.960	0.475	-7.485	30	PASS

Note: 1. RB conversion formula: $10 \cdot \log(500\text{KHz}/\text{RBW})$

2. Test plots see Attachment A.



5. BANDWIDTH MEASUREMENT

5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

The following procedure shall be used for measuring 26 bandwidth.

5.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.1.5 TEST RESULTS**

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5180	19.89	Pass
5200	20.00	Pass
5240	19.78	Pass
802.11n(HT20)		
5180	20.14	Pass
5200	20.14	Pass
5240	20.23	Pass
802.11n(HT40)		
5190	41.79	Pass
5230	40.24	Pass
802.11ac(VHT20)		
5180	22.55	Pass
5200	20.03	Pass
5240	20.14	Pass
802.11ac(VHT40)		
5190	40.25	Pass
5230	40.68	Pass
802.11ac(VHT80)		
5210	80.26	Pass



Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5260	19.85	Pass
5300	19.80	Pass
5320	19.73	Pass
802.11n(HT20)		
5260	20.06	Pass
5300	20.04	Pass
5320	20.34	Pass
802.11n(HT40)		
5270	40.26	Pass
5310	40.34	Pass
802.11ac(VHT20)		
5260	20.22	Pass
5300	20.24	Pass
5320	20.15	Pass
802.11ac(VHT40)		
5270	40.60	Pass
5310	40.13	Pass
802.11ac(VHT80)		
5290	80.27	Pass



Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	19.88	Pass
5785	19.95	Pass
5825	19.71	Pass
802.11n(HT20)		
5745	20.29	Pass
5785	20.20	Pass
5825	20.04	Pass
802.11n(HT40)		
5755	40.19	Pass
5795	40.27	Pass
802.11ac(VHT20)		
5745	20.18	Pass
5785	20.45	Pass
5825	20.18	Pass
802.11ac(VHT40)		
5755	40.42	Pass
5795	40.06	Pass
802.11ac(VHT80)		
5775	80.26	Pass

Test plots see Attachment B.



5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth.

5.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

5.2.2 DEVIATION FROM STANDARD

No deviation.

5.2.3 TEST SETUP



5.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.2.5 TEST RESULTS**

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5180	16.44	Pass
5200	16.42	Pass
5240	16.42	Pass
802.11n(HT20)		
5180	17.57	Pass
5200	17.54	Pass
5240	17.54	Pass
802.11n(HT40)		
5190	36.04	Pass
5230	35.98	Pass
802.11ac(VHT20)		
5180	17.54	Pass
5200	17.54	Pass
5240	17.54	Pass
802.11ac(VHT40)		
5190	35.96	Pass
5230	35.93	Pass
802.11ac(VHT80)		
5210	75.30	Pass



Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5260	16.43	Pass
5300	16.42	Pass
5320	16.42	Pass
802.11n(HT20)		
5260	17.55	Pass
5300	17.53	Pass
5320	17.56	Pass
802.11n(HT40)		
5270	35.96	Pass
5310	35.97	Pass
802.11ac(VHT20)		
5260	17.52	Pass
5300	17.55	Pass
5320	17.54	Pass
802.11ac(VHT40)		
5270	35.94	Pass
5310	35.94	Pass
802.11ac(VHT80)		
5290	75.29	Pass



Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5745	16.41	Pass
5785	16.42	Pass
5825	16.41	Pass
802.11n(HT20)		
5745	17.55	Pass
5785	17.54	Pass
5825	17.55	Pass
802.11n(HT40)		
5755	36.01	Pass
5795	35.98	Pass
802.11ac(VHT20)		
5745	17.56	Pass
5785	17.53	Pass
5825	17.55	Pass
802.11ac(VHT40)		
5755	35.96	Pass
5795	35.95	Pass
802.11ac(VHT80)		
5775	75.24	Pass

Test plots See Attachment B.



5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

5.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.2 DEVIATION FROM STANDARD

No deviation.

5.3.3 TEST SETUP



5.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.3.5 TEST RESULTS**

Frequency (MHz)	6dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	15.29	Pass
5785	15.11	Pass
5825	15.68	Pass
802.11n(HT20)		
5745	15.67	Pass
5785	15.64	Pass
5825	15.03	Pass
802.11n(HT40)		
5755	35.09	Pass
5795	35.10	Pass
802.11ac(VHT20)		
5745	15.93	Pass
5785	15.06	Pass
5825	15.08	Pass
802.11ac(VHT40)		
5755	35.12	Pass
5795	35.11	Pass
802.11ac(VHT80)		
5775	75.63	Pass

Test plots see Attachment C.

6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Peak Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or 11 dBm + 10 log (26 dB emission bandwidth)	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	


6.2 TEST PROCEDURE

The EUT was directly connected to the Power Sensor&PC

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

**6.6 TEST RESULTS**


Band I (5.15-5.25GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
36	5180	11.25	0.092	11.34	23.98
40	5200	11.35	0.092	11.44	23.98
48	5240	11.12	0.092	11.21	23.98
802.11n(HT20)					
36	5180	11.13	0.081	11.21	23.98
40	5200	11.15	0.081	11.23	23.98
48	5240	10.84	0.081	10.92	23.98
802.11n(HT40)					
38	5190	10.84	0.232	11.07	23.98
46	5230	10.67	0.232	10.90	23.98
802.11ac(VHT20)					
36	5180	11.06	0.113	11.17	23.98
40	5200	11.09	0.113	11.20	23.98
48	5240	10.91	0.113	11.02	23.98
802.11ac(VHT40)					
38	5190	10.73	0.243	10.97	23.98
46	5230	10.59	0.243	10.83	23.98
802.11ac(VHT80)					
42	5210	9.60	0.498	10.10	23.98




Band II(5.25-5.35GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
52	5260	10.85	0.092	10.94	23.98
60	5300	10.30	0.092	10.39	23.98
64	5320	10.18	0.092	10.27	23.98
802.11n(HT20)					
52	5260	10.59	0.098	10.69	23.98
60	5300	10.14	0.098	10.24	23.98
64	5320	10.03	0.098	10.13	23.98
802.11n(HT40)					
54	5270	10.23	0.233	10.46	23.98
62	5310	9.76	0.233	9.99	23.98
802.11ac(VHT20)					
52	5260	10.67	0.097	10.77	23.98
60	5300	10.15	0.097	10.25	23.98
64	5320	9.95	0.097	10.05	23.98
802.11ac(VHT40)					
54	5270	10.16	0.206	10.37	23.98
62	5310	9.75	0.206	9.96	23.98
802.11ac(VHT80)					
58	5290	9.50	0.462	9.96	23.98




Band IV (5.725-5.85GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
149	5745	11.94	0.092	12.03	30.00
157	5785	12.15	0.092	12.24	30.00
165	5825	12.41	0.092	12.50	30.00
802.11n(HT20)					
149	5745	11.69	0.098	11.79	30.00
157	5785	12.11	0.098	12.21	30.00
165	5825	12.27	0.098	12.37	30.00
802.11n(HT40)					
151	5755	11.38	0.232	11.61	30.00
159	5795	11.57	0.232	11.80	30.00
802.11ac(VHT20)					
149	5745	11.56	0.113	11.67	30.00
157	5785	12.01	0.113	12.12	30.00
165	5825	12.20	0.113	12.31	30.00
802.11ac(VHT40)					
151	5755	11.35	0.205	11.56	30.00
159	5795	11.73	0.205	11.94	30.00
802.11ac(VHT80)					
155	5775	8.26	0.475	8.73	30.00



5210MHz



5290MHz



5775MHz



Duty cycle

Band1				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.405	1.435	97.91%	0.092
n20	1.320	1.345	98.14%	0.081
n40	0.656	0.692	94.80%	0.232
ac20	1.325	1.360	97.43%	0.113
ac40	0.660	0.698	94.56%	0.243
ac80	0.329	0.369	89.16%	0.498
Band2				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.405	1.435	97.91%	0.092
n20	1.310	1.340	97.76%	0.098
n40	0.654	0.690	94.78%	0.233
ac20	1.325	1.355	97.79%	0.097
ac40	0.660	0.692	95.38%	0.206
ac80	0.330	0.367	89.92%	0.462
Band4				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	1.405	1.435	97.91%	0.092
n20	1.310	1.340	97.76%	0.098
n40	0.656	0.692	94.80%	0.232
ac20	1.325	1.360	97.43%	0.113
ac40	0.662	0.694	95.39%	0.205
ac80	0.329	0.367	89.65%	0.475



Band 1-a20



Band 1-n20



Band 1-n40



Band 1-ac20




Band 1-ac40



Band 1-ac80



Band 2-a20



Band 2-n20




Band 2-n40



Band 2-ac20




Band 2-ac40



Band 2-ac80



Band 4-a20



Band 4-n20



Band 4-n40



Band 4-ac20



Band 4-ac40



Band 4-ac80



7. AUTOMATICALLY DISCONTINUE TRANSMISSION

7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission





8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.



**APPENDIX - PHOTOS OF TEST SETUP**

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※

