



849 NW STATE ROAD 45  
NEW BERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP:// WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

<b>APPLICANT</b>	AUDIO-TECHNICA CORPORATION
	2-46-1 Nishi-Naruse Machida Tokyo 194-8666 JAPAN
<b>FCC ID</b>	JFZDSR7BT
<b>IC</b>	1752B-DSR7BT
<b>MODEL NUMBER</b>	ATH-DSR7BT
<b>PRODUCT DESCRIPTION</b>	Bluetooth In-Ear Headphones
<b>STANDARD APPLIED</b>	CFR 47 Part 2.1091
<b>PREPARED BY</b>	

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

## GENERAL REMARKS

### Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**



**Authorized Signatory Name:**

Cory Leverett

Engineering Project Manager

**Date: 12/ 19/ 2016**

## RF Exposure Requirements

### General information

Device type: Bluetooth In-Ear Headphones

KDB 447498 D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

**100 MHz to 6 GHz at separation distance less than or equal to 50 mm**

#### SAR Test Exclusion Calculator for Portable Devices

**Insert values in yellow highlighted boxes to determine SAR Exclusion**

Max Power **4.9** mW

Min Separation **5** mm

Frequency **2.48** GHz

**When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.**

**Answer 1.5 Must be less than or equal to 3.0 for SAR Exclusion**

**KDB 388624 D02 Permit But Ask List v15, Item II. A. 5.**

**PBA is required if:**

**General Population:** The Answer is equal to or greater than 24 (8x threshold)

**Controlled Use:** The Answer is equal to or greater than 60 (20x threshold)

**and**, when published RF exposure KDB procedures are not established for SAR testing or when SAR

**Please also note the following:** [FCC KDB quote] These test exclusion conditions are based on source-based time-averaged

Applicant: AUDIO-TECHNICA CORPORATION

FCC ID: JFZDSR7BT

Report: 2318AUT16RF EXP MPE RPT\_Rev1