

TEST REPORT

Product Name : Wireless Stereo earphone
Brand Mark : YunGuo
Model No. : YGM1
FCC ID : 2A8GH-YGM1A
Report Number : BLA-EMC-202208-A7502
Date of Sample Receipt : 2022/8/25
Date of Test : 2022/8/25 to 2022/8/29
Date of Issue : 2022/8/29
Test Standard : 47 CFR Part 15, Part1.1307
47 CFR Part 15, Part2.1093
KDB447498D04 General RF Exposure
Guidance v01
Test Result : Pass

Prepared for:

Dongguan Liesheng Electronic Co., Ltd.
Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District,
Dongguan City, Guangdong, China.

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: *Charlie*

Review by: *Sueels*

Approved by: *Blue Zhong*

Date:

2022/9/01



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/9/1	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY.....	4
2	GENERAL INFORMATION.....	5
3	GENERAL DESCRIPTION OF E.U.T.....	5
4	LABORATORY LOCATION.....	6
5	RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1	RF EXPOSURE COMPLIANCE REQUIREMENT	7
	<i>Standard Requirement</i>	7
	<i>Limits</i>	7

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	PASS

2 GENERAL INFORMATION

Applicant	Yunguo (Shenzhen) Technology Co., LTD
Address	502, 5th floor, building a, No. 3, North District, shangxue Science Park, Xinxue community, Bantian street, Longgang District, Shenzhen City, Guangdong Province
Manufacturer	Shenzhen StrongSine Technology Co., LTD
Address	Room A404,1,Block AB, Building 1, Jinshun Industrial Park, 29 Anliang Community, Yuanshan Street, Longgang District, Shenzhen, China
Factory	Shenzhen StrongSine Technology Co., LTD
Address	Room A404,1,Block AB, Building 1, Jinshun Industrial Park, 29 Anliang Community, Yuanshan Street, Longgang District, Shenzhen, China
Product Name	Wireless Stereo earphone
Test Model No.	YGM1

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.1
Software Version	V1.0
BR/EDR	
Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	2.67 dBi

4 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 RF EXPOSURE COMPLIANCE REQUIREMENT

Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$EIRP = p_t \times g_t = (E \times d)^2 / 30$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((\text{dBuV/m})/20)/106$

d = measurement distance in meters (m) --- 3m

$$\text{So } p_t = (E \times d)^2 / 30 \times g_t$$

$$\text{Ant gain} = 2.67\text{dBi}$$

$$\text{Max Output power} = 3.676\text{dBm @2402MHz}$$

$$\text{ERP} = 3.676\text{dBm} + 2.67\text{dBi} - 2.15 = 4.196\text{dBm}$$

So

worse case:

$$10^{0.4196} = 2.63 \text{ mW} < 2.72 \text{ mW}$$

Then SAR evaluation is not required

-----END OF REPORT-----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.