



Certificate #4312.01

TEST REPORT

Product Name: Compact Hotel Phone
Trade Mark: GRANDSTREAM
Model No. / HVIN: GHP611W
Add. Model No. / HVIN: GHP610W
Report Number: 220716463EMC-1
Test Standards: FCC 47 CFR Part 15 Subpart B
ICES-003 Issue 7
FCC ID: YZZGHP61XW
Test Result: PASS
Date of Issue: September 23, 2022

Prepared for:

Grandstream Networks, Inc.
126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
technology park, Longhua district, Shenzhen, China

TEL: +86-755-2823 0888**FAX: +86-755-2823 0886**

Prepared by:

Kieron Luo
Project Engineer

Reviewed by:

Henry Lu
Team Leader

Approved by:

Kevin Liang
Assistant Manager

Date: September 23, 2022

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Version

Version No.	Date	Description
V1.0	September 23, 2022	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES.....	4
1.3 DESCRIPTION OF SUPPORT UNITS	5
1.4 TEST LOCATION.....	5
1.5 TEST FACILITY.....	5
1.6 DEVIATION FROM STANDARDS	6
1.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.9 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	8
4. TEST CONFIGURATION	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING.....	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE.....	9
4.2 TEST MODES.....	9
4.3 TEST SETUP	10
4.3.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP	11
4.4 SYSTEM TEST CONFIGURATION.....	11
5. REFERENCE DOCUMENTS FOR TESTING.....	12
6. EMC REQUIREMENTS SPECIFICATION	12
6.1 RADIATED EMISSION.....	12
6.2 CONDUCTED EMISSION	26
APPENDIX 1 PHOTOS OF TEST SETUP.....	33
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS.....	33

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Grandstream Networks, Inc.
Address of Applicant:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA
Manufacturer:	Grandstream Networks, Inc.
Address of Manufacturer:	126 Brookline Ave., 3rd Floor Boston, MA 02215, USA

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Compact Hotel Phone
Model No. / HVIN:	GHP611W
Add. Model No. / HVIN:	GHP610W
Trade Mark:	GRANDSTREAM
DUT Stage:	Identical Prototype
Rated Voltage:	☒ 100-240V~50/60Hz
Classification of digital devices:	Class B
Highest Internal Frequency:	5825 MHz
Sample Received Date:	July 13, 2022
Sample Tested Date:	July 27, 2022 to July 31, 2022

Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance color of others models listed in the report is different from main-test model GHP611W, but the circuit and the electronic construction do not change, declared by the manufacturer.

Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

Adapter(1)	
Model No.:	F06US1200050A
Input:	100-240 V~50/60 Hz 0.2 A max
Output:	12 V $\Rightarrow$ 0.5 A
DC Cable:	1.8 Meter, Unshielded without ferrite

Adapter(2)	
Model No.:	NBS05B120050VU
Input:	100-240 V~50/60 Hz 0.2 A
Output:	12.0 V $\Rightarrow$ 0.5 A
DC Cable:	1.8 Meter, Unshielded without ferrite

Adapter(3)	
Model No.:	GQ06-120050-ZU
Input:	100-240 V~50/60 Hz 0.3 A Max
Output:	12.0 V $\Rightarrow$ 0.5 A
DC Cable:	1.8 Meter, Unshielded without ferrite

Cable	
Connector:	Phone Cord
Cable Type:	Unshielded without ferrite
Length:	3.0 Meter

Others
Charging base

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	Lenovo B40-80	MP12NEQ6	UnionTrust
IP Phone	GRANDSTREAM	GRP2614	N/A	Applicant
Wireless Router	ASUA	RT-AC2200	2019AJ4850	UnionTrust
POE	Social	N/A	N/A	UnionTrust
Power over Ethernet Injector	Cisco	MA-INJ-4	QS-6593-01N A02	UnionTrust

Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Ethernet Cable	RJ45	1.5 Unshielded without ferrite	UnionTrust
2	Ethernet Cable	RJ45	2.0 Unshielded without ferrite	UnionTrust
3	Ethernet Cable	RJ45	5.0 Unshielded without ferrite	UnionTrust

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.6 dB
5	Radiated emission 1GHz-18GHz	± 4.4 dB
6	Radiated emission 18GHz-26GHz	± 4.6 dB
7	Radiated emission 26GHz-40GHz	± 4.6 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart B Test Cases			
Test Item	Test Requirement	Test Method	Result
Conducted Emission	FCC 47 CFR Part 15.107 ICES-003 Issue 7 Section 3.2.1	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109 ICES-003 Issue 7 Section 3.2.2	ANSI C63.4-2014	PASS



3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3m SAC	ETS-LINDGREN	3m	Euroshiedpn-CT001270-1317	Jan. 22, 2021	Jan. 21, 2024
☒	Receiver	R&S	ESIB26	100114	Nov. 05, 2021	Nov. 04, 2022
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 11, 2021	Nov. 10, 2023
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 11, 2021	Nov. 10, 2023
☒	Preamplifier	HP	8447F	2805A02960	Nov. 05, 2021	Nov. 04, 2022
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	Apr. 30, 2021	Apr. 29, 2023
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	Nov. 06, 2021	Nov. 05, 2022
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Nov. 14, 2020	Nov. 13, 2023
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	Nov. 17, 2020	Nov. 16, 2022
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Nov. 05, 2021	Nov. 04, 2022
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 05, 2021	Nov. 04, 2022
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 05, 2021	Nov. 04, 2022
☒	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 05, 2021	Nov. 04, 2022
☒	Test Software	Audix	e3	Software Version: 9.160323		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NV/NT	+15 to +35	Powered by DC 12V/0.5A	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test sample

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Conducted Emission	23.4	42	101.1	S20220713183-ZJA02/5	Davin Zhang
Radiated Emission	25.1	52	100.02		Andy Lin

4.2 TEST MODES

Test Item	EMI Test Modes
Radiated Emission	Test Mode 1: AC120V/60Hz (Adaptor1) + Charging base + Voice (Earphone + Microphone running) Test Mode 2: AC120V/60Hz (Adaptor1) + Charging base + Hands free (Speaker running) Test Mode 3: AC120V/60Hz (Adaptor1) + Charging base + WLAN Link + Worse from mode 1~2(Mode2) Test Mode 4: AC240V/50Hz (Adaptor1) + Worse from mode 1~3 Test Mode 5: Worse from mode 1~4 (Adaptor2)(Mode3) Test Mode 6: Worse from mode 1~4 (Adaptor3)(Mode3)
Conducted Emission	Test Mode 1: AC120V/60Hz (Adaptor1) + Charging base + Voice (Earphone + Microphone running) Test Mode 2: AC120V/60Hz (Adaptor1) + Charging base + Hands free (Speaker running) Test Mode 3: AC120V/60Hz (Adaptor1) + Charging base + WLAN Link + Worse from mode 1~2 Test Mode 4: AC240V/50Hz (Adaptor1) + Worse from mode 1~3 Test Mode 5: Worse from mode 1~4 (Adaptor2)(Mode2) Test Mode 6: Worse from mode 1~4 (Adaptor3)(Mode2)
Remark: The above test modes in boldface were the worst cases.	

4.3 TEST SETUP

4.3.1 For Radiated Emissions test setup

Figure 1. 30MHz to 1GHz






Figure 2. Above 1GHz



4.3.2 For Conducted Emissions test setup

Figure 3. Conducted Emissions setup



4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ICES-003 Issue 7	Information Technology Equipment (Including Digital Apparatus)
3	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
5	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109
ICES-003 Issue 7 Clause 3.2.2

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
$30 \leq f \leq 1\,000$	Quasi Peak	120 kHz	300 kHz
$f \geq 1000$	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

FCC 47 CFR Part 15 Subpart B

Frequency (MHz)	limits at 3m (dBμV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 960	46.0		
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

ICES-003 Issue 7

Frequency (MHz)	limits at 3m (dBμV/m)		
	QP Detector	PK Detector	AV Detector
30 – 88	40.0	--	--
88 – 216	43.5	--	--
216 – 230	46.0		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

230 – 960	47.0	--	--
960 – 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.3.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:
 - 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
 - 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
 - 3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.
2. Above 1GHz test procedure as below:
 - 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
 - 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
 - 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.

Test Result: Pass


The measurement data as follows:

The measurement data for FCC 47 CFR Part 15 Subpart B as follows:

Below 1GHz(Quasi Peak):

Test Mode3

Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	90.420	42.76	-16.14	26.62	43.50	-16.88	QP
2	124.925	44.57	-15.82	28.75	43.50	-14.75	QP
3	170.189	42.15	-11.45	30.70	43.50	-12.80	QP
4	240.144	37.55	-9.09	28.46	46.00	-17.54	QP
5	384.545	37.33	-4.81	32.52	46.00	-13.48	QP
6	887.398	28.17	4.12	32.29	46.00	-13.71	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



Below 1GHz(Quasi Peak):
Test Mode5
Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	54.135	42.52	-16.71	25.81	40.00	-14.19	QP
2	143.776	47.81	-15.68	32.13	43.50	-11.37	QP
3	175.040	43.00	-10.68	32.32	43.50	-11.18	QP
4	384.545	37.33	-4.81	32.52	46.00	-13.48	QP
5	433.340	38.79	-4.34	34.45	46.00	-11.55	QP
6	887.398	29.22	4.12	33.34	46.00	-12.66	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



Below 1GHz(Quasi Peak):
Test Mode6
Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	48.378	39.00	-13.61	25.39	40.00	-14.61	QP
2	104.798	43.51	-15.71	27.80	43.50	-15.70	QP
3	145.811	44.52	-15.62	28.90	43.50	-14.60	QP
4	336.482	40.54	-5.68	34.86	46.00	-11.14	QP
5	590.351	33.69	-1.08	32.61	46.00	-13.39	QP
6	887.398	32.54	4.12	36.66	46.00	-9.34	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Vertical



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	33.101	36.24	-4.83	31.41	40.00	-8.59	QP
2	45.733	45.14	-11.70	33.44	40.00	-6.56	QP
3	85.477	50.62	-16.69	33.93	40.00	-6.07	QP
4	115.632	45.15	-15.74	29.41	43.50	-14.09	QP
5	288.284	32.41	-6.93	25.48	46.00	-20.52	QP
6	590.351	32.33	-1.08	31.25	46.00	-14.75	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Above 1GHz(Peak & Average)
Test Mode3
Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1078.208	45.21	-13.36	31.85	74.00	-42.15	Peak
2	4379.978	41.54	-2.61	38.93	74.00	-35.07	Peak
3	5241.490	40.45	-1.27	39.18	74.00	-34.82	Peak
4	7637.782	39.10	2.07	41.17	74.00	-32.83	Peak
5	10811.890	39.47	7.02	46.49	74.00	-27.51	Peak
6	16217.810	38.20	12.06	50.26	74.00	-23.74	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-EMC-ICES003-V1.2




Above 1GHz(Peak & Average)
Test Mode5
Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1053.514	46.14	-13.42	32.72	74.00	-41.28	Peak
2	3040.819	42.90	-6.56	36.34	74.00	-37.66	Peak
3	3969.238	42.44	-3.21	39.23	74.00	-34.77	Peak
4	7682.150	39.60	2.12	41.72	74.00	-32.28	Peak
5	14868.200	35.86	11.85	47.71	74.00	-26.29	Peak
6	17385.170	35.92	13.33	49.25	74.00	-24.75	Peak



Above 1GHz(Peak & Average)
Test Mode6
Horizontal



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	1053.514	45.90	-13.42	32.48	74.00	-41.52	Peak
2	3855.931	42.20	-3.61	38.59	74.00	-35.41	Peak
3	5618.776	40.33	-0.13	40.20	74.00	-33.80	Peak
4	9685.139	38.68	5.57	44.25	74.00	-29.75	Peak
5	11324.690	39.36	7.21	46.57	74.00	-27.43	Peak
6	16791.350	35.95	12.61	48.56	74.00	-25.44	Peak

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2



Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.
5. For Radiated Emission above 18GHz, there was not any unwanted emission detected.
6. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.
7. The limit of ICES-003 in the 230MHz to 960MHz band is higher than that of FCC Part 15B, so the radiation emission test data conform to the limit of ICES-003.

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107
ICES-003 Issue 7 Section 3.2.1

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:

- 1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- 2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.


Test Result: Pass

The measurement data as follows:

Quasi Peak and Average:


Test Mode2

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.310	15.56	10.13	25.69	49.97	-24.28	Average
2	0.310	28.56	10.13	38.69	59.97	-21.28	QP
3	0.534	27.87	10.16	38.03	46.00	-7.97	Average
4	0.534	37.87	10.16	48.03	56.00	-7.97	QP
5	1.022	22.59	10.22	32.81	46.00	-13.19	Average
6	1.022	34.59	10.22	44.81	56.00	-11.19	QP
7	1.766	20.49	10.23	30.72	46.00	-15.28	Average
8	1.766	32.49	10.23	42.72	56.00	-13.28	QP
9	4.077	17.14	10.29	27.43	46.00	-18.57	Average
10	4.077	30.14	10.29	40.43	56.00	-15.57	QP
11	9.452	27.42	10.56	37.98	50.00	-12.02	Average
12	9.452	40.42	10.56	50.98	60.00	-9.02	QP


Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.318	15.66	10.11	25.77	49.76	-23.99	Average
2	0.318	28.66	10.11	38.77	59.76	-20.99	QP
3	0.534	28.97	10.13	39.10	46.00	-6.90	Average
4	0.534	40.97	10.13	51.10	56.00	-4.90	QP
5	0.918	22.89	10.15	33.04	46.00	-12.96	Average
6	0.918	33.89	10.15	44.04	56.00	-11.96	QP
7	1.942	18.46	10.18	28.64	46.00	-17.36	Average
8	1.942	32.46	10.18	42.64	56.00	-13.36	QP
9	5.565	19.87	10.39	30.26	50.00	-19.74	Average
10	5.565	32.87	10.39	43.26	60.00	-16.74	QP
11	9.628	27.62	10.59	38.21	50.00	-11.79	Average
12	9.628	43.62	10.59	54.21	60.00	-5.79	QP

Quasi Peak and Average: Test Mode5

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.166	26.79	10.13	36.92	55.16	-18.24	Average
2	0.166	37.79	10.13	47.92	65.16	-17.24	QP
3	0.470	29.35	10.15	39.50	46.52	-7.02	Average
4	0.470	38.35	10.15	48.50	56.52	-8.02	QP
5	1.286	22.89	10.22	33.11	46.00	-12.89	Average
6	1.286	31.89	10.22	42.11	56.00	-13.89	QP
7	2.222	19.04	10.24	29.28	46.00	-16.72	Average
8	2.222	30.04	10.24	40.28	56.00	-15.72	QP
9	6.141	21.38	10.40	31.78	50.00	-18.22	Average
10	6.141	31.38	10.40	41.78	60.00	-18.22	QP
11	14.891	23.93	10.88	34.81	50.00	-15.19	Average
12	14.891	36.93	10.88	47.81	60.00	-12.19	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.150	19.38	10.11	29.49	56.00	-26.51	Average
2	0.150	37.38	10.11	47.49	66.00	-18.51	QP
3	0.470	21.60	10.13	31.73	46.52	-14.79	Average
4	0.470	35.60	10.13	45.73	56.52	-10.79	QP
5	1.070	15.56	10.15	25.71	46.00	-20.29	Average
6	1.070	30.56	10.15	40.71	56.00	-15.29	QP
7	2.566	13.82	10.23	24.05	46.00	-21.95	Average
8	2.566	27.82	10.23	38.05	56.00	-17.95	QP
9	5.645	15.79	10.40	26.19	50.00	-23.81	Average
10	5.645	28.79	10.40	39.19	60.00	-20.81	QP
11	15.651	20.01	10.84	30.85	50.00	-19.15	Average
12	15.651	33.01	10.84	43.85	60.00	-16.15	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Quasi Peak and Average: Test Mode6

Live Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.158	18.18	10.13	28.31	55.57	-27.26	Average
2	0.158	33.18	10.13	43.31	65.57	-22.26	QP
3	0.446	18.65	10.14	28.79	46.95	-18.16	Average
4	0.446	29.65	10.14	39.79	56.95	-17.16	QP
5	0.870	17.27	10.20	27.47	46.00	-18.53	Average
6	0.870	28.27	10.20	38.47	56.00	-17.53	QP
7	1.350	12.53	10.22	22.75	46.00	-23.25	Average
8	1.350	23.53	10.22	33.75	56.00	-22.25	QP
9	4.373	22.74	10.30	33.04	46.00	-12.96	Average
10	4.373	32.74	10.30	43.04	56.00	-12.96	QP
11	6.997	27.67	10.46	38.13	50.00	-11.87	Average
12	6.997	37.67	10.46	48.13	60.00	-11.87	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

Neutral Line



No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.158	17.54	10.12	27.66	55.57	-27.91	Average
2	0.158	34.54	10.12	44.66	65.57	-20.91	QP
3	0.422	16.08	10.12	26.20	47.41	-21.21	Average
4	0.422	31.08	10.12	41.20	57.41	-16.21	QP
5	1.094	12.94	10.15	23.09	46.00	-22.91	Average
6	1.094	23.94	10.15	34.09	56.00	-21.91	QP
7	3.997	18.80	10.31	29.11	46.00	-16.89	Average
8	3.997	29.80	10.31	40.11	56.00	-15.89	QP
9	6.757	21.74	10.46	32.20	50.00	-17.80	Average
10	6.757	34.74	10.46	45.20	60.00	-14.80	QP
11	14.851	20.48	10.83	31.31	50.00	-18.69	Average
12	14.851	34.48	10.83	45.31	60.00	-14.69	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-ICES003-V1.2

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

***** End of Report *****

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
