

**RF Exposure**

HMD19110003  
Test Requirement: FCC 47CFR 15.247(i)  
Test Date: 2019-11-01  
Mode of Operation: Tx mode

**Test Method:**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.  
This evaluation used FCC 47CFR 2.1091 to perform.

**Test Results:**

The EUT complied with the requirement(s) of this section.  
EUT meets the requirements of these sections as proven through MPE calculation  
The MPE calculation for EUT @ 20cm  
Based on the highest P =1.367 mW

$$\begin{aligned} P_d &= PG / 4\pi R^2 = (1.367 \times 1.995) / 12.566 \times (20)^2 \\ &= (2.727) / 12.566 \times 400 = 2.727 / 5026.4 \\ &= 0.000543 \text{ mW/cm}^2 \end{aligned}$$

where:

- \*Pd = power density in mW/cm<sup>2</sup>
- \* G = Antenna numeric gain (1.995); Log G = g/10 ( g = 3dBi ).
- \* P = Conducted RF power to antenna (1.367 mW).
- \* R = Minimum allowable distance.(20 cm)

- \*The power density Pd = 0.000543 mW/cm<sup>2</sup> is less than 1 mW/cm<sup>2</sup> (listed MPE limit)
- \*The SAR evaluation is not needed ( this is a desk top device, R> 20 cm )
- \* The EUT( antenna ) must be 0.2 meters away from the General Population.