

# FCC SAR Exclusion Report

Report No.	: SA190906C18
Applicant	: Sennheiser electronic GmbH & Co. KG
Address	: Am Labor 1, D-30900 Wedemark, Germany
Product	: MOMENTUM True Wireless 2
Brand	: SENNHEISER
FCC ID	: DMOM3IETW2L
Model No.	: M3IETW2 L
Standards	: FCC 47 CFR Part 2 (2.1093), IEEE C95.1:1992, IEEE Std 1528:2013 KDB 865664 D01 v01r04, KDB 865664 D02 v01r02, KDB 447498 D01 v06
Sample Received Date	: Sep. 06, 2019
Date of Evaluation	: Oct. 15, 2019
Lab Address	: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location	: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City, Taiwan

CERTIFICATION: The above equipment have been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

Approved By :

Shelly Hunch Shelly Hsueh / Specialist

Gordon Lin / Manager



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report Format Version 5.0.0 Report No. : SA190906C18

## FCC SAR Exclusion Report



## **Table of Contents**

Rel	ease C	ontrol Record	3
		nary of Maximum SAR Value	
		iption of Equipment Under Test	
		Measurement Evaluation	
		Maximum Output Power	
	•••	3.1.1 Maximum Target Conducted Power	
		3.1.2 Measured Conducted Power Result	
		3.1.3 Time-Avg. Power calculation.	
	3.2	SAR Testing Exclusions	7
		nation on the Testing Laboratories	

Appendix A. Photographs of EUT





## **Release Control Record**

Reason for Change	Date Issued
Initial release	Oct. 25, 2019



## 1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported SAR <sub>1g</sub> (W/kg)
DSS	Bluetooth	Not Required

Note:

 The SAR limit (Head & Body: SAR<sub>1g</sub> 1.6 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.



## 2. Description of Equipment Under Test

EUT Type	MOMENTUM True Wireless 2		
Brand Name	SENNHEISER		
FCC ID	DMOM3IETW2L		
Model Name	M3IETW2 L		
Tx Frequency Bands	Bluetooth : 2402 ~ 2480		
(Unit: MHz)	Diueluulii . 2402 ~ 2400		
Uplink Modulations	Bluetooth : GFSK, π/4-DQPSK, 8-DPSK		
Maximum Tune-up Conducted Power	Please refer to section 3.1 of this report		
(Unit: dBm)	רופמטב ובובו נט טבטווטון ט.ד טו נוווט ובאטונ		
Antenna Type	Monopole antenna		
EUT Stage	Engineering Sample		

#### Note:

- 1. The EUT has two samples, white and black color. The samples are electrically identical, only different in appearance.
- 2. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.



### 3. SAR Measurement Evaluation

#### 3.1 Maximum Output Power

#### 3.1.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

#### <Bluetooth>

Mode	Channel	Frequency (MHz)	Tune-up Power	
	0	2402	9	
Bluetooth BR	39	2441	9	
	78	2480	9	
	0	2402	9.5	
Bluetooth LE	19	2440	9.5	
	39	2480	9.5	

#### 3.1.2 Measured Conducted Power Result

The measuring conducted power (Unit: dBm) are shown as below.

#### <Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power	
	0	2402	8.17	
Bluetooth BR	39	2441	8.35	
	78	2480	8.43	
	0	2402	9.16	
Bluetooth LE	19	2440	9.21	
	39	2480	9.10	

#### 3.1.3 Time-Avg. Power calculation.

The calculation of time-avg. power (Unit: dBm) Including duty cycle.

#### <The calculated average power with duty cycle>

Mode	Max Tune-up Power Duty cycle (%)		Calculated Time-Avg. Power	
BT BR	9.0	46.51	5.68	
BT LE	9.5	41.37	5.67	

### FCC SAR Exclusion Report



#### 3.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance <= 50 mm

$$\frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[ \text{(Threshold at 50 mm in Step 1)} + \text{(Test Separation Distance} - 50 mm) \times \left( \frac{f_{(MHz)}}{150} \right) \right]_{(mW)}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

[(Threshold at 50 mm in Step 1) + (Test Separation Distance -50 mm) × 10]<sub>(mW)</sub>

	Time-Avg. Time-Avg.		Left Earbud (C)		Left Earbud (D)			
Mode	Power (dBm)	Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
BT BR	5.68	4	8.325	0.76	No	9.348	0.67	No
BT LE	5.67	4	8.325	0.76	No	9.348	0.67	No

#### Note:

- 1. When separation distance <= 50 mm and the calculated result shown in above table is <= 3.0, the SAR testing exclusion is applied.
- 2. When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

#### Summary:

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.



### 4. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

#### Taiwan Huaya Lab:

Add: No. 19, Huaya 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan Tel: +886-(0)3-318-3232 Fax: +886-(0)3-211-5834

#### Taiwan Linkou Lab:

Add: No. 47-2, Baodoucuokeng, Linkou Dist., New Taipei City 244, Taiwan Tel: +886-(0)2-2605-2180 Fax: +886-(0)2-2605-2943

#### Taiwan Hsinchu Lab1:

Add: E-2, No. 1, Lixing 1st Rd., East Dist., Hsinchu City 300, Taiwan Tel: +886-(0)3-666-8565 Fax: +886-(0)3-666-8323

#### Taiwan Hsinchu Lab2:

Add: No. 49, Ln. 206, Wende Rd., Qionglin Township, Hsinchu County 307, Taiwan Tel: +886-(0)3-512-0595 Fax: +886-(0)3-512-0568

#### Taiwan Xindian Lab:

Add: B2F., No. 215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan Tel: +886-(0)2-8914-5882 Fax: +886-(0)2-8914-5840

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a> Web Site: <a href="https://ee.bureauveritas.com.tw/BVInternet/Default">https://ee.bureauveritas.com</a>

The road map of all our labs can be found in our web site also.

---END----



Appendix A. Photographs of EUT