

CERTIFICATE OF COMPLIANCE **SAR EVALUATION**

Test Lab:

CELLTECH RESEARCH INC.
Testing and Engineering Lab
1955 Moss Court
Kelowna, B.C.
Canada V1Y 9L3
Phone: 250 - 860-3130
Fax: 250 - 860-3110
Toll Free: 1-877-545-6287
e-mail: info@celltechlabs.com
web site: www.celltechlabs.com

Applicant Information:


TOPAZ3, LLC
10828 NW Air World Drive,
Kansas City, Missouri 64153-1238

FCC ID:	O7KPL450A
Model(s):	PL2445
EUT Type:	Portable UHF PTT Radio Transceiver
Modulation:	FM (UHF Band)
Tx Frequency Range:	450.0125 - 489.9875 MHz
Max. Power Tested:	2.16 Watts (Conducted)
No. of Channels:	4
FCC Rule Part(s):	2.1093; ET Docket 96-326

This wireless portable device has been shown to be compliant for localized Specific Absorption Rate (SAR) for controlled environment/occupational exposure limits specified in ANSI/IEEE Std. C95.1-1992 and has been tested in accordance with the measurement procedures specified in ANSI/IEEE Std. C95.3-1999.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Celltech Research Inc. certifies that no party to this application has been denied FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).



Shawn McMillen
General Manager
Celltech Research Inc.



TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
2.0	DESCRIPTION OF EUT.....	1
3.0	SAR MEASUREMENT SYSTEM	2
4.0	MEASUREMENT SUMMARY.....	3-5
5.0	DETAILS OF SAR EVALUATION.....	6
6.0	EVALUATION PROCEDURES.....	6
7.0	SAR LIMITS.....	7
8.0	SYSTEM VALIDATION.....	7
9.0	SIMULATED EQUIVALENT TISSUES.....	8
10.0	TISSUE PARAMETERS.....	8
11.0	SYSTEM SPECIFICATIONS.....	9
12.0	TEST EQUIPMENT LIST.....	10
13.0	MEASUREMENT UNCERTAINTIES.....	11
14.0	REFERENCES.....	12
	APPENDIX A - SAR MEASUREMENT DATA.....	13
	APPENDIX B - DIPOLE VALIDATION.....	14
	APPENDIX C - PROBE CALIBRATION.....	15
	APPENDIX D - SAR TEST SETUP PHOTOGRAPHS.....	16
	APPENDIX E - EUT PHOTOGRAPHS.....	17

1.0 INTRODUCTION

This measurement report shows compliance of the TOPAZ3 PL2445 Portable UHF PTT Radio Transceiver FCC ID: O7KPL450A with the regulations and procedures specified in FCC Part 2.1093, ET Docket 96-326 Rules (controlled exposure) for mobile and portable devices. The test procedures, as described in American National Standards Institute C95.1-1992 (1), FCC OET Bulletin 65-1997 were employed. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

2.0 DESCRIPTION of Equipment Under Test (EUT)

Rule Part(s)	FCC 2.1093; ET Docket 96.326	Modulation	FM (UHF Band)
EUT Type	Portable UHF PTT Radio Transceiver	Tx Frequency Range (MHz)	450.0125 - 489.9875
Model No.(s)	PL2445	Max. RF Output Power Tested	2.16 Watts (Conducted)
Serial No.	Pre-production	Power Supply	7.2V NiMH Battery
Antenna Type	Whip	Antenna Length	153 mm



Front of EUT



Right Side of EUT



Left Side of EUT



Back of EUT



EUT with Holster

3.0 SAR MEASUREMENT SYSTEM

Celltech Research SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the generic twin phantom containing brain or muscle equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



DASY3 SAR Measurement System

4.0 MEASUREMENT SUMMARY

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the EUT are reported in Appendix A.

Face-Held SAR Measurements

Frequency (MHz)	Chan.	Mode	Conducted Power Tested (Watts)	Antenna Position	Separation Distance (cm)	SAR (w/kg)	
						100% Duty Cycle	50% Duty Cycle
450.0125	Low	Unmod.	2.06	Fixed	4.0	0.913	0.4565
470.0125	Mid	Unmod.	2.16	Fixed	4.0	0.939	0.4695
489.9875	High	Unmod.	2.01	Fixed	4.0	0.876	0.438
Mixture Type: Brain Dielectric Constant: 48.9 Conductivity: 0.61			ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Controlled Exposure/Occupational BRAIN: 8.0 W/kg (averaged over 1 gram)				

Notes:

1. The SAR values found were below the maximum limit of 8.0 w/kg (controlled exposure).
2. The highest SAR level found was 0.4695 w/kg (50% duty cycle).



Face SAR Test Setup

MEASUREMENT SUMMARY (CONT.)

Body-Worn SAR Measurements with Metal Belt Clip

Frequency (MHz)	Chan.	Mode	Conducted Power Tested (Watts)	Antenna Position	Belt-Clip Separation Distance (cm)	SAR (w/kg)	
						100% Duty Cycle	50% Duty Cycle
450.0125	Low	Unmod.	2.06	Fixed	1.0	6.73	3.365
470.0125	Mid	Unmod.	2.16	Fixed	1.0	6.44	3.22
489.9875	High	Unmod.	2.01	Fixed	1.0	5.29	2.645
Mixture Type: Muscle Dielectric Constant: 57.5 Conductivity: 0.84			ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Controlled Exposure/Occupational BODY: 8.0 W/kg (averaged over 1 gram)				

Notes:

1. The SAR values found were below the maximum limit of 8.0 w/kg (controlled exposure).
2. The highest SAR level found was 3.365 w/kg (50% duty cycle).
3. The EUT was tested for body-worn SAR using the supplied metal belt-clip providing a 1.0cm separation distance between the back of the EUT and the outer surface of the planar phantom.



Body SAR Test Setup
with 1.0cm Belt-Clip

MEASUREMENT SUMMARY (CONT.)

Body-Worn SAR Measurements with Leather Belt-Holster

Frequency (MHz)	Chan.	Mode	Conducted Power Tested (Watts)	Antenna Position	Holster Separation Distance (cm)	SAR (w/kg)	
						100% Duty Cycle	50% Duty Cycle
450.0125	Low	Unmod.	2.06	Fixed	0.9	3.92	1.96
470.0125	Mid	Unmod.	2.16	Fixed	0.9	4.03	2.015
489.9875	High	Unmod.	2.01	Fixed	0.9	3.64	1.82
Mixture Type: Muscle Dielectric Constant: 57.5 Conductivity: 0.84			ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Controlled Exposure/Occupational BODY: 8.0 W/kg (averaged over 1 gram)				

Notes:

1. The SAR values found were below the maximum limit of 8.0 w/kg (controlled exposure).
2. The highest SAR value found was 2.015 w/kg (50% duty cycle).
3. The EUT was tested for body-worn SAR using the supplied leather belt-holster providing a 0.9cm separation distance between the back of the EUT and the outer surface of the planar phantom.



Body SAR Test Setup
with 0.9cm Belt-Holster

5.0 DETAILS OF SAR EVALUATION

The TOPAZ3 PL2445 Portable UHF PTT Radio Transceiver FCC ID: O7KPL450A was found to be compliant for localized Specific Absorption Rate (SAR) based on the following test provisions and conditions:

- 1) The EUT was tested in a face-held configuration with the front of the device placed parallel to and at a nominal distance of 40mm from the outer surface of the planar phantom.
- 2) The EUT was tested in a body-worn configuration with the attached metal belt-clip providing a 1.0cm separation distance between the back of the EUT and the outer surface of the planar phantom.
- 3) The EUT was tested in a body-worn configuration with the attached leather belt-holster providing a 0.9cm separation distance between the back of the EUT and the outer surface of the planar phantom.
- 4) The EUT was evaluated for SAR at maximum power and the unit was operated for an appropriate period prior to the evaluation in order to minimize drift. The conducted power levels were checked before and after each test.
- 5) The device was operated continuously in the transmit mode for the duration of the test.
- 6) The location of the maximum spatial SAR distribution (Hot Spot) was determined relative to the device and its antenna. This location was then related to a phantom that possesses human like facial attributes. The hot spot location of the EUT occurred around the mounting point of the antenna. In a normal operating position this places the hotspot just below the left eye.
- 7) The EUT was tested with a fully charged battery.

6.0 EVALUATION PROCEDURES

The Specific Absorption Rate (SAR) evaluation was performed in the following manner:

- a. (i) The evaluation was performed in an applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated at the center frequency of the band at maximum power. The ear position that produced the greatest SAR determined which side of the phantom would be used for the entire evaluation. FCC OET Bulletin 65 Supplement C dictated the test position of the device relative to the phantom.
(ii) For face-held and body-worn devices, or devices which can be operated within 20cm of the body, the planar section of the phantom was used.
- b. The SAR was determined by a pre-defined procedure within the DASY3 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 20mm x 20mm.
- c. For frequencies below 500MHz a 4x4x7 matrix was performed around the greatest spatial SAR distribution found during the area scan of the applicable exposed region. For frequencies above 500MHz a 5x5x7 matrix was performed. SAR values were then calculated using a 3-D spline interpolation algorithm and averaged over spatial volumes of 1 and 10 grams.
- d. If the EUT had any appreciable drift over the course of the evaluation, then the EUT was re-evaluated. Any unusual anomalies over the course of the test also warranted a re-evaluation.

7.0 SAR SAFETY LIMITS

EXPOSURE LIMITS	SAR (W/Kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.0	20.0

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

8.0 SYSTEM VALIDATION

Prior to the assessment, the system was verified in the planar region of the phantom. For devices operating below 1GHz, an 835MHz dipole or 900MHz was used, depending on the operating frequency of the EUT. For devices operating above 1GHz, an 1800MHz dipole was used. A forward power of 250mW was applied to the dipole and system was verified to a tolerance of $\pm 3\%$. Following the validation, the fluid remained or was changed depending on the particular part of the body being evaluated. The applicable verifications are as follows (see Appendix B for validation test plot):

Dipole Validation Kit	Target SAR 1g (w/kg)	Measured SAR 1g (w/kg)
D835V2	2.06	2.02

9.0 SIMULATED TISSUES

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The fluid was prepared according to standardized procedures and measured for dielectric parameters (permittivity and conductivity).

INGREDIENT	MIXTURE		
	835MHz Brain % (Validation)	450MHz Brain %	450MHz Muscle %
Water	40.1	42.0	50.0
Sugar	58.1	56.0	48.2
Salt	0.7	1.7	1.6
HEC	1.0	0.1	0.1
Bactericide	0.1	0.2	0.1

10.0 TISSUE PARAMETERS

The dielectric parameters of the fluids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer. The dielectric parameters of the fluid are as follows:

Equivalent Tissue (450MHz)	Dielectric Constant ϵ_r	Conductivity σ (mho/m)	ρ (Kg/m ³)
Brain (835MHz Validation)	44.2 \pm 5%	0.80 \pm 10%	1000
Brain	48.9 \pm 5%	0.61 \pm 10%	1000
Muscle	57.5 \pm 5%	0.84 \pm 10%	1000

11.0 ROBOT SYSTEM SPECIFICATIONS

Specifications

POSITIONER: Stäubli Unimation Corp. Robot Model: RX60L
Repeatability: 0.02 mm
No. of axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium III
Clock Speed: 450 MHz
Operating System: Windows NT
Data Card: DASY3 PC-Board

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic
Software: DASY3 software
Connecting Lines: Optical downlink for data and status info.
Optical uplink for commands and clock

PC Interface Card

Function: 24 bit (64 MHz) DSP for real time processing
Link to DAE3
16 bit A/D converter for surface detection system
serial link to robot
direct emergency stop output for robot

E-Field Probe

Model: ET3DV6
Serial No.: 1387
Construction: Triangular core fiber optic detection system
Frequency: 10 MHz to 6 GHz
Linearity: ± 0.2 dB (30 MHz to 3 GHz)

Phantom

Phantom: Generic Twin
Shell Material: Fiberglass
Thickness: 2.0 \pm 0.1 mm

12.0 TEST EQUIPMENT LIST

SAR MEASUREMENT SYSTEM		
<u>EQUIPMENT</u>	<u>SERIAL NO.</u>	<u>CALIBRATION DATE</u>
DASY3 System -Robot -ET3DV6 E-Field Probe -DAE -835MHz Validation Dipole -900MHz Validation Dipole -1800MHz Validation Dipole -Generic Twin Phantom V3.0	599396-01 1387 383 411 054 247 N/A	N/A Sept 1999 Sept 1999 Aug 1999 Aug 1999 Aug 1999 N/A
85070C Dielectric Probe Kit	N/A	N/A
Gigatronics 8652A Power Meter -Power Sensor 80701A -Power Sensor 80701A	1835272 1833535 1833542	Oct 1999 Oct 1999 Oct 1999
E4408B Spectrum Analyzer	US39240170	Nov 1999
8594E Spectrum Analyzer	3543A02721	Mar 2000
8753E Network Analyzer	US38433013	Nov 1999
8648D Signal Generator	3847A00611	N/A
5S1G4 Amplifier Research Power Amplifier	26235	N/A

13.0 MEASUREMENT UNCERTAINTIES

Uncertainty Description	Error	Distribution	Weight	Standard Deviation	Offset
Probe Uncertainty					
Axial isotropy	± 0.2 dB	U-Shaped	0.5	± 2.4 %	
Spherical isotropy	± 0.4 dB	U-Shaped	0.5	± 4.8 %	
Isotropy from gradient	± 0.5 dB	U-Shaped	0	\pm	
Spatial resolution	± 0.5 %	Normal	1	± 0.5 %	
Linearity error	± 0.2 dB	Rectangle	1	± 2.7 %	
Calibration error	± 3.3 %	Normal	1	± 3.3 %	
SAR Evaluation Uncertainty					
Data acquisition error	± 1 %	Rectangle	1	± 0.6 %	
ELF and RF disturbances	± 0.25 %	Normal	1	± 0.25 %	
Conductivity assessment	± 10 %	Rectangle	1	± 5.8 %	
Spatial Peak SAR Evaluation Uncertainty					
Extrapolated boundary effect	± 3 %	Normal	1	± 3 %	± 5 %
Probe positioning error	± 0.1 mm	Normal	1	± 1 %	
Integrated and cube orientation	± 3 %	Normal	1	± 3 %	
Cube Shape inaccuracies	± 2 %	Rectangle	1	± 1.2 %	
Device positioning	± 6 %	Normal	1	± 6 %	
Combined Uncertainties				± 11.7 %	± 5 %

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, the estimated measurement uncertainties in SAR are less than 15-25 %.

According to ANSI/IEEE C95.3, the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of ± 1 to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least ± 2 dB can be expected.

According to CENELEC, typical worst-case uncertainty of field measurements is ± 5 dB. For well-defined modulation characteristics the uncertainty can be reduced to ± 3 dB.

14.0 REFERENCES

- (1) ANSI, *ANSI/IEEE C95.1: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 Ghz*, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992;
- (2) Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C. 20554, 1997;
- (3) Thomas Schmid, Oliver Egger, and Neils Kuster, “Automated E-field scanning system for dosimetric assessments”, *IEEE Transaction on Microwave Theory and Techniques*, Vol. 44, pp. 105 – 113, January, 1996.
- (4) Niels Kuster, Ralph Kastle, and Thomas Schmid, “Dosimetric evaluation of mobile communications equipment with know precision”, *IEICE Transactions of Communications*, vol. E80-B, no. 5, pp. 645 – 652, May 1997.

APPENDIX A - SAR MEASUREMENT DATA

Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (90°,90°)

Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0

450MHz Brain: $\sigma = 0.61$ mho/m $\epsilon_r = 48.9$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;

Cube 4x4x7

SAR (1g): 0.913 mW/g, SAR (10g): 0.659 mW/g

Face-held SAR with 4.0cm Separation Distance

Portable UHF PTT Radio Transceiver


Topaz3 Model: PL2445

Unmodulated Carrier

Low Channel [450.0125 MHz]

Conducted Power: 2.06 Watts

Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (90°,90°)

Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0

450MHz Brain: $\sigma = 0.61$ mho/m $\epsilon_r = 48.9$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;

Cube 4x4x7

SAR (1g): 0.939 mW/g, SAR (10g): 0.722 mW/g

Face-held SAR with 4.0cm Separation Distance

Portable UHF PTT Radio Transceiver


Topaz3 Model: PL2445

Unmodulated Carrier

Mid Channel [470.0125 MHz]

Conducted Power: 2.16 Watts

Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (90°,90°)

Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0

450MHz Brain: $\sigma = 0.61$ mho/m $\epsilon_r = 48.9$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;

Cube 4x4x7

SAR (1g): 0.876 mW/g, SAR (10g): 0.672 mW/g

Face-held SAR with 4.0cm Separation Distance

Portable UHF PTT Radio Transceiver


Topaz3 Model: PL2445

Unmodulated Carrier

High Channel [489.9875 MHz]

Conducted Power: 2.01 Watts


Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (270°,270°)
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0
450MHz Muscle: $\sigma = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;
Cube 4x4x7
SAR (1g): 6.73 mW/g, SAR (10g): 4.34 mW/g


Body-worn SAR with 1.0cm Metal Belt-Clip
Portable UHF PTT Radio Transceiver
Topaz3 Model: PL2445
Unmodulated Carrier
Low Channel [450.0125 MHz]
Conducted Power: 2.06 Watts
Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (270°,270°)
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0
450MHz Muscle: $\sigma = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;
Cube 4x4x7
SAR (1g): 6.44 mW/g, SAR (10g): 4.14 mW/g


Body-worn SAR with 1.0cm Metal Belt-Clip
Portable UHF PTT Radio Transceiver
Topaz3 Model: PL2445
Unmodulated Carrier
Mid Channel [470.0125 MHz]
Conducted Power: 2.16 Watts
Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (270°,270°)
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0
450MHz Muscle: $\sigma = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;
Cube 4x4x7
SAR (1g): 5.29 mW/g, SAR (10g): 3.42 mW/g

Body-worn SAR with 1.0cm Metal Belt-Clip
Portable UHF PTT Radio Transceiver
Topaz3 Model: PL2445
Unmodulated Carrier
High Channel [489.9875 MHz]
Conducted Power: 2.01 Watts
Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (270°,270°)
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0
450MHz Muscle: $\sigma = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;

Cube 4x4x7

SAR (1g): 3.92 mW/g, SAR (10g): 2.80 mW/g

Body-worn SAR with 0.9cm Leather Belt-Holster

Portable UHF PTT Radio Transceiver


Topaz3 Model: PL2445

Unmodulated Carrier

Low Channel [450.0125 MHz]

Conducted Power: 2.06 Watts

Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (270°,270°)
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0
450MHz Muscle: $\sigma = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;

Cube 4x4x7

SAR (1g): 4.03 mW/g, SAR (10g): 2.92 mW/g

Body-worn SAR with 0.9cm Leather Belt-Holster

Portable UHF PTT Radio Transceiver


Topaz3 Model: PL2445

Unmodulated Carrier

Mid Channel [470.0125 MHz]

Conducted Power: 2.16 Watts

Date Tested: May 31, 2001



Topaz3 LLC FCC ID: O7KPL450A

Generic Twin Phantom; Flat Section; Position: (270°,270°)
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0
450MHz Muscle: $\sigma = 0.84$ mho/m $\epsilon_r = 57.5$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0;

Cube 4x4x7

SAR (1g): 3.64 mW/g, SAR (10g): 2.69 mW/g

Body-worn SAR with 0.9cm Leather Belt-Holster

Portable UHF PTT Radio Transceiver


Topaz3 Model: PL2445

Unmodulated Carrier

High Channel [489.9875 MHz]

Conducted Power: 2.01 Watts

Date Tested: May 31, 2001



APPENDIX B - DIPOLE VALIDATION

Dipole 835 MHz

Generic Twin Phantom; Flat Section; Position: (90°,90°);
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;


Brain 835 MHz: $\sigma = 0.80$ mho/m $\epsilon_r = 44.2$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 2.02 mW/g, SAR (10g): 1.34 mW/g

Validation Date: May 31, 2001



Validation Dipole D835V2 SN:411, $d = 15\text{mm}$

Frequency: 835 MHz; Antenna Input Power: 250 [mW]


Generic Twin Phantom; Flat Section; Grid Spacing: $D_x = 20.0$, $D_y = 20.0$, $D_z = 10.0$

Probe: ET3DV5 - SN1342/DAE3; ConvF(5.75,5.75,5.75); Brain 835 MHz: $\sigma = 0.80\text{ mho/m}$ $\epsilon_r = 44.2$ $\rho = 1.00\text{ g/cm}^3$

Cubes (2): Peak: $3.07\text{ mW/g} \pm 0.05\text{ dB}$, SAR (1g): $2.06\text{ mW/g} \pm 0.05\text{ dB}$, SAR (10g): $1.38\text{ mW/g} \pm 0.05\text{ dB}$, (Worst-case extrapolation)

Penetration depth: 13.6 (12.7, 14.8) [mm]

Powerdrift: -0.00 dB



APPENDIX C - PROBE CALIBRATION

Probe ET3DV6

SN:1387

Manufactured:	September 21, 1999
Last calibration:	September 22, 1999

Calibrated for System DASY3

DASY3 - Parameters of Probe: ET3DV6 SN:1387

Sensitivity in Free Space

NormX	1.55 $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	1.65 $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	1.64 $\mu\text{V}/(\text{V}/\text{m})^2$

Diode Compression

DCP X	98 mV
DCP Y	98 mV
DCP Z	98 mV

Sensitivity in Tissue Simulating Liquid

Brain **450 MHz** $\epsilon_r = 48 \pm 5\%$ $\sigma = 0.50 \pm 10\%$ mho/m

ConvF X	6.76 extrapolated	Boundary effect:	
ConvF Y	6.76 extrapolated	Alpha	0.30
ConvF Z	6.76 extrapolated	Depth	2.52

Brain **900 MHz** $\epsilon_r = 42.5 \pm 5\%$ $\sigma = 0.86 \pm 10\%$ mho/m

ConvF X	6.34 $\pm 7\%$ (k=2)	Boundary effect:	
ConvF Y	6.34 $\pm 7\%$ (k=2)	Alpha	0.47
ConvF Z	6.34 $\pm 7\%$ (k=2)	Depth	2.25

Brain **1500 MHz** $\epsilon_r = 41 \pm 5\%$ $\sigma = 1.32 \pm 10\%$ mho/m

ConvF X	5.78 interpolated	Boundary effect:	
ConvF Y	5.78 interpolated	Alpha	0.69
ConvF Z	5.78 interpolated	Depth	1.88

Brain **1800 MHz** $\epsilon_r = 41 \pm 5\%$ $\sigma = 1.69 \pm 10\%$ mho/m


ConvF X	5.50 $\pm 7\%$ (k=2)	Boundary effect:	
ConvF Y	5.50 $\pm 7\%$ (k=2)	Alpha	0.81
ConvF Z	5.50 $\pm 7\%$ (k=2)	Depth	1.70

Sensor Offset


Probe Tip to Sensor Center	2.7	mm
Optical Surface Detection	1.6 \pm 0.2	mm

Receiving Pattern (ϕ , $\theta = 0^\circ$)


f = 30 MHz, TEM cell ifi110




f = 100 MHz, TEM cell ifi110




f = 300 MHz, TEM cell ifi110




f = 900 MHz, TEM cell ifi110






Isotropy Error (ϕ), $\theta = 0^\circ$





Frequency Response of E-Field


(TEM-Cell:ifi110, Waveguide R22, R26)




Dynamic Range $f(\text{SAR}_{\text{brain}})$ (TEM-Cell:ifi110)



Conversion Factor Assessment



Receiving Pattern (ϕ) (in brain tissue, z = 5 mm)



APPENDIX D - SAR TEST SETUP PHOTOGRAPHS

FACE-HELD SAR TEST SETUP PHOTOGRAPHS
4.0cm Separation Distance



**BODY-WORN SAR TEST SETUP PHOTOGRAPHS
with 1.0cm Metal Belt-Clip**



**BODY-WORN SAR TEST SETUP PHOTOGRAPHS
with 0.9cm Leather Belt-Holster**



APPENDIX E - EUT PHOTOGRAPHS

EUT PHOTOGRAPHS



**EUT PHOTOGRAPHS
with 1.0cm Metal Belt-Clip**



**EUT PHOTOGRAPHS
with 0.9cm Leather Belt-Holster**



EUT PHOTOGRAPHS
0.9cm Leather Belt-Holster

