

Product Description

The A-FOUR Tech CO., Ltd. Model: RFMSW-15 (referred to as the EUT in the report) is a RF mouse transmitter that uses FSK radio frequency technology to operate a special designed receiver which associated with an IBM compatible PC. Center frequency designed for EUT operation is 27.045 or 27.145MHz (selected by switch). It is considered as a low power Communication device transmitter.

Details of technical specification for EUT, refer to the follows:

(1) Transmitter Frequency Designation

Operating Frequency Range : 27.045 MHz and 27.145MHz

Frequency Tolerance : ± 3 KHz @ center frequency.

(2) Power Rating

3V powered by either battery

(3) Operation Methodology

The mouse encoder generates a pulse code serially transmit (typical designation) into the modulator(or called as mixer) stage in circuit. This pulse signal mixed with the carrier at modulator(mixer) stage by way of FSK mode frequency modulation. The modulation depth is designed such as ± 5 KHz in this application, that means the pulse(may be at high level state or low level state) will trigger the oscillator to generate a frequency at a specified fundamental frequency +5KHz or -5KHz, depended on the designation. For example, if the carrier frequency defined as fundamental frequency +5KHz at high level state, then the alternative carrier frequency will be fundamental frequency -5KHz at low level state.

Then the modulator(mixer) will output a modulated signal into RF amplifier stage and finally to the transmit antenna.