


# 3.2 x 1.6 x 0.5 (mm) WiFi/Bluetooth Ceramic Chip Antenna (AA055U) Engineering Specification

## 1. Product Number

H 2 U 3 4 W 1 H 1 Z 0 7 0 0



## 2. Features

- \*Stable and reliable in performances
- \*Low profile, compact size
- \*RoHS 2.0 compliance
- \*SMT processes compatible

## 3. Applications

- \*ISM 2.4 GHz applications
- \*ZigBee/BLE applications
- \*Bluetooth earphone systems
- \*Hand-held devices when WiFi / Bluetooth functions are needed, e.g., Smart phones
- \*IEEE802.11 b/g/n
- \*Wireless PCMCIA cards or USB dongles

## 4. Description

Unictron's AA055U ceramic chip antenna is designed for ISM 2.4GHz applications, covering frequencies 2400~2500MHz. Fabricated with proprietary design and processes, AA055U shows excellent performance and is fully compatible with SMT processes which can decrease the assembly cost and improve device's quality and consistency.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification

DOCUMENT  
NO.

H2U34W1H1Z0700


REV.  
C

## 5. Layout Guide & Electrical Specifications

### 5-1. Layout Guide (unit:mm)

Solder Land Pattern:

The solder land pattern (gold marking areas) is shown below. Recommendation on matching circuit will be provided according to customer's installation conditions.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification

DOCUMENT  
NO.

H2U34W1H1Z0700

REV.  
C

## 5-2. Electrical Specifications (Evaluation Board Dimensions: 80 x 40 mm<sup>2</sup>)


### 5-2-1. Electrical Table

| Characteristics            |             | Specifications      | Unit |
|----------------------------|-------------|---------------------|------|
| Outline Dimensions         |             | 3.2 x 1.6 x 0.5     | mm   |
| Ground Plane Dimensions    |             | 80 x 40             | mm   |
| Working Frequency          |             | 2400~2500           | MHz  |
| VSWR (@ center frequency)* |             | 2 Max.              |      |
| Characteristic Impedance   |             | 50                  | Ω    |
| Polarization               |             | Linear Polarization |      |
| Peak Gain                  | (@2442 MHz) | 1.8 (typical**)     | dBi  |
| Efficiency                 |             | 76.3 (typical**)    | %    |

\*Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.

\*\*A typical value is for reference only, not guaranteed.

### 5-2-2. Frequency vs. V.S.W.R. and Total Radiation Gain



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification


DOCUMENT  
NO.

H2U34W1H1Z0700

REV.  
C

## 6. Outline Dimensions of Antenna & Evaluation Board (unit: mm)


### 6-1. Antenna Dimensions



#### NOTE:

1. All materials are RoHS 2.0 compliant.
2. "A~C" Critical Dimensions.
3. "( )" Reference Dimensions.

### PIN Definition



| PIN           | 1      | 2               |
|---------------|--------|-----------------|
| Soldering PAD | Signal | Tuning / Ground |



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

**TITLE :** 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification



**DOCUMENT**  
**NO.**

**H2U34W1H1Z0700**

**REV.**

**C**

## 6-2. Evaluation Board with Antenna



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

**TITLE :** 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip Antenna (AA055U) Engineering Specification

**DOCUMENT NO.**





**H2U34W1H1Z0700**

**REV.**

**C**

## 7. 3D Radiation Gain Pattern (with 80 x 40 mm<sup>2</sup> Evaluation Board)

3D Radiation Gain Pattern @ 2442 MHz (unit: dBi)



2019-12-10

Document Control Center



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification

DOCUMENT  
NO.

H2U34W1H1Z0700


REV.

C




## 8. Frequency tuning and Matching circuit

### 8-1. Chip antenna tuning scenario :



### 8-2. Matching circuit :

With the following recommended values of matching and tuning components, the center frequencies will be about 2442 MHz at our standard 80x40 mm<sup>2</sup> evaluation board. However, these are typical reference values which may need to be changed when circuit boards or part vendors are different.



| System Matching Circuit Component |               |        |           |
|-----------------------------------|---------------|--------|-----------|
| Location                          | Description   | Vendor | Tolerance |
| 1                                 | 1.2pF, (0402) | MURATA | ±0.05 pF  |
| 2                                 | 3.3nH, (0402) | MURATA | ±0.1 nH   |
| 3                                 | NA            |        |           |
| Fine tuning element 4             | 1.2pF, (0402) | MURATA | ±0.05 pF  |

\*Typical reference values which may need to be changed when circuit boards or part vendors are different.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert



TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification

DOCUMENT  
NO.

H2U34W1H1Z0700

REV.  
C

### 8-3. Reference for the frequency tuning element



Unictron  
Technologies Corp.  
2019-12-10  
Document  
Control Center



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification

DOCUMENT  
NO.


H2U34W1H1Z0700

REV.  
C



## 9. Soldering Condition

Solder paste alloy: SAC305 (Sn96.5/Ag3/Cu0.5) Lead Free solder paste



\*Recommended solder paste alloy: SAC305 (Sn96.5 /Ag3 /Cu0.5) Lead Free solder paste

## 10. Reminders for users of Unictron's AA055U ceramic chip antennas

- 10-1. This chip antenna is made of ceramic materials which are relatively more rigid and brittle compared to printed circuit board materials. Bending of circuit board at the locations where chip antenna is mounted may cause the cracking of solder joints or antenna itself.
- 10-2. Punching/cutting of the break-off tab of PCB panel may cause severe bending of the circuit board which may result in cracking of solder joints or chip antenna itself. Therefore break-off tab shall be located away from the installation site of chip antenna.
- 10-3. Be cautious when ultrasonic welding process needs to be used near the locations where chip antennas are installed. Strong ultrasonic vibration may cause the cracking of chip antenna solder joints.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

**TITLE :** 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip Antenna (AA055U) Engineering Specification

**DOCUMENT NO.**


**H2U34W1H1Z0700**

**REV.**  
**C**

## 11. Packing

- (1) Packaging method is implemented according to "MSL 2a 包裝作業指導書"
- (2) Quantity/Reel: 5000 pcs/Reel
- (3) Plastic tape: Black conductive polystyrene.


a. Tape Drawing



b. Tape Dimensions (unit: mm)

| Feature | Specifications | Tolerances     |
|---------|----------------|----------------|
| W       | 12.00          | ±0.30          |
| P       | 4.00           | ±0.10          |
| E       | 1.75           | ±0.10          |
| F       | 5.50           | ±0.10          |
| P2      | 2.00           | ±0.10          |
| D       | 1.50           | +0.10<br>-0.00 |
| Po      | 4.00           | ±0.10          |
| 10Po    | 40.00          | ±0.20          |

c. Reel Drawing



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification

DOCUMENT  
NO.

H2U34W1H1Z0700

REV.

C

## 12. Operating & Storage Conditions

### 12-1. Operating

- (1) Maximum Input Power: 2 W
- (2) Operating Temperature: -40°C to 85°C
- (3) Relative Humidity: 10% to 70%

### 12-2. Storage (sealed)

- (1) Storage Temperature: -5°C to 40°C
- (2) Relative Humidity: 20% to 70%
- (3) Shelf Life: 1 year

### 12-3. Storage (unsealed)

Meet the criteria of J-STD-033 MSL2a

### 12-4. Storage (After mounted on customer's PCB with SMT process)

- (1) Storage Temperature: -40°C to 85°C
- (2) Relative Humidity: 10% to 70%

## 13. Notice

### (1) Installation Guide:

Please refer to Unictron's application note "General guidelines for the installation of Unictron's chip antennas" for further information.

### (2) All specifications are subject to change without notice.



詠業科技股份有限公司  
Unictron Technologies Corporation  
Website: www.unictron.com

Prepared by : Jane

Designed by : James

Checked by : Mike

Approved by : Herbert

TITLE : 3.2 x 1.6 x 0.5(mm) WiFi/Bluetooth Ceramic Chip  
Antenna (AA055U) Engineering Specification

DOCUMENT  
NO.

H2U34W1H1Z0700

REV.  
C