



## FCC 47 CFR MPE REPORT

Sellmark Corporation

DARK30 PTZ 384 Camera

Model Number: DT27001

FCC ID: 2BGAS-DT27001

Applicant:	Sellmark Corporation
Address:	2201 Heritage Parkway, Mansfield, Texas 76063, United States
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2501138
Date of Test:	Aug. 29, 2024~ Jan. 14, 2025
Date of Report:	Jan. 16, 2025

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
BLE 1M	2402	2.83	1.919
	2440	2.89	1.945
	2480	3.07	2.028
IEEE 802.11b	2412	16.17	41.400
	2437	15.64	36.644
	2462	15.43	34.914
IEEE 802.11g	2412	21.83	152.405
	2437	20.89	122.744
	2462	20.78	119.674
IEEE 802.11n HT20	2412	21.67	146.893
	2437	20.94	124.165
	2462	20.71	117.761
IEEE 802.11n HT40	2422	21.62	145.211
	2437	21.29	134.586
	2452	20.95	124.451

### 3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm <sup>2</sup> )	Limited of Power Density (S) (mW /cm <sup>2</sup> )	Test Result
				(dBi)	(Linear)			
2.4G Band								
BLE	3.07	3±1	4	2.9	1.950	0.00097	1	Complies
IEEE 802.11b	16.17	16±1	17	3.1	2.042	0.02036	1	Complies
IEEE 802.11g	21.83	21±1	22	3.1	2.042	0.06438	1	Complies
IEEE 802.11n HT20	21.67	21±1	22	3.1	2.042	0.06438	1	Complies
IEEE 802.11n HT40	21.62	21±1	22	3.1	2.042	0.06438	1	Complies

**End of Test Report**