



Tengxiang Technology.Inc

Product Number: AN2400-0906RS-B

Product Name: Antenna

Specification For Approval

Customer: _____

Customer P/N: _____

Tengxiang P/N: AN2400-0906RS-B

Description : 2.4G 3.5dBi ANTENNA SMA公头母针镀镍

Tengxiang Checked By:	Customer Approved By:
工程: dwf 射频: 韦佳 腾祥电子有限公司 工程课	



腾祥电子
TENGXIANG ELECTRONIC

Tengxiang Technology.Inc

NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>

Product Number: AN2400-0906RS-B

Product Name: 2.4GHz Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	2400 ~ 2500 MHz
V.S.W.R.	≤ 2.0
Antenna Gain	3.5dBi
Polarization	Linear
Impedance	50 Ohm
B. Material & Mechanical Characteristics	
Material of Radiator	Cu
Material of Plastic	TPEE / ABS / POM
Connector Type	公头母针
C. Environmental	
Operation Temperature	- 30 °C ~ + 65°C
Storage Temperature	- 30 °C ~ + 65°C

2. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements
C1	V.S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification
C2	Antenna Gain	Set DUT on Antenna Chamber; make individual calibration to test	Directive DUT specification



Tengxiang Technology.Inc

Product Number: AN2400-0906RS-B


Product Name: 2.4GHz Antenna

M1	Vibration	MIL-STD-202G, 201A Amplitude: 0.03 inch (0.76mm); Freq: 10 to 55 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol.<= 5%
M2	Random Drop	Height: 1.5 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol.<= 5%
M3	Solderability	MIL-STD-202G, 210F, cond. A Solder iron: 350±10°C; Duration: 5 seconds	1. Mounted on PCB 2. No Visual Damage
M4	Terminal-Pull Test	MIL-STD-202G, 211A, cond. A Holding with individual specification; force applied to axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M5	Terminal-Torque Test	MIL-STD-202G, 211A, cond. E Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M6	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	MIL-STD-202G, 101E, cond. B Temp: 35°C; RH: >= 95%; NaCl solution: >= 5%; Time: 24 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E2	Humidity	MIL-STD-202G, 103B, cond. B Temp: 40°C; RH: >= 95%; Time: 24 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E3	Thermal Shock	1 Cycle: - 30°C (30 minutes) to + 65°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E4	Life (High Temp.)	MIL-STD-202G, 108A, cond. A Temp: 65°C; Time: 24hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2015/863/EU

Product Number: AN2400-0906RS-B


Product Name: 2.4GHz Antenna

3. Antenna - S Parameter Test Data




4. Antenna - Radiation Pattern Test Data

Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Gain (dBi)	3.47	3.41	3.46	3.49	3.48	3.50	3.56	3.43	3.51	3.43	3.50
Efficiency (%)	84.72	84.47	86.32	86.91	85.97	86.44	86.84	86.55	86.28	86.33	85.02




Product Number: AN2400-0906RS-B

Product Name: 2.4GHz Antenna



5. Mechanical Drawing (See attached files)



產品包裝規範

PACKING CRITERION

Date: 2022.03.30

Page: 1 of 1


Part Number : AN2400-0906RS-B

Revision : A


Name: 2.4GHz 3.5dBi Antenna

Customer : ALL


1 . Enter PE bag。




2.PACKING 。




3. SEALING。



SIDE



FRONT



APPROVED BY : YCX

CHECKED BY : HC

DESIGNED BY : dwf