



JianYan Testing Group Shenzhen Co., Ltd.

Report No.: JYTSZ-R12-2201603

RF Exposure Evaluation Report

Applicant: PAX Technology Limited

Address of Applicant: Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour, Hong

Kong

Equipment Under Test (EUT)

Product Name: POS Terminal

Model No.: Q25

Trade mark: PAX

FCC ID: V5PQ25W

Applicable standards: FCC CFR Title 47 Part 2 (§2.1091)

Date of sample receipt: 15 Aug., 2022

Date of Test: 16 Aug., to 02 Dec., 2022

Date of report issue: 05 Dec., 2022

Test Result: PASS

Tested by: Date: 05 Dec., 2022

Reviewed by: Date: 05 Dec., 2022

Approved by: Date: 05 Dec., 2022

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.





1 Version

| Version No. | Date | Description | | |
|-------------|---------------|-------------|--|--|
| 00 | 05 Dec., 2022 | Original | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |





2 Contents

| | | | Page |
|---|---------|---|------|
| С | over Pa | age | 1 |
| 1 | Ver | rsion | 2 |
| 2 | Cor | ntents | 3 |
| 3 | | neral Information | |
| | 3.1 | Client Information | 4 |
| | 3.2 | General Description of E.U.T. | 4 |
| | 3.3 | Operating Modes | 4 |
| | 3.4 | Additions to, deviations, or exclusions from the method | 4 |
| | 3.5 | Laboratory Facility | 5 |
| | 3.6 | Laboratory Location | 5 |
| 4 | Tec | chnical Requirements Specification | 6 |
| | 4.1 | Limits | 6 |
| | 4.2 | Test Procedure | 6 |
| | 4.3 | Result | 7 |
| | 4.4 | Conclusion | 7 |
| | | | |





3 General Information

3.1 Client Information

| Applicant: | PAX Technology Limited |
|---------------|---|
| Address: | Room 2416, 24/F., Sun Hung Kai Centre, 30 Harbour, Hong Kong |
| Manufacturer: | PAX Computer Technology (Shenzhen) Co., Ltd. |
| Address: | 401 and 402, Building 3, Shenzhen Software Park, Nanshan District, Shenzhen City, Guangdong Province, P.R.C |

3.2 General Description of E.U.T.

| Product Name: | POS Terminal | | | |
|--|---|--|--|--|
| Model No.: | Q25 | | | |
| Operation Frequency: 2.4G Wi-Fi: 2412MHz~2462MHz | | | | |
| | 5.2G Wi-Fi Band 1: 5150MHz~5250MHz | | | |
| | 5.3G Wi-Fi Band 2: 5250MHz~5350MHz | | | |
| | 5.6G Wi-Fi Band 3: 5470MHz~5725MHz | | | |
| | 5.8G Wi-Fi Band 4: 5725MHz~5850MHz | | | |
| Modulation technology: | 802.11b: DSSS, 802.11a/g/n/ac: OFDM | | | |
| Antenna Type: | Internal Antenna | | | |
| Antenna gain: | 2.4GWi-Fi: 0.5 dBi; 5GWi-Fi: 3.65 dBi | | | |
| Test Sample Condition: | The test samples were provided in good working order with no visible defects. | | | |

3.3 Operating Modes

| Operating mode | Detail description |
|----------------|---|
| 2.4G WIFI mode | Keep the EUT in continuously transmitting in 2.4G WIFI mode |
| 5G WIFI mode | Keep the EUT in continuously transmitting in 5G WIFI mode |

3.4 Additions to, deviations, or exclusions from the method

| <u> </u> | raditions to, doridions, or exclusions from the mountain |
|----------|--|
| | No |



Report No.: JYTSZ-R12-2201603

3.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC - Designation No.: CN1211

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● ISED - CAB identifier.: CN0021

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

• CNAS - Registration No.: CNAS L15527

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

• A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

3.6 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xingiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: http://jyt.lets.com



4 Technical Requirements Specification

4.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|--|--|--|
| (A) Limits for Occupational/Controlled Exposures | | | | | | | |
| 0.3–3.0 614 1.63 *(100) 6 | | | | | | | |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 | | | |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 | | | |
| 300–1500 | | | f/300 | 6 | | | |
| 1500–100,000 | | | 5 | 6 | | | |
| (B) Limits for General Population/Uncontrolled Exposure | | | | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 | | | |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 | | | |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 | | | |
| 300–1500 | | | f/1500 | 30 | | | |
| 1500–100,000 | | | 1.0 | 30 | | | |

4.2 Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna





4.3 Result

| Frequency (MHz) | Maximum Output power (dBm) | Maximum Output power (mW) | Antenna Gain (dBi) | Antenna Gain (numeric) | Distance (cm) | Result (mW/cm²) | Limits for General Population/ Uncontrolled Exposure (mW/cm²) |
|--------------------|-------------------------------------|------------------------------------|--------------------------|------------------------------|------------------|--------------------|--|
| | 2.4G Wi-Fi | | | | | | |
| 2437 | 13.79 | 23.93 | 0.5 | 1.12 | 20.00 | 0.005 | 1.0 |
| | | | 5.2G | Wi-Fi | | | |
| 5180 | 15.08 | 32.21 | 3.65 | 2.32 | 20.00 | 0.015 | 1.0 |
| 5.3G Wi-Fi | | | | | | | |
| 5320 | 14.32 | 27.04 | 3.65 | 2.32 | 20.00 | 0.012 | 1.0 |
| 5.6G Wi-Fi | | | | | | | |
| 5500 | 14.11 | 25.76 | 3.65 | 2.32 | 20.00 | 0.012 | 1.0 |
| | 5.8G Wi-Fi | | | | | | |
| 5745 | 12.67 | 18.49 | 3.65 | 2.32 | 20.00 | 0.009 | 1.0 |

Note: Just the worst case mode was shown in report.

4.4 Conclusion

The device is exempt from the SAR test and satisfies RF exposure evaluation.

-----End of report-----