

TEST REPORT

For Bluetooth-LE



Report No. : CHTW24010102 Report Verification:

Project No..... : SHT2310048501EW

FCC ID..... : 2AN9S-ABX00083

Applicant's name..... : Arduino S.r.l.

Address..... : Via Andrea Appiani, 25 Monza, MB, 20900 Italy

Product Name : Arduino Nano ESP32 with headers, Arduino Nano ESP32

Trade Mark : Arduino

Model No. : ABX00083

Listed Model(s) : ABX00092

Standard : FCC CFR Title 47 Part 15 Subpart C § 15.247

Date of receipt of test sample..... : Oct.23, 2023

Date of testing..... : Oct.23, 2023- Jan.30, 2024

Date of issue..... : Jan.31, 2024

Result..... : PASS


Compiled by
(Position+Printed name+Signature): File administrators Kiki Kong



Supervised by
(Position+Printed name+Signature): Project Engineer Kiki Kong



Approved by
(Position+Printed name+Signature): RF Manager Xu yang



Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address..... : Building 7, Baiwang Idea Factory, No.1051, Songbai Road,
Yangguang Community, Xili Subdistrict, Nanshan District,
Shenzhen, Guangdong, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

1.	TEST STANDARDS AND REPORT VERSION	3
1.1.	Test Standards	3
1.2.	Report version	3
2.	TEST DESCRIPTION	4
3.	SUMMARY	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
4.	TEST CONFIGURATION	7
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test sample information	7
4.4.	Support unit used in test configuration and system	8
4.5.	Testing environmental condition	8
4.6.	Statement of the measurement uncertainty	8
4.7.	Equipment Used during the Test	9
5.	TEST CONDITIONS AND RESULTS	11
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	17
5.6.	99% Occupied Bandwidth	18
5.7.	Duty Cycle	19
5.8.	Conducted Band edge and Spurious Emission	20
5.9.	Radiated Band edge Emission	21
5.10.	Radiated Spurious Emission	24
6.	TEST SETUP PHOTOS	31
7.	EXTERNAL AND INTERNAL PHOTOS	34
7.1.	External Photos	34
7.2.	Internal Photos	37
8.	APPENDIX REPORT	37

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC CFR Title 47 Part 15 Subpart C § 15.247](#): Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2020](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2024-01-31	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247(c)	PASS	Xiangyu Wei
5.2	AC Conducted Emission	15.207	PASS	JUNMAN.WANG
5.3	Peak Output Power	15.247(b)(3)	PASS	Xiangyu Wei
5.4	Power Spectral Density	15.247(e)	PASS	Xiangyu Wei
5.5	6dB Bandwidth	15.247(a)(2)	PASS	Xiangyu Wei
5.6	99% Occupied Bandwidth	-	PASS ^{*1}	Xiangyu Wei
5.7	Duty cycle	-	PASS ^{*1}	Xiangyu Wei
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS	Xiangyu Wei
5.9	Radiated Band Edge Emission	15.205/15.209	PASS	Yifan Wang
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS	Yifan Wang

Note:

- The measurement uncertainty is not included in the test result.
- ^{*1}: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	Arduino S.r.l.
Address:	Via Andrea Appiani, 25 Monza, MB, 20900 Italy
Manufacturer:	Arduino S.r.l.
Address:	Via Andrea Appiani, 25 Monza, MB, 20900 Italy

3.2. Product Description

Main unit information:	
Product Name:	Arduino Nano ESP32 with headers, Arduino Nano ESP32
Trade Mark:	Arduino
Model No.:	ABX00083
Listed Model(s):	ABX00092
Power supply:	DC 5V
Hardware version:	0.3
Software version:	2.0.13

3.3. Radio Specification Description

Bluetooth version:	V5.0
Support function:	BLE1M,BLE2M
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	PCB Antenna
Antenna gain:	3.0dBi

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2404
.
19	2440
.
38	2478
39	2480

4.2. Descriptions of Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For Radiated spurious emissions:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.3. Test sample information

Test item	HTW sample no.
RF Conducted test items	Please refer to the description in the appendix report
RF Radiated test items	YPHT23100485001
EMI test items	YPHT23100485001

Note:

RF Conducted test items: Peak Output Power, Power Spectral Density, 6dB Bandwidth, 99% Occupied Bandwidth, Duty cycle, Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission

EMI test items: AC Conducted Emission

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
✓ Yes			
Item	Equipment	Trade Name	Model No.
1	Laptop	DELL	Inspiron 13-5378
2			

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Peak Output Power	1.07
3	Power Spectral Density	1.07
4	6dB Bandwidth	0.002%
5	99% Occupied Bandwidth	0.002%
6	Duty cycle	-
7	Conducted Band Edge and Spurious Emission	1.68dB
8	Radiated Band Edge Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
9	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.7. Equipment Used during the Test

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2023/08/22	2024/08/21
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2023/08/22	2024/08/21
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2023/05/23	2024/05/22
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2023/8/22	2024/8/21
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2023/8/18	2024/8/17
●	Protection Network	SCHWARZBECK	HTWE0567	VTSD9561FN	00899	2023/8/18	2024/8/17
●	ISN	FCC	HTWE0148	FCC-TLISN-T2-02	20371	2023/8/18	2024/8/17
●	ISN	FCC	HTWE0150	FCC-TLISN-T8-02	20375	2023/8/18	2024/8/17
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission – 9kHz~30MHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/4/6	2026/4/5
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2023/8/22	2024/8/21
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/4/6	2024/4/5
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission - 30MHz~1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/4/6	2026/4/5
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2023/8/22	2024/8/21
●	Ultra-Broadband Antenna	SCHWARZBEC K	HTWE0119	VULB9163	546	2023/2/22	2026/2/21
●	Pre-Amplifier	SCHWARZBEC K	HTWE0295	BBV 9742	/	2023/5/25	2024/5/24
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission-Above 1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/4/17	2026/4/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2023/8/22	2024/8/21
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/2/14	2026/2/13
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2023/2/20	2026/2/19
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2023/5/25	2024/5/24
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

REQUIREMENT

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

TEST RESULT

☒ Passed ☐ Not Applicable

The antenna type is a PCB antenna, please refer to the below antenna photo.

|



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE

Refer to the clause 4.2


TEST RESULT

☒ Passed ☐ Not Applicable

BLE 1M:

Test Line:


L

**Final Result**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.1755	---	38.59	54.70	16.10	L1	10.9
0.1795	50.19	---	64.51	14.32	L1	10.9
0.1875	49.03	---	64.15	15.12	L1	10.9
0.2155	---	33.48	52.99	19.51	L1	10.9
0.2315	---	29.16	52.40	23.23	L1	10.9
0.2595	39.50	---	61.45	21.95	L1	10.9
0.2995	32.73	---	60.26	27.53	L1	10.9
0.4435	---	32.38	47.00	14.62	L1	10.9
0.4835	---	34.87	46.28	11.41	L1	11.0
0.4835	39.10	---	56.28	17.18	L1	11.0
0.5115	39.95	---	56.00	16.05	L1	11.0
0.5155	---	35.66	46.00	10.34	L1	11.0

Test Line:

N


**Final Result**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.1580	53.42	---	65.57	12.15	N	10.7
0.1675	---	38.60	55.08	16.49	N	10.7
0.1715	51.61	---	64.89	13.28	N	10.7
0.2075	43.03	---	63.30	20.28	N	10.7
0.3675	---	27.51	48.56	21.05	N	10.7
0.3955	33.70	---	57.95	24.25	N	10.6
0.4315	---	25.10	47.22	22.12	N	10.7
0.4515	33.89	---	56.85	22.96	N	10.7
0.4915	---	35.27	46.14	10.87	N	10.7
0.5155	---	33.79	46.00	12.21	N	10.7
0.5155	40.05	---	56.00	15.95	N	10.7
0.5235	---	33.75	46.00	12.25	N	10.7

BLE 2M:

Test Line:


L

**Final Result**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.1500	49.40	---	66.00	16.60	L1	10.8
0.1580	---	34.41	55.57	21.16	L1	10.9
0.1595	48.16	---	65.49	17.33	L1	10.9
0.1675	47.72	---	65.08	17.37	L1	10.9
0.1675	---	36.52	55.08	18.56	L1	10.9
0.1995	---	36.54	53.63	17.09	L1	10.9
0.2555	38.85	---	61.58	22.73	L1	10.9
0.3715	---	21.09	48.47	27.37	L1	10.9
0.4475	30.81	---	56.92	26.11	L1	10.9
0.5035	---	37.55	46.00	8.45	L1	11.0
0.5075	---	38.22	46.00	7.78	L1	11.0
0.5075	42.04	---	56.00	13.96	L1	11.0

Test Line:

N

**Final Result**


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.1540	51.93	---	65.78	13.85	N	10.7
0.1540	---	36.29	55.78	19.49	N	10.7
0.1580	48.78	---	65.57	16.79	N	10.7
0.1765	---	37.63	54.65	17.02	N	10.7
0.1835	---	37.00	54.33	17.33	N	10.7
0.2035	44.19	---	63.47	19.27	N	10.7
0.2075	45.01	---	63.30	18.29	N	10.7
0.2595	34.26	---	61.45	27.19	N	10.7
0.2635	---	23.36	51.32	27.96	N	10.7
0.4715	---	31.47	46.49	15.01	N	10.7
0.4995	---	36.86	46.01	9.15	N	10.7
0.4995	40.91	---	56.01	15.10	N	10.7

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW ≥ 3 × RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW \geq RBW
Sweep=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE

Refer to the clause 4.2

TEST DATA


Refer to the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

BLE 1M:

Test channel		CH00			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	47.30	27.86	4.01	41.80	37.37	74.00	-36.63	Peak
2	2390.01	46.88	27.54	4.31	41.80	36.93	74.00	-37.07	Peak
Test channel		CH00			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	46.87	27.86	4.01	41.80	36.94	74.00	-37.06	Peak
2	2390.12	53.22	27.54	4.31	41.80	43.27	74.00	-30.73	Peak

Test channel		CH39			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	59.03	27.33	4.18	41.80	48.74	74.00	-25.26	Peak
2	2500.00	47.40	27.30	4.19	41.80	37.09	74.00	-36.91	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	47.03	27.33	4.18	41.80	36.74	54.00	-17.26	Average
2	2500.00	39.05	27.30	4.19	41.80	28.74	54.00	-25.26	Average
Test channel		CH39			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	63.50	27.33	4.18	41.80	53.21	74.00	-20.79	Peak
2	2500.00	48.93	27.30	4.19	41.80	38.62	74.00	-35.38	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	50.97	27.33	4.18	41.80	40.68	54.00	-13.32	Average
2	2500.00	39.00	27.30	4.19	41.80	28.69	54.00	-25.31	Average

BLE 2M:

Test channel		CH00			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	47.17	27.86	4.01	41.80	37.24	74.00	-36.76	Peak
2	2390.01	46.72	27.54	4.31	41.80	36.77	74.00	-37.23	Peak
Test channel		CH00			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	47.07	27.86	4.01	41.80	37.14	74.00	-36.86	Peak
2	2390.01	46.53	27.54	4.31	41.80	36.58	74.00	-37.42	Peak

Test channel		CH39			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	65.23	27.33	4.18	41.80	54.94	74.00	-19.06	Peak
2	2500.00	47.82	27.30	4.19	41.80	37.51	74.00	-36.49	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	55.73	27.33	4.18	41.80	45.44	54.00	-8.56	Average
2	2500.00	38.93	27.30	4.19	41.80	28.62	54.00	-25.38	Average
Test channel		CH39			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	68.86	27.33	4.18	41.80	58.57	74.00	-15.43	Peak
2	2500.00	48.35	27.30	4.19	41.80	38.04	74.00	-35.96	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	60.85	27.33	4.18	41.80	50.56	54.00	-3.44	Average
2	2500.00	40.07	27.30	4.19	41.80	29.76	54.00	-24.24	Average

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + $40 \cdot \log(300/3)$ = Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m + $40 \cdot \log(30/3)$ = Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

For 9 kHz ~ 30 MHz

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.


For 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

BLE 1M:

Polarization:


Horizontal

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
52.9163	18.95	40.00	21.05	100.0	H	355.0	-8.9
53.8863	17.89	40.00	22.11	100.0	H	12.0	-9.1
215.8763	20.28	43.50	23.22	100.0	H	105.0	-10.6
348.1600	22.80	46.00	23.20	100.0	H	223.0	-5.5
480.0800	32.64	46.00	13.36	100.0	H	255.0	-2.8
910.8813	33.42	46.00	12.58	300.0	H	206.0	6.9

Polarization:

Vertical


**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
437.5213	30.32	46.00	15.68	100.0	V	184.0	-3.3
480.0800	29.55	46.00	16.45	100.0	V	145.0	-2.8
687.5388	31.93	46.00	14.07	100.0	V	11.0	2.1
778.9613	31.81	46.00	14.19	100.0	V	70.0	4.2
945.3163	34.64	46.00	11.36	100.0	V	82.0	7.1
948.5900	40.80	46.00	5.20	100.0	V	321.0	7.1

BLE 2M:

Polarization:


Horizontal

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
53.6438	19.07	40.00	20.93	100.0	H	154.0	-9.0
55.3413	18.34	40.00	21.66	100.0	H	2.0	-9.1
82.9863	14.74	40.00	25.26	100.0	H	104.0	-15.2
213.6725	20.20	43.50	23.30	100.0	H	123.0	-10.7
479.9588	30.44	46.00	15.56	100.0	H	84.0	-2.8
949.8025	34.21	46.00	11.79	100.0	H	135.0	7.1

Polarization:

Vertical

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
687.5388	32.61	46.00	13.39	100.0	V	0.0	2.1
787.6913	31.68	46.00	14.32	100.0	V	36.0	4.4
822.6113	32.28	46.00	13.72	100.0	V	0.0	5.0
909.6688	33.16	46.00	12.84	100.0	V	317.0	6.8
945.3163	35.41	46.00	10.59	100.0	V	6.0	7.1
948.4688	34.73	46.00	11.27	100.0	V	103.0	7.1

For 1 GHz ~ 25 GHz BLE 1M:

Test channel		CH00			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3579.82	44.20	29.26	5.10	41.60	36.96	74.00	-37.04	Peak
2	5762.24	42.73	31.92	6.66	40.71	40.60	74.00	-33.40	Peak
3	6696.01	40.99	34.11	7.25	40.79	41.56	74.00	-32.44	Peak
4	10480.59	38.83	39.98	9.75	40.86	47.70	74.00	-26.30	Peak

Test channel		CH00			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3561.64	43.14	29.22	5.16	41.60	35.92	74.00	-38.08	Peak
2	6363.65	40.74	33.25	7.08	40.60	40.47	74.00	-33.53	Peak
3	8104.56	40.38	36.98	8.11	40.59	44.88	74.00	-29.12	Peak
4	10507.31	39.21	40.00	9.76	40.95	48.02	74.00	-25.98	Peak

Test channel		CH19			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3325.07	43.94	28.30	4.85	41.60	35.49	74.00	-38.51	Peak
2	4501.49	42.72	30.60	5.97	41.40	37.89	74.00	-36.11	Peak
3	5762.24	43.06	31.92	6.66	40.71	40.93	74.00	-33.07	Peak
4	10480.59	39.13	39.98	9.75	40.86	48.00	74.00	-26.00	Peak

Test channel		CH19			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	4128.28	42.64	29.90	5.65	41.40	36.79	74.00	-37.21	Peak
2	5762.24	42.74	31.92	6.66	40.71	40.61	74.00	-33.39	Peak
3	8063.40	40.32	37.00	8.19	40.68	44.83	74.00	-29.17	Peak
4	10400.86	39.51	39.90	9.71	40.60	48.52	74.00	-25.48	Peak

Test channel		CH39			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3588.94	42.22	29.28	5.08	41.60	34.98	74.00	-39.02	Peak
2	6379.86	39.56	33.32	7.15	40.60	39.43	74.00	-34.57	Peak
3	8042.90	40.10	37.00	8.19	40.72	44.57	74.00	-29.43	Peak
4	10374.42	39.24	39.82	9.69	40.65	48.10	74.00	-25.90	Peak

Test channel		CH39			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3883.62	43.07	29.67	5.30	41.52	36.52	74.00	-37.48	Peak
2	5762.24	41.44	31.92	6.66	40.71	39.31	74.00	-34.69	Peak
3	7941.19	40.00	36.85	7.97	40.93	43.89	74.00	-30.11	Peak
4	10888.51	39.53	40.48	9.95	42.19	47.77	74.00	-26.23	Peak

For 1 GHz ~ 25 GHz BLE 2M:

Test channel		CH00			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2947.25	44.08	28.50	4.64	41.68	35.54	74.00	-38.46	Peak
2	5507.65	40.21	31.78	6.58	40.81	37.76	74.00	-36.24	Peak
3	8068.44	40.07	37.00	8.18	40.67	44.58	74.00	-29.42	Peak
4	11520.82	39.18	40.46	10.37	42.30	47.71	74.00	-26.29	Peak

Test channel		CH00			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3553.53	42.65	29.21	5.18	41.60	35.44	74.00	-38.56	Peak
2	5087.05	40.20	31.92	6.29	41.07	37.34	74.00	-36.66	Peak
3	7395.21	40.13	36.20	7.78	41.00	43.11	74.00	-30.89	Peak
4	10398.41	38.13	39.90	9.70	40.60	47.13	74.00	-26.87	Peak

Test channel		CH19			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3308.19	45.14	28.30	4.85	41.60	36.69	74.00	-37.31	Peak
2	5073.59	39.83	31.84	6.22	41.07	36.82	74.00	-37.18	Peak
3	7981.72	41.12	36.96	7.99	40.85	45.22	74.00	-28.78	Peak
4	11457.21	40.06	40.46	10.33	42.30	48.55	74.00	-25.45	Peak


Test channel		CH19			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3308.19	43.90	28.30	4.85	41.60	35.45	74.00	-38.55	Peak
2	5762.24	40.26	31.92	6.66	40.71	38.13	74.00	-35.87	Peak
3	8042.90	39.42	37.00	8.19	40.72	43.89	74.00	-30.11	Peak
4	10453.95	39.98	39.95	9.73	40.77	48.89	74.00	-25.11	Peak


Test channel		CH39			Polarity		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2950.14	43.78	28.50	4.65	41.68	35.25	74.00	-38.75	Peak
2	5762.24	41.62	31.92	6.66	40.71	39.49	74.00	-34.51	Peak
3	8063.40	40.90	37.00	8.19	40.68	45.41	74.00	-28.59	Peak
4	11341.14	39.24	40.22	10.25	42.30	47.41	74.00	-26.59	Peak

Test channel		CH39			Polarity		Vertical		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3983.75	43.93	29.77	5.60	41.47	37.83	74.00	-36.17	Peak
2	5762.24	42.48	31.92	6.66	40.71	40.35	74.00	-33.65	Peak
3	7941.19	39.93	36.85	7.97	40.93	43.82	74.00	-30.18	Peak
4	10999.95	40.03	40.50	10.00	42.30	48.23	74.00	-25.77	Peak

6. TEST SETUP PHOTOS

Radiated Emission











AC Conducted Emission




7. EXTERNAL AND INTERNAL PHOTOS

7.1. External Photos







7.2. Internal Photos



8. APPENDIX REPORT


APPENDIX REPORT




Project No.	SHT2310048501EW	Radio Specification	Bluetooth BLE
Test sample No.	YPHT23100485001	Model No.	ABX00083
Start test date	2024-01-24	Finish date	2024-01-25
Temperature	24.1℃	Humidity	48%
Test Engineer	Xiangyu Wei	Auditor	Xiaodong Zheo

Appendix clause	Test item	Result
A	Peak Output Power	PASS
B	Power Spectral Density	PASS
C	6 dB Bandwidth	PASS
D	99% Occupied Bandwidth	PASS
E	Duty cycle	PASS
F	Band edge and Spurious Emissions (conducted)	PASS

Appendix A: Peak Output Power

Test rate	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
1Mbps	00	2.86	2.83	≤ 30.00	Pass
	19	0.15	0.13		
	39	-0.41	-0.44		
2Mbps	00	1.93	1.89	≤ 30.00	Pass
	19	-0.02	-0.05		
	39	-0.66	-0.70		






Test rate:		2Mbps
CH00		
CH19		
CH39		

Appendix B: Power Spectral Density


Test rate	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
1Mbps	00	-14.57	≤8.00	Pass
	19	-16.39		
	39	-16.64		
2Mbps	00	-20.19	≤8.00	Pass
	19	-20.80		
	39	-20.78		

Test rate: 1Mbps	
CH00	<div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Att 20 dB</div><div>Offset 0.50 dB</div><div>RBW 3 kHz</div><div>SWT 632.3 μs</div><div>VBW 10 kHz</div><div>Mode Auto FFT</div><div>Count 100/100</div></div><div><div>IFk Max</div><div>M1[1]</div><div>-14.57 dBm</div><div>2.40201880 GHz</div></div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>CF 2.402 GHz</div><div>691 pts</div><div>Span 1.0 MHz</div></div></div></div><div><div>Date: 26.03.2024 08:07:04</div></div></div>
CH19	<div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Att 20 dB</div><div>Offset 0.50 dB</div><div>RBW 3 kHz</div><div>SWT 632.3 μs</div><div>VBW 10 kHz</div><div>Mode Auto FFT</div><div>Count 100/100</div></div><div><div>IFk Max</div><div>M1[1]</div><div>-10.39 dBm</div><div>2.44000870 GHz</div></div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>CF 2.44 GHz</div><div>691 pts</div><div>Span 1.0 MHz</div></div></div></div><div><div>Date: 26.03.2024 08:30:40</div></div></div>
CH39	<div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Att 20 dB</div><div>Offset 0.50 dB</div><div>RBW 3 kHz</div><div>SWT 632.3 μs</div><div>VBW 10 kHz</div><div>Mode Auto FFT</div><div>Count 100/100</div></div><div><div>IFk Max</div><div>M1[1]</div><div>-10.04 dBm</div><div>2.48000870 GHz</div></div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>CF 2.48 GHz</div><div>691 pts</div><div>Span 1.0 MHz</div></div></div></div><div><div>Date: 26.03.2024 08:33:22</div></div></div>

Test rate: 2Mbps	
CH00	 <p>Spectrum plot for CH00. The plot shows a peak at 2.4020870 GHz with a power level of -20.19 dBm. The plot shows a Gaussian-like curve centered at the carrier frequency.</p>
CH19	 <p>Spectrum plot for CH19. The plot shows a peak at 2.4400870 GHz with a power level of -20.80 dBm. The plot shows a Gaussian-like curve centered at the carrier frequency.</p>
CH39	 <p>Spectrum plot for CH39. The plot shows a peak at 2.4800870 GHz with a power level of -20.78 dBm. The plot shows a Gaussian-like curve centered at the carrier frequency.</p>

Appendix C: 6dB bandwidth


Type	Channel	6dB Bandwidth(kHz)	Limit (kHz)	Result
1Mbps	00	660.00	≥500	Pass
	19	658.00		
	39	660.00		
2Mbps	00	1325.00	≥500	Pass
	19	1290.00		
	39	1320.00		






Test rate:		2Mbps																																																																																					
CH00	<div><div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Offset 0.50 dB</div><div>RBW 100 kHz</div></div><div><div>Att 20 dB</div><div>SWT 19 μs</div><div>VBW 300 kHz</div></div><div>Count 500/500</div><div>Mode Auto FFT</div></div><div><div>IFK view</div><div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>01 -7.389 dBm</div></div></div><div><div>CF 2.402 GHz</div><div>1001 pts</div><div>Span 5.0 MHz</div></div><div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.40133 GHz</td><td>-7.56 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.401995 GHz</td><td>-1.39 dBm</td><td></td><td></td></tr><tr><td>DS</td><td>M1</td><td>1</td><td>1.325 MHz</td><td>0.16 dB</td><td></td><td></td></tr></table></div></div></div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Offset 0.50 dB</div><div>RBW 100 kHz</div></div><div><div>Att 20 dB</div><div>SWT 19 μs</div><div>VBW 300 kHz</div></div><div>Count 500/500</div><div>Mode Auto FFT</div></div><div><div>IFK view</div><div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>01 -9.442 dBm</div></div></div><div><div>CF 2.44 GHz</div><div>1001 pts</div><div>Span 5.0 MHz</div></div><div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.43933 GHz</td><td>-9.58 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.43999 GHz</td><td>-3.44 dBm</td><td></td><td></td></tr><tr><td>DS</td><td>M1</td><td>1</td><td>1.29 MHz</td><td>-0.05 dB</td><td></td><td></td></tr></table></div></div></div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Offset 0.50 dB</div><div>RBW 100 kHz</div></div><div><div>Att 20 dB</div><div>SWT 19 μs</div><div>VBW 300 kHz</div></div><div>Count 500/500</div><div>Mode Auto FFT</div></div><div><div>IFK view</div><div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>01 -10.084 dBm</div></div></div><div><div>CF 2.48 GHz</div><div>1001 pts</div><div>Span 5.0 MHz</div></div><div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.47933 GHz</td><td>-10.24 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.47999 GHz</td><td>-4.08 dBm</td><td></td><td></td></tr><tr><td>DS</td><td>M1</td><td>1</td><td>1.32 MHz</td><td>0.13 dB</td><td></td><td></td></tr></table></div></div></div></div></div>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40133 GHz	-7.56 dBm			M2	1		2.401995 GHz	-1.39 dBm			DS	M1	1	1.325 MHz	0.16 dB			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.43933 GHz	-9.58 dBm			M2	1		2.43999 GHz	-3.44 dBm			DS	M1	1	1.29 MHz	-0.05 dB			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.47933 GHz	-10.24 dBm			M2	1		2.47999 GHz	-4.08 dBm			DS	M1	1	1.32 MHz	0.13 dB		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																																																	
M1	1		2.40133 GHz	-7.56 dBm																																																																																			
M2	1		2.401995 GHz	-1.39 dBm																																																																																			
DS	M1	1	1.325 MHz	0.16 dB																																																																																			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																																																	
M1	1		2.43933 GHz	-9.58 dBm																																																																																			
M2	1		2.43999 GHz	-3.44 dBm																																																																																			
DS	M1	1	1.29 MHz	-0.05 dB																																																																																			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																																																	
M1	1		2.47933 GHz	-10.24 dBm																																																																																			
M2	1		2.47999 GHz	-4.08 dBm																																																																																			
DS	M1	1	1.32 MHz	0.13 dB																																																																																			
CH19	<div><div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Offset 0.50 dB</div><div>RBW 100 kHz</div></div><div><div>Att 20 dB</div><div>SWT 19 μs</div><div>VBW 300 kHz</div></div><div>Count 500/500</div><div>Mode Auto FFT</div></div><div><div>IFK view</div><div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>01 -9.442 dBm</div></div></div><div><div>CF 2.44 GHz</div><div>1001 pts</div><div>Span 5.0 MHz</div></div><div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.43933 GHz</td><td>-9.58 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.43999 GHz</td><td>-3.44 dBm</td><td></td><td></td></tr><tr><td>DS</td><td>M1</td><td>1</td><td>1.29 MHz</td><td>-0.05 dB</td><td></td><td></td></tr></table></div></div></div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Offset 0.50 dB</div><div>RBW 100 kHz</div></div><div><div>Att 20 dB</div><div>SWT 19 μs</div><div>VBW 300 kHz</div></div><div>Count 500/500</div><div>Mode Auto FFT</div></div><div><div>IFK view</div><div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>01 -10.084 dBm</div></div></div><div><div>CF 2.48 GHz</div><div>1001 pts</div><div>Span 5.0 MHz</div></div><div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.47933 GHz</td><td>-10.24 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.47999 GHz</td><td>-4.08 dBm</td><td></td><td></td></tr><tr><td>DS</td><td>M1</td><td>1</td><td>1.32 MHz</td><td>0.13 dB</td><td></td><td></td></tr></table></div></div></div></div></div>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.43933 GHz	-9.58 dBm			M2	1		2.43999 GHz	-3.44 dBm			DS	M1	1	1.29 MHz	-0.05 dB			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.47933 GHz	-10.24 dBm			M2	1		2.47999 GHz	-4.08 dBm			DS	M1	1	1.32 MHz	0.13 dB																														
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																																																	
M1	1		2.43933 GHz	-9.58 dBm																																																																																			
M2	1		2.43999 GHz	-3.44 dBm																																																																																			
DS	M1	1	1.29 MHz	-0.05 dB																																																																																			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																																																	
M1	1		2.47933 GHz	-10.24 dBm																																																																																			
M2	1		2.47999 GHz	-4.08 dBm																																																																																			
DS	M1	1	1.32 MHz	0.13 dB																																																																																			
CH39	<div><div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Offset 0.50 dB</div><div>RBW 100 kHz</div></div><div><div>Att 20 dB</div><div>SWT 19 μs</div><div>VBW 300 kHz</div></div><div>Count 500/500</div><div>Mode Auto FFT</div></div><div><div>IFK view</div><div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>01 -10.084 dBm</div></div></div><div><div>CF 2.48 GHz</div><div>1001 pts</div><div>Span 5.0 MHz</div></div><div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.47933 GHz</td><td>-10.24 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.47999 GHz</td><td>-4.08 dBm</td><td></td><td></td></tr><tr><td>DS</td><td>M1</td><td>1</td><td>1.32 MHz</td><td>0.13 dB</td><td></td><td></td></tr></table></div></div></div><div><div><div>Spectrum</div><div><div>Ref Level 10.50 dBm</div><div>Offset 0.50 dB</div><div>RBW 100 kHz</div></div><div><div>Att 20 dB</div><div>SWT 19 μs</div><div>VBW 300 kHz</div></div><div>Count 500/500</div><div>Mode Auto FFT</div></div><div><div>IFK view</div><div><div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div><div>-80 dBm</div></div><div><div>01 -10.084 dBm</div></div></div><div><div>CF 2.48 GHz</div><div>1001 pts</div><div>Span 5.0 MHz</div></div><div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.47933 GHz</td><td>-10.24 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.47999 GHz</td><td>-4.08 dBm</td><td></td><td></td></tr><tr><td>DS</td><td>M1</td><td>1</td><td>1.32 MHz</td><td>0.13 dB</td><td></td><td></td></tr></table></div></div></div></div></div>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.47933 GHz	-10.24 dBm			M2	1		2.47999 GHz	-4.08 dBm			DS	M1	1	1.32 MHz	0.13 dB			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.47933 GHz	-10.24 dBm			M2	1		2.47999 GHz	-4.08 dBm			DS	M1	1	1.32 MHz	0.13 dB																														
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																																																	
M1	1		2.47933 GHz	-10.24 dBm																																																																																			
M2	1		2.47999 GHz	-4.08 dBm																																																																																			
DS	M1	1	1.32 MHz	0.13 dB																																																																																			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																																																																	
M1	1		2.47933 GHz	-10.24 dBm																																																																																			
M2	1		2.47999 GHz	-4.08 dBm																																																																																			
DS	M1	1	1.32 MHz	0.13 dB																																																																																			



Appendix D: 99% Occupied Bandwidth

Test rate	Channel	99% Occupied Bandwidth(MHz)	Limit (kHz)	Result
1Mbps	00	1.03	-	Pass
	19	1.03		
	39	1.03		
2Mbps	00	2.04	-	Pass
	19	2.04		
	39	2.04		



Test rate: 2Mbps	
CH00	 <p>2.401995800 GHz -6.01 dBm 2.037962030 MHz</p>
CH19	 <p>2.439995800 GHz -8.50 dBm 2.037962030 MHz</p>
CH39	 <p>2.479995800 GHz -9.06 dBm 2.037962030 MHz</p>

Appendix E: Duty cycle



Test Item:	Band edge	Test Rate:	2Mbps
------------	-----------	------------	-------

CH00

Spectrum

Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep
Count 300/300

IFK Max

Start 2.31 GHz 691 pts Stop 2.405 GHz

Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1			1	2.40204 GHz	-1.57 dBm		
M2			1	2.4 GHz	-47.77 dBm		
M3			1	2.39 GHz	-65.46 dBm		
M4			1	2.31 GHz	-65.12 dBm		
M5			1	2.399905 GHz	-54.28 dBm		

CH39




Spectrum




Ref Level 10.50 dBm Offset 0.50 dB RBW 100 kHz
Att 20 dB SWT 50.9 μs VBW 300 kHz Mode Auto FFT
Count 100/100




IFK Max




Start 2.478 GHz 691 pts Stop 2.5 GHz




Marker	Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1			1	2.47999 GHz	-4.21 dBm		
M2			1	2.4835 GHz	-61.43 dBm		
M3			1	2.5 GHz	-68.75 dBm		
M4			1	2.4827391 GHz	-59.06 dBm		




Test Item:	SE	Test Rate:	1Mbps
CH00 Reference level	<div><div>Spectrum</div><div><div>Ref Level 20.50 dBm</div><div>Att 30 dB</div><div>Count 100/100</div></div><div><div>Offset 0.50 dB</div><div>SWT 75.9 μs</div><div>RBW 100 kHz</div><div>VBW 300 kHz</div><div>Mode Auto FFT</div></div></div> <div><div><div>IPk Max</div><div>M1[1]</div><div>0.49 dBm</div><div>2.402000 GHz</div></div><div>CF 2.402 GHz691 ptsSpan 30.0 MHz</div></div> <div><div>Date: 24 JAN 2024 08:07:50</div></div>		
CH00 30MHz~1000MHz	<div><div>Spectrum</div><div><div>Ref Level 20.00 dBm</div><div>Att 30 dB</div><div>Count 10/10</div></div><div><div>Offset 0.50 dB</div><div>SWT 30.1 ms</div><div>RBW 100 kHz</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div></div></div> <div><div><div>IPk Max</div><div>M1[1]</div><div>-52.49 dBm</div><div>857.3340 MHz</div></div><div>Start 30.0 MHz30001 ptsStop 1.0 GHz</div></div> <div><div>Date: 24 JAN 2024 08:08:05</div></div>		
CH00 1GHz~26GHz	<div><div>Spectrum</div><div><div>Ref Level 20.00 dBm</div><div>Att 30 dB</div><div>Count 10/10</div></div><div><div>Offset 0.50 dB</div><div>SWT 250 ms</div><div>RBW 100 kHz</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div></div></div> <div><div><div>IPk Max</div><div>M1[1]</div><div>-43.94 dBm</div><div>15.915833 GHz</div></div><div>Start 1.0 GHz30001 ptsStop 26.0 GHz</div></div> <div><div>Date: 24 JAN 2024 08:08:01</div></div>		

CH19 Reference level	 <p>Spectrum</p> <p>Ref Level 20.50 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100</p> <p>IPK Max</p> <p>M1[1] -2.33 dBm 2.440000 GHz</p> <p>CF 2.44 GHz 691 pts Span 30.0 MHz</p> <p>Date: 24 JAN 2024 08:30:45</p>
CH19 30MHz~1000MHz	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>IPK Max</p> <p>M1[1] -32.63 dBm 991.3190 MHz</p> <p>O1 -22.330 dBm</p> <p>Start 30.0 MHz 30001 pts Step 1.0 GHz</p> <p>Date: 24 JAN 2024 08:31:00</p>
CH19 1GHz~26GHz	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>IPK Max</p> <p>M1[1] -44.43 dBm 15.135833 GHz</p> <p>O1 -22.330 dBm</p> <p>Start 1.0 GHz 30001 pts Stop 26.0 GHz</p> <p>Date: 24 JAN 2024 08:31:15</p>

<p>CH39 Reference level</p>	 <p>The spectrum plot shows a single sharp peak at 2.480000 GHz with a power level of -2.77 dBm. The y-axis ranges from -70 dBm to 10 dBm, and the x-axis is centered at 2.48 GHz with a span of 30.0 MHz. The plot includes a peak marker M1[1] and a noise floor around -55 dBm.</p>
<p>CH39 30MHz~1000MHz</p>	 <p>The spectrum plot shows a wide range from 30.0 MHz to 1000 MHz. The y-axis ranges from -70 dBm to 10 dBm. A red horizontal line is drawn at -22.770 dBm. The plot shows a noisy baseline with a peak marker M1[1] at -32.84 dBm. The plot includes a peak marker M1 and a noise floor around -55 dBm.</p>
<p>CH39 1GHz~26GHz</p>	 <p>The spectrum plot shows a wide range from 1.0 GHz to 26 GHz. The y-axis ranges from -70 dBm to 10 dBm. A red horizontal line is drawn at -22.770 dBm. The plot shows a noisy baseline with a peak marker M1[1] at -43.26 dBm. The plot includes a peak marker M1 and a noise floor around -55 dBm.</p>

Test Item:	SE	Test Rate:	2Mbps
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			

CH19 Reference level	
CH19 30MHz~1000MHz	
CH19 1GHz~26GHz	

CH39 Reference level	 <p>Spectrum</p> <p>Ref Level 20.50 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100</p> <p>IFK Max</p> <p>M1[1] -5.15 dBm 2.4799570 GHz</p> <p>CF 2.48 GHz 691 pts Span 30.0 MHz</p> <p>Date: 24 JAN 2024 08:39:35</p>
CH39 30MHz~1000MHz	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>IFK Max</p> <p>M1[1] -32.87 dBm 218.6750 MHz</p> <p>Start 30.0 MHz 30001 pts Step 1.0 GHz</p> <p>Date: 24 JAN 2024 08:39:50</p>
CH39 1GHz~26GHz	 <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>IFK Max</p> <p>M1[1] -44.23 dBm 15.800833 GHz</p> <p>Start 1.0 GHz 30001 pts Stop 26.0 GHz</p> <p>Date: 24 JAN 2024 08:40:05</p>

-----End of Report-----