

APPENDIX C - RF EXPOSURE EVALUATION

Applicable Standard

FCC §1.1307(b)(3)(i)(A)

a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

Procedure

According to 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.2- 1-mW Test Exemption:

Per §1.1307(b)(3)(i)(A), a single RF source is *exempt RF device* (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

Measurement Result

Frequency (MHz)	Maximum EIRP (dBm)	Maximum ERP		1-mW Test Exemption
		dBm	mW	
27.145	-31.24	-33.39	0.001	Compliant

Note:

1. This device maximum E-Field level is 63.96dBμV/m at 3m, so the EIRP power is -31.24dBm.
2. Pout EIRP(dBm)=Field Strength of Fundamental(dBuV/m)-95.2
3. ERP(dBm) = EIRP(dBm)-2.15

Result: Compliant. RF Exposure is exemption.

***** END OF REPORT *****