

## ROGERS LABS, INC.

4405 West 259<sup>th</sup> Terrace Louisburg, KS 66053 Phone / Fax (913) 837-3214

January 23, 2001

Federal Communications Commission Equipment Approval Services P.O. Box 35815 Pittsburgh, PA 15251-3315

Applicant: INTERMEC TECHNOLOGIES CORPORATION

6001 36th Avenue West Everett, WA 98203-9280 Phone: (505) 856-8054

RE: Correspondence Reference Number: 17631

Equipment: FCC ID: HN21555-900

## Gentlemen:

Please find enclosed the response to request for additional information regarding the submittal for grant of certification of Intentional Radiators operated in the frequency range of 902 – 928 MHz. It has been requested that the information contained in the block diagrams, operational description and schematics of the application be held confidential per Section 0.459.

Joe. The unit does meet these specifications. I had Jerry Johnson of Intermec write a statement and have attached it to this file. The information requested has been uploaded to the FCC web site. Please continue to process this application.

ROGERS LABS, INC. INTERMEC TECHNOLOGIES CORPORATION 4405 W. 259th Terrace MODEL: 1555 Hand Held Reader

Louisburg, KS 66053 Test #: 000815 FCCID#: HN21555-900

Phone/Fax: (913) 837-3214 Test to: FCC Parts 2 and 15 FCCresponseletterref17613B.doc 01/23/2001

● Page 2 January 23, 2001

AN-22-01	05:05PM	FROM-INTERMEC AMTECH ABQ	+5058570715	T-603	P.01/01 F	-754
	Înt	ermec				
			<u> </u>	A <b>UNDVA</b> Company		
					Intermec Technologies C	orporation
	Fax				Amtech System: 8600 Jefferson: S Albuquetque, N Phone: 505 856 Fax: 505 857 0 E-mail	St NE M. 87113 5.8000
Da	ue. Januar	January 22, 2001				
	ro: Scot R	Scot Rogers			_	
Compa	ny: Interm	ec			_	
Fax N	lo.: 913 83	37-3214			_	
Fro	m Jerry Johnson		Fax No : 505 857-0715		-	
			Telephone: 505 856-8059	7000		
Pal	Gez: 1	(Including this page)				
	For rep	For repeat transmission requests, please specify page numbers and respond as soon as possible.				

"Are the data signal and powering signal duplexed by time division? Do the signals occur on the same frequency and do they occur within the 400ms limit before the device hops to the next frequency in the pseudo-random sequence?"

Yes, the data signal and the power signal that controls the modulation is time division duplexed. These signals occur at the same frequency, with the maximum pseudo-random hop interval being less than 120 msec, well below the 400 msec limit.

Jerry Johnson Project Manager Intermec Technologies Corporation

## WARNING - PRIVILEGED AND CONFIDENTIAL MATERIAL

This transmission is intended only for the use of the individual of entity to which it is addressed and may contain information that is privileged confidential and exempt from quotosure under applicable tow if the reader of this transmission is not the intended receipent or the employee or agent responsible for delivering the transmission to the intended receipent or the employee or agent responsible for delivering the transmission to the intended receipent you are bereby notified that any dissemination, distribution or copying of this communication, is strictly prohibered if you have received this communication in error, please notify us introducted by phone and return the original transmission to us at the address above will the O.S. Postar Service. Thank you

Should you require any further information, please contact the undersigned. Thank you for your consideration in this matter. Sincerely,

ROGERS LABS, INC.

Scot DRogers

INTERMEC TECHNOLOGIES CORPORATION

4405 W. 259th Terrace

MODEL: 1555 Hand Held Reader

Louisburg, KS 66053 Phone/Fax: (913) 837-3214 Test #: 000815 FCCID#: HN21555-900

Test to: FCC Parts 2 and 15

FCCresponseletterref17631a.doc 01/23/2001

• Page 3 January 23, 2001

Scot Rogers Rogers Labs, Inc. Enclosures

ROGERS LABS, INC. 4405 W. 259th Terrace

Louisburg, KS 66053 Test #: 000815

FCCID#: HN21555-900

Phone/Fax: (913) 837-3214 Test to: FCC Parts 2 and 15 FCCresponseletterref17631a.doc 01/23/2001

MODEL: 1555 Hand Held Reader

INTERMEC TECHNOLOGIES CORPORATION