



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

Test Report

Report No. : CQASZ20190400012EX-01

Applicant: Hangzhou Meari Technology Co., Ltd.

Address of Applicant: No.91, Chutian Road,Xixing Block, Binjiang, Hangzhou, 310051 Zhejiang, CHINA

Manufacturer: Hangzhou Meari Technology Co., Ltd.

Address of Manufacturer: No.91, Chutian Road,Xixing Block, Binjiang, Hangzhou, 310051 Zhejiang, CHINA

Equipment Under Test (EUT):

Product: IP Camera

Model No.: Speed 5S

Brand Name: N/A

FCC ID: 2AG7C-SPEED5S

Standards: 47 CFR FCC Part 15 Subpart C 15.247

Date of Test: Apr. 18, 2019 to May 20, 2019

Date of Issue: May 20, 2019

Test Result : PASS

Tested By:

Daisy Qin

(Daisy Qin)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

2 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190400012EX-01	Rev.01	Initial report	May 20, 2019

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

4 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST LOCATION	7
5.6 TEST FACILITY	7
5.7 STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
5.8 DEVIATION FROM STANDARDS	8
5.9 ABNORMALITIES FROM STANDARD CONDITIONS	8
5.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
5.11 EQUIPMENT LIST	9
6 TEST RESULTS AND MEASUREMENT DATA.....	10
6.1 ANTENNA REQUIREMENT	10
6.2 CONDUCTED EMISSIONS	11
6.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER	14
6.4 6dB OCCUPY BANDWIDTH	15
6.5 POWER SPECTRAL DENSITY	20
6.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS	26
6.7 RF CONDUCTED SPURIOUS EMISSIONS	30
6.8 RADIATED SPURIOUS EMISSIONS.....	46
6.8.1 Radiated emission below 1GHz.....	49
6.8.2 Transmitter emission above 1GHz	51
6.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	53
7 PHOTOGRAPHS - EUT TEST SETUP	59
7.1 RADIATED SPURIOUS EMISSION.....	59
7.2 CONDUCTED EMISSION.....	60
8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	61

5 General Information

5.1 Client Information

Applicant:	Hangzhou Meari Technology Co., Ltd.
Address of Applicant:	No.91, Chutian Road,Xixing Block, Binjiang, Hangzhou, 310051 Zhejiang, CHINA
Manufacturer:	Hangzhou Meari Technology Co., Ltd.
Address of Manufacturer:	No.91, Chutian Road,Xixing Block, Binjiang, Hangzhou, 310051 Zhejiang, CHINA

5.2 General Description of EUT

Product Name:	IP Camera
Model No.:	Speed 5S
Trade Mark:	N/A
Hardware version:	REV1.1AK737F-A0
Software version:	V1.0
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Product Type:	☐ Mobile ☐ Portable ☒ Fix Location
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type	Internal Antenna
Antenna Gain	3.0dBi
Power Supply:	DC 5V from adapter
Adapter Information:	Model: TPA-46B050100UU Input: 100-240V 50/60Hz 0.2A Output: 5V 1000mA

Note: Please refer to the instruction manual for details.

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	/	/

Operation Frequency each of channel(802.11n HT40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
/	/	4	2427MHz	7	2442MHz	/	/
/	/	5	2432MHz	8	2447MHz	/	/
3	2422MHz	6	2437MHz	9	2452MHz	/	/

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz

Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1010mbar
Transmitting mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. Note: In the process of transmitting of EUT, the duty cycle >98%.

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

5.5 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

5.7 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	time	0.6 %.	(1)
14	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

5.8 Deviation from Standards

None.

5.9 Abnormalities from Standard Conditions

None.

5.10 Other Information Requested by the Customer

None.

5.11 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2018/9/26	2019/9/25
Spectrum analyzer	R&S	FSU26	CQA-038	2018/10/28	2018/10/27
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2018/9/26	2019/9/25
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2018/11/2	2019/11/1
Loop antenna	Schwarzbeck	FMZB1516	CQA-087	2018/10/28	2020/10/27
Bilog Antenna	R&S	HL562	CQA-011	2018/9/26	2020/9/25
Horn Antenna	R&S	HF906	CQA-012	2018/9/26	2020/9/25
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2018/9/26	2020/9/25
Coaxial Cable (Above 1GHz)	CQA	N/A	C019	2018/9/26	2019/9/25
Coaxial Cable (Below 1GHz)	CQA	N/A	C020	2018/9/26	2019/9/25
Spectrum analyzer	Agilent	E4440A	CQA-103	2018/10/28	2018/10/27
Antenna Connector	CQA	RFC-01	CQA-080	2018/9/26	2019/9/25
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2018/9/26	2019/9/25
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2018/9/26	2019/9/25
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2018/9/26	2019/9/25
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2018/9/26	2019/9/25
EMI Test Receiver	R&S	ESPI3	CQA-013	2018/9/26	2019/9/25
LISN	R&S	ENV216	CQA-003	2018/11/5	2019/11/4
Coaxial cable	CQA	N/A	CQA-C009	2018/9/26	2019/9/25

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	Antenna 
The antenna is internal antenna. The best case gain of the antenna is 3.0dBi.	


6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Setup:			
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.		

Page:12 of 70

Neutral Line:

80.0 dBuV




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2500	57.91	-0.11	57.80	61.75	-3.95	peak	
2		0.1780	61.83	-0.13	61.70	64.57	-2.87	peak	
3	*	16.6940	58.96	-0.28	58.68	60.00	-1.32	peak	
4		0.1835	32.34	-0.13	32.21	54.32	-22.11	AVG	
5		0.2980	31.61	-0.01	31.60	50.30	-18.70	AVG	
6		16.6940	51.68	-0.28	51.40	60.00	-8.60	QP	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


6.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

Type	Test channel	Peak Output Power (dBm)	Average Output Power dBm)	Limit (dBm)	Result
802.11b	Lowest	16.893	14.006	30.00	Pass
	Middle	14.366	11.317		
	Highest	14.658	11.313		
802.11g	Lowest	15.693	8.676	30.00	Pass
	Middle	19.604	12.575		
	Highest	19.897	12.889		
802.11n(HT20)	Lowest	15.309	7.981	30.00	Pass
	Middle	15.629	8.242		
	Highest	15.832	8.489		
802.11n(HT40)	Lowest	12.455	5.352	30.00	Pass
	Middle	12.536	5.428		
	Highest	12.493	5.43		

Note: 1.The test results including the cable lose.


6.4 6dB Occupy Bandwidth




Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass




Measurement Data




Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	Lowest	10.077	≥ 500	Pass
	Middle	10.098		
	Highest	9.638		
802.11g	Lowest	16.605	≥ 500	Pass
	Middle	16.61		
	Highest	16.654		
802.11n(HT20)	Lowest	17.865	≥ 500	Pass
	Middle	17.839		
	Highest	17.931		
802.11n(HT40)	Lowest	36.521	≥ 500	Pass
	Middle	36.541		
	Highest	36.498		

Test plot as follows:




11G/LCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq 2.41200000 GHz Center Freq: 2.41200000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 10.00 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 16.514 MHz Total Power 14.4 dBm Transmit Freq Error 5.117 kHz % of OBW Power 99.00 % x dB Bandwidth 16.61 MHz x dB -6.00 dB Frequency Center Freq 2.41200000 GHz CF Step 4.000000 MHz Auto Man Freq Offset 0 Hz
11G/MCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq 2.43700000 GHz Center Freq: 2.43700000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 16.547 MHz Total Power 18.6 dBm Transmit Freq Error 42.057 kHz % of OBW Power 99.00 % x dB Bandwidth 16.61 MHz x dB -6.00 dB Frequency Center Freq 2.43700000 GHz CF Step 4.000000 MHz Auto Man Freq Offset 0 Hz
11G/HCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq 2.46200000 GHz Center Freq: 2.46200000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 16.676 MHz Total Power 19.1 dBm Transmit Freq Error -1.4545 MHz % of OBW Power 99.00 % x dB Bandwidth 16.65 MHz x dB -6.00 dB Frequency Center Freq 2.46200000 GHz CF Step 4.000000 MHz Auto Man Freq Offset 0 Hz

11N20/LCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq 2.41200000 GHz Center Freq: 2.41200000 GHz Trig: Free Run #Atten: 30 dB Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 10.00 dBm Center 2.412 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 17.741 MHz Total Power 13.8 dBm Transmit Freq Error 36.731 kHz % of OBW Power 99.00 % x dB Bandwidth 17.86 MHz x dB -6.00 dB Frequency Center Freq 2.41200000 GHz CF Step 4.000000 MHz Auto Man Freq Offset 0 Hz
11N20/MCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq 2.43700000 GHz Center Freq: 2.43700000 GHz Trig: Free Run #Atten: 30 dB Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 10.00 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 17.725 MHz Total Power 14.1 dBm Transmit Freq Error 32.473 kHz % of OBW Power 99.00 % x dB Bandwidth 17.84 MHz x dB -6.00 dB Frequency Center Freq 2.43700000 GHz CF Step 4.000000 MHz Auto Man Freq Offset 0 Hz
11N20/HCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq 2.46200000 GHz Center Freq: 2.46200000 GHz Trig: Free Run #Atten: 30 dB Avg/Hold: 100/100 Radio Std: None Radio Device: BTS 10 dB/div Ref 10.00 dBm Center 2.462 GHz #Res BW 100 kHz #VBW 300 kHz Span 40 MHz Sweep 3.867 ms Occupied Bandwidth 17.995 MHz Total Power 14.5 dBm Transmit Freq Error -509.79 kHz % of OBW Power 99.00 % x dB Bandwidth 17.93 MHz x dB -6.00 dB Frequency Center Freq 2.46200000 GHz CF Step 4.000000 MHz Auto Man Freq Offset 0 Hz

11N40/LCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq: 2.42200000 GHz Center Freq: 2.42200000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 2.422 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms Occupied Bandwidth 36.107 MHz Total Power 11.5 dBm Transmit Freq Error 41.997 kHz % of OBW Power 99.00 % x dB Bandwidth 36.52 MHz x dB -6.00 dB	Frequency Center Freq 2.42200000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz
11N40/MCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq: 2.43700000 GHz Center Freq: 2.43700000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 2.437 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms Occupied Bandwidth 36.118 MHz Total Power 11.6 dBm Transmit Freq Error 44.442 kHz % of OBW Power 99.00 % x dB Bandwidth 36.54 MHz x dB -6.00 dB	Frequency Center Freq 2.43700000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz
11N40/HCH	 Keysight Spectrum Analyzer - Occupied BW Center Freq: 2.45200000 GHz Center Freq: 2.45200000 GHz Trig: Free Run Avg/Hold: 100/100 Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 2.452 GHz #Res BW 100 kHz #VBW 300 kHz Span 80 MHz Sweep 7.667 ms Occupied Bandwidth 36.079 MHz Total Power 11.5 dBm Transmit Freq Error 46.269 kHz % of OBW Power 99.00 % x dB Bandwidth 36.50 MHz x dB -6.00 dB	Frequency Center Freq 2.45200000 GHz CF Step 8.000000 MHz Auto Man Freq Offset 0 Hz


6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass




Measurement Data

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	Lowest	-16.485	8	Pass
	Middle	-18.574		
	Highest	-12.797		
802.11g	Lowest	-20.435	8	Pass
	Middle	-16.052		
	Highest	-12.653		
802.11n(HT20)	Lowest	-20.148	8	Pass
	Middle	-20.582		
	Highest	-18.923		
802.11n(HT40)	Lowest	-23.881	8	Pass
	Middle	-25.57		
	Highest	-24.644		


Test plot as follows:



11B/HCH	Keysight Spectrum Analyzer - Swept SA Center Freq 2.46200000 GHz 10 dB/div Log Ref 20.00 dBm Mkr1 2.459 947 GHz -12.797 dBm Center 2.462000 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 14.46 MHz Sweep 1.534 s (501 pts)	Frequency Auto Tune Center Freq 2.46200000 GHz Start Freq 2.454771500 GHz Stop Freq 2.469228500 GHz CF Step 1.445700 MHz Man Freq Offset 0 Hz Scale Type Log
11G/LCH	Keysight Spectrum Analyzer - Swept SA Center Freq 2.41200000 GHz 10 dB/div Log Ref 20.00 dBm Mkr1 2.411 05 GHz -20.435 dBm Center 2.41200 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 24.91 MHz Sweep 2.643 s (501 pts)	Frequency Auto Tune Center Freq 2.41200000 GHz Start Freq 2.399546250 GHz Stop Freq 2.42453750 GHz CF Step 2.490750 MHz Man Freq Offset 0 Hz Scale Type Log
11G/MCH	Keysight Spectrum Analyzer - Swept SA Center Freq 2.43700000 GHz 10 dB/div Log Ref 20.00 dBm Mkr1 2.436 10 GHz -16.052 dBm Center 2.43700 GHz #Res BW 3.0 kHz #VBW 9.1 kHz Span 24.92 MHz Sweep 2.644 s (501 pts)	Frequency Auto Tune Center Freq 2.43700000 GHz Start Freq 2.424542500 GHz Stop Freq 2.449457500 GHz CF Step 2.491500 MHz Man Freq Offset 0 Hz Scale Type Log


11G/HCH	
11N20/LCH	
11N20/MCH	

11N20/HCH







11N40/LCH		Frequency Auto Tune Center Freq 2.422000000 GHz Start Freq 2.394609250 GHz Stop Freq 2.449390750 GHz CF Step 5.478150 MHz Auto Man Freq Offset 0 Hz Scale Type Log Lin
11N40/MCH		Frequency Auto Tune Center Freq 2.437000000 GHz Start Freq 2.409594250 GHz Stop Freq 2.464405750 GHz CF Step 5.481150 MHz Auto Man Freq Offset 0 Hz Scale Type Log Lin
11N40/HCH		Frequency Auto Tune Center Freq 2.452000000 GHz Start Freq 2.424626500 GHz Stop Freq 2.479373500 GHz CF Step 5.474700 MHz Auto Man Freq Offset 0 Hz Scale Type Log Lin


6.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass


Test plot as follows:




11G/HCH		Frequency Auto Tune Center Freq 2.466000000 GHz Start Freq 2.432000000 GHz Stop Freq 2.500000000 GHz CF Step 6.800000 MHz Man Freq Offset 0 Hz Scale Type Log Lin
11N20/LCH		Frequency Auto Tune Center Freq 2.376000000 GHz Start Freq 2.310000000 GHz Stop Freq 2.442000000 GHz CF Step 13.200000 MHz Man Freq Offset 0 Hz Scale Type Log Lin
11N20/HCH		Frequency Auto Tune Center Freq 2.466000000 GHz Start Freq 2.432000000 GHz Stop Freq 2.500000000 GHz CF Step 6.800000 MHz Man Freq Offset 0 Hz Scale Type Log Lin





6.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass


Test plot as follows:











10GHz-26GHz
















10GHz-26GHz














Remark:

Pretest 9kHz to 26GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

6.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for

	the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel h. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40) For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Only the worst case is recorded in the report.
Test Results:	Pass

6.8.1 Radiated emission below 1GHz

30MHz~1GHz		
Test mode:	Transmitting	Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	30.9619	43.40	-5.71	37.69	40.00	-4.25	QP	100	251
2		64.2074	49.07	-18.81	30.26	40.00	-10.72	QP	100	232
3		84.7019	52.07	-18.39	33.68	40.00	-8.27	QP	100	124
4		166.6514	44.88	-13.34	31.54	43.50	-12.82	QP	100	23
5		196.5098	49.57	-13.68	35.89	43.50	-9.88	QP	100	48
6		208.5803	46.59	-14.28	32.31	43.50	-12.53	QP	100	16

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal
------------	--------------	------------



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		31.1798	36.62	-5.88	30.74	40.00	-10.23	QP	200	126
2		54.8348	47.33	-19.17	28.16	40.00	-12.83	QP	200	151
3	*	84.1100	54.70	-18.45	36.25	40.00	-5.78	QP	200	14
4		95.0930	45.68	-16.19	29.49	43.50	-15.25	QP	200	48
5		166.6514	45.06	-13.34	31.72	43.50	-12.72	QP	200	186
6		207.8501	43.48	-14.18	29.30	43.50	-15.36	QP	200	291

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

6.8.2 Transmitter emission above 1GHz

Test mode:		802.11b(1Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4824.000	60.50	-4.26	56.24	74	-17.76	PK	H
4824.000	41.08	-4.26	36.82	54	-17.18	AV	H
7236.000	63.16	1.18	64.34	74	-9.66	PK	H
7236.000	40.03	1.18	41.21	54	-12.79	AV	H
4824.000	59.47	-4.26	55.21	74	-18.79	PK	V
4824.000	39.34	-4.26	35.08	54	-18.92	AV	V
7236.000	63.73	1.18	64.91	74	-9.09	PK	V
7236.000	41.27	1.18	42.45	54	-11.55	AV	V

Test mode:		802.11b(1Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4874.000	59.55	-4.12	55.43	74	-18.57	PK	H
4874.000	39.35	-4.12	35.23	54	-18.77	AV	H
7311.000	60.88	1.46	62.34	74	-11.66	PK	H
7311.000	42.20	1.46	43.66	54	-10.34	AV	H
4874.000	63.66	-4.12	59.54	74	-14.46	PK	V
4874.000	39.74	-4.12	35.62	54	-18.38	AV	V
7311.000	59.06	1.46	60.52	74	-13.48	PK	V
7311.000	41.97	1.46	43.43	54	-10.57	AV	V

Test mode:		802.11b(1Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	59.17	-4.03	55.14	74	-18.86	PK	H
4924.000	39.03	-4.03	35.00	54	-19.00	AV	H
7386.000	60.05	1.66	61.71	74	-12.29	PK	H
7386.000	42.03	1.66	43.69	54	-10.31	AV	H
4924.000	61.84	-4.03	57.81	74	-16.19	PK	V
4924.000	41.32	-4.03	37.29	54	-16.71	AV	V
7386.000	61.74	1.66	63.40	74	-10.60	PK	V
7386.000	43.79	1.66	45.45	54	-8.55	AV	V

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case, only the worst case was recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:	
-------------	--




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
-----------------	--

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g ; 6.5Mbps of rate is the worst case of 802.11n(HT20) ; 13.5Mbps of rate is the worst case of 802.11n(HT40) Only the worst case is recorded in the report.
Test Results:	Pass

Test data:

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	60.52	-9.2	51.32	74	-22.68	PK	H
2390.000	38.54	-9.2	29.34	54	-24.66	AV	H
2400.000	57.05	-9.39	47.66	74	-26.34	PK	H
2400.000	39.95	-9.39	30.56	54	-23.44	AV	H
2390.000	59.81	-9.2	50.61	74	-23.39	PK	V
2390.000	38.16	-9.2	28.96	54	-25.04	AV	V
2400.000	56.56	-9.39	47.17	74	-26.83	PK	V
2400.000	42.34	-9.39	32.95	54	-21.05	AV	V

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	59.99	-9.29	50.70	74	-23.30	PK	H
2483.500	37.74	-9.29	28.45	54	-25.55	AV	H
2483.500	68.50	-9.29	59.21	74	-14.79	PK	V
2483.500	44.53	-9.29	35.24	54	-18.76	AV	V

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	59.78	-9.2	50.58	74	-23.42	PK	H
2390.000	38.67	-9.2	29.47	54	-24.53	AV	H
2400.000	57.38	-9.39	47.99	74	-26.01	PK	H
2400.000	41.61	-9.39	32.22	54	-21.78	AV	H
2390.000	61.53	-9.2	52.33	74	-21.67	PK	V
2390.000	37.39	-9.2	28.19	54	-25.81	AV	V
2400.000	56.63	-9.39	47.24	74	-26.76	PK	V
2400.000	40.66	-9.39	31.27	54	-22.73	AV	V

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	58.36	-9.29	49.07	74	-24.93	PK	H
2483.500	37.74	-9.29	28.45	54	-25.55	AV	H
2483.500	59.10	-9.29	49.81	74	-24.19	PK	V
2483.500	38.36	-9.29	29.07	54	-24.93	AV	V

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	60.15	-9.29	50.86	74	-23.14	PK	H
2390.000	37.13	-9.29	27.84	54	-26.16	AV	H
2400.000	57.19	-9.29	47.90	74	-26.10	PK	H
2400.000	40.59	-9.29	31.30	54	-22.70	AV	H
2390.000	60.24	-9.29	50.95	74	-23.05	PK	V
2390.000	37.16	-9.29	27.87	54	-26.13	AV	V
2400.000	59.19	-9.29	49.90	74	-24.10	PK	V
2400.000	41.31	-9.29	32.02	54	-21.98	AV	V

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	59.00	-9.29	49.71	74	-24.29	PK	H
2483.500	37.27	-9.29	27.98	54	-26.02	AV	H
2483.500	61.78	-9.29	52.49	74	-21.51	PK	V
2483.500	37.40	-9.29	28.11	54	-25.89	AV	V

Worse case mode:		802.11n(HT40)(13.5Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	59.68	-9.2	50.48	74	-23.52	PK	H
2390.000	38.68	-9.2	29.48	54	-24.52	AV	H
2400.000	58.41	-9.39	49.02	74	-24.98	PK	H
2400.000	41.56	-9.39	32.17	54	-21.83	AV	H
2390.000	58.53	-9.2	49.33	74	-24.67	PK	V
2390.000	37.46	-9.2	28.26	54	-25.74	AV	V
2400.000	58.46	-9.39	49.07	74	-24.93	PK	V
2400.000	40.51	-9.39	31.12	54	-22.88	AV	V

Worse case mode:		802.11n(HT40)(13.5Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	63.55	-9.2	54.35	74	-19.65	PK	H
2483.500	42.88	-9.2	33.68	54	-20.32	AV	H
2483.500	61.10	-9.29	51.81	74	-22.19	PK	V
2483.500	42.46	-9.29	33.17	54	-20.83	AV	V


Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

7 Photographs - EUT Test Setup

7.1 Radiated Spurious Emission




7.2 Conducted Emission




8 Photographs - EUT Constructional Details

External Photos















Internal Photos














THE END