




TEST REPORT

 eurofins KCTL Eurofins KCTL Co.Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR24-SRF0156 Page (1) of (15)		
1. Client - Name : Samsung Electronics Co., Ltd. - Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea - Date of Receipt : 2024-10-17 2. Use of Report : Certification 3. Name of Product / Model : Wi-Fi/BT Transceiver / WCF733R 4. Manufacturer / Country of Origin : Samsung Electronics Co., Ltd. / Korea, Vietnam, China 5. FCC ID : A3LWCF733R 6. IC Certificate No. : 649E-WCF733R 7. Date of Test : 2024-10-18 to 2024-11-06 8. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing (Address: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea) 9. Test method used : FCC Part 15 Subpart E, 15.407 RSS-247 Issue 3 August 2023 RSS-Gen Issue 5 February 2021 10. Test Result : Refer to the test result in the test report This laboratory is not accredited for the test results marked. *			
Affirmation	Tested by Name : Minki Kim (Signature)	Technical Manager Name : Heesu Ahn (Signature)	
The above testing certificate is the accredited test result by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.			
2024-11-07			
Accredited by KOLAS, Republic of KOREA		Eurofins KCTL Co.,Ltd.	
As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.			

 Eurofins KCTL Co.Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR24-SRF0156 Page (2) of (15)	 
--	--	---

REPORT REVISION HISTORY

Date	Revision	Page No
2024-11-07	Originally issued	-

This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is certified according to KS Q ISO/IEC 17025 and KOLAS recognition.

General remarks for test reports

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

☒ Statement not required by the standard or client used for type testing

CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Frequency/channel operations.....	5
3.	Summary of tests.....	6
4	Test results	7
4.1.	DFS (Dynamic Frequency Selection).....	7
5.	Measurement equipment	15

1. General information

Client	: Samsung Electronics Co., Ltd.
Address	: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Manufacturer	: Samsung Electronics Co., Ltd.
Address	: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Factory 1	: CHEMTRONICS CO., LTD.
Address 1	: 35, Buk-ri, Namsa-myeon, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Factory 2	: CHEMTROVINA COMPANY LIMITED
Address 2	: Nhon Trach 2-Loc Khang IZ, Hiep Phuoc Town, Nhon Trach District,, Dong Nai Province, Vietnam
Factory 3	: SJIT CO., LTD.
Address 3	: #54-11, Dongtanhana 1gil, Hwaseong-si, Gyeonggi-do, Korea
Factory 4	: SJIT VINA Co., Ltd
Address 4	: Lot X2, Ho Nai Industrial Zone, Ho Nai 3 Commune, Trang Bom District, Dong Nai Province, Vietnam
Factory 5	: Chengdu Xuguang Technology Co., Ltd.
Address 5	: No.86 2nd Section, Park Road, Longquanyi District, Chengdu City, Sichuan Province, P.R.China
Factory 6	: XUGUANG TECHNOLOGY (VIETNAM) COMPANY LIMITED
Address 6	: Factory No.4, Lot CN1, An Duong Industrial Park, Hong Phong Commune, An Duong District, Hai Phong City, Vietnam
Laboratory	: Eurofins KCTL Co.,Ltd.
Address	: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations	: FCC Site Designation No: KR0040, FCC Site Registration No: 687132 VCCI Registration No. : R-20080, G-20078, C-20059, T-20056 CAB Identifier: KR0040, ISED Number: 8035A KOLAS No.: KT231

2. Device information

Equipment under test	: Wi-Fi/BT Transceiver
Model	: WCF733R
Modulation technique	: Bluetooth(BDR/EDR)_GFSK, $\pi/4$ DQPSK, 8DPSK Bluetooth(BLE)_GFSK WLAN(802.11b/g/n/a/ac)_DSSS, OFDM, OFDMA
Number of channels	: BT/LE : 79 ch(BDR/EDR), 40 ch(BLE) 2.400 GHz band : 11 ch (20 MHz) 5 GHz band UNII-1 : 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz) UNII-2A : 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz) UNII-2C : 12 ch (20 MHz), 6 ch (40 MHz), 3 ch (80 MHz) UNII-3 : 5 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)
Power source	: DC 5 V
Antenna type	: BT/LE : PCB antenna WLAN : Metal antenna
Antenna gain	: BT/LE : -4.06 dBi Antenna 1 : -1.51 dBi Antenna 2 : -0.71 dBi 2.400 GHz band : -1.51 dBi 5 GHz band UNII-1 : 1.11 dBi UNII-2A : 1.31 dBi UNII-2C : 1.23 dBi UNII-3 : 1.43 dBi 0.66 dBi 0.77 dBi 0.34 dBi -0.53 dBi
Frequency range	: 2.400 GHz band : 2 402 MHz ~ 2 480 MHz (Bluetooth/BLE) 2 412 MHz ~ 2 472 MHz (802.11b/g/n_HT20) 5 GHz band UNII-1 : 5 180 MHz ~ 5 240 MHz (802.11a/n/ac_HT20/VHT20) 5 190 MHz ~ 5 230 MHz (802.11n/ac_HT40/VHT40) 5 210 MHz (802.11ac_VHT80)

UNII-2A	:	5 260 MHz ~ 5 320 MHz	(802.11a/n/ac_HT20/VHT20)
	:	5 270 MHz ~ 5 310 MHz	(802.11n/ac_HT40/VHT40)
	:	5 290 MHz	(802.11ac_VHT80)
UNII-2C	:	5 500 MHz ~ 5 720 MHz	(802.11a/n/ac_HT20/VHT20)
	:	5 510 MHz ~ 5 710 MHz	(802.11n/ac_HT40/VHT40)
	:	5 530 MHz ~ 5 690 MHz	(802.11ac_VHT80)
UNII-3	:	5 745 MHz ~ 5 825 MHz	(802.11a/n/ac_HT20/VHT20)
	:	5 755 MHz ~ 5 795 MHz	(802.11n/ac_HT40/VHT40)
	:	5 775 MHz	(802.11ac_VHT80)

Software version : v **.0.*
(0 is related to RF and the * is not related to RF.)

Hardware version : WCF733R

Test device serial No. : Conducted : 6C70CBEF66F6
Radiated : 6C70CBEF6708

Operation temperature : -10 °C ~ 50 °C

2.1. Frequency/channel operations

This device contains the following capabilities:

Bluetooth(BDR, EDR), Bluetooth Low Energy(1 Mbps, 2 Mbps, 125 kbps, 500 kbps),
WLAN 2.4 GHz_802.11b/g/n(HT20), WLAN 5 GHz_802.11a/n(HT20/40)/ac(VHT20/40/80)

UNII-2A

Ch.	Frequency (MHz)
52	5 260
56	5 280
64	5 320

UNII-2C

Ch.	Frequency (MHz)
100	5 500
120	5 600
140	5 700
144	5 720

Table 2.1.1. WLAN 5 GHz(802.11a/n_HT20/ac_VHT20)

UNII-2A

Ch.	Frequency (MHz)
54	5 270
62	5 310

UNII-2C

Ch.	Frequency (MHz)
102	5 510
118	5 590
134	5 670
142	5 710

Table 2.1.2. WLAN 5 GHz(802.11n/ac HT40/VHT40)

UNII-2A

Ch.	Frequency (MHz)
58	5 290

UNII-2C

Ch.	Frequency (MHz)
106	5 530
122	5 610
138	5 690

Table 2.1.3. WLAN 5 GHz(802.11ac_VHT80)

Notes:

1. The device supports DFS bands between UNII-2A and UNII-2C and operates as a slave device controlled by master.

3. Summary of tests

FCC Part section(s)	IC Rule Reference	Parameter	Test results
15.407(h)	RSS-247 Issue 3, 6.3	DFS -Channel closing transmission time -Channel move time -Non occupied period	Pass

Notes:

1. The test procedure(s) in this report were performed in accordance as following.
 - ♦ KDB 905462 D02 UNII DFS compliance procedure new rules.
 - ♦ KDB 905462 D03 UNII client without radar detection new rules.
2. The device does not support radar detection feature.

4 Test results

4.1. DFS (Dynamic Frequency Selection)

Test description

- Applicability of DFS requirements prior to use of a channel

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client (with radar detection)
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

- Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	<u>Yes</u>
Channel Move Time	Yes	<u>Yes</u>
Bandwidth	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	<u>Test using the widest BW mode available for the link</u>
All other tests	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

- Requirements of client devices

- a) A Client Device will not transmit before having received appropriate control signals from a Master Device.
- b) A Client Device will stop all its transmissions whenever instructed by a Master Device to which it is associated and will meet the Channel Move Time and Channel Closing Transmission Time requirements. The Client Device will not resume any transmissions until it has again received control signals from a Master Device.
- c) If a Client Device is performing In-Service Monitoring and detects a Radar Waveform above the DFS Detection Threshold, it will inform the Master Device. This is equivalent to the Master Device detecting the Radar Waveform and d) through f) of section 5.1.1 apply.
- d) Irrespective of Client Device or Master Device detection the Channel Move Time and Channel Closing Transmission Time requirements remain the same.
- e) The client test frequency must be monitored to ensure no transmission of any type has occurred for 30 minutes. Note: If the client moves with the master, the device is considered compliant if nothing appears in the client non-occupancy

- DFS Response requirement values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.	

- Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see note)
≥ 200 milliwatt	-64 dBm
< 200 milliwatt power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

- Radar test waveforms

Type	Pulse Width (μ sec)	PRI (μ sec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μ sec, with a minimum increment of 1 μ sec, excluding PRI values selected in Test A	$\text{Roundup}\left\{\left(\frac{1}{360}\right) \cdot \left(\frac{19 \cdot 10^6}{PRI_{\mu\text{sec}}}\right)\right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.

Note 2: This report was applied Short Pulse Radar Type 0.


*Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μs)	Chirp Width (MHz)	PRI (μs)	Number of Pulses per Burst	Number of Bursts	Minimum percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

*Long Pulse Radar Test Waveform

Radar Waveform	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (μs)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

*Frequency Hopping Radar Test Waveform

Test setup**- Setup for Client with injection at the Master****- Spectrum analyzer setting parameter**

This setting parameter is shown below and it according to the 905462 D02 UNII DFS Compliance Procedures New Rules.

- 1) RBW/VBW ≥ 3 MHz
- 2) Detector = peak
- 3) Span = zero span

- Conducted test procedure

- 1) One frequency will be chosen from the Operating Channels of the UUT within the 5 250-5 350 MHz or 5 470-5 725 MHz bands.
- 2) The Client Device (EUT) is set up the above diagram and communications between the Master device and the Client is established.
- 3) Stream the channel loading test file from the Master Device to the Client Device on the test Channel for the entire period of the test.
- 4) An additional 1 dB is added to the radar test signal to ensure it is at or above the DFS Detection Threshold, accounting for equipment variations/errors.
- 5) Observe the transmissions of the UUT at the end of the Burst on the Operating Channel for duration greater than 12 seconds for Radar Type 0 to ensure detection occurs.
- 6) After the initial radar burst the channel is monitored for 30 minutes to ensure no transmissions or beacons occur. A second monitoring setup is used to verify that the Master and Client have both moved to different channels.


- Master device information

Equipment Name	Manufacturer	Model No.	Serial No.	FCC ID
Access Point	ASUSTeK Computer Inc.	GT-AXE11000	M6IAJF202801	MSQ-RTAXJF00


Test result

Plot of radar waveform

5 320 MHz




5 500 MHz




Plot of LAN traffic


5 320 MHz



5 500 MHz



Plot of channel move time and aggregate time




Channel move time = 0.739 375 s

Closing time = 0.000 625 s x 32 = 0.020 000 s

(Closing time : Burst unit time(20 s / 32 001 points) * Number of burst(between 2 markers))

UNII-2A: 802.11 a, 5 320 MHz



Channel move time = 0.801 875 s


Closing time = 0.000 625 s x 32 = 0.020 000 s

(Closing time : Burst unit time(20 s / 32 001 points) * Number of burst(between 2 markers))


UNII-2C: 802.11 a, 5 500 MHz

Plot of Non-occupancy period

5 320 MHz



5 500 MHz



5. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R&S	FSV30	100808	25.07.01
DC Power Supply	TOYOTECH	TL305TP	21040092	25.07.01
Attenuator	R&S	DNF	0006	25.01.18
SPLITTER	Mini-Circuits	ZX10-2-98-S+	1635-1	25.01.19
SPLITTER	Mini-Circuits	ZX10-2-98-S+	1635-2	25.01.19
Step Attenuator	AGILENT	8494B	MY42140941	25.01.19
Step Attenuator	AGILENT	8495D	MY42144296	25.01.19
50Ω Termination	NONE	50Ω	R1	25.06.24
Vector Signal Generator	R&S	SMBV100A	257566	25.07.01
Signal Generator	R&S	SMB100A	176206	25.01.18

End of test report