

RF Exposure Evaluation Declaration

Product Name : Wireless N ADSL2+ Modem Router
Model No. : RG-A100L
FCC ID. : 2AA5WRGA100L

Applicant : NEC AccessTechnica, Ltd.

Address : 800 Shimomata, Kakegawa, Shizuoka 436-8501 Japan

Date of Receipt : 2013/09/11
Date of Declaration : 2013/11/13
Report No. : 139322R-RF-US-Exp
Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	Wireless N ADSL2+ Modem Router
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2dBi or 1.58 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	31.4051	0.00987
6	2437	22.8034	0.00717
11	2462	18.7068	0.00588

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	45.2898	0.01424
6	2437	34.0408	0.01070
11	2462	28.2488	0.00888

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless N ADSL2+ Modem Router
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2dBi or 1.58 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz) ANT 0			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	35.4813	0.01115
6	2437	26.8534	0.00844
11	2462	21.7771	0.00685

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless N ADSL2+ Modem Router
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2dBi or 1.58 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (40MHz) ANT 0			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
3	2422	12.4738	0.00392
6	2437	10.4713	0.00329
9	2452	9.0991	0.00286

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².